HTE# 16-5-39009 Harnett County Department of Public Health	29068
Improvement Permit	3
A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: Structure:	LOT # 32
Proposed Wastewater System Type: 2502 Red Projected Daily Flow: 4900 GPD Number of bedrooms: 7 Number of Occupants: 8 max Basement 94s 100	
Pump Required: 🗆 Yes 💿 No 💿 May be required based on final location and elevations of facilities Type of Water Supply: 🗆 Community 💭 Public 💭 Well Distance from well feet Permit valid for Permit conditions:	: E Five years No expiration
EAL Lolons	
Authorized State Kgent: Date: Date: Date: SEE The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bod site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	ATTACHED SITE SKETCH ies in meeting their requirements. This ct to compliance with the provisions of
Construction Authorization	
(Required for Building Permit)	
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout.	
ISSUED TO: Wyw Construction tre PROPERTY LOCATION: <u>Br. 1425</u> Chalyheaters Facility Type: <u>SP</u> New Expansion Repair	
Basement? I Yes I No Basement Fixtures? I Yes I No	
Type of Wastewater System** 25% 100000000 System (Initial) Wastewater Flor (See note below, if applicable []) 25% Reduction (Benair)	w: <u>490</u> GPD
Installation Requirements/Conditions Number of trenches Z	
Pump Tank Size 1200 gallons Trenches shall be installed on contour at a Soil Cover:	Feet on Center inches
Maximum Trench Depth of: 28718 inches (Maximum soil cover sh (Trench bottoms shall be level to +/-1/4" 36" above the trench in all directions)	
Pump Requirements:ft. TDH vs GPM	inches below pipe
Conditions: Aggregate Depth:	2 inches above pipe 12 inches total
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.	
Owner/Legal Representative Signature:	
Owner/Legal Representative Signature: Date:	in ownership of the site. This
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.	
Authorized State Agent:	
	and the second se

HTE# 16-5-39009 Permit # 29068 Harnett County Department of Public Health Site Sketch Authorized State Agent: ______ Marlon & Marlon & Date: ______ Date: _______ ASTUB Plukig out AT Grade on conver of Hone and pump away art BE NEEDSD

