Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit							
ISSUED TO: ONSTE HOMES LLC PROPERTY LOCATION: SANGRASS CT. SUBDIVISION WALNUT GROVE LOT # 2)							
ISSUED TO: UNSTEE HOMES LOT # 2) NEW X REPAIR □ EXPANSION □ SUBDIVISION WALRUT GROVE LOT # 2) Site Improvements required prior to Construction Authorization Issuance:							
Type of Structure: SEO(M3°×6)')							
Proposed Wastewater System Type: Existing 25% DED 575							
Projected Daily Flow: 360 GPD							
Number of bedrooms:							
Basement 🗆 Yes 🔀 No							
Pump Required: Wes On May be required based on final location and elevations of facilities							
Type of Water Supply: Community Public Well Distance from well 100 feet Permit valid for: Five years No expiration							
Authorized State Agent:: Date: 22807 SEE ATTACHED SITE SKETCH							
Authorized State Agent:: Date: Date: Dat							
Construction Authorization							
officer to the court to the cou							
(Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958 and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance							
with the attached system layout.							
SSUED TO: ORSITE HOMES LLC PROPERTY LOCATION: SANGRASS G. SUBDIVISION WALNUT GROVE LOT # 2)							
SUBDIVISION WALNUT GROVE LOT # 2)							
acility Type: 3 5 CG3 76 7							
Basement? Yes No Basement Fixtures? Yes No							
Basement? Yes No Basement Fixtures? Yes No Type of Wastewater System** Existing QS10 Reduction System* (Initial) Wastewater Flow: GPD							
(See note below if applicable)							
Puns To 25% (Repair)							
nstallation Requirements/Conditions Number of trenches							
eptic Tank Size 1000 gallons Exact length of each trench feet Trench Spacing: Feet on Center							
Cump Tank Size 1000 gallons Trenches shall be installed on contour at a Soil Cover: inches							
Maximum Trench Depth of: inches (Maximum soil cover shall not exceed							
(Trench bottoms shall be level to $\pm \frac{1}{4}$ 36" above the trench bottom)							
in all directions) Pump To Expanse							
tump Requirements: ft. TDH vs GPM 5757600 inches below pipe							
Aggregate Depth: inches above pip							
onditions: inches tota							
micros tota							
VATED LINES (INCLUDING IDDICATION) MUST BE 10FT EDOM ANY DART OF SERVIC SYSTEM OF REPAIR AREA							
/ATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.							
O UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.							
*If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.							
wner/Legal Representative Signature: Date: Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This							
onstruction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.							
uthorized State Agent: Date: 2 28 07,							
Construction Authorization Expiration Date: 2 2 2							

HTE#	16-	-5.	39	681	102
HILTT	(120 P. 120)		20771-02		1 0-

Permit # 29412

Harnett County Department of Public Health Site Sketch

		PROPERTY LOCATON: 500	GRASS Cr.	
ISSUED TO: UNS 15	E HOMES LLC	SUBDIVISION WALN		F01 # _ <i>ラノ</i>
Authorized State Agent:	The state of the s	IS COLIMAN TO EXPORT	Date: 2)28/17	
Authorized State Agent.			Date:	

