HTE# 17-5-41414

Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued w		
	CATION: Ow US42]	
ISSUED TO: MOUSE KUTZA SUBDIVISION		# 3
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:	:
Type of Structure: SGD (77 ×77)		
Proposed Wastewater System Type: 25% REDUCTION STOREN		
Projected Daily Flow: 360 GPD		
Number of bedrooms: Number of Occupants: max		
Basement 🗆 Yes 🔀 No		
Pump Required: ☐Yes No ☐ May be required based on final location and ele	vations of facilities	
Type of Water Supply: Community Public Well Distance from well _	feet Permit valid for: Five ye	ars
Permit conditions:	☐ No exp	iration
	_1 \	
Authorized State Agent: Date:	5 3 3 17) SEE ATTACHED SITE SKE	
The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permits are considered to the permits of the pe		
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	e affected by a change in ownership of the site. This permit is subject to compliance with th	e provisions of
the cams and noies for sewage freatment and disposal and to conditions of this period.		
		+
Construction A	<u>uthorization</u>	
(Required for Bui	Iding Permit)	
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959		in accordance
with the attached system layout.		
ISSUED TO: MOUSE KUTZA PROPER	() 12-12	
SUBDIVI	101 4388 0 to US421 LOT #	3_
Facility Type: SEO (77 AT) New Expa	ansion 🗆 Repair	
Basement? ☐ Yes ☒ No Basement Fixtures? ☐ Yes ☒ No _		
Type of Wastewater System** 25% RGDUCTION S	(Initial) Wastewater Flow: 360	GPD
(See note below, if applicable)	() (T "
25% DED. Sys	(Repair)	
	(ncpair)	
Installation Requirements/Conditions Number of trenches 1	190	
Septic Tank Size 1000 gallons Exact length of each trench		ter
Pump Tank Size gallons Trenches shall be installed on	Annual Management of the Control of	
Maximum Trench Depth of:	18-22 inches (Maximum soil cover shall not exceed	
(Trench bottoms shall be level	1 to +/-1/4" 36" above the trench bottom)	
in all directions)	,	
Pump Requirements:ft. TDH vs GPM	inches	below pipe
1 dilly requirements1t. 1011 13 0111	Aggregate Depth: inches	
6 82		1
Conditions:		inches total
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF	SEPTIC SYSTEM OR REPAIR AREA.	
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.		
**If applicable: I understand the system type specified is different from the type specified	ified on the application. I accept the specifications of this permit.	
Owner/Legal Representative Signature:	Date:	
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Cons		
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment	and Disposal and to the conditions of this permit. SEE ATTACHED SIT	F 2KETCH
	_1)	
Authorized State Agent:	Date: 5/3) 17	
	orization Expiration Date: 53)	

Harnett County Department of Public Health Site Sketch

