Harnett County Department of Public Health

Improvement Permit

A	building permit cannot be issued with only an Improvement P	Permit NRFAX DRIVE
ISSUED TO: WEAVER HOMES !		
NEW REPAIR . EXPANSIO		C2055/19 LOT # 1)
Type of Structure: SFD (35×54)	N 🗀 Site improvements requi	ired prior to Construction Authorization Issuance:
Proposed Wastewater System Type: 25% RE	OLIETON SVERM	
Projected Daily Flow: 360 GPD	200 200	
Number of bedrooms: 3 Number of Occup	nants: 6 max	
Basement □Yes ☒ No	ansnax	
	red based on final location and elevations of facilities	
Type of Water Supply: Community Public	☐ Well Distance from well feet	Permit valid for: Five years
Permit conditions:		□ No expiration
Authorized State Agent::	PGHS Date: 612 17	SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarar	itees the suance of other permits. The permit holder is responsible for checki	ing with appropriate governing bodies in meeting their requirements. This
the Laws and Rules for Sewage Treatment and Disposal and to condition	hanges. The Improvement Permit shall not be affected by a change in ownersh	hip of the site. This permit is subject to compliance with the provisions of
	Construction Authorization	
-	(Required for Building Permit)	
The construction and installation requirements of Rules .1950, .1952, .19 with the attached system layout.	954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references int	to this permit and shall be met. Systems shall be installed in accordance
ISSUED TO: WEAVER HOMES !	PROPERTY LOCATION: 219	FAKEFAX DENE
Facility Type: SFD (35'×54')	SUBDIVISION PITMEN	Caossing LOT # 11
Facility Type: SFS 135 45	New 🗆 Expansion 🗆 Repair	
Basement? Yes No Basement Fixt	tures? 🗆 Yes 💢 No	
Type of Wastewater System** 25%	LEDUCTION SXSTEM	(Initial) Wastewater Flow: GPD
(See note below if applicable)		
25%	RED. Sys, (Repair)	
Installation Requirements/Conditions	Number of trenches 1	
Septic Tank Size 1000 gallons		Trench Spacing: Feet on Center
Pump Tank Size gallons		Soil Cover: 6-)2 inches
7 dilip 7 dilik 3120 8 dilolis	Maximum Trench Depth of: 18-24 inches	(Maximum soil cover shall not exceed
	(Trench bottoms shall be level to +/-1/4"	
		36" above the trench bottom)
Down Barrison (6 TDI)	in all directions)	-11-T
Pump Requirements:ft. TDH vs		inches below pipe
6 11		Aggregate Depth: inches above pipe
Conditions:		inches total
WATER LINES (INCLUDING IRRIGATION) MUST B	BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR RE	PAIR AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR D	RAIN FIELD AREA.	
**If applicable: I understand the system type specified	is different from the type specified on the application	I account the energifications of this normit
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.		
Owner/Legal Representative Signature:		Date:
	olat, or the intended use changes. The Construction Authorization shall not be	A THE CONTRACT OF THE CONTRACT
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.		
		al. 1
Authorized State Agent:	REHS Date:	6 12 17
Construction Authorization Expiration Date: 6 12 22		

Harnett County Department of Public Health Site Sketch

