HTE#17-5-4782 Harnett County Department of Public Health	29706
18-5-43780 Improvement Permit	
A building permit cannot be issued with only an Improvement Permit	
ISSUED TO: GARY ROBINSON HOMES LLC SUBDIVISION	LOT # _ 8
NEW REPAIR EXPANSION Site Improvements required prior to Construction Au Type of Structure: 500(74)-61	thorization Issuance:
Proposed Wastewater System Type: Pume To 25% Rep. Sys.	
Projected Daily Flow: GPD	
Number of bedrooms: Number of Occupants: max BasementYes No	
Pump Required: Afes INO May be required based on final location and elevations of facilities	X
Type of Water Supply: Community X Public Well Distance from well feet Permit valid for:	
	No expiration
Authorized State Agent::	ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the resuance of other permits. The permit holder is responsible for checking with appropriate governing bodin site is subject to revocation if the site plan, plat, or the intended use changes. The improvement Permit shall not be affected by a change in ownership of the site. This permit is subject	es in meeting their requirements. This
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	t to compliance with the provisions of
Construction Authorization	
(Required for Building Permit)	
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Syst with the attached system layout.	tems shall be installed in accordance
ISSUED TO: GART ROBINSON HOMES PROPERTY LOCATION: PEANUT LN	
Facility Type: SUBDIVISION Facility Type: SUBDIVISION Image: Structure Structure Image: Structure Structure S	LOT # <u>8</u>
Basement? Ves No Basement Fixtures? Ves No	
Type of Wastewater System** Pume To 25% REDUCTION SYSTEM (Initial) Wastewater Flor	600
	w: <u>600</u> GPD
(See note below, if applicable L) <u>Pume To Low Profile Commotel</u> (Repair) <u>Installation Requirements/Conditions</u> Number of trenches	
Installation Requirements/Conditions Number of trenches 2	
Septic Tank Size 1250 gallons Exact length of each trench 225 feet Trench Spacing: 7	Feet on Center
Pump Tank Size 1250 gallons Trenches shall be installed on contour at a Soil Cover: 6	
Maximum Trench Depth of: 12-12 inches (Maximum soil cover sha	
(Trench bottoms shall be level to +/-1/4" 36" above the trench b	
in all directions)	
Pump Requirements:ft. TDH vs GPM	inches below pipe
Aggregate Depth:	inches above pipe
Conditions: 6"OF SOMER NEEDED OVER DRAINFIELD. CENTER FEED D-BOX PERMIT BASED ON PROPOSAL FROM APPLICANTS LSS	inches total
PARTY PARTY ON TROPOSAL TILOM MPPLICANTS LSD	
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of	f this permit.
Owner/Legal Representative Signature: Date:	
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in	n ownership of the site. This
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH	
Authorized State Agent: Consecuction Authorization Expiration Date: Bag	
Construction Authorization Expiration Date: 823	

