HTE# 17-5-42705

Harnett County Department of Public Health

Improvement Permit

A b	ouilding permit cannot be issued with only an Improvement	Permit 64 (NG (101)
ISSUED TO: Robert Crabtree Bld	SUBDIVISION SONO BCC	nnibrack Robe (US 40/N)
NEW REPAIR EXPANSION	Ste Improvements require	uired prior to Construction Authorization Issuance:
Type of Structure: 382 42 × 35 5 F		area prior to construction Authorization issuance.
Proposed Wastewater System Type: 25% Ned Sus		
Projected Daily Flow: 360 GPD)3,	
Number of bedrooms:3 Number of Occupa	ints: max	
Basement Yes No		
Pump Required: ☐Yes ☐ No ☐ May be require	ed based on final location and elevations of facilities	
Type of Water Supply: Community Public	☐ Well Distance from well _ ~A feet	Permit valid for: Five years
Permit conditions:		☐ No expiration
	11/10/15	ol 7-
Authorized State Agent::	Date: 12/04/20	
		cking with appropriate governing bodies in meeting their requirements. This rship of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions		sup of the site. This permit is subject to compliance with the provisions of
	*	
	Construction Authorization	
The contraction and installation requirement of Bules 1950, 1952, 190	(Required for Building Permit)	inco ship armite and shall be more Contains aball he installed in accordance
with the attached system layout.	54, .1955, .1956, .1957, .1958. and .1959 are incorporated by references i	
ISSUED TO: Robert Crabtree Blds Irc. PROPERTY LOCATION: 334 Donnibrook Ct. (US 401 2) SUBDIVISION Donnibrook Run LOT # 114		
	SUBDIVISION Donnil	orack Run LOT # 14
Facility Type: 3BR 421×351 SFD	New Expansion Repair	
Basement? Yes No Basement Fixtu	ures? 🗆 Yes 🗆 No	
Type of Wastewater System**	Reduction 5.55.	(Initial) Wastewater Flow: 360 GPD
(See note below, if applicable)	ŕ	
_25% red	(Repair)	
Installation Requirements/Conditions	Number of trenches	
Septic Tank Size gallons	Exact length of each trench Feet	Trench Spacing: Feet on Center
Pump Tank Size gallons	Trenches shall be installed on contour at a	Soil Cover: 8 inches
8	Maximum Trench Depth of: inches	(Maximum soil cover shall not exceed
		36" above the trench bottom)
	in all directions)	so above the trener betterny
Pump Requirements:ft. TDH vs	Desir otto esacendo e	inches below pipe
rump requirementsnt. 10n vs	_ drii	· ·
C. Pri		Aggregate Depth: inches above pipe
Conditions:		inches total
	E 10FT. FROM ANY PART OF SEPTIC SYSTEM OR F	REPAIR AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR D	RAIN FIELD AREA.	
**If applicable: I understand the system type specified	is different from the type specified on the application.	I account the energifications of this permit
<u> </u>	is unievent from the type specified on the application.	raccept the specifications of this perint.
Owner/Legal Representative Signature:		Date:
	lat, or the intended use changes. The Construction Authorization shall not b	
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.		
Authorized State Agent:	1247 Date:	12/04/2617
	Company Andrews Contraction D	
ANDREW WIL	Construction Authorization Expiration D	alc. 10110000

Harnett County Department of Public Health Site Sketch

