30001

HTE# 18-5-43369

## Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Impr

A panalis betilit calliot be issued	OCATION: Docs Ro
ISSUED TO: H+H CONSTRUCTORS INC SUBDIVISION	W Oaxman
NEW ★ REPAIR □ EXPANSION □	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: SEO (37'×63')	one improvements required prior to construction Authorization issuance:
Proposed Wastewater System Type: 25%, REDUCTION SYSTEM	
Projected Daily Flow: GOO GPD	
Number of bedrooms: 5 Number of Occupants: 10 max	
Basement 🗆 Yes 💌 No	
Pump Required: ☐Yes ☐ No 🄀 May be required based on final location and e	elevations of facilities
Type of Water Supply:   Community Public   Well Distance from well	feet Permit valid for: Five years
Permit conditions:	No expiration
	1
Authorized State Agent:: Date	
The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The pusite is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	ermit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
Construction /	Authorization
(Required for Bu	
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .195 with the attached system layout.	9 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
ISSUED TO: H+H CONSTRUCTORS 1~C PROPE	RTY LOCATION: Docs Ro
SUBDIV	1510N OREMONT LOT # 294
Facility Type: SEO(37°×63') New Exp	ansion   Repair
Basement?  Yes  No Basement Fixtures?  Yes  No	•
Type of Wastewater System** _ 25% Reduction Sy	(Initial) Wastewater Flow: GPD
(Con mate heless if emplicable [])	
25% RED. Sys.	(Renair)
Installation Requirements/Conditions  Number of trenches	(\\\\-\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Septic Tank Size \> > 50 gallons Exact length of each trench	
Pump Tank Size gallons Trenches shall be installed or	· · ·
Maximum Trench Depth of:	
(Trench bottoms shall be leve	el to +/-1/4" 36" above the trench bottom)
in all directions)	
Pump Requirements:ft. TDH vs GPM	inches below pipe
	Aggregate Depth: inches above pipe
Conditions:	inches total
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF	SEPTIC SYSTEM OR REPAIR AREA
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	
**If applicable: I understand the system type specified is different from the type spec	cified on the application. I accept the specifications of this permit.
Owner/Legal Representative Signature:	Date:
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes.	
Construction Authorization is subject to compliance with the previsions of the Laws and Rules for Sewage Treatment	and Disposal and to the conditions of this permit.  SEE ATTACHED SITE SKETCH
	1 1
Authorized State Agent:	Date: 3 13 X
Construction Auth	portization Expiration Date: 3 18 23

	10	- 1	SON
HTE#	18-	2.6	13369

## Harnett County Department of Public Health Site Sketch

13.// C		PROPERTY LOCATON:		)	
ISSUED TO: HAH C	phasiquoting 1	~ C. SUBDIVISION _	OAKMON	L(	OT # <u>294</u>
		1		1 1	
Authorized State Agent:	BryR	(OLIVER TOLKSDOF	び) Date:	3 13 18	
•				7 1	

