30063

HTE# 18-5-44002

Harnett County Department of Public Health

Improvement Permit

A	PROPERTY LOCATION: 431 Ausley 72d. (511422)
ISSUED TO MOSTAL O NEW BILL	
NEW REPAIR EXPANSION	
Type of Structure: 381 GO XGO S	
Proposed Wastewater System Type:	
Projected Daily Flow: 360 GPD	
Number of bedrooms: Number of Occupa	ants: max
Basement □Yes No	
Pump Required: ☐Yes ☐ No ☐ May be required	red based on final location and elevations of facilities
Type of Water Supply: Community Public Permit conditions:	□ Well Distance from well 100 feet Permit valid for: □ Five years □ No expiration
	7
	111/1/1/2 05/11/2000
	tees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This panges. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of this permit.
	Construction Authorization
The construction and installation requirements of Rules 1950 1952 19	(Required for Building Permit) 54, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	
Facility Type: 3BR 60'x60' STD PROPERTY LOCATION: 431 A wsley Rd. (501422) Facility Type: 3BR 60'x60' STD Property Location: 431 A wsley Rd. (501422) Facility Type: 3BR 60'x60' STD Property Location: 431 A wsley Rd. (501422) Facility Type: 3BR 60'x60' STD Property Location: 431 A wsley Rd. (501422) Facility Type: 3BR 60'x60' STD Property Location: 431 A wsley Rd. (501422)	
Facility Type: 3872 60'x60' 515	New Expansion Repair
	ures? \(\text{Yes} \) No
Type of Wastewater System** Pump to	
(See note below if applicable [])	9
Pump to	25% ned - Sus (Renair)
Installation Requirements/Conditions	Number of trenches (Repair)
Septic Tank Size 1000 gallons	Exact length of each trench feet
Pump Tank Size \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Trenches shall be installed on contour at a Soil Cover: Sinches
Tullip Talik Size gallons	Maximum Trench Depth of: inches (Maximum soil cover shall not exceed
	(Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)
	in all directions)
Duma Paguiramentes ft TNU vs	. ^
Pump Requirements:ft. TDH vs	
Condition	
Conditions:	Inches total
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.	
Owner/Legal Representative Signature:	Date:
	olat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This
The state of the s	the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH
The second secon	
Authorized State Agent:	1 Coll 1 1 Date: 05 131 2018
ANDREW WIL	Construction Authorization Expiration Date: 05/31/2023

Harnett County Department of Public Health Site Sketch

ISSUED TO: Keith Bollar Blds, Inc. SUBDIVISION Assley Rd. (32 1428) War S Date: 05/31/2018 Authorized State Agent: _ PART REPAIR * 23% NEOUCTION 225FT * MAY REQUIRE TO REPAIR MEET ONSTE ANEA P-67 181 PROPOSED 332 60'x601 30 SFD 26 165)