HTE#11-5-27971

Harnett County Department of Public Health

Improvement Permit

26857

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: LASATER RD ISSUED TO: HUGH STORES BULLOGES SUBDIVISION NEW

REPAIR □

Type of Structure: SFO (5C'×85') Site Improvements required prior to Construction Authorization Issuance: Proposed Wastewater System Type: 25°Lo REDUCKION SYSTEM Projected Daily Flow: 480 GPD Number of Occupants: _____ max Number of bedrooms: Basement □Yes ➤ No Pump Required: □Yes ➤ No ☐ May be required based on final location and elevations of facilities Type of Water Supply: □ Community ☑ Public □ Well Distance from well 100 0 feet Permit valid for: Five years Permit conditions: ☐ No expiration REMS Date: 12/19/11 Authorized State Agent:: site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: HUGY SURVES BUNDOGES PROPERTY LOCATION: LASATER RD SUBDIVISION Facility Type: SED (56785) New □ Expansion □ Repair Basement? Yes No Basement Fixtures?

Yes System (Initial) Wastewater Flow: 480 GPD 25% REDUCKTON Type of Wastewater System** (See note below, if applicable) 25% REDUCTION SYSTEM RUMP (Repair) Installation Requirements/Conditions Number of trenches Exact length of each trench \(\frac{1}{200} \) feet Trench Spacing: \(\frac{9}{2} \) Feet on Center Trenches shall be installed on contour at a Soil Cover: \(\frac{6}{2} \) inches Septic Tank Size 1000 gallons Pump Tank Size gallons Maximum Trench Depth of: 12-14 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to $\pm \frac{1}{4}$ " 36" above the trench bottom) in all directions) Pump Requirements: ft. TDH vs. GPM _____ inches below pipe Aggregate Depth: ______ inches above pipe Conditions: MINIMUM OF 6" OF COVER NEEDED OVER DRAWFIELD inches total WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA. **If applicable: / understand the system type specified is different from the type specified on the application. I accept the specifications of this permit, Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is society to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Authorized State Agent: Construction Authorization Expiration Date: 12

Permit # _____26857_____

Harnett County Department of Public Health Site Sketch

PROPERTY LOCATON:_ LOT # <u>ユ)</u> ISSUED TO: 1700 SUBDIVISION Authorized State Agent: 245, I10' 378' 337 pump REPAIR 5(~~85' ARGA DR ٧ <u>۲</u>

LASATERRO