## HTE#14-5-32745A

## Harnett County Department of Public Health

27788

Improvement Permit

PROPERTY LOCATION: USHAIN
ISSUED TO: JAMES AYLOR SUBDIVISION JAMES TAYLOR LOT # A
NEW ★ REPAIR ■ EXPANSION ■ Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: DUOLEY
Proposed Wastewater System Type: 25% REDUCTION 375-EM
Projected Daily Flow: 240 GPD
Number of bedrooms: Number of Occupants: H max
Basement
Pump Required: □Yes No □ May be required based on final location and elevations of facilities
Type of Water Supply:   Community Public Well Distance from well 100 feet Permit valid for: Five years
Permit conditions: THIS PERMIT IS FOR HALF OF A HTOTAL BEDROOM   No expiration
DUOLEX, EACH SOE WILL HAVE A SEPARATE SEPTIC SYSTEM
Authorized State Agent:: SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.
the Land and local to senage regulation and to conditions of this period.
Construction Authorization
Construction Authorization
(Required for Building Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout.
ISSUED TO: DAMES PROPERTY LOCATION: US 421 D
SUBDIVISION TAMES TAYLOR LOT # 1
Facility Type: Ovolson 🗆 Repair
Basement?  Yes No Basement Fixtures? Yes No
Type of Wastewater System** 25% REDUCTION SYSTEM (Initial) Wastewater Flow: 240 GPD
(See note below if applicable [])
25% REDUCTION (Repair)
Installation Requirements/Conditions Number of trenches 2
Septic Tank Size 1000 gallons Exact length of each trench 70 feet Trench Spacing: 9 Feet on Center
Pump Tank Size gallons
Maximum Trench Depth of: A inches (Maximum soil cover shall not exceed
(Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)
in all directions)
Pump Requirements:ft. TDH vs inches below pip
Aggregate Depth: inches above pi
Conditions: inches total
NATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.
Owner/Legal Representative Signature:  Date:  Chis Construction Authorization is subject to revocation if the site plan, and parts or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This
This Construction Authorization is subject to reversation if the site plan Arthur its plan Art
Construction Authorization is sobject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.  SEE ATTACHED SITE SKETCH
Construction Authorization is sobject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.  SEE ATTACHED SITE SKETCH

## Harnett County Department of Public Health Site Sketch

Authorized State Agent:

PROPERTY LOCATON: US421N

SUBDIVISION TAMES TRYLOR LOT # M

OLIVER TOLKSDOKE Date: 2/14/14

