30417

HTE# EH 1903-0010

Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

	PROPERTY LOCATION: 822065 Buildings 745
NEW - REPAIR E EXPANSION -	SUBDIVISIONLOT #
Type of Structure: Ey SAD	Site Improvements required prior to Construction Authorization Issuance:
Proposed Wastewater System Type: 25000	
Projected Daily Flow: 240 GPD	
Number of hadrooms 2. No. 1. Co U	mau.
Basement Ves No	max
Pump Required: ☐Yes ☐ No ☐ May be required based on final lo	estion and alaustine of facilities
	te from well feet
	REAS
Authorized State Agentinos 2 / Asshmax	Date: 3-27-15 SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement P the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This ermit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
Constru	ıction Authorization
	ired for Building Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, . with the attached system layout.	1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
ISSUED TO: BockeTT W Tunkington Th	PROPERTY LOCATION: 5,2005 Brichards PD
	SUBDIVISION LOT #
Facility Type: New	Expansion Repair
Basement? Yes No Basement Fixtures? Yes	No.
Type of Wastewater System [*]	(Initial) Wastewater Flow: 240 CPD
Type of Wastewater System** (See note below, if applicable ()	(Initial) Wastewater Flow: 240 GPD
(See note below, if applicable □)	
(See note below, if applicable)	(Repair)
(See note below, if applicable □) 25% Releasing S Installation Requirements/Conditions Number of trenche	Repair)
(See note below, if applicable □) Sometimes Conditions Conditi	(Repair) ach trench 180 feet Trench Spacing: 7 Feet on Center
(See note below, if applicable □) Compared Compared Conditions Conditions	(Repair) ch trench (Repair) installed on contour at a Soil Cover: (Feet on Center inches)
(See note below, if applicable □) C500 Colored	rinstalled on contour at a Soil Cover: Feet on Center installed of contour at a Soil Cover: inches Center inches Cover shall not exceed
(See note below, if applicable □) Septic Tank Size	(Repair) ch trench (Repair) installed on contour at a Soil Cover: (Feet on Center inches)
(See note below, if applicable □) Sometimes Conditions	rich trench 180 feet Trench Spacing: Feet on Center installed on contour at a Soil Cover: inches (Maximum soil cover shall not exceed hall be level to +/-1/4" Trench Spacing: Feet on Center inches (Maximum soil cover shall not exceed 36" above the trench bottom)
(See note below, if applicable □) Septic Tank Size	rinstalled on contour at a Soil Cover: Feet on Center installed of contour at a Soil Cover: inches Center inches Cover shall not exceed
(See note below, if applicable □) Sometimes Conditions	Inch trench 180 feet Trench Spacing: 7 Feet on Center Soil Cover: 6 inches Depth of: 22718 inches (Maximum soil cover shall not exceed hall be level to +/-1/4" Aggregate Depth: 7 inches below pipe inches above pipe
Conditions: Conditions Co	Continues Cont
(See note below, if applicable □) Comparison Compar	ch trench 180 feet Trench Spacing: 7 Feet on Center Soil Cover: 6 inches Depth of: 22718 inches (Maximum soil cover shall not exceed hall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: 7 inches above pipe 12 inches total
Conditions: Conditions Co	ch trench 180 feet Trench Spacing: 7 Feet on Center Soil Cover: 6 inches Depth of: 22718 inches (Maximum soil cover shall not exceed hall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: 7 inches above pipe 12 inches total
Conditions: Conditions Co	Continued 180 feet Trench Spacing: Feet on Center installed on contour at a Soil Cover: Goil Cover shall not exceed inches (Maximum soil cover shall not exceed 36" above the trench bottom) Aggregate Depth: Z inches above pipe inches above pipe inches total
See note below, if applicable	Check 180 feet Trench Spacing:
See note below, if applicable	Check 180 feet Trench Spacing:
Installation Requirements/Conditions Septic Tank Size	Check 180 feet Trench Spacing:

Harnett County Department of Public Health Site Sketch

RS
LOT #
15