30502

HTE# EH 1904-0016

Harnett County Department of Public Health

Improvement Permit

A	uilding permit cannot be issued with only an Improvement Permit
	PROPERTY LOCATION: 34504 (Jpscomb 12)
ISSUED TO: 1/LAVIS Lee COHEN	SUBDIVISION LOT #
NEW ☑ REPAIR ☐ EXPANSION	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure:	
Proposed Wastewater System Type: 250 Rea	tus
Projected Daily Flow: 480 GPD	
Number of bedrooms: Y Number of Occupa	nts: 8 max
Basement Tyes No	IIIGIIIAX
	ed based on final location and elevations of facilities
71	□ Well Distance from well feet Permit valid for: □ Five years
Permit conditions:	No expiration
5 W/	TERS - 3 IS
Authorized State Agent:	Date: 5-23-17 SEE ATTACHED SITE SKETCH
	ees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
	inges. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions	or this permit
	Construction Authorization
	(Required for Building Permit)
The rest of the last of the la	
with the attached system layout.	4, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
ISSUED TO: IRAUFS Lee Colte	PROPERTY LOCATION: 5 1504 Comb 145
	SUBDIVISION LOT #
Facility Type: Modulan	_ ✓ New □ Expansion □ Repair
Basement? Yes No Basement Fixtu	
Type of Wastewater System** 25% RB	$\frac{1}{1}$ (Initial) Wastewater Flow: $\frac{420}{1}$ GPD
(See note below, if applicable □)	
50% RE	(Repair)
Installation Requirements/Conditions	Number of trenches
Septic Tank Size 1200 gallons	Exact length of each trench feet Trench Spacing: Feet on Center
	1 0 ,
Pump Tank Size gallons	Trenches shall be installed on contour at a Soil Cover: inches
/1/	Maximum Trench Depth of: inches (Maximum soil cover shall not exceed
Tenffec	(Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)
Pated	in all directions)
Pump Requirements:ft. TDH vs	GPM inches below pipe
Tump requirements.	
111	Aggregate Depth: 2 inches above pipe
Conditions: May MOTO Dunp	It matter and IS 080 And 12 inches total
3 dt to second	late 22" Frol Dragues
WATER LINES (INCLUDING IRRIGATION) MILST R	E 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR D	AIN FIELD AKEA.
**If applicable: / understand the system type specified	is different from the type specified on the application. I accept the specifications of this permit.
	// / // // // // // // // // // // // /
Owner/Legal Representative Signature:	Data:
	Date:
30 CO	at, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This
construction Authorization is subject to compliance with the provisions of	the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH
A d : 10: 1	The the second
Authorized State Agent:	Date: 5-23-19
	Construction Authorization Expiration Date: 5-23-74

Harnett County Department of Public Health Site Sketch

,	PROPERTY LOCATON: 2545	04 GDSC	mb RD
ISSUED TO: TRAVES LEE COLLENS	SUBDIVISION		LOT # <u>30</u>
Authorized State Agent: Many	haster 18115	Date:	5-23-19

