## Harnett County Department of Public Health

Improvement Permit

A building permit	PROPERTY LOCATION: 5. 1810 STEWART RD					
ISSUED TO: NOC! DONSEY BUIE	SUBDIVISION LOT #					
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:					
Type of Structure: EX SAD	the improvements required prior to construction realism assume.					
Proposed Wastewater System Type: Low Partie CHamber	en					
Projected Daily Flow: 240 GPD						
Number of bedrooms:	max					
Basement Nes No						
	nal location and elevations of facilities					
Type of Water Supply: Community Public Well I	Distance from well 50' offeet Permit valid for: Five years					
Permit conditions:	□ No expiration					
S M 1	FIE REAS					
Authorized State Agent James ( Anhan	Date: 4-24-23 SEE ATTACHED SITE SKETCH					
	of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This					
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	ement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of					
the latter and the service of the se						
Con	estruction Authorization					
<u>Ç01</u>	struction Authorization					
	(Required for Building Permit)					
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, with the attached system layout.	.1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance					
ISSUED TO: NOR! Donsey BUTF.	PROPERTY LOCATION: SLIBIO STEWART FOR  SUBDIVISION LOT #  LOT #					
Facility Type: By SFB D N	SUBDIVISIONLOT #					
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						
Basement? Yes No Basement Fixtures? Yes						
Type of Wastewater System**	(Initial) Wastewater Flow: 240 GPD					
(See note below, if applicable )						
Low Protein	Chamber (Repair)					
Installation Requirements/Conditions Number of						
Septic Tank Size 1000 gallons Exact length	of each trench 225 feet Trench Spacing: Feet on Center					
	all be installed on contour at a Soil Cover:inches					
	rench Depth of: 16 inches (Maximum soil cover shall not exceed					
	toms shall be level to +/-1/4" 36" above the trench bottom)					
in all direct						
Pump Requirements:ft. TDH vsGPM	inches below pipe					
rump requirementsit. 10ft 450ff						
f # d	Aggregate Depth:inches above pipe inches total					
Conditions:	inches total					
WATER LINES ANGLINGING IRRIGATIONS WHIST RE JOST FRO	ALL AND DADE OF CENTIC CUCTEM OR DEDAID ADDA					
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FRO						
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD	AREA.					
**If applicable: 1 understand the system type specified is different to	from the type specified on the application. I accept the specifications of this permit.					
Owner/Legal Representative Signature:	Date:					
	d use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This					
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.  SEE ATTACHED SITE SKETCH						
1 1 DA REHS						
S M I to						
Authorized State Agent:	Date: 1 27 63					

## Harnett County Department of Public Health Site Sketch

Property Location: _	511810	STEWA	nt 1215			
Issued To: Noel			Subdivision			Lot #
			Manhard	ZEHS ZEHS	Date: _	4-24-23

