Harnett County Department of Public Health

Improvement Permit

Λ.	•
Kepa	-18
1	

A	building permit cannot be issued with only an Improvement Permit	
	PROPERTY LOCATION:	
ISSUED TO:	SUBDIVISION LOT #	
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:	
Type of Structure:		
Proposed Wastewater System Type:		
Projected Daily Flow: GPD		
Number of bedrooms: Number of Occupa	ants:max	
Basement Yes No		
	red based on final location and elevations of facilities	
Type of Water Supply: Community Public	☐ Well Distance from well	
Permit conditions:	No expiration	
Authorized State Agent::		
The issuance of this permit by the Health Department in no way guaran site is subject to revocation if the site plan, plat, or the intended use of the Laws and Rules for Sewage Treatment and Disposal and to condition	tees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This hanges. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is sobject to compliance with the provisions of sof this permit.	
	Construction Authorization	
	(Required for Building Permit)	
The construction and installation requirements of Rules .1950, .1952, .15 with the attached system layout.	954, 1955, 1956, 1957, 1958, and 1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance	
ISSUED TO: Ross Mentzer	PROPERTY LOCATION: 182 Navaho Trl (SR1320)	
13,000 10,	SUBDIVISION Summerlin LOT # 44	
Fully Ton Existing A RP home		
Facility Type: Existing 4 BR home		
	tures? Tyes No	
Type of Wastewater System**	(Initial) Wastewater Flow: 480 GPD	
(See note below, if applicable)		
	(Repair)	
Installation Requirements/Conditions	Number of trenches	
Septic Tank Size 1000 gallons	Exact length of each trenchfeet Trench Spacing: Feet on Center	
Pump Tank Sizegallons	Trenches shall be installed on contour at a Soil Cover:inches	
rump tank sizeganons		
	Maximum Trench Depth of:inches (Maximum soil cover shall not exceed	
	(Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)	
	in all directions)	
Pump Requirements:ft. TDH vs	GPM inches below pipe	
50 C 1 C 1 C 1 C 1 C 1 C 1 C 1 C 1 C 1 C	Aggregate Depth: inches above pipe	
Conditions: Dig up and replace crush	00 0	
WATER LINES (INCLUDING IRRIGATION) MUST E	BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.	
NO UTILITIES ALLOWED IN INITIAL OR REPAIR D	RAIN FIELD AREA.	
**If applicable: 1 understand the system type specified	is different from the type specified on the application. I accept the specifications of this permit.	
0 - 4 - 1 0	Data	
Owner/Legal Representative Signature:	Date:	
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is subject to compliance with the provisions of the laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH		
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH		
Authorized State Agent: 10/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/		
Authorized State Agent:	00201.	
/	Construction Authorization Expiration Date: 09-29-26	

Harnett County Department of Public Health Site Sketch

ued To: Ross Mentzer	Subdivision Summerlin	Lot # 44
thorized State Agent:	M REH	Date: 09-29-21
	Le pair	
	90' - 19 190' - 19 42' - 19'	Digupt fix Crus Arna of the Drain
	1 m' 53.	
	Wavaho Trl	