App# <u>EHZ110</u>— Inty Department of Public Health Improvement Permit 3126 Suichmille 125 Harnett County Department of Public Health

	2 - 0 - 1 - 2
· - +	PROPERTY LOCATION: Sr 2065 Baulpul (2)
ISSUED TO: VASITINA JUNENTEUA	SUBDIVISION LOT #
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: FX SPD	
Proposed Wastewater System Type: 1 ANK	
Projected Daily Flow: 340 GPD	
Number of bedrooms: Number of Occupant	s:max
Basement Yes No	
	based on final location and elevations of facilities
Type of Water Supply: Community Public	
Permit conditions:	No expiration
2 1	1 / 18 2048
Authorized State Agent	ANNAST Date: 10-20-21 SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees	the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
	es. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of	this permit.
	Construction Authorization
	(Required for Building Permit)
	.1955, .1956, .1957, 1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	
ISSUED TO: VASILENA TUNINTSEN	PROPERTY LOCATION: Je 2005 Bricknill 2005
135UEU 10: THE FIRM TOWN SEV	107 1/
1 -0	30001131011
Facility Type: EX SFD	□ New □ Expansion □ Repair
Basement? Yes No Basement Fixture	es? Yes Ho
Type of Wastewater System**	(Initial) Wastewater Flow: 366 GPD
(See note below, if applicable)	
TANK	(Recoir)
	(Repair)
	Number of trenches 9
Septic Tank Size 1000 gallons	Exact length of each trenchfeet
D. T.I.C. II. 1	6 - 3
Pump lank size gallons	
- 6	Trenches shall be installed on contour at a Soil Cover:inches
	Trenches shall be installed on contour at a Soil Cover:inches Maximum Trench Depth of:inches (Maximum soil cover shall not exceed
	Trenches shall be installed on contour at a Soil Cover: inches Maximum Trench Depth of: inches Trench bottoms shall be level to +/-1/4" Soil Cover: inches (Maximum soil cover shall not exceed 36" above the trench bottom)
· (Trenches shall be installed on contour at a Soil Cover: inches Maximum Trench Depth of: inches (Maximum soil cover shall not exceed 36" above the trench bottom) In all directions
· (Trenches shall be installed on contour at a Soil Cover: inches Maximum Trench Depth of: inches (Maximum soil cover shall not exceed 36" above the trench bottom) In all directions directions inches below pipe
Pump Requirements:ft. TDH vs	Trenches shall be installed on contour at a Soil Cover: inches Maximum Trench Depth of: inches Trench bottoms shall be level to +/-1/4"
Pump Requirements:ft. TDH vs	Trenches shall be installed on contour at a Soil Cover: inches Maximum Trench Depth of: inches Trench bottoms shall be level to +/-1/4"
Pump Requirements:ft. TDH vs	Trenches shall be installed on contour at a Soil Cover: inches Maximum Trench Depth of: inches (Maximum soil cover shall not exceed 36" above the trench bottom) In all directions) GPM inches below pipe
Pump Requirements:ft. TDH vs	Trenches shall be installed on contour at a Maximum Trench Depth of:inches Trench bottoms shall be level to +/-1/4" In all directions) GPM Aggregate Depth:inches below pipe
Pump Requirements:ft. TDH vs	Trenches shall be installed on contour at a Soil Cover: inches Maximum Trench Depth of: inches Trench bottoms shall be level to +/-1/4"
Pump Requirements:ft. TDH vs Conditions:ft. TDH vs WATER LINES (INCLUDING IRRIGATION) MUST BE	Soil Cover:
Pump Requirements:ft. TDH vs Conditions:ft. TDH vs WATER LINES (INCLUDING IRRIGATION) MUST BE NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRA	Trenches shall be installed on contour at a Soil Cover:
Pump Requirements:ft. TDH vs Conditions:ft. TDH vs WATER LINES (INCLUDING IRRIGATION) MUST BE NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRA	Soil Cover:
Pump Requirements:ft. TDH vs Conditions:ft. TDH vs WATER LINES (INCLUDING IRRIGATION) MUST BE NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRA	Trenches shall be installed on contour at a Soil Cover:
Pump Requirements:ft. TDH vs Conditions:ft. TDH vs WATER LINES (INCLUDING IRRIGATION) MUST BE NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRA **If applicable:	Soil Cover:
Pump Requirements:ft. TDH vs Conditions:ft. TDH vs WATER LINES (INCLUDING IRRIGATION) MUST BE NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRA **If applicable:	Soil Cover:
Pump Requirements:	Trenches shall be installed on contour at a Soil Cover:
Pump Requirements:	Trenches shall be installed on contour at a Soil Cover:
Pump Requirements:	Trenches shall be installed on contour at a Soil Cover:
Pump Requirements:	Trenches shall be installed on contour at a Soil Cover:

Application # EA ZIIO - 0006

Harnett County Department of Public Health Site Sketch

Property Location: Sn. 2005 Bruckmill 12D Issued To: VASTIVA TUNINGSBVA Subdivision	Lot #
Authorized State Agent: James & Manhart III 12845	Date: 10-20-21
Et 3006	
Et John Color	
100 100 100 100 100 100 100 100 100 100	
Et Al	
SR 2005 Brickmill	RD

This drawing is for illustrative purposes only. System installation must meet all pertinent laws, rules, and regulations.