
Harnett County Department of Public Health

Improvement Permit

	roperty Location: 1+w = 210 N
ISSUED TO: Dept of Interiors / Knic Kanas	NOTENII LUCATION: 11 W 9 2/0 /
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: Business	
Proposed Wastewater System Type: 25% Travers	
Projected Daily Flow: 200 GPD	17.005
Projected Daily Flow: Zoo GPD Number of bedrooms: Number of Occupants: 8 Bmpm	ax yeas
Basement Yes No	
Pump Required: Yes No May be required based on final loca	tion and elevations of facilities
Type of Water Supply: Community Public Well Distance	
Permit conditions: US Design Pronont IS SL	
Termit conditions.	
1 100	
Authorized State Agent Same & Manufacture State	Date: 1-10-27 SEE ATTACHED SITE SKETCH
. / /	ermits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
	rmit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	
Constru	ction Authorization
Constru	ction Authorization
(Requi	red for Building Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .19	958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	
10. 11. 11. 11. 11. 11. 11. 11. 11. 11.	PROPERTY LOCATION: Huy 210 N 26 Comm Park in LOT #_
ISSUED TO: DEPT of Laborator Force KARA-	PROPERTY LOCATION: Army 21010
, ,	SUBDIVISIONLOT #
Facility Type: New	Expansion Repair
Basement? Yes No Basement Fixtures? Yes	₹ ₩0
Type of Wastewater System** 25% 725000000000000000000000000000000000000	(Initial) Wastewater Flow: ZOO GPD
	(Initial) Wastewater How.
	,
(See note below, if applicable)	1-
25 26 RBW 020-Sq.	
Installation Requirements/Conditions Number of trenche	2
Installation Requirements/Conditions Number of trenche	2
Installation Requirements/Conditions Number of trenche Septic Tank Size 1000 gallons Exact length of each	s \mathbb{Z} ch trench \mathbb{S} feet Trench Spacing: \mathbb{G} Feet on Center
Installation Requirements/Conditions Number of trenches Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Trenches shall be in	ch trench 50 feet Trench Spacing: 2 Feet on Center nstalled on contour at a Soil Cover: 6 inches
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Trenches shall be in Maximum Trench D	ch trench 50 feet Trench Spacing: 9 Feet on Center Installed on contour at a Soil Cover: 6 inches Soil Cover shall not exceed
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Trenches shall be in Maximum Trench Distriction (Trench bottoms shall be in the condition of the con	ch trench 50 feet Trench Spacing: 2 Feet on Center nstalled on contour at a Soil Cover: 6 inches
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Trenches shall be in Maximum Trench Districtions of the control of the con	ch trench
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Trenches shall be in Maximum Trench Distriction (Trench bottoms shall be in the condition of the con	ch trench 50 feet Trench Spacing: 9 Feet on Center Installed on contour at a Soil Cover: 6 inches Soil Cover shall not exceed
Installation Requirements/Conditions Number of trenche Septic Tank Size	ch trench 50 feet Trench Spacing: 2 Feet on Center stalled on contour at a soil Cover: 6 inches lepth of: 24 inches (Maximum soil cover shall not exceed all be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: 2 inches above pipe
Installation Requirements/Conditions Number of trenche Septic Tank Size	ch trench 50 feet Trench Spacing: 2 Feet on Center stalled on contour at a soil Cover: 6 inches lepth of: 24 inches (Maximum soil cover shall not exceed all be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: 2 inches above pipe
Installation Requirements/Conditions Number of trenche Septic Tank Size	ch trench 50 feet Trench Spacing: 2 Feet on Center stalled on contour at a soil Cover: 6 inches lepth of: 24 inches (Maximum soil cover shall not exceed all be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: 2 inches above pipe
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench Described in all directions in all directions of the TDH vs. GPM Conditions: Pennet Dased off of SL 2018 - Los Desson Septic System Proposal	th trench 50 feet Trench Spacing:
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench Do (Trench bottoms shall directions) Pump Requirements:ft. TDH vsGPM Conditions: Pennt Dased off of SL 2018 - 1 LSS Design Septic System Proposal WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM AND	th trench 50 feet Trench Spacing:
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench Described in all directions in all directions of the TDH vs. GPM Conditions: Pennet Dased off of SL 2018 - Los Desson Septic System Proposal	th trench 50 feet Trench Spacing:
Installation Requirements/Conditions Number of trenche Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench D (Trench bottoms shain all directions) Pump Requirements:	ch trench 50 feet Trench Spacing:
Installation Requirements/Conditions Number of trenche Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench D (Trench bottoms shain all directions) Pump Requirements:	th trench 50 feet Trench Spacing:
Installation Requirements/Conditions Number of trenche Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench D (Trench bottoms shain all directions) Pump Requirements:	ch trench 50 feet Trench Spacing:
Installation Requirements/Conditions Number of trenche Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench D (Trench bottoms shain all directions) Pump Requirements:	ch trench 50 feet Trench Spacing:
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench Described bottoms shall directions) Pump Requirements:	th trench 50 feet Trench Spacing:
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Pump Tank Size 1000 gallons Frenches shall be in Maximum Trench Described bottoms shall directions) Pump Requirements:	ch trench 50 feet Trench Spacing:
Installation Requirements/Conditions Number of trenche Septic Tank Size	th trench
Installation Requirements/Conditions Number of trenche Septic Tank Size	th trench
Installation Requirements/Conditions Number of trenche Septic Tank Size	th trench
Installation Requirements/Conditions Number of trenche Septic Tank Size	ch trench 50 feet Trench Spacing:

Harnett County Department of Public Health Site Sketch

Property Location: Hance 210 N	26 Comm Park LN	
Issued To: Dept Tikeros / Gree Kar Subdivision		Lot #
Property Location: Hug21010 Issued To: Dept of Tukurus / Equal Kan Subdivision Authorized State Agent: 2 Manual State Authorized State	2 1045 Date: _	1-10-22
* Pennit Brosed off of SL 2018	-114 Section 11. (c)	



This drawing is for illustrative purposes only. System installation must meet all pertinent laws, rules, and regulations.

HAL OWEN & ASSOCIATES, INC.

SOIL & ENVIRONMENTAL SCIENTISTS

P.O. Box 400, Lillington NC 27546-0400 Phone (910) 893-8743 / Fax (910) 893-3594 www.halowensoil.com

PROPERTY INFORMATION

Project Name:	26 Comm Park Ln, Angier	
Site Address:	26 Comm Park Ln, Angier, NC 27501	
S/D Name and Lot#	210 Commercial Park Lot 6	
PIN:	0673-24-0911	
Size (Acre)	0.64 acre	
County:	Harnett	

APPLICANT INFORMATION

Name:	Dept of Interiors, Inc.	
Mailing Address:	PO Box 396, Fuquay-Varina, NC 27526	
Telephone Number:	919-669-7292	
E-mail Address:	deptofinteriorsinc@yahoo.com	

The LSS Evaluation attached to this application is to be used to produce, design, and construct features for permitting in accordance with SL 2018-114 Section 11.(c).

Miller	owner	1-7-22
Authorized Signature	Title	Date
(Please legibly print name here:)

HAL OWEN & ASSOCIATES, INC.

SOIL & ENVIRONMENTAL SCIENTISTS

P.O. Box 400, Lillington NC 27546-0400 Phone (910) 893-8743 / Fax (910) 893-3594 www.halowensoil.com

18 June 2021

Eric Kara Dept of Interiors, Inc. PO Box 396 Fuquay-Varina, NC 27526

Reference: LSS Evaluation (SL 2018-114) 26 Comm Park Ln, Angier, NC

Dear Mr. Kara,

A site investigation was conducted on 9 June 2021 for the above referenced property, which is located at 26 Comm Park Lane off of NC 210 N in Harnett County, North Carolina. The purpose of the investigation was to determine the ability of this lot to support a subsurface sewage waste disposal system and 100% repair area for a proposed business with a maximum of eight employees or a proposed daily flow of 200 gallons. Public water supplies will be utilized. At the time of the investigation, the site had been cleared, the lot corners marked, and the building footprint pinned.

This LSS Evaluation is being submitted pursuant to and meets the requirements of SL 2018-114 Section 11.(c). The evaluation of soil conditions and site features is provided in accordance with G.S. 130A-335. All ratings and determinations were made in accordance with "Laws and Rules for Sewage Treatment and Disposal Systems, 15A NCAC 18A .1900". This report represents my professional opinion as a Licensed Soil Scientist.

SOIL INVESTIGATION

The soils were evaluated under moist soil conditions through the advancing of auger borings. Soils at the site appeared to be formed from sedimentary parent. The soils indicated as provisionally suitable for subsurface sewage waste disposal systems are so rated due to clayey textured subsoil layers (Figure 1). The subsoils were observed to be well drained, friable sandy clay loams and extended to greater than 42 inches below ground surface (see attached soil/site evaluation form). These soils appear adequate to support long-term acceptance rates of 0.5 gal/day/sqft for conventional drainlines.

SEPTIC SYSTEM DESIGN

Adequate amounts of usable soils were observed on this lot to support an initial septic system and 100% repair area. Initial and repair septic systems have been designed for the proposed business utilizing a design daily flow of 200 gallons. A 1000 gallon (at minimum) septic tank and an approved septic effluent filter is required. A 1000 gallon (at minimum) pump tank will be required to lift effluent to the nitrification field. The long term application rate used to design both the initial and repair drainfields was 0.5 gal/day/ft².

The initial septic system is proposed as a pump driven system to two 50-ft long accepted status drainlines utilizing a 25% reduction in total drainline length. The drainlines should be installed on contour with maximum trench bottom depths at 24 inches below surface.

The repair septic system is proposed as a pump driven system to two 50-ft long accepted status drainlines utilizing a 25% reduction in total drainline length. The drainlines should be installed on contour with maximum trench bottom depths at 24 inches below surface.

Conformance to all regulatory setbacks shall be maintained. The minimum horizontal setback from a septic system to a property line is 10 ft, to a building foundation is 5 feet, and to a water line is 10 feet. All drainlines shall be installed on nine foot centers or greater, as flagged at the site.

Potential septic system drainlines have been demonstrated with various colored pin flags that are located on the lot. **It is important that you do not disturb the septic system area**. It is recommended that a staked line or protective fence be placed around the system prior to construction to eliminate any potential damage to the soil or the layout of the system.

SYSTEM MAINTENANCE

It is recommended that care be taken to preserve the life of the septic system. The septic tank, pump tank, and distribution boxes should be kept accessible for pumping and adjustment. Your septic system should be inspected periodically and the septic tank pumped out every 3 to 5 years by a professional contractor. Promptly repair leaky fixtures to avoid hydraulically overloading the septic system. Disposal of oils, fats, and grease into the septic system should be avoided because they could clog drainlines and conveyance pipes. Protect the tanks and nitrification field from vehicular traffic. A list of other useful suggestions can be found at https://content.ces.ncsu.edu/septic-system-owners-guide

CONCLUSION

This report and the attached septic system design information will need to be submitted to the Local Health Department for review and the permitting process. I appreciate the opportunity to provide this service and hope to be allowed to assist you again in the future. If you have any questions or need additional information, please contact me at your convenience.



Sincerely,

Krissina B. Newcomb

Krissina B. Newcomb

Hal Owen

Licensed Soil Scientist

SOIL/SITE EVALUATION FOR ON-SITE WASTEWATER SYSTEM


		1000		oc. OWNER:	AGENT:	PHONE:	919-669-7292	2
			uay-Varina, l		D . W W EV OV		0 - 1	
				PROPOSED				
			mm Park Ln,	Angier		TY SIZE: 0.6		
	: Harnet					TY ID #067		
				nmunity. Well [],				
				Pit 🗌			9 June 2021	
EVALUA	TED BY:	Hal Owen,	LSS 1102, S	Steven Boor, Hay	es Christenbu	iry		
PROFIL	F 1							
ROFIL			T	MOTTLES	T	.1941		CONSIS-
HORIZON	DEPTH	MATRIX	MOTTLES	ABUNDANCE/	(a)(1)	(a)(2)	(a)(3)	TENCE
	(IN)			SIZE/CONTRAST	TEXTURE		MINEROLOGY	MOIST
	0-6				LS	2 M GR	NEXP	VFR
	6-38				SL	2 M GR	NEXP	VFR
	38-48				SCL	2 M SBK	NEXP	FR
.1940 LANI	OSCAPE POS	S./ SLOPE%	L - 1%	.1956 SAPROLIT	E CLASS		NA	
.1942 SOIL	WETNESS (CONDITION	>48"	.1944 RESTRICT	IVE HORIZON		>48"	
.1943 SOIL	DEPTH		>48"	PROFILE CLASS	SIFICATION & L	TAR	PS 0.5 GPD/S	SF
COMMENT	S							
			INITIAL SY	YSTEM	REPAIR SYS	STEM	1	
1945 AV	AII ARI F	SPACE	400 of tren	NOTE OF THE PARTY	400 of trans			

	INITIAL SYSTEM	REPAIR SYSTEM
.1945 AVAILABLE SPACE	400 sf trench bottom	400 sf trench bottom
SYSTEM TYPE	Accepted status	Accepted status
SITE LTAR (gpd/ft ²)	0.5	0.5
.1946 OTHER FACTORS:_		
.1948 SITE CLASSIFICAT	ION: Provisionally Suitable	The state of the s

LEGEND OF ABBREVIATIONS FOR SITE EVALUATION FORM

V LANDS G L DE DO GAME CAN	TEXTURE	TEXTURE		.1955 LTAR
LANDSCAPE POSITION	GROUP	CLASS		(gal/day/sqft)
CC - Concave Slope	I	S - Sand		1.2-0.8
CV - Convex Slope		LS - Loamy Sand		
DS - Debris Slump				
D - Depression	II	SL - Sandy Loam		0.8 - 0.6
DW - Drainage Way		L - Loam		
FP - Flood Plain				
FS - Foot Slope	III	SCL - Sandy Clay Los	am	0.6 - 0.3
H - Head Slope		CL - Clay Loam		
L - Linear Slope		SiL - Silt Loam		
N - Nose Slope		Si - Silt		
R - Ridge		SiCL-Silt Clay Loam		
S - Shoulder Slope				
T - Terrace	IV	SC - Sandy Clay		0.4 - 0.1
		C - Clay		
MINEROLOGY		SiC - Silty Clay		
SEXP - Slightly Expansive				
EXP - Expansive		O - Organic		none
STRUCTURE	MOIST CON	SISTENCE	WET	CONSISTENCE
G - Single Grain	VFR - Very I		NS	- Non Stick
M - Massive	FR - Friable	2	SS	- Slightly Sticky
CR - Crumb	FI - Firm		MS	- Moderately Stick
GR - Granular	VFI - Very F	Firm	VS	- Very Sticky
SBK - Subangular Blocky		nely Firm		, , , ,
ABK - Angular Blocky	Administrative superior and the superior superio		NP	- Non Plastic
PL - Platy	MINERALO	GY	SP	- Slightly Plastic
PR - Prismatic		n Expansive	MP	- Moderately Plastic
	200 Company (Company Company C	ghtly Expansive	VP	- Very Plastic
		pansive	V 1	, or y 1 lastic
MOTTLES				
f – few 1 - fine		F - Faint		
c – common 2 - med		D - Distinct		
m - many 3 - coa		P - Prominent		
Give Horizon Depth in inches below			ala arra 1	1 C-


Give Horizon Depth in inches below natural soil surface and Fill Depth in inches above land surface. Depth to Soil Wetness: inches below land surface to free water or to soil colors with chroma 2 or less. Classification S – Suitable PS – Provisionally Suitable U – Unsuitable




Soil Science Investigations • Wetland Delineations, Permitting, and Consulting

LSS Evaluation (SL 2018-114) Soil Investigation and Septic System Design for 26 Comm Park Ln, Angier 18 June 2021 Scale 1 in = 50 ft

Figure 2. Septic system design and layout









MOLLANDOL ALLY MANAGES	MISSON STREET, WINDS STORY STREET	ADVANCE STRANGE STOMASSOR	WATERIST AW	PENA PLOCO WAP	NOT IN COOL IS BACKET	BUILDING FOOTPRING	BUILDING HIGHY	WHY STOWISHING STRONGING	DISTRIBUTED AREA	STORES SAME NAME OF STREET	GROW Olsey DWOMPER	PARKED REQUESTS	SCAR - SAPE SCHRON	SDE VARD SETTANCE	KUTHLIS BIPA LINCKS	SALL ASPRANCES	SANT, MOLLD/TRUSPICO	HOURS OF OPERATOR	MIT GROWDING	SUC BREEZE	*75c*	ZOMBNG	ON NA GO ALENSYN	ACCHESIS.	LOT NUMBER	45 COMBIED DISE	WORLANDING.	SITE
MECHANIS THOSE 30,000 St. NO. 1034 21289 TOWN 21289 TOWN 2185 WAR	BICH	40.12	4/4	3720069000 EFFECTIVE 10/3/2008	NOW ON WAS TO J	V300.2k	197	3.32 ADRCS	0.5e ACRES	Drds i	12 SPACES TOTAL (NO. AGA BELOW)	PARCE RECORD - 12 SPACE BANG - 1 DANGERS - 1 DANGERS - 1	20	70	307	τ.	V-0	TAM-SPU WOMEN' THRU SATURDAY	MANUEL THRONOLINE	VACAN1	5.38CW 04.0	PEDEJMING TROPICS - 30	2873-24-7811 (99)	26 COMM PARK LARE	*	DEZD 800W 3577 PACE 97	218 COAMERCAL PARK	E DATA

- PRODUCTION RESIDENCE NO FRANCE NO PROJECT NO MARCH TO MARCH TO PROJECT NO PRO

- NO THE RESIDENCE SHALL BE PROJUCED.

 LINESCLUS RESILLATED AND MANESHADE PER ANDRE (BE) 7 A.7 AND 7 A.5.
 LINESCLUS RESILLATED AND MANESHADE PER ANDRE (BE) 7 A.7 AND 7 A.5.
 LINESCLUS RESILLATED TO BE (PERSONED BY GERECONEL).

SITE PLAN



TANCTULE 2" 2023



26 COMM PARK LANE

COVER SHEET & SITE PLAN

 \overline{c}