Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

ISSUED TO: Jim Brown	PROPERTY LOCATION: 996 PEACH FAITH Rd (SR 1251) SUBDIVISION LOT #
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure:	
Proposed Wastewater System Type:	
Projected Daily Flow: GPD	
Number of bedrooms: Number of Occupants:	max
Basement Yes No	
Pump Required: Yes No May be required based on final le	
Type of Water Supply: Community Public Well Distant	
Permit conditions:	No expiration
Authorized State Agent::	Date: SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other	r permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and rules for sewage treatment and Disposal and to Conditions of this permit.	
Constr	uction Authorization
	uired for Building Permit)
the construction and installation requirements of Kules (1950, (1952, (1954, (1955, (1956, (1957, With the attached system layout.)	.1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
ISSUED TO: Jim Brown	PROPERTY LOCATION: Peach Farm Rd (SR 1251)
- · · · · · -	LOT #
Facility Type: Existing 4Br Home New	Expansion Repair
Basement? Yes No Basement Fixtures? Yes	⊠ No
Type of Wastewater System**	(Initial) Wastewater Flow: 480 GPD
(See note below, if applicable)	(Initial) Wastewater Flow: 480 GPD
(See note below, if applicable) 25% reduction	(Initial) Wastewater Flow: 480 GPD (Repair)
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Number of trenc	(Initial) Wastewater Flow: 480 GPD (Repair)
(See note below, if applicable)	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center
(See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Septic Tank Size gallons Frenches shall be	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center e installed on contour at a Soil Cover: 6 inches
(See note below, if applicable) 25% reduction Installation Requirements/Conditions	(Repair) hes 3 each trench 80 installed on contour at a Depth of: 18" - 26" inches (Initial) Wastewater Flow: 480 GPD Feet on Center inches (Maximum soil cover shall not exceed
(See note below, if applicable) 25% reduction Installation Requirements/Conditions	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center e installed on contour at a Soil Cover: 6 inches
(See note below, if applicable) 25% reduction Installation Requirements/Conditions	(Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center soil Cover: 6 installed on contour at a Depth of: 18" - 26" inches shall be level to +/-1/4" [Repair] (Repair) feet Trench Spacing: 9 Feet on Center soil Cover: 6 inches (Maximum soil cover shall not exceed) 36" above the trench bottom)
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Frenches shall be Maximum Trench (Trench bottoms	(Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center soil Cover: 6 installed on contour at a Depth of: 18" - 26" inches shall be level to +/-1/4" [Repair] (Repair) feet Trench Spacing: 9 Feet on Center soil Cover: 6 inches (Maximum soil cover shall not exceed) 36" above the trench bottom)
See note below, if applicable	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet on Center sinstalled on contour at a Depth of: 18" - 26" inches shall be level to +/-1/4" (Maximum soil cover shall not exceed 36" above the trench bottom) inches below pipe
See note below, if applicable	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet on Center sinstalled on contour at a Depth of: 18" - 26" inches shall be level to +/-1/4" (Maximum soil cover shall not exceed 36" above the trench bottom) inches below pipe
See note below, if applicable	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet on Center sinstalled on contour at a Depth of: 18" - 26" inches shall be level to +/-1/4" (Maximum soil cover shall not exceed 36" above the trench bottom) inches below pipe
See note below, if applicable	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet on Center sinstalled on contour at a Depth of: 18" - 26" inches shall be level to +/-1/4" (Maximum soil cover shall not exceed 36" above the trench bottom) inches below pipe
See note below, if applicable	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center installed on contour at a Soil Cover: 6 inches Depth of: 18" - 26" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches above pipe inches above pipe inches total As Shallow as possible, even moved ever MY PART OF SEPTIC SYSTEM OR REPAIR AREA. Task by 4" To meet
See note below, if applicable 25% reduction	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center installed on contour at a Soil Cover: 6 inches Depth of: 18" - 26" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe Aggregate Depth: inches above pipe Aggregate Depth: inches above pipe And As Shallow as possible, even moved ever NY PART OF SEPTIC SYSTEM OR REPAIR AREA. Tash by Ci" To meet
See note below, if applicable 25% reduction	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center installed on contour at a Soil Cover: 6 inches Depth of: 18" - 26" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches above pipe inches above pipe inches total As Shallow as possible, even moved ever MY PART OF SEPTIC SYSTEM OR REPAIR AREA. Task by 4" To meet
See note below, if applicable 25% reduction 25% reduction 25% reduction Septic Tank Size 1000 gallons Exact length of Pump Tank Size gallons Trenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements: ft. TDH vs. GPM GPM	(Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center e installed on contour at a Depth of: 18" - 26" inches shall be level to +/-1/4" Aggregate Depth: inches inches below pipe Aggregate Depth: inches inches above pipe Aggregate Depth: inches above pipe Appropriate well inches above pipe inches total As Shallow as possible, aver moved ever NY PART OF SEPTIC SYSTEM OR REPAIR AREA. Task by Ci'To meet A. the type specified on the application. I accept the specifications of this permit.
See note below, if applicable 25% reduction 25% reduction 25% reduction Septic Tank Size 1000 gallons Exact length of Pump Tank Size gallons Trenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements: ft. TDH vs. GPM GPM	(Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center sinstalled on contour at a Depth of: 18" - 26" inches shall be level to +/-1/4" Aggregate Depth: inches inches above pipe and As Shallow as possible, aver mound ever NY PART OF SEPTIC SYSTEM OR REPAIR AREA. The type specified on the application. I accept the specifications of this permit. Date:
See note below, if applicable 25% reduction Septic Tank Size 1000	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center e installed on contour at a Soil Cover: 6 inches Depth of: 18" - 26" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches above pipe inches total and As Shallow as possible, even mound even MY PART OF SEPTIC SYSTEM OR REPAIR AREA. Task by Cy" To MERT A. the type specified on the application. I accept the specifications of this permit. Date:
See note below, if applicable 25% reduction 25% reduction 25% reduction Septic Tank Size 1000 gallons Exact length of Pump Tank Size gallons Trenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements: ft. TDH vs. GPM GPM	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center e installed on contour at a Soil Cover: 6 inches Depth of: 18" - 26" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches above pipe inches total and As Shallow as possible, even mound even MY PART OF SEPTIC SYSTEM OR REPAIR AREA. Task by Cy" To MERT A. the type specified on the application. I accept the specifications of this permit. Date:
See note below, if applicable 25% reduction 1000 gallons Exact length of Pump Tank Size 1000 gallons Trenches shall be Maximum Trench (Trench bottoms in all directions) 25% reduction Exact length of Pump Tank Size gallons Trenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements: ft. TDH vs. GPM	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center installed on contour at a Soil Cover: 6 inches Depth of: 18" - 26" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches below pipe Aggregate Depth: inches above pipe inches total As Shallow as Poss, ble, Over Mound ever NY PART OF SEPTIC SYSTEM OR REPAIR AREA. Tank by Cy" To MERT A. the type specified on the application. I accept the specifications of this permit. Date: Changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH
See note below, if applicable 25% reduction	(Initial) Wastewater Flow: 480 GPD (Repair) hes 3 each trench 80 feet Trench Spacing: 9 Feet on Center e installed on contour at a Soil Cover: 6 inches Depth of: 18" - 26" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches above pipe inches total and As Shallow as possible, even mound even MY PART OF SEPTIC SYSTEM OR REPAIR AREA. Task by Cy" To MERT A. the type specified on the application. I accept the specifications of this permit. Date:

Harnett County Department of Public Health Site Sketch

Keep Drain Unes //	Subdivision	Lot# Date: 04-12-22
(eep TOP (1) & 5 OFF OF The Storage room IT back of house Remove Magnolia Ter To Make room IT (3) 80'x3' Prain lines Keep Drain lines		Date: 04-12-22
(Rep TOP (1) & 5 OFF OF The Storage room Thoch of house Remove Magnolia Let To Make room (3) 80'x3' Tain lines Keep Drain lines		
Lemove Magnolia Lemove Magnolia Le To Make room (3) 80'x3' ain lines Leep Drain lines		
Lemove Magnolia Lemove Magnolia Le To Make room (3) 80'x3' Zin lines Leep Drain lines		
Emove Magnolia 1 To Make room (3) 80'x3' Zin lines		
Lemove Magnolia 1 To Make room (3) 80'x3' Zin lines		
Lemove Magnolia Le To Make room (3) 80'x3' Zin lines Leep Drain lines		
Lemove Magnolia Le To Make room (3) 80'x3' Zin lines Leep Drain lines		
Lemove Magnolia Le To Make room (3) 80'x3' Zin lines Leep Drain lines	/	
(3) 80'x3' Zin lines Leep Drain lines	ſ	
(3) 80'x3' Zin lines Leep Drain lines		(کمیه (
(3) 80'x3' ain lines Leep Drain lines		Wooded
(3) 80'x3' Zin lines Leep Drain lines		ω
Leep Drain lines	Fence	
Leep Drain lines		
Leep Drain Lines	That - Tour	-80
eep Drain lines //		-80'
		80 magnolia
Menter //	Br 1	Tres
	buse 1	
(4)	/ /	
7 4	///	/
Stala grown		
TATO True	& Bornd	
	WIT.	
1 /		
()		
()		
. 11		I castaly
} }		aha
<i>i 1</i>		
/ 1		
This drawing is for illustrative purposes only	- /	