Harnett County Department of Public Health

Improvement Permit

	PROPERTY LOCATION: 15 Transpired (1)
ISSUED TO: Ramon Atkins	PROPERTY LOCATION: 15 Tranguil (1 (5R 1268) SUBDIVISION LOT #
NEW ☐ REPAIR ☑ EXPANSION ☐	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: Existing Home	
Proposed Wastewater System Type: 25% reduction	
Projected Daily Flow: 720 GPD	
Number of bedrooms: 6 Number of Occupants: 12	max
Basement Yes 🖾 No	
	l location and elevations of facilities
Type of Water Supply: Community Public Well Dis	
Permit conditions:	No expiration
Authorized State Agent:: Mah Department in no way guarantees the issuance of this nermit by the Health Department in no way guarantees the issuance of the instance of the ins	Date: 2-/6-23 SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of o	other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
- 스팅 (Participation) 등 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ent Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	
Cons	truction Authorization
1	Required for Building Permit)
,	757, 1958, and 1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	
ISSUED TO: Ramon Atkins	PROPERTY LOCATION: 15 Transcript (UR 1268)
133010 10.	PROPERTY LOCATION: 15 Tranquil (a (JR1268) SUBDIVISION LOT #
Facility Type: Existing System New	v ☐ Expansion ☐ Repair
	The state of the s
Basement? Yes No Basement Fixtures? Yes	⊠ No
Type of Wastewater System**	(Initial) Wastewater Flow: 720 GPD
(See note below, if applicable)	
	(Repair)
	enches 5
Septic Tank Size 1500 gallons Exact length	of each trench 120feet Trench Spacing: Feet on Center
Pump Tank Sizegallons Trenches shall	be installed on contour at a Soil Cover: 6inches
Maximum Trei	nch Depth of: 18-22 inches (Maximum soil cover shall not exceed
	ns shall be level to +/-1/4" 36" above the trench bottom)
The state of the s	500 VOCESSE STATE CHARGE AND SEE SEE SEE SEE SEE SEE SEE SEE SEE SE
in all direction	ns)
in all direction	
Pump Requirements:ft. TDH vsGPM	inches below pipe
Pump Requirements:ft. TDH vsGPM	inches below pipe
Pump Requirements:ft. TDH vsGPM	inches below pipe
Pump Requirements:ft. TDH vsGPM Conditions:ft. TDH vsGPM Drain line Will be required To	Aggregate Depth: inches below pipe Aggregate Depth: inches above pipe inches total Divert Conternal Ground Water Away From System
Pump Requirements:ft. TDH vsGPM Conditions:ft. TDH vsGPM Drain line will be required To WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM	Aggregate Depth: inches below pipe Aggregate Depth: inches above pipe inches total Divert Cotteral Ground Water Away From System ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.
Pump Requirements:ft. TDH vsGPM Conditions:ft. TDH vsGPM Drain line Will be required To	Aggregate Depth: inches below pipe Aggregate Depth: inches above pipe inches total Divert Cotteral Ground Water Away From System ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.
Pump Requirements:ft. TDH vsGPM Conditions:ft. TDH vsGPM Drain Line Will be required To WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD A	Aggregate Depth: inches below pipe Aggregate Depth: inches above pipe inches total Divert Cotteral Ground Water Away From System ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.
Pump Requirements:ft. TDH vsGPM Conditions:ft. TDH vsGPM Conditions:	Aggregate Depth:inches below pipe inches above pipe inches above pipe inches total Divert Cotteral Ground Water Away From System I ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. REA. The type specified on the application. I accept the specifications of this permit.
Pump Requirements:ft. TDH vsGPM Conditions:	Aggregate Depth:inches below pipe inches above pipe inches above pipe inches total Divert Conternal Ground Woter Away from System ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. REA. The type specified on the application. I accept the specifications of this permit. Date:
Pump Requirements:	Aggregate Depth:
Pump Requirements:	Aggregate Depth:
Pump Requirements:	Aggregate Depth:
Conditions:	Aggregate Depth:

Harnett County Department of Public Health Site Sketch

Property Location: 15 Tranquil (n Issued To: Ramon AT kins	Subdivision	Lot #
Authorized State Agent: Mah M	-REHS	Date: 2-16-23
	* 1 36" De	ep Curtain Drain will be requi
		ance of 16' Above the New
7	Drain Line	
	A The Area	of the Drain Field Will need and Off For Animal Traffic a
	To be block Vehicle Tr	affic
	Tentos.	
(&		
(0.		
		i
		1605
		Barn
	116	Existing 6Br Hame
	120. — \$5. —	11/15
a	120'	
	+15' 120'	
	CUTTOIA DI	1
		Gare Al