	Page _1_ of
PROPERTY ID #:	
COUNTY:	Harrott

SOIL/SITE EVALUATION for ON-SITE WASTEWATER SYSTEM

OWNE ADDR	ER: Bol	by J	517502	(Complete all			DAT	E EVALU	ATED: <u>/- </u>	20-24
PROPO	OSED FACILITY TION OF SITE:	: 55 45	SFD PR Hectors C	OPOSED DESIGN	FLOW (.0400): レ・ルニ・2フ	360 896	PROPE	ERTY SIZI ERTY REC	ORDED:	
	R SUPPLY: <	-	gle Family Well er Boring Pit		Spring Oth		WATEI	R SUPPLY	SETBACK: Strength	10+50 IPWW Web
P R O F			SOIL MO	RPHOLOGY	OTHER PROFILE FACTORS					
L E #	.0502 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	.0503 STRUCTURE/ TEXTURE	.0503 CONSISTENCE/ MINERALOGY	.0504 SOIL WETNESS/ COLOR	.0505 SOIL DEPTH	.0506 SAPRO CLASS	.0507 RESTR HORIZ	.0509 PROFILE CLASS & LTAR*	.0503 SLOPE CORRE CTION
		0-8	5L-5CL	MERNSNP					BPJ	
1	3.406	8-21	SIM	Fre Sole S.P.	20"	24"+		_	,3	
34	576				_					
					-					
2										
3					-					
3					_					
4					-			×		
<u></u>				A STATE OF THE ASSESSMENT OF T					-	
	ESCRIPTION le Space (.0508)	INITIAL SYS	STEM REPAIR S		SSIFICATION (	.0509): [1	-75-			
System Site LT.	Type(s) AR		6w	EVALUAT OTHER(S)	SSIFICATION ( TED BY: PRESENT:	Jnja	DT   P	·L		
	ım Tranch Danth	+	6"							

Meet in SITG Prior to INSTAY

Comments:

## **LEGEND**

LANDSCAPE POSITION	SOIL GROUP	SOIL TEXTURE	CONVENTIONAL LTAR (gpd/ft²)	CONTRACT.	PROLITE R (gpd/ft²)	LPP LTAR (gpd/ft²)	MINERALOGY/ CONSISTENCE		STRUCTURE
CC (Concave slope)		S (Sand)		C	0.6 - 0.8		MOIST	WET	SG (Single grain)
CV (Convex Slope)	1	LS (Loamy sand)	0.8 - 1.2	0.5 -0.7		0.4 -0.6	Lo (Loose)	NS (Non-sticky)	M (Massive)
D (Drainage way)	. 11	SL (Sandy loam)	0.6 - 0.8	(	0.4 -0.6	0.3 - 0.4	VFR (Very friable)	SS (Slightly sticky)	GR (Granular)
FP (Flood plain)		L (Loam)		C	0.2 - 0.4		FR (Friable)	S (Sticky)	SBK (Subangular blocky)
FS (Foot slope)		SiL (Silt loam)	0.3 - 0.6	C	0.1 - 0.3	0.15 - 0.3	FI (Firm)	VS (Very sticky)	ABK (Angular blocky)
H (Head slope)		SCL (Sandy clay loam)		0.0	5 - 0.15**		VFI (Very firm)	NP (Non-plastic)	PR (Prismatic)
L (Linear Slope)	III	CL (Clay loam)			None		EFI (Extremely firm)	SP (Slightly plastic)	PL (Platy)
N (Nose slope)		SiCL (Silty clay loam)						P (Plastic)	
R (Ridge/summit)		Si (Silt)						VP (Very plastic)	
S (Shoulder slope)	SC (Sandy clay)				SEXP (Slightly expansive)				
T (Terrace)	IV	IV SiC (Silty clay)	0.1 - 0.4			0.05 - 0.2	EXP (Expansive)		
TS (Toe Slope)	C (Clay)								
	•	O (Organic)	None						

<sup>\*</sup> Adjust LTAR due to depth, consistence, structure, soil wetness, landscape, position, wastewater flow and quality.

HORIZON DEPTH In inches below natural soil surface DEPTH OF FILL

In inches from land surface

RESTRICTIVE HORIZON Thickness and depth from land surface

SAPROLITE S(suitable) or U(unsuitable); Evaluation of saprolite shall be by pits.

Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation SOIL WETNESS

S (Suitable) or U (Unsuitable) CLASSIFICATION

Show profile locations and other site features (dimensions, reference or benchmark, and North). 6 (4) 0 0

<sup>\*\*</sup>Sandy clay loam saprolite can only be used with advanced pretreatment in accordance with 15A NCAC 18E .1200.

