DEPARTMENT OF HEALTH AND HUMAN SERVICES DIVISION OF PUBLIC HEALTH, ENVIRONMENTAL HEALTH SECTION ON-SITE WATER PROTECTION BRANCH

SOIL/SITE EVALUATION for ON-SITE WASTEWATER SYSTEM

ROP	ER: Joseph ESS: 330 DSED FACILITY TION OF SITE:	: SFD	PR	OPOSED DESIGN I	FLOW (.0400):	360	PROPE	ERTY SIZI ERTY REC	E: ORDED:	
				☐ Shared Well ☐ ☐ Cut TY					SETBACK:_Strength	
P R O F I L E	.0502 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	SOIL MO	RPHOLOGY	отны	R PROFII	LE FACTORS			
			.0503 STRUCTURE/ TEXTURE	.0503 CONSISTENCE/ MINERALOGY	.0504 SOIL WETNESS/ COLOR	.0505 SOIL DEPTH	.0506 SAPRO CLASS	.0507 RESTR HORIZ	.0509 PROFILE CLASS & LTAR*	.0503 SLOPE CORRE CTION
1	2.3% LS	0.7 7-34 34-48	SCLISOK CL, SMSBK	FI,55,5p,5E	7.57R 7/1=34"	48"			. 3	
2, 3	1-1%		56, 50 K 66, 58 K 66, 58 K	EJ, 55, 89, 5E	7.5y L 7/1:30"	48"			. 7	
3										
4										
Availab System Site LT	ım Trench Depth	INITIAL SYS		SITE CLAS EVALUAT OTHER(S)	SSIFICATION (. ED BY: A U PRESENT:	.0509):	5			

LEGEND

LANDSCAPE POSITION	SOIL GROUP	SOIL TEXTURE	CONVENTIONAL LTAR (gpd/ft²)	SAPROLITE LTAR (gpd/ft²)	LPP LTAR (gpd/ft²)	MINERALOGY/ CONSISTENCE		STRUCTURE
CC (Concave slope)		S (Sand)		0.6 - 0.8		MOIST	WET	SG (Single grain)
CV (Convex Slope)		LS (Loamy sand)	0.8 - 1.2	0.5 -0.7	0.4 -0.6	Lo (Loose)	NS (Non-sticky)	M (Massive)
D (Drainage way)	. 11	SL (Sandy loam)	0.6 - 0.8	0.4 -0.6	0.3 - 0.4	VFR (Very friable)	SS (Slightly sticky)	GR (Granular)
FP (Flood plain)		L (Loam)		0.2 - 0.4		FR (Friable)	S (Sticky)	SBK (Subangular blocky)
FS (Foot slope)		SiL (Silt loam)	0.3 - 0.6	0.1 - 0.3	0.15 - 0.3	FI (Firm)	VS (Very sticky)	ABK (Angular blocky)
H (Head slope)		SCL (Sandy clay loam)		0.05 - 0.15**		VFI (Very firm)	NP (Non-plastic)	PR (Prismatic)
L (Linear Slope)	III	CL (Clay loam)		None		EFI (Extremely firm)	SP (Slightly plastic)	PL (Platy)
N (Nose slope)		SiCL (Silty clay loam)					P (Plastic)	
R (Ridge/summit)		Si (Silt)					VP (Very plastic)	
S (Shoulder slope)	IV	SC (Sandy clay)	0.1 - 0.4		0.05 - 0.2	SEXP (Slightly expansive)		
T (Terrace)		SiC (Silty clay)				EXP (Expansive)		
TS (Toe Slope)		C (Clay)						-
	10	O (Organic)	None					

HORIZON DEPTH

In inches below natural soil surface In inches from land surface

DEPTH OF FILL RESTRICTIVE HORIZON

Thickness and depth from land surface

SAPROLITE SOIL WETNESS S(suitable) or U(unsuitable); Evaluation of saprolite shall be by pits.

CLASSIFICATION

Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation S (Suitable) or U (Unsuitable)

Show profile locations and other site features (dimensions, reference or benchmark, and North). way of the state o 0 Tank EX. SCD wen Warren Rd

^{*} Adjust LTAR due to depth, consistence, structure, soil wetness, landscape, position, wastewater flow and quality.

**Sandy clay loam saprolite can only be used with advanced pretreatment in accordance with 15A NCAC 18E .1200.