

DIVISION 16 - ELECTRICAL

PART 1 - GENERAL

- 1.1 DESCRIPTION OF THE WORK
- Work under this section includes, but is not necessarily limited to, furnishing and installing the following:
 - Electrical service and service equipment.
 - Lighting and power distribution system.
 - Provide lighting fixtures selected by owner with lamps to match.
 - Wiring devices, boxes, cover plates, etc.
 - Source of power for all items of equipment.
 - Grounding.
 - Other requirements and/or systems where shown.
 - All work shall be complete and items, equipment, etc., shall be electrically connected for proper and correct operation.
 - All work under this contract shall be installed in accordance with the latest edition of the following codes and standards insofar as they apply:
 - The 2017 National Electrical Code.
 - The National Electrical Safety Code.
 - Underwriter's Laboratories, Inc., Standards and approved listings.
 - Electrical Testing Laboratories standards.
 - North Carolina Building Code, Latest Edition and Revisions.
 - All local codes and ordinances.
 - The Electrical Contractor shall be licensed in the State of North Carolina and have all local licenses required for the work.
 - Obtain all permits, licenses, inspections, etc., required for the work and pay for the same. Furnish final certificate of inspection and approval from the electrical Inspector having jurisdiction prior to acceptance of the work.
 - All work shall be done by skilled mechanics and shall present a neat, trim, workmanlike condition when complete.
- 1.2 INTENT
- The intent of these specifications and the accompanying drawings is to convey as reasonably as possible the requirements for a complete job ready for the building to operate. The Electrical Contractor shall take this into consideration and include in his base bid allowance for contingencies as will allow him to provide minor pieces of equipment and labor not specifically indicated but required for the job to operate properly, at no additional cost to the Owner.
- 1.3 COORDINATION
- Coordinate work with other contractors. Notify Architect of apparent conflicts early to expedite construction. If structural damage appears imminent, stop work and notify Architect for a decision before resuming operations.
 - Locations shown are approximate. The drawings do not give exact details as to elevations and locations of various pipes, fittings, ducts, conduit, etc., and do not show all offsets and other installation details which may be required. Coordinate all locations with architect before any rough-in.
- 1.4 SHOP DRAWINGS
- Shop drawings shall be submitted for panels and service equipment, lighting, wiring devices, and cover plates. These may consist of the manufacturer's standard catalog or test sheets and shall have the exact items being offered clearly identified.

PART 2 - PRODUCTS AND MATERIALS

2.1 GENERAL

- All material shall be new and shall bear the manufacturer's name, trade name, and UL label where such standard has been established for the particular material. Materials shall be the standard products of manufacturer's regularly engaged in the manufacturer of the required type of equipment and the manufacturer's latest approved design.
 - Boxes installed in concealed locations shall be set flush with the finished surfaces.
 - Provide rated boxes in all fire barriers & walls installed per code.
- NOT USED
- CONDUCTORS
 - Conductors shall be color coded, sizes #8 and larger may be color taped on the job. Color coding shall be: Standard Practices.
 - Conductors shall be manufactured by Dodge, Southwire or approved equal. Conductors shall meet the latest requirements of NEMA and IPCEA and shall be UL approved.
 - Metallic sheathed "MC" cable may be used where allowed by N.E.C.
 - Conductors shall be spliced and taped as follows:
 - Size #10 and #12, use ideal "Wing Nuts" or TAB "Piggy" connectors. Connectors shall be rated for 150 degrees C for use in recessed lighting fixtures.
 - Size #8 and larger shall be solderless screw and screw-clamping type, smoothly covered and shaped with rubber gum type with final cover vinyl plastic electrical type. In lieu of rubber gum and vinyl plastic type, factory fabricated approved preformed insulating covers may be used. All connectors shall be UL approved.
 - No split-bolt type connectors may be used.
 - All branch wire and connections shall be copper and sized per National Electric Code.
 - All conductors shall be continuous without splice between junction, outlet, device boxes, etc. No splicing will be permitted in panelboard cabinets, safety switches, etc.
 - All wiring in mechanical spaces shall be plenum rated.
 - Provide GFI protection within 6'-0" of any sink.
 - All multi-wire branch circuits shall comply with 2017 NEC, 210.4(B).
 - All wiring at medical facilities shall comply with 2017 NEC, 517.1.

2.4 PANELBOARDS, SAFETY SWITCHES

- Panelboards shall comply with NEMA Standard PB 1 - Latest Edition and as manufactured by Siemens D or IT-Clements.
- The contractor shall be responsible for correctly phasing the circuits in the panelboards.
- Safety switches shall be general duty type, size and rating as required for load service. Safety switches shall be fused or unfused as shown and/or as required. Safety switches serving motor loads shall be horsepower rated for load served.

2.5 NOT USED

2.6 WIRING DEVICES

- Wiring devices shall be commercial grade by Bryant, Leviton, or approved equal. With matching cover. Color by Architect.
- Wiring devices installed under a Kitchen Hood shall have stainless steel covers.
- Wiring devices installed over counters shall comply with ANSI A117.1.

2.7 NOT USED

2.8 CONDUIT

- PVC conduit will be allowed where N.E.C. approved.
- All service conduit shall be rigid where exposed below 8'-0" AFF or exposed to the elements or hazardous conditions.

PART 3 - EXECUTION

3.1 CIRCUIT GROUNDING

- All circuits shall contain an insulated, green, copper grounding conductor, sized in accordance with Table 250-95 of the NEC. Grounding conductors shall be connected to equipment grounding bus in panelboard and securely attached and grounded to the device or enclosure at the other end.

3.2 GROUNDING TYPE CONVENIENCE OUTLETS AND SWITCHES

- Outlets and switches shall be solidly grounded to equipment grounding system with a green colored insulated conductor. Electrical connections shall be continuous from equipment ground bus in panelboard to the hex nut on the convenience outlet or switch.

3.3 MOTORS

- All motors shall be connected to conduit system with short length (minimum length 24" and maximum length 36") of flexible liquidtight conduit.

3.4 NOT USED

3.5 EQUIPMENT LABELING

- Provide permanent name plates for all panelboards, safety switches, wiring troughs, etc., for identification of equipment controlled, services, etc. Nameplates shall be securely and permanently attached to equipment with stainless steel screws. Nameplates shall include the name of the equipment and where it is fed from.
- All switch plates, receptacle plates and outlet covers shall be labeled with machine printed vinyl labels identifying the circuit(s) within.
- All empty conduit runs shall be identified and indicated where they terminate.
- Provide typewritten directory in each panelboard to clearly identify each circuit, service, etc.

3.6 NOT USED

3.7 NOT USED

3.8 JUNCTION AND/OR PULL BOXES

- Boxes shall be installed where necessary to avoid excessive runs and/or too many bends between outlets.

3.9 PULL WIRE

- Leave pull wire in each empty conduit run.

3.10 NOT USED

3.11 GROUNDING

- All grounding shall be in accordance with Article 250 of the NEC. In addition, the following requirements shall be met:
 - Grounding conductors shall be installed as to permit the shortest and most direct path from equipment to ground. All connections to grounding conductors shall be accessible.
 - Equipment ground continuity shall be maintained through flexible metal conduit.
 - All wiring devices equipped with grounding connection shall be solidly grounded to ground system with grounding conductors.
 - The frame of all lighting fixtures shall be securely grounded to the equipment ground system with grounding conductors.
 - All equipment enclosures, and non-current-carrying metallic parts of electrical equipment, raceway systems, etc., shall be effectively and adequately bonded to ground.
 - All equipment enclosures, and non-current-carrying metallic parts of electrical equipment, raceway systems, etc., shall be effectively and adequately bonded to ground.

3.12 ELECTRICAL WORK IN CONNECTION WITH OTHER WORK


- PLUMBING WORK: The Electrical Contractor shall furnish and install switches and devices as shown and electrically connect electric water heaters, etc. All other electrical work required will be performed by the PLUMBING CONTRACTOR.
- HEATING AND AIR CONDITIONING WORK: The Electrical Contractor shall provide all disconnect switches, starters, and associated hardware for the equipment furnished including all line and load side wiring and conduit. Final connections to the equipment will be by the HVAC contractor. All control wiring will be accomplished by the HVAC contractor. Coordinate all work associated with the HVAC contractor.

3.13 CLEAN UP

- During construction, keep the site clean of debris. Upon completion, and before final inspection, clean up the premises to remove all evidence of work. In addition upon completion of construction leave equipment clean.

3.14 GUARANTEE

- Guarantee all materials and labor included in the electrical work for a period of one year from date of final acceptance by the Owner. Any part or parts of the work or equipment which prove to be defective during the guarantee period shall be replaced at no additional cost to the Owner.



ELECTRICAL EQUIPMENT WORKING CLEARANCE PER ARTICLE 110-26 OF N.E.C.

WORKING CLEARANCES			
VOLTAGE TO GROUND NOMINAL	MIN. CLEAR DISTANCE IN FEET		
CONDITION:	1	2	3
0-150	3	3	3
151-600	3	3-1/2	4

1 ELECTRICAL CLEARANCES
SCALE: NTS

GENERAL NOTES

- ALL ELECTRICAL WORK SHALL BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE AND ALL LOCAL CODES HAVING JURISDICTION.
- ALL BRANCH CIRCUIT CONDUCTORS TO BE COPPER (SERVICE CONDUCTORS MAY BE ALUMINUM WITH SAME AMPACITY AS COPPER CONDUCTORS. RE-SIZE CONDUCTORS AND CONDUIT PER NEC.)
- ALL CIRCUITS TO BE 2 #12, 1 #12 GND IN 1/2" EMT CONDUIT AS A MINIMUM. PROVIDE WIRING FOR LARGER CIRCUITS AS REQUIRED BY NEC. RIGID CONDUIT IS REQUIRED WHERE EXPOSED BELOW 8'-0" A.F.F.
- ALL EMPTY CONDUIT RUNS IN EXCESS OF 10 FEET SHALL BE PROVIDED WITH A PULL WIRE OR FISH TAPE/CORD.
- CONTRACTOR SHALL VERIFY THAT ALL DOOR SWINGS ARE CORRECT BEFORE INSTALLING LIGHT SWITCH OUTLETS.
- ALL BRANCH CIRCUIT CONDUCTORS FROM THE PANEL TO THE FIRST OUTLET SHALL BE INCREASED TO THE NEXT LARGER SIZE WHERE THE LENGTH OF THE HOME RUN EXCEEDS 120 FEET ON 120V AND 208V CIRCUITS.
- THE CORRECT NUMBER OF WIRES MAY NOT BE INDICATED FOR ALL CIRCUITS, ONLY THOSE WHERE CLARIFICATION IS NECESSARY. THE ELECTRICAL CONTRACTOR SHALL PROVIDE ALL WIRES NECESSARY FOR THE PROPER FUNCTION OF THE SYSTEM WHETHER INDICATED ON DRAWINGS OR NOT.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR CORRECTLY PHASING THE CIRCUITS IN THE PANELBOARDS.
- THE ELECTRICAL CONTRACTOR SHALL VERIFY THE TYPE OF CEILING SYSTEM WITH THE GENERAL CONTRACTOR TO INSURE THAT ALL LIGHTING FIXTURES ARE COMPATIBLE WITH THE CEILING SYSTEM BEING INSTALLED. LIGHTING FIXTURES SHOULD NOT BE ORDERED UNTIL TYPE OF CEILING HAS BEEN VERIFIED.
- ELECTRICAL REQUIREMENTS INDICATED ON DRAWINGS MAY DIFFER FROM ACTUAL EQUIPMENT FURNISHED. IF FURNISHED EQUIPMENT DIFFERS FROM RATINGS ON DRAWINGS CONTRACTOR SHALL NOTIFY ARCHITECT/ENGINEER FOR APPROPRIATE ACTION TO BE TAKEN.
- IT SHALL BE THE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR TO COORDINATE EXACT BREAKER REQUIREMENTS FOR ALL EQUIPMENT PRIOR TO ORDERING PANEL. ADJUST BREAKER AND WIRE SIZES AS REQUIRED.
- PROVIDE BOXES, JACKS, WIRING AND CONDUIT FROM LOCATIONS SHOWN TO MTP LOCATION. VERIFY EXACT REQUIREMENTS WITH OWNER.
- ELECTRICAL CONTRACTOR SHALL PROVIDE ALL DISCONNECTS FOR MECHANICAL & PLUMBING EQUIPMENT. DISCONNECTS SHALL BE PER MANUFACTURERS RECOMMENDATIONS AND FUSED PER NAME PLATE. PROVIDE NEMA 3R ENCLOSURES ON EXTERIOR. COORDINATE FUSE SIZES.
- THE EC SHALL MEET WITH THE ARCHITECT AND TENANT PRIOR TO INSTALLING OUTLET BOXES TO VERIFY LOCATIONS AND MOUNTING HEIGHTS OF RECEPTACLES AND TELEPHONE OUTLETS.

APPENDIX B

2018 BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS

ELECTRICAL DESIGN
(PROVIDE ON THE ELECTRICAL SHEETS IF APPLICABLE)
ELECTRICAL SUMMARY

ELECTRICAL SYSTEM AND EQUIPMENT

Method of Compliance

- Energy Code: Prescriptive Energy Cost Budget
- ASHRAE 90.1: Prescriptive Energy Cost Budget

Lighting Schedule

lamp type required in fixture
number of lamps in fixture
ballast type used in fixture
number of ballasts in fixture
total wattage in fixture
total interior wattage specified vs. allowed
total exterior wattage specified vs. allowed

See Light Fixture Schedule

1158VA / 1616VA
40VA / 750VA

Additional Prescriptive Compliance

- 506.2.1 More Efficient Mechanical Equipment
- 506.2.2 Reduced Lighting Power Density
- 506.2.3 Energy Recovery Ventilation Systems
- 506.2.4 Higher Efficiency Service Water Heater
- 506.2.5 On-Site Supply of Renewable Energy
- 506.2.6 automatic Daylighting Control System


THIS FIGURE ILLUSTRATES THE WORKING SPACE IN FRONT OF THE ELECTRICAL EQUIPMENT REQUIRED BY SECTION 110-26 OF THE N.E.C.

WHERE THE CONDITIONS ARE AS FOLLOWS:

- EXPOSED LIVE PARTS ON ONE SIDE AND NO LIVE OR GROUNDED PARTS ON THE OTHER SIDE OF THE WORKING SPACE, OR EXPOSED LIVE PARTS ON BOTH SIDES EFFECTIVELY GUARDED BY SUITABLE WOOD OR INSULATED BUSBARS OPERATING AT NOT OVER 300V SHALL NOT BE CONSIDERED LIVE PARTS.
- EXPOSED LIVE PARTS ON ONE SIDE AND GROUNDED PARTS ON THE OTHER SIDE.
- EXPOSED LIVE PARTS ON BOTH SIDES OF THE WORK SPACE (NOT GUARDED AS PROVIDED IN CONDITION 1) WITH THE OPERATOR BETWEEN.


ELECTRICAL LEGEND

- LIGHT FIXTURE: LETTER DENOTES FIXTURE TYPE (REFER TO LIGHTING PLAN AND FIXTURE SCHEDULE). NL = NIGHT LIGHT (NOT SWITCHED/ALWAYS ON)
- DUPLEX RECEPTACLE - 120V; MOUNT 18" TO CENTER AFF UNLESS NOTED OTHERWISE; 'WP' INDICATES WEATHER PROOF, 'GFI' INDICATES GROUND FAULT CURRENT INTERRUPT PROTECTED. 'U' INDICATES RECEPTACLE WITH (2) USB PORTS. (S) INDICATES SHUNT TRIP BREAKER, OR WIRING THROUGH RELAYS IN HOOD CONTROL CABINET
- QUADRUPLEX RECEPTACLE - 120V
- FLOOR OR CEILING OUTLET (AS NOTED) - 120V
- SPECIAL PURPOSE RECEPTACLE - REFER TO POWER PLAN AND PANEL SCHEDULE
- LIGHT SWITCH
- SWITCH WITH INTEGRAL PIR/US MOTION SENSOR FOR AUTOMATIC SHUT-OFF WITH UP TO 2 HOUR ADJUSTABLE DELAY.
- DIMMABLE LIGHT SWITCH
- MOTOR RATED SWITCH
- JUNCTION BOX
- TELE/DATA OUTLET - PROVIDE JUNCTION BOX WITH CONDUIT BACK TO MTP. PROVIDE (1) TELEPHONE JACK AND (1) CAT 5 DATA JACK
- SINGLE-POLE HOMERUN TO PANELBOARD
- TWO-POLE OR 3-POLE HOMERUN TO PANELBOARD
- EXIT LIGHT
- EMERGENCY EGRESS FIXTURE
- PHOTOCCELL
- BRANCH CIRCUIT WIRING
- SWITCH LEG
- GROUND CONNECTION
- DISTRIBUTION PANELBOARD
- DISCONNECTING MEANS AS REQUIRED BY CODE




ELECTRICAL EQUIPMENT DEDICATED SPACE PER ARTICLE 110.26.F.1 OF N.E.C.

2 DEDICATED SPACE
SCALE: NTS



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com

ENGINEER
BLUFKE DESIGN GROUP, PA
CONSULTING ENGINEERS
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.771.1916 fax: 919.779.0826
email: benburke@nc.rr.com
Corp. License # C-2652



PROJECT TITLE
MI CUNCUN

115 S. RALEIGH ST.
ANGIER, NORTH CAROLINA



PROJECT NO.
2006r
DRAWING TITLE
ELECTRICAL SPECIFICATIONS

PLOT DATE 12/30/2020


This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA, 2020

NOTE:
 THE EXISTING INFORMATION SHOWN ON THIS DRAWING IS FROM A FIELD INVESTIGATION.
 THE CONTRACTOR IS RESPONSIBLE FOR VISITING THE SITE AND FIELD VERIFYING ALL RELEVANT INFORMATION.
 THE SUBMISSION OF A BID INDICATES ACCEPTANCE OF EXISTING CONDITIONS. NOTIFY THE ENGINEER
 OF ANY DISCREPANCIES NOTED.


MI Cancun Angier E2
WALL LEGEND

	EXISTING WALL TO REMAIN
	EXISTING WALL TO BE REMOVED

THE SCOPE OF DEMOLITION IS AS FOLLOWS--
 REMOVE ALL LIGHTING AND CIRCUITS BACK TO THE PANEL UNLESS OTHERWISE NOTED.
 REMOVE ALL DEMOTED LIGHT FIXTURES AND PROPERLY DISPOSE OF ALL FIXTURES, BALLASTS, ETC.
 REMOVE ALL DEVICES AND CIRCUITS BACK TO THE PANEL UNLESS OTHERWISE NOTED.
 REMOVE ALL WIRING AND CONDUITS BACK TO CONCEALED JUNCTION POINT.




1 DEMO LIGHTING PLAN
 SCALE: 1/4" = 1'-0"



W. S. ARCHITECTS, PA
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.779.9797
 www.wsarchitectspa.com

ENGINEER
BURKE DESIGN GROUP, PA
 CONSULTING ENGINEERS
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.771.1918 fax: 919.779.0828
 email: benburke@nc.rr.com
 Corp. License # C-2652




PROJECT TITLE
MI CUNCUN

115 S. RALEIGH ST.
 ANGIER, NORTH CAROLINA

PROJECT NO.
2006r


DRAWING TITLE
DEMO LIGHTING PLAN



PLOT DATE 12/30/2020


This original sheet is 24" x 36", other dimensions indicate it has been altered.
 All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020

NOTE:
 THE EXISTING INFORMATION SHOWN ON THIS DRAWING IS FROM A FIELD INVESTIGATION.
 THE CONTRACTOR IS RESPONSIBLE FOR VISITING THE SITE AND FIELD VERIFYING ALL RELEVANT INFORMATION.
 THE SUBMISSION OF A BID INDICATES ACCEPTANCE OF EXISTING CONDITIONS. NOTIFY THE ENGINEER
 OF ANY DISCREPANCIES NOTED.



W. S. ARCHITECTS, PA
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.779.9797
 www.wsarchitectspa.com

ENGINEER
BURKE DESIGN GROUP, PA
 CONSULTING ENGINEERS
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.771.1916 fax: 919.779.0826
 email: benburke@ncr.com
 Corp. License # C-2652



LIGHTING SCHEDULE *									
MARK	MANUFACTURER	CATALOG NO.	VOLT.	LAMPS NO.	LAMPS TYPE	BALLAST W	W/FIXTURE	REMARKS	
A	COLUMBIA	LJT24-40VLSM-FSA12-EU	120	-	LED	-	60	LED 2X4 SURFACE-MOUNT FIXTURE, FOOD GRADE LENS	*
C	PRESCOUTE	LF8LED64-6LFLED6439K	120	-	LED	-	20	LED 6" RECESSED CAN LIGHT	*
E	COMPASS	CIJSD	120	-	LED	-	10	EMERGENCY EGRESS FIXTURE - DUAL MODE, NORMAL AND EMERGENCY OPERATION	*
F	HUBBELL	VTC-SK-G-U	120	-	LED	-	28	LED VAPOR TIGHT, COOLER	*
G	COLUMBIA	LXEM4-35ML-RFA-EDU	120	-	LED	-	42	ENCLOSED GASKETED LED STRIP LIGHT	*
U	ASPECT LED	AL-SL-NR-U	120	-	LED	-	3W/FT	LED FLEX STRIP LIGHTING, COLOR/FINISH BY ARCH	*
W	ECLIPSE	BU-D-4-4K-EBU	120	-	LED	-	40	LED WALL-MOUNT DIRECT LIGHT FIXTURE, FOOD GRADE LENS	COLOR/FINISH BY ARCH *
EXIT	MULE	PVT-U-B-R-U-SD	120	-	LED	-	-	EXIT LIGHT, COLOR/FINISH BY ARCH	*
EXIT	MULE	SQRXU	120	-	LED	-	-	COMBINATION EMERGENCY/EXIT LIGHT, COLOR/FINISH BY ARCH	*
EXIT	MULE	SQLED	120	-	LED	-	-	EMERGENCY LIGHT, COLOR/FINISH BY ARCH	*

* OR APPROVED EQUAL. PROVIDE CUT SHEETS FOR OWNER APPROVAL PRIOR TO ORDERING FIXTURES.

HEALTH DEPARTMENT LIGHTING NOTES

PRIOR TO INSPECTION, EC SHALL VERIFY THAT THE FOLLOWING MINIMUM LIGHT LEVELS ARE PROVIDED:

10 fc AT A DISTANCE OF 2'-6" ABOVE THE FLOOR IN DRY STORAGE AREAS AND IN OTHER AREAS AND ROOMS DURING CLEAN-UP.

20 fc AT SELF-SERVICE COUNTERS SUCH AS BUFFETS AND SALAD BARS, WHERE FRESH PRODUCE OR PACKAGED FOOD IS SOLD OR OFFERED FOR CONSUMPTION, INSIDE EQUIPMENT SUCH AS REACH-IN AND UNDER-COUNTER REFRIGERATORS, AND AT A DISTANCE OF 2'-6" ABOVE THE FLOOR IN AREAS USED FOR HANDWASHING, WAREWASHING, EQUIPMENT AND UTENSIL STORAGE, AND IN TOILET ROOMS.


50 fc AT FOOD PREPARATION SURFACES AND SURFACES WHERE EMPLOYEE SAFETY IS A FACTOR SUCH WHERE USING KNIVES, SLICERS, GRINDERS, OR SAWS, ETC.

EC SHALL ADJUST LIGHTING AS REQUIRED TO PROVIDE THE NECESSARY MINIMUM LIGHT LEVELS.

THE LIGHTING IN THE KITCHEN AND PREP AREAS ARE DESIGNED AROUND HEALTH DEPARTMENT REQUIREMENTS FOR MINIMUM LIGHT LEVELS. PER SECTION 101.3 OF THE 2012 NC ENERGY CODE, THESE SPACES ARE EXEMPT FROM MEETING THE REQUIRED INTERIOR ENERGY ALLOWANCE PER TABLE 505.5.2.

EC SHALL VERIFY THAT 50fc IS PROVIDED AT ALL EQUIP UNDER THE HOOD PRIOR TO HEALTH DEPT INSPECTION. PROVIDE NEW OR SHIT FIXTURE LOCATIONS AS NECESSARY.

PROVIDE JUNCTION BOXES FOR WALK-IN COOLER LIGHTS. COORDINATE LOCATION AND REQUIREMENTS.
 MINIMUM 10fc SHALL BE MAINTAINED IN WALK-IN COOLER. EC SHALL PROVIDE SUPPLEMENTAL FIXTURES IF FREEZER/COOLER GLOBES ARE NOT ADEQUATE.
 PROVIDE CONDUIT SEALS FOR ALL LOCATIONS WHERE CONDUITS PENETRATE WALK-IN COOLER WALLS.



1 LIGHTING PLAN
 SCALE: 1/4" = 1'-0"

NOTE:
 PROVIDE LABELING ON EACH SWITCH NOTING CIRCUIT SERVED.
 AUTOMATIC LIGHTING SHUTOFF IS NOT SHOWN IN THE EGRESS PATH LIGHTING AS ALLOWED PER 505.2.2.1 EXCEPTION #3, WHERE AUTOMATIC SHUTOFF WOULD ENDANGER OCCUPANT SAFETY.
 Tie ALL EXIT AND EMERGENCY LIGHTS TO NEAREST AVAILABLE UNSWITCHED LIGHTING CIRCUIT IN THE AREA SERVED.
 VERIFY HEIGHT/LOCATION OF ALL SWITCHES AND DEVICES PRIOR TO INSTALLATION.

PROJECT TITLE
MI CANCUN

115 S. RALEIGH ST.
 ANGLIER, NORTH CAROLINA

PROJECT NO.
2006r

DRAWING TITLE
LIGHTING PLAN



E3

PLOT DATE 12/31/2020


This original sheet is 24" x 36"; other dimensions indicate it has been altered.
 All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020

NOTE:
 THE EXISTING INFORMATION SHOWN ON THIS DRAWING IS FROM A FIELD INVESTIGATION.
 THE CONTRACTOR IS RESPONSIBLE FOR VISITING THE SITE AND FIELD VERIFYING ALL RELEVANT INFORMATION.
 THE SUBMISSION OF A BID INDICATES ACCEPTANCE OF EXISTING CONDITIONS. NOTIFY THE ENGINEER
 OF ANY DISCREPANCIES NOTED.


MI Cancun Angier E4
WALL LEGEND

	EXISTING WALL TO REMAIN
	EXISTING WALL TO BE REMOVED

THE SCOPE OF DEMOLITION IS AS FOLLOWS--
 REMOVE ALL DEVICES AND CIRCUITS BACK TO THE PANEL UNLESS OTHERWISE NOTED.
 REMOVE ALL WRING AND CONDUITS BACK TO CONCEALED JUNCTION POINT.




1 DEMO POWER PLAN
 SCALE: 1/4" = 1'-0"



W. S. ARCHITECTS, PA
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.779.8797
 www.wsarchitectspa.com

ENGINEER
BURKE DESIGN GROUP, PA
 CONSULTING ENGINEERS
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.771.1916 fax: 919.779.0826
 email: benburke@nc.rr.com
 Corp. License # C-2652



PROJECT TITLE
MI CUNCUN

115 S. RALEIGH ST.
 ANGIER, NORTH CAROLINA

PROJECT NO.
2006r

DRAWING TITLE
DEMO POWER PLAN

E4

PLOT DATE 12/30/2020

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
 All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020

NOTE:
THE EXISTING INFORMATION SHOWN ON THIS DRAWING IS FROM A FIELD INVESTIGATION.
THE CONTRACTOR IS RESPONSIBLE FOR VISITING THE SITE AND FIELD VERIFYING ALL RELEVANT INFORMATION.
THE SUBMISSION OF A BID INDICATES ACCEPTANCE OF EXISTING CONDITIONS. NOTIFY THE ENGINEER
OF ANY DISCREPANCIES NOTED.

Mi Cancun Angier E6 EXISTING PANEL 'A'		MAKE: CUTLER HAMMER	RATING: 120/240 1 PHASE 3 WIRE	M.L.O. MAIN CIRCUIT BREAKER		
		TYPE: VERIFY	MOUNTING: FLUSH	EQUIPMENT GROUND BUS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO		
		MINIMUM AIC: VERIFY		SERVICE ENTRY RATED <input type="checkbox"/> YES <input type="checkbox"/> NO		
LOAD SERVICE	CKT BRKR	WATTS PER PHASE A B	CKT NO NEUTRAL A B	WATTS PER PHASE A B	CKT BRKR	LOAD SERVICE
WALK-IN FREEZER	30A	---	1	2	30A	SPARE
WALK-IN COOLER	20A	---	3	4	20A	HOT BAR
SPARE	30A	---	5	6	20A	REGISTER
LTS	20A	---	7	8	20A	SPARE
HEATER	20A	---	9	10	20A	SPARE
ICE MACHINE	20A	---	11	12	20A	LTS
SPARE	20A	---	13	14	100A	AC-1
SPARE	20A	---	15	16	20A	SPARE
SPARE	20A	---	17	18	20A	SPARE
SPARE	20A	---	19	20	20A	SPARE
SPARE	20A	---	21	22	20A	SPARE
LTS	20A	---	23	24	20A	SPARE
SPARE	20A	---	25	26	20A	SPARE
SPARE	20A	---	27	28	60A	SPARE
SPARE	30A	---	29	30	60A	SPARE
NOTES		SUB-TOTALS 'B'		200A BUS	SUB-TOTALS 'A'	
				200A LUGS	SUB-TOTALS 'B'	
				200A FEED	GRAND TOTAL	
				VERIFY SIZE	AMPS/PHASE	
					TOTAL CONNECTED LOAD	

Mi Cancun Angier E6 EXISTING PANEL 'B'		MAKE: CUTLER HAMMER	RATING: 120/240 1 PHASE 3 WIRE	M.L.O. MAIN CIRCUIT BREAKER		
		TYPE: VERIFY	MOUNTING: FLUSH	EQUIPMENT GROUND BUS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO		
		MINIMUM AIC: VERIFY		SERVICE ENTRY RATED <input type="checkbox"/> YES <input type="checkbox"/> NO		
LOAD SERVICE	CKT BRKR	WATTS PER PHASE A B	CKT NO NEUTRAL A B	WATTS PER PHASE A B	CKT BRKR	LOAD SERVICE
SPARE	20A	---	1	2	20A	HOOD LTS
SPARE	20A	---	3	4	20A	SPARE
REFRIG	20A	---	5	6	20A	SPARE
SPARE	20A	---	7	8	20A	SPARE
OUTSIDE FAN	20A	---	9	10	30A	SPARE
SPARE	20A	---	11	12	30A	SPARE
LTS	20A	---	13	14	30A	SPARE
REC	20A	---	15	16	30A	SPARE
REC	20A	---	17	18	30A	SPARE
LTS	20A	---	19	20	30A	SPARE
REFRIG	20A	---	21	22	50A	AC-2
SPACE	20A	---	23	24	30A	AC-3
SPACE	20A	---	25	26	30A	AC-3
SPACE	20A	---	27	28	30A	AC-3
SPACE	20A	---	29	30	30A	SPACE
NOTES		SUB-TOTALS 'B'		200A BUS	SUB-TOTALS 'A'	
				200A LUGS	SUB-TOTALS 'B'	
				200A FEED	GRAND TOTAL	
				VERIFY SIZE	AMPS/PHASE	
					TOTAL CONNECTED LOAD	


Mi Cancun Angier E6 REVISED PANEL 'A'		MAKE: CUTLER HAMMER	RATING: 120/240 1 PHASE 3 WIRE	M.L.O. MAIN CIRCUIT BREAKER																																																																								
		TYPE: VERIFY	MOUNTING: FLUSH	EQUIPMENT GROUND BUS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO																																																																								
		MINIMUM AIC: VERIFY		SERVICE ENTRY RATED <input type="checkbox"/> YES <input type="checkbox"/> NO																																																																								
LOAD SERVICE	CKT BRKR	WATTS PER PHASE A B	CKT NO NEUTRAL A B	WATTS PER PHASE A B	CKT BRKR	LOAD SERVICE																																																																						
WALK-IN COOLER/FREEZER	20A	1200	1	2	1200	WALK-IN COOLER/FREEZER																																																																						
CIRC PUMP	20A	300	3	4	1200	SPARE																																																																						
SPARE	30A	---	5	6	1200	STEP-IN KEG COOLER																																																																						
SPARE	30A	---	7	8	1200	SPARE																																																																						
LTS DINING HALL	20A	484	9	10	360	REC. POS																																																																						
CHW CNTRLS	20A	300	11	12	720	REC. BARDINING																																																																						
NITRO GENERATOR (63)	20A	600	13	14	720	REC. OFFICE/DINING																																																																						
DRAFT BEER CHILLER (62)	20A	1452	15	16	674	20A LTS: HALLWAY/KITCHEN																																																																						
SPARE	20A	---	17	18	4572	50A RTU-1																																																																						
SPARE	20A	---	19	20	4572	50A RTU-1																																																																						
SPARE	20A	---	21	22	4572	50A RTU-1																																																																						
SPARE	20A	---	23	24	4572	50A RTU-1																																																																						
SPARE	20A	---	25	26	4572	50A RTU-1																																																																						
LTS EXT. COOLER	20A	320	27	28	5520	60A AHU-1																																																																						
HP-1	50A	3312	29	30	5520	60A AHU-1																																																																						
NOTES		SUB-TOTALS 'B'		200A BUS	SUB-TOTALS 'A'																																																																							
				200A LUGS	SUB-TOTALS 'B'																																																																							
				200A FEED	GRAND TOTAL																																																																							
				VERIFY SIZE	AMPS/PHASE																																																																							
					TOTAL CONNECTED LOAD																																																																							
NEC ALLOWABLE DEMAND FACTORS		DIVERSIFIED LOAD SUMMARY																																																																										
① DEMAND FACTORS PER NEC 220 ② LARGEST OF: NEC TABLE 220.12 OR CONNECTED LOAD ③ NEC TABLE 220.56 ④ NEC 220.51 ⑤ NEC 220.43A, 200 VA/LINEAR FT ⑥ NON-COINCIDENT LOADS, LARGEST OF THE TWO LOADS IS COUNTED		<table border="1"> <thead> <tr> <th>LOAD TYPE</th> <th>DEMAND FACTOR</th> <th>A</th> <th>B</th> <th>TOTAL DIVERSIFIED LOAD</th> </tr> </thead> <tbody> <tr><td>GENERAL LIGHTING</td><td>125%</td><td>1243</td><td>805</td><td>1848</td></tr> <tr><td>TRACK LIGHTING</td><td>125%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>GENERAL USE</td><td>100%</td><td>1080</td><td>1440</td><td>2520</td></tr> <tr><td>RECEPTACLES</td><td>100%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>MOTORS AND EQUIPMENT</td><td>LARGEST 125%</td><td>4140</td><td>4140</td><td>8280</td></tr> <tr><td>WATER HEATERS</td><td>ALL OTHERS 100%</td><td>10092</td><td>10092</td><td>20184</td></tr> <tr><td>KITCHEN EQUIPMENT</td><td>65%</td><td>3284</td><td>2730</td><td>6014</td></tr> <tr><td>FIX. ELEC. SPACE HEAT.</td><td>100%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>SHOW WINDOW LIGHTS</td><td>125%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>SIGN</td><td>100%</td><td>1500</td><td>1500</td><td>3000</td></tr> <tr><td>MISC</td><td>100%</td><td>800</td><td>800</td><td>1600</td></tr> <tr><td>PHASE (TOTAL VA)</td><td></td><td>20439</td><td>20507</td><td>40946</td></tr> <tr><td>TOTAL AMPS</td><td></td><td>170A</td><td>171A</td><td>VOLTS = 171A TOTAL AMPS</td></tr> </tbody> </table>					LOAD TYPE	DEMAND FACTOR	A	B	TOTAL DIVERSIFIED LOAD	GENERAL LIGHTING	125%	1243	805	1848	TRACK LIGHTING	125%	---	---	---	GENERAL USE	100%	1080	1440	2520	RECEPTACLES	100%	---	---	---	MOTORS AND EQUIPMENT	LARGEST 125%	4140	4140	8280	WATER HEATERS	ALL OTHERS 100%	10092	10092	20184	KITCHEN EQUIPMENT	65%	3284	2730	6014	FIX. ELEC. SPACE HEAT.	100%	---	---	---	SHOW WINDOW LIGHTS	125%	---	---	---	SIGN	100%	1500	1500	3000	MISC	100%	800	800	1600	PHASE (TOTAL VA)		20439	20507	40946	TOTAL AMPS		170A	171A	VOLTS = 171A TOTAL AMPS
LOAD TYPE	DEMAND FACTOR	A	B	TOTAL DIVERSIFIED LOAD																																																																								
GENERAL LIGHTING	125%	1243	805	1848																																																																								
TRACK LIGHTING	125%	---	---	---																																																																								
GENERAL USE	100%	1080	1440	2520																																																																								
RECEPTACLES	100%	---	---	---																																																																								
MOTORS AND EQUIPMENT	LARGEST 125%	4140	4140	8280																																																																								
WATER HEATERS	ALL OTHERS 100%	10092	10092	20184																																																																								
KITCHEN EQUIPMENT	65%	3284	2730	6014																																																																								
FIX. ELEC. SPACE HEAT.	100%	---	---	---																																																																								
SHOW WINDOW LIGHTS	125%	---	---	---																																																																								
SIGN	100%	1500	1500	3000																																																																								
MISC	100%	800	800	1600																																																																								
PHASE (TOTAL VA)		20439	20507	40946																																																																								
TOTAL AMPS		170A	171A	VOLTS = 171A TOTAL AMPS																																																																								

Mi Cancun Angier E6 REVISED PANEL 'B'		MAKE: CUTLER HAMMER	RATING: 120/240 1 PHASE 3 WIRE	M.L.O. MAIN CIRCUIT BREAKER																																																																								
		TYPE: VERIFY	MOUNTING: FLUSH	EQUIPMENT GROUND BUS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO																																																																								
		MINIMUM AIC: VERIFY		SERVICE ENTRY RATED <input type="checkbox"/> YES <input type="checkbox"/> NO																																																																								
LOAD SERVICE	CKT BRKR	WATTS PER PHASE A B	CKT NO NEUTRAL A B	WATTS PER PHASE A B	CKT BRKR	LOAD SERVICE																																																																						
1-DOOR REFRIG (2)	20A	264	1	2	800	HOOD LTS/CNTRLS																																																																						
MARGARITA MACHINE (4)	20A	1700	3	4	284	1-DOOR LC REFRIG. (28)																																																																						
GLASS FROSTER (8)	20A	192	5	6	1500	CHIP WARMER (27)																																																																						
BACK BAR REFRIG (9)	20A	336	7	8	528	80" REFRIG UNIT (26)																																																																						
BACK BAR REFRIG (9)	20A	336	9	10	2000	HOT HOLDING TABLE (25)																																																																						
SODA DISP. (18)	20A	712	11	12	456	28" REFRIG UNIT (22)																																																																						
LTS: KITCHEN	20A	864	13	14	228	LC FREEZER (38)																																																																						
BAG N BOX (20)	20A	1668	15	16	972	HOOD KNUA																																																																						
COFFEE BREWER (17)	20A	1776	17	18	1392	HOOD KEF-1																																																																						
TEA BREWER (16)	20A	1776	19	20	1392	HOOD KEF-2																																																																						
TEA BREWER (16)	20A	1776	21	22	3564	50A SHIP-1																																																																						
DISH MACHINE (42)	20A	1368	23	24	3564	50A SHIP-1																																																																						
2-DOOR REACH-IN (54)	20A	276	25	26	1440	ICE MACHINE (1)																																																																						
FLY FAN (85)	20A	500	27	28	1440	ICE MACHINE (1)																																																																						
REFRIG CHEF BASE (34)	20A	384	29	30	---	SPACE																																																																						
NOTES		SUB-TOTALS 'B'		200A BUS	SUB-TOTALS 'A'																																																																							
				200A LUGS	SUB-TOTALS 'B'																																																																							
				200A FEED	GRAND TOTAL																																																																							
				VERIFY SIZE	AMPS/PHASE																																																																							
					TOTAL CONNECTED LOAD																																																																							
NEC ALLOWABLE DEMAND FACTORS		DIVERSIFIED LOAD SUMMARY																																																																										
① DEMAND FACTORS PER NEC 220 ② LARGEST OF: NEC TABLE 220.12 OR CONNECTED LOAD ③ NEC TABLE 220.56 ④ NEC 220.51 ⑤ NEC 220.43A, 200 VA/LINEAR FT ⑥ NON-COINCIDENT LOADS, LARGEST OF THE TWO LOADS IS COUNTED		<table border="1"> <thead> <tr> <th>LOAD TYPE</th> <th>DEMAND FACTOR</th> <th>A</th> <th>B</th> <th>TOTAL DIVERSIFIED LOAD</th> </tr> </thead> <tbody> <tr><td>GENERAL LIGHTING</td><td>125%</td><td>880</td><td>---</td><td>880</td></tr> <tr><td>TRACK LIGHTING</td><td>125%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>GENERAL USE</td><td>100%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>RECEPTACLES</td><td>100%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>MOTORS AND EQUIPMENT</td><td>LARGEST 125%</td><td>4455</td><td>4455</td><td>8910</td></tr> <tr><td>WATER HEATERS</td><td>ALL OTHERS 100%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>KITCHEN EQUIPMENT</td><td>65%</td><td>7956</td><td>7732</td><td>15688</td></tr> <tr><td>FIX. ELEC. SPACE HEAT.</td><td>100%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>SHOW WINDOW LIGHTS</td><td>125%</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>SIGN</td><td>100%</td><td>1500</td><td>1500</td><td>3000</td></tr> <tr><td>MISC</td><td>100%</td><td>800</td><td>800</td><td>1600</td></tr> <tr><td>PHASE (TOTAL VA)</td><td></td><td>13311</td><td>12187</td><td>25498</td></tr> <tr><td>TOTAL AMPS</td><td></td><td>111A</td><td>102A</td><td>VOLTS = 105A TOTAL AMPS</td></tr> </tbody> </table>					LOAD TYPE	DEMAND FACTOR	A	B	TOTAL DIVERSIFIED LOAD	GENERAL LIGHTING	125%	880	---	880	TRACK LIGHTING	125%	---	---	---	GENERAL USE	100%	---	---	---	RECEPTACLES	100%	---	---	---	MOTORS AND EQUIPMENT	LARGEST 125%	4455	4455	8910	WATER HEATERS	ALL OTHERS 100%	---	---	---	KITCHEN EQUIPMENT	65%	7956	7732	15688	FIX. ELEC. SPACE HEAT.	100%	---	---	---	SHOW WINDOW LIGHTS	125%	---	---	---	SIGN	100%	1500	1500	3000	MISC	100%	800	800	1600	PHASE (TOTAL VA)		13311	12187	25498	TOTAL AMPS		111A	102A	VOLTS = 105A TOTAL AMPS
LOAD TYPE	DEMAND FACTOR	A	B	TOTAL DIVERSIFIED LOAD																																																																								
GENERAL LIGHTING	125%	880	---	880																																																																								
TRACK LIGHTING	125%	---	---	---																																																																								
GENERAL USE	100%	---	---	---																																																																								
RECEPTACLES	100%	---	---	---																																																																								
MOTORS AND EQUIPMENT	LARGEST 125%	4455	4455	8910																																																																								
WATER HEATERS	ALL OTHERS 100%	---	---	---																																																																								
KITCHEN EQUIPMENT	65%	7956	7732	15688																																																																								
FIX. ELEC. SPACE HEAT.	100%	---	---	---																																																																								
SHOW WINDOW LIGHTS	125%	---	---	---																																																																								
SIGN	100%	1500	1500	3000																																																																								
MISC	100%	800	800	1600																																																																								
PHASE (TOTAL VA)		13311	12187	25498																																																																								
TOTAL AMPS		111A	102A	VOLTS = 105A TOTAL AMPS																																																																								

EQUIPMENT WIRING SCHEDULE

EQUIPMENT	MCA	MOCF	VOLTS	PH	WIRE SIZE
AHU-1	58.5A	60A	240V	1	3-#8, 1-#10 GND IN 1" CONDUIT
HP-1	34.2A	50A	240V	1	3-#8, 1-#10 GND IN 3/4" CONDUIT
RTU-1	47.3A	50A	208V	1	3-#8, 1-#10 GND IN 3/4" CONDUIT

NOTE:
THE ELECTRICAL CONTRACTOR SHALL VERIFY ALL EQUIPMENT ELECTRICAL REQUIREMENTS
PRIOR TO ROUGH-IN AND RELEASING GEAR. ADJUST BREAKER, WIRE SIZES, ETC. AS REQUIRED.




1 ELECTRICAL SERVICE RISER
SCALE: NTS



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com

ENGINEER
BURKE DESIGN GROUP, PA
CONSULTING ENGINEERS
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.771.1916 fax: 919.779.0826
email: benburke@nc.rr.com
Corp. License # C-2652



PROJECT TITLE
MI CANCUN

115 S. RALEIGH ST.
ANGIER, NORTH CAROLINA

PROJECT NO.
2006r
DRAWING TITLE
ELECTRICAL PANELS & RISER



PLOT DATE 12/30/2020

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020