

LANDSCAPE POSITION	GROUP	TEXTURE	ILLAR	MOIST (STAR)		MINERALOGY/CONSISTENCE	STRUCTURE
CC - CONCAVE SLOPE	I	S - SAND	LS - 0.5	MEST - NON-EXPANSIVE MEST - SLIGHTLY EXPANSIVE EXP - EXPANSIVE	MONT VFR - VERY FRABLE FR - FRABLE FI - FIRM VFI - VERY FIRM EFX - EXTREMELY FIRM	WET NS - NON-STICKY SS - SLIGHTLY STICKY S - STICKY VS - VERY STICKY NP - NON-PLASTIC SP - SLIGHTLY PLASTIC P - PLASTIC VP - VERY PLASTIC	SB - SINGLE GRAIN M - MASSIVE CR - CRUMB GR - GRANULAR SBK - SUBANGULAR BLOCKY ABK - ANGULAR BLOCKY FL - FLATY PB - PRISMATIC
CY - CONVEX SLOPE		LS - LOAMY SAND					
D - DRAINAGE WAY		SL - SANDY LOAM	LL - 0.5 - 0.6				
DE - DEBRIS SLUMP		L - LOAM					
FP - FLOOD PLAIN	II	SH - SILT	SL - 0.6 - 0.7	MONT VFR - VERY FRABLE FR - FRABLE FI - FIRM VFI - VERY FIRM EFX - EXTREMELY FIRM	WET NS - NON-STICKY SS - SLIGHTLY STICKY S - STICKY VS - VERY STICKY NP - NON-PLASTIC SP - SLIGHTLY PLASTIC P - PLASTIC VP - VERY PLASTIC	SB - SINGLE GRAIN M - MASSIVE CR - CRUMB GR - GRANULAR SBK - SUBANGULAR BLOCKY ABK - ANGULAR BLOCKY FL - FLATY PB - PRISMATIC	
FS - FOOT SLOPE		SH - SILT					
H - HEAD SLOPE		SCL - SILTY CLAY LOAM	CL - 0.7 - 0.8				
L - LEGAL SLOPE		CL - CLAY LOAM					
N - NOSE SLOPE	III	SCL - SANDY CLAY LOAM	SL - 0.9 - 1.0	MONT VFR - VERY FRABLE FR - FRABLE FI - FIRM VFI - VERY FIRM EFX - EXTREMELY FIRM	WET NS - NON-STICKY SS - SLIGHTLY STICKY S - STICKY VS - VERY STICKY NP - NON-PLASTIC SP - SLIGHTLY PLASTIC P - PLASTIC VP - VERY PLASTIC	SB - SINGLE GRAIN M - MASSIVE CR - CRUMB GR - GRANULAR SBK - SUBANGULAR BLOCKY ABK - ANGULAR BLOCKY FL - FLATY PB - PRISMATIC	
R - RIDGE		SLC - SILTY LOAM CLAY					
S - SHOULDER SLOPE		SC - SANDY CLAY	CL - 1.1 - 1.2				
T - TERRACE		SC - SILTY CLAY					
	IV	OC - ORGANIC	NONE				

NOTES:

HORIZON DEPTH IN INCHES BELOW NATURAL SOIL SURFACE
 DEPTH OF FILL IN INCHES FROM LAND SURFACE
 RESTRICTIVE HORIZON— THICKNESS AND DEPTH FROM LAND SURFACE
 SAPROLITE S (SUITABLE) OR U (UNSUITABLE)
 SOIL WETNESS - INCHES FROM LAND SURFACE TO FREE WATER OR INCHES FROM LAND SURFACE TO SOIL COLORS WITH CHROMA 2 OR LESS - RECORD MUNSELL COLOR CHIP DESIGNATION. CLASSIFICATION - S (SUITABLE), PS (PROVISIONALLY SUITABLE), OR U (UNSUITABLE)
 EVALUATION OF SAPROLITE SHALL BE BY PITS.

LONG-TERM ACCEPTANCE RATE: GAL/DAY/FT³

