DEPARTMENT OF ENVIRONMENT, HEALTH, AND NATURAL RESOURCES DIVISION OF ENVIRONMENTAL HEALTH ON-SITE WASTEWATER SECTION

	Sheet	of
PROPER	TY ID #:	5
C	OUNTY: 7	Honre

Jeff Endy

SOIL/SITE EVALUATION for ON-SITE WASTEWATER SYSTEM

OWN	VER:	Dan	ville L	ingdon	A PDI ICATI	PPLICANT:	Sam	DAME EL		F -2/-61
PRO	POSED FACIL	ITY:	Home H	PROPOS	APPLICATION OF COLORS	(.1949):	PRO	DATE EV OPERTY SIZ	ZE:	140,
EVA	LUATION ME	ETHOD:	Auger Bo	ring (Pit Cut	Other _	PRC	PERTY REC	CORDED: _	
P R O F I L E	.1940 LAND- SCAPE POSITION/ SLOPE %	HORI- ZON DEPTH (IN.)	SOIL MORPHOLOGY (.1941)			OTHER PROFILE FACTORS				
				41 TURE/ TURE	.1941 CONSISTENCE/ MINERALOGY	.1942 SOIL WETNESS/ COLOR	.1943 SOIL DEPTH	.1956 SAPRO .CLASS	.1944 RESTR HORIZ	PROFILE CLASS & LTAR
	(. 0-20	15		VFR					.8
1		20-48	54		VFR	-	74			4.8
	0-159.		, ,							
2	0-157.	0-12	45		VFK					
		12-20	SL		VEN	-				- 6
		20-48	ScL	sbk	FR.					
	4	0-20	45		UFE					
2	0-15%	20-24	54		FR	-				.5
3		24-48	sch to sc	sbt	FR	-			*	
1										
4										
00000000	DESCRIPTION-	INIT	TAL SYSTEM	REPAIR	SYSTEM OTHER EA	CTOPS (104C)				
Ava	ilable Space (.19		A.K	b K	' SITE CLAS	CTORS (.1946) SIFICATION (.		P5		

EVALUATED BY:

OTHER(S) PRESENT:

OK

Pumpto CONV.

11 4

System Type(s)

Site LTAR

COMMENTS:					
	- M				

LEGEND .. use the following standard abbreviations

LANDSCAPE POSITION	GROUP	SOIL <u>TEXTURE</u>	CONVENTIONAL .1955 LTAR	LPP .1957 LTAR*	MINERALOGY/ CONSISTENCE	STRECTURE
	A	-		***	Amara Ol-	C (Single Crain)
CC (Concave Slope)	I	S (Sand)	1.2 - 0.8	0.6 - 0.4	NEXP (Non-expansive)	G (Single Grain) M (Massive)
CV (Convex Slope)		LS (Loamy Sand)			SEX7 (Slightly Expansive)	CR (Crumb)
D (Drainage Way)			0.0.06	04.02	EXP (Expansive)	GR (Granular)
DS (Debris Slump)	II	SL (Sandy Loam)	0.8 - 0.6	0.4 - 0.3		SBK (Subangular Blocky)
FP (Flood Plain)		L (Loam)				ABK (Angular Blocky)
FS (Foot Slope)		61 (6:14)	0.6 - 0.3	0.3 - 0.15		PL (Platy)
H (Head Slope)	III	SI (Silt) SICL (Silty Clay Loam)	0.0 - 0.5	0.5 - 0.15		PR (Prismatic)
L (Linear Slope)		CL (Clay Loam)				,
N (Nose Slope)		SCL (Sandy Clay Loam)			MOIST	WET
R (Ridge) S (Shoulder Slope)		SLC (Silt Loam Clay)				
T (Terrace)	,	oze (om zom om)			VFR (Very Friable)	NS (Non-sticky)
(Terrace)	IV	SC (Sandy Clay)	0.4 - 0.1	0.2 - 0.05	FR (Friable)	SS (Slightly Sticky)
	1.4	SIC (Silty Clay)			FI (Firm)	S (Sticky)
		Clay.			VFI (Very Firm v. Very Sticky)	VS (Very Sticky)
		O (Organic)	None	31	EFI (Extremely Firm)	NP (Non-plastic)
						SP (Slightly Plastic)
						P (Plastic) VP (Very Plastic)
<i>NOTES</i>						vi (very riastic)

HORIZON DEPTH

DEPTH OF FILL

SAPROLITE

CLASSIFICATION

SOIL WETNESS

In inches below natural soil surface

In inches from land surface RESTRICTIVE HORIZON Thickness and depth from land surface

S(suitable) or U(unsuitable) Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation

S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

Evaluation of saprolite shall be by pits.

Long-term Acceptance Rate (LTAR): gal/day/ft2

