A 1' 1' 1'	
Application #_	

Harnett County Central Permitting
PO Box 65 Lillington, NC 27546 - Ph: 910-893-7525 - Fx: 910-893-2793 - www.hamett.org/permits Certification of Work Performed By Owner/Contractor (Individual Trade Application)

Owner (s) of Structure: Dalores LANE Phone: 910-470-9476
Owner (s) Mailing Address: 82 Hustocto Dr
Dung NC. 28334
Land Owner Name (s): Phone:
Construction or Site Address:
PIN # Parcel #
Job Cost: 4500.00 Description of Work to be done Set - P tank - Tostall Cin to generate Pressure test system
Mechanical: New Unit With Ductwork New Unit Without Ductwork Gas Piping Other
Electrical*: 200 Amp <200 Amp Service Change Service Reconnect Other * For Progress Energy customers we need the premise number
Plumbing: Water/Sewer Tap Number of Baths Water Heater
Specific Directions to Job from Lillington: No. 37 toward Bassen - Rton Red H. II Ch. Rl. Rtinto Hustington Sul- 32h house on Rd
Subdivision: Lot #: 82
(Contractors Name) will provide the Cooping labor on this structure.
I am the building owner or my NC state license number is 175/7, which entitles me to
perform such work on the above structure legally. All work shall comply with the State Building Code and all
other applicable State and local laws, ordinances and regulations.
McLambis LP Gas Contractor's Company Name Telephone Telephone
Address N.C. 37504 INFO no landele gas. com Email Address
17517 License #
Structure Owner / Contractor Signature: D. Name Me Look by Dat Date: 11/10/20
By signing this application you affirm that you have obtained permission from the above listed license holder to purchase permits on their behalf. If doing the work as owner you understand that you cannot rent, lease or sell the listed property for 12 months after completion of the listed work.

*Company name, address, & phone must match information on license

Please call for credit card payment. 919-894-3842

PROPANE SAFETY SI	Н	EET
-------------------	---	-----

Service Date						c	ounty	Harnet	*			
Account Number						-				-44 on Ral		
Name Delones LANE							Mill Ch. Pol. Let into Hearty					
Address 82 Hunting Dr.								Sul. 3d Jone on Rt.				
Dung N.C. 28334												
Telephone: (Home)						_ c	losest Cust	omer)		
(Office)	ON THE PARTY OF TH	(Ce	ell) 910	- 47	0-9	474						
APPLIANCE			, <u> </u>						VORK DES	CRIR	TION	
TYPE		Locs (نمو	Ta		-	Set 2nd (20 +prok-installe				
MANUFACTUR	ER	1		Gene	-						2# suchan	
MODEL NUMB	ER	_		126				Const	1 +0 +a	u k	- Con t	
SERIAL NUMB	ER		,					z tale				
LOCATION		Den	_ 0	Outside					Ens tan			
BTU		30.0		327.0	_					_	MARINE CONTRACTOR OF THE PARTY	
AGE			•	202	20							
MANUAL SHUT	OFF	-			-		٨	لمحمله	100			
VENTING				_					S LP Ga	LP Gas & Supply		
SEDIMENT TR	The second secon									2 South		
RECALL VALU					-				on, NC 2			
RED TAG (Remo	ive from Service)			_/				(919) 894-3842				
acknowledges tank pressure test, and Customer Signat	ownership as in 3) has given the	dicated at	oove. The s safety instr	ervicer	nan ac	knowledges th	nat he/s	he 1) performs	ed odor test,	2) per	6) that the customer formed leak test and	
TANK SPECIFIC		1				T				2011	COMPANY OF A PARK YEAR	
SIZE	SERIAL#	MF	G.	MFG. DATE					RELIEF VALVE COND. FITTIN			
120	2276457	Mana	hot	2000				New	New ok		ok	
PIPING/REGULA	ATOR OPERAT	ION/COM	NDITION:									
REGULATOR TYPE	PE PIPING MA	TERIAL	PIPING SIZE		REGULATOR DATE CODE		E MFG.	MFG./MODEL		REGULATOR VENT PROTECT.		
Int. Two-Stage	. Two-Stage											
1st Stage	t Stage Cu		y		2000		FE	Film		Done		
2nd Stage												
SYSTEM LEAK	TEST (Lock up	pressu	re):									
MEASURED START M		MEASURED END TI		ME HELD MINUTES	SYST	EM CHECK (OK)	REMARKS		ARKS			
Int. Two-Stage												
1st Stage 10 we		2	10 m			10		ok_				
2nd Stage	*								4			
2nd Stage regulat	or pressure with	all applia	ances runn	ing: _			inche	es w.c.				
								T Ct	- 10:- 10		!-!	

Piping Test for New Construction:

1st Stage 50 psig: 2nd Stage and Integral Two-Stage 10 psig. 10-minute minimum Lock up pressure should not exceed 14 inches w.c.

Working Pressure Requirement:

Working pressure should not fall below 10 inches w.c. or manufacturers recommendations