





 <b>REC</b>		<b>REC TwinPeak 3 Mono Black Series</b> <b>REC325TP3M Black</b> Serial Number: FFB-3009442598		Phone: +85 6495 9228 www.recgroup.com	
Power Output (Pmax)	325 W	 • Conforms to UL Std. 61730-1/-2 • Certified to CSA Std. C22.2#61730-1/-2 • UL Fire Rating Type 2™			
Watt Class Sorting	0/+5 W				
Power Production Tolerance	+/- 3 %	 • IEC 61215 • IEC 61730			
Rated Voltage (Vmpp)	34.1 V				
Rated Current (Impp)	9.54 A	  Application Class: Safety Class II			
Open Circuit Voltage (Voc) (+/- 3%)	40.9 V				
Short Circuit Current (Isc) (+/- 3%)	10.36 A	Manufactured: <b>24.02.2021</b>			
Maximum System Voltage (Vsys)	1000 V				
Maximum Series Fuse (DC) (UL)	25 A				
Maximum Series Fuse (DC) (IEC)	25 A				
Design Load	+3600 / -1600 Pa*				
Maximum Test Load	+5400 / -2400 Pa*				
(Values at STC: 1000 W/m <sup>2</sup> AM 1.5, cell temp 25°C)					
* See installation manual for *) mechanical installation requirements and +) installation requirements to achieve a specified system fire class					
<p><b>Warning electrical hazard.</b> This module produces electricity when exposed to light. Follow all applicable electricity safety precautions. Only qualified personnel should install or perform maintenance work on the module. Be aware of dangerous high DC voltage when connecting or disconnecting modules. Do not damage or scratch the rear surface of the module. Do not handle or install modules when they are wet. Refer to installation and operation manuals before installing, servicing or operating this unit.</p> <p><b>Avertissement: Risque de choc électrique.</b> Ce module solaire produit de l'électricité lorsqu'il</p>					

























