



EATON

General Use Safety Switch
This switch is designed to provide a safe means
of interrupting the flow of electric power.
NEMA 3R, 4X, 4XW
Complies with UL 941
UL Listed for use in wet or damp locations
and in corrosive atmospheres.
For other information, consult
the literature or contact your distributor.
EATON is a registered trademark of Eaton Corporation.
⚠ DANGER
ELECTRICAL SHOCK HAZARD
TERMINALS ON THE LINE AND
LOAD SIDES MAY BE ENERGIZED
IN THE OPEN POSITION
⚠ PRECAUTION
Always use proper safety procedures
when working on electrical equipment.
Always use proper safety procedures
when working on electrical equipment.

⚠ WARNING
DUAL POWER SUPPLY
SOURCES: UTILITY GRID
AND PV SOLAR
ELECTRIC SYSTEM

⚠ WARNING
ELECTRICAL SHOCK HAZARD
TERMINALS ON THE LINE AND
LOAD SIDES MAY BE ENERGIZED
IN THE OPEN POSITION



PHOTOVOLTAIC AC DISCONNECT
MAXIMUM AC BREAKING CURRENT **37.5 A**
NOMINAL OPERATING AC VOLTAGE **740 V**
PHOTOVOLTAIC
AC DISCONNECT

**MAIN PHOTOVOLTAIC
SYSTEM
AC DISCONNECT**