



20332227557400251

ENGINEERED, DESIGNED AND QUALITY TESTED BY Q CELLS IN GERMANY


Q.PEAK DUO BLK ML-G10+ 400

Q CELLS

PERFORMANCE AT STANDARD TEST CONDITIONS*

Nominal Power* (P _{max})	P _{max} [W]	400
Short circuit current*	I _{sc} [A]	11.14
Open circuit voltage*	V _{oc} [V]	45.30
Current at maximum power	I _{mp} [A]	10.77
Voltage at maximum power	V _{mp} [V]	37.13
Maximum system voltage	V _{sys} [V]	1000(IEC) 1000(UL)
Weight	M [kg / lbs]	22.0 / 4.4

Assembled in USA



DANGER!

Risk of electric shock!
DO NOT connect or disconnect plug contacts while system is under load current. Refer to the installation and Operation Manual before installing, operating or servicing this unit.

DANGER!

Risque de choc électrique!
NE PAS connecter ou déconnecter les connecteurs lorsque le système est en charge. Consultez le manuel d'installation et d'utilisation avant installation, utilisation et entretien de produit.

Fire Rating: Class C / Type 2

Design load: 50 kg/110 lb

Free Rating: 20.4

For field connections, use minimum No. 12 AWG copper wire insulated for a minimum of 90 °C

U.S. Patent No. 8,893,228
(wire only)

EMAIL: service@q-cells.com
WEB: www.q-cells.com

*Measurement tolerances: P_{max} ± 3%, I_{sc}, V_{oc} ± 0.5% at STC: 1000 W/m², 25 ± 2 °C.
AM 1.5 according to IEC 60904-3. Data given are rated (nominal) values.
IEC 61215:2016; IEC 61730:2016.



UL-Mark
E-1111220277



20332227557400251

Hersteller Q CELLS USA Inc.,
200 Nava Drive, Dalton GA 30701, USA
Certification number: Hersteller Q CELLS GmbH