





























Do Not Remove 154E9342-38



SolarEdge Technologies Ltd.  
SolarEdge Technologies GmbH/  
Werner-Eckert-Straße 6/81829 Munich/Germany



### CAUTION

HOT SURFACES-TO REDUCE THE RISK OF BURNS-DO NOT TOUCH. RISK OF ELECTRIC SHOCK-WHEN THE PHOTOVOLTAIC ARRAY IS EXPOSED TO LIGHT, IT SUPPLIES A DC VOLTAGE TO EQUIPMENT. COVER PV MODULE WITH OPAQUE MATERIAL BEFORE CONNECTING OR DISCONNECTING THIS OPTIMIZER. DURING FAULT, ZERO CURRENT IS SOURCED INTO DC ARRAY BY CONVERTER.

**WARNING** ELECTRIC SHOCK HAZARD. THE DC CONDUCTORS OF THIS PHOTOVOLTAIC SYSTEM ARE UNGROUNDED AND MAY BE ENERGIZED.

### AVERTISSEMENT

RISQUE DE CHOC ELECTRIQUE: QUAND LE CHAMP PHOTOVOLTAIQUE EST EXPOSE A LA LUMIERE, UNE TENSION CC EST FOURNIE A CET EQUIPEMENT. SURFACES CHAUDES: NE PAS TOUCHER, AFIN DE REDUIRE LES RISQUES DE BRULURES LE COURANT DE RETOUR INJECTE PAR LE CONVERTISSEUR EN CAS DE DEFAILLANCE DANS LE MODULE PV EST TOUJOURS NUL.



(UL) E5085













TrinaSolar  
FD1210008547436



TrinaSolar  
TSM-340DEMBX-06111

Model: TSM-340DEMBX-06111  
Power (W): 340  
Voltage (V): 18.2  
Current (A): 18.7  
Efficiency (%): 20.4  
Dimensions (mm): 1700x1050x35  
Weight (kg): 18.5

For more information, please visit our website: [www.trina.com](http://www.trina.com)  
or contact our sales team: [sales@trina.com](mailto:sales@trina.com)

**WARNING: ELECTRICAL HAZARD**  
Please refer to the safety manual for more information.

• Please refer to the safety manual for more information.  
• Please refer to the safety manual for more information.  
• Please refer to the safety manual for more information.



Assembled in Thailand





**TrinaSolar**  
TrinaSolar Energy Systems, Inc.  
10000 W. 10th Ave., Suite 100  
Boulder, CO 80501, USA  
Tel: +1 303 440-8888  
www.trinasolar.com

**TrinaSolar**  
TM30-180CWA-K5000

Model: TM30-180CWA-K5000  
Power (Wp): 180  
Voltage (V): 18  
Current (A): 10  
Dimensions (mm): 1750x1000x35  
Weight (kg): 20.5

TrinaSolar Energy Systems, Inc. warrants that the product is free from defects in materials and workmanship under normal use and service for a period of 12 years from the date of shipment. This warranty is limited to the original purchaser and does not cover damage caused by fire, theft, vandalism, or other external causes. For more information, please contact your local distributor or visit our website at www.trinasolar.com.

**CE** **RoHS** **REACH** **UL** **IEC**

MADE IN CHINA





**TrinaSolar**  
POLYCRYSTALLINE SILICON

**TrinaSolar**  
TM40-120V-60W (max)

Model: TM40-120V-60W (max)  
Power (P<sub>max</sub>): 60W  
Voltage (V<sub>mp</sub>): 12.0V  
Current (I<sub>mp</sub>): 5.00A  
Open Circuit Voltage (V<sub>oc</sub>): 18.0V  
Short Circuit Current (I<sub>sc</sub>): 5.50A

WARRANTY INFORMATION: 5 Year Power Output Guarantee, 10 Year Limited Product Warranty

CE, RoHS, REACH, ISO 9001, ISO 14001















