





























 REC Alpha Pure Series REC405AA-Pure Serial Number: FBB-4010060376		Phone: +65 6489 8228 www.recgroup.com
Power Output (Pmax)	405 W	 Certified to UL 6173-1 & 2 Certified to CSA CUL 6173-1 & 2 IEC 61734 - UL Fire Safety Test V
Watt Class Sorting	0/+5 V	
Power Production Tolerance	+/- 3 %	 - IEC 61734 / IEC 61735
Rated Voltage (Vmp)	42.4 V	
Rated Current (Imp)	9.56 A	 
Open Circuit Voltage (Voc) (+/- 3%)	48.9 V	
Short Circuit Current (Isc) (+/- 3%)	10.30 A	
Maximum System Voltage (Vmax)	1000 V	
Maximum Series Fuse (DC) (UL)	25 A	Warning electrical hazard. This module produces electricity when exposed to light. CAUTION: DO NOT DISCONNECT UNDER LOAD Avertissement: Risque de choc électrique. Ce module génère produit de l'électricité lorsque est exposé à la lumière. ATTENTION: NE PAS DECONNECTER SOUS TENSION For field connections, use min. 6 mm (1/2 AWG) UL PV wires insulated for a min. of 60°C Made in Singapore by REC SOLAR PTE. LTD. 25 TUBAS SOUTH AVENUE, 18, SINGAPORE 627312, SINGAPORE EU/UK/EFTA Contact REC Solar EMEA GmbH E-mail: rec@rec-solar.com Phone: +49 39289 442 30000 For other regions see www.recgroup.com/contact
Maximum Series Fuse (DC) (IEC)	25 A	
Design Load	+4666 / -2666 Pa*	Manufactured: 28.03.2022
Maximum Test Load	+7000 / -4000 Pa*	
<small>*Values at STC, 1000 W/m² AM1.5, Cell Temp 25°C</small>		

Jovan Almonte
 ID# 564218
 12-5-2022





















































