



840-00388-17
250VAC 20A
+79°C 2236



200

179

ENPHASE
IQ7A

Grid Support Interactive Inverter

Power factor range: ± 0.99
DC input range: 18 - 58 V
DC input current: 15 A
Max. input short-circuit current: 208 / 240 V
AC output current: 1.0 A
AC output frequency: 50 Hz / 60 Hz
AC output power (peak): 230 / 360 VA
AC output power (max. continuous): 200 / 340 VA
Operating temperature: -30°C to $+50^{\circ}\text{C}$
Ingress protection: NEMA Type 6
UL1741 SA Compliant | Assembled in Mexico

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference. (2) This device must accept any interference received, including interference that may cause undesired operation.

WARNING: RISK OF SHOCK. WARRANTY VOID IF COVER REMOVED. NO USER-SERVICEABLE PARTS INSIDE. REFER TO QUALIFIED SERVICE PERSONNEL.
CAUTION: RISK OF SHOCK. PHOTOVOLTAIC SYSTEMS ARE UNGROUNDABLE AND MAY BE ENERGIZED. AC AND DC VOLTAGE SOURCES TERMINATE INSIDE THIS EQUIPMENT. DISCONNECT BOTH AC AND DC SOURCES BEFORE WORKING ON THE EQUIPMENT. ALWAYS EXPOSED TO LIGHT AND HOT SURFACES. TO REDUCE THE RISK OF BURNING, DO NOT TOUCH.

ATTENTION: RESQUE D'ÉLECTROCUTION. LES CONDUCTEURS COULES SONT PHOTOVOLTAÏQUES. LE SYSTÈME PHOTOVOLTAÏQUE NE SAIT PAS ÊTRE MISE À LA TERRE ET PEUT ÊTRE ÉNERGÉ. LES SOURCES D'ÉNERGIE ALTERNATIVE ET CONTINUE SE TERMINENT À L'INTÉRIEUR DE CE MATÉRIEL. DÉCONNECTEZ À LA FOIS LES SOURCES D'ÉNERGIE ALTERNATIVE ET CONTINUE AVANT D'INTERVENIR SUR L'ÉQUIPEMENT. TOUJOURS EXPOSÉ À LA LUMIÈRE ET À LA CHALEUR. POUR RÉDUIRE LE RISQUE DE BRÛLURE, NE PAS TOUCHER.



20224217547
889-01123 05
IQ7A-72-M-US
QR code





















