























Serial No. **M230509-B0424**



Model Number **MSE3968XR**  
 Rated Maximum Power [W] **396 (-0/+3%)**  
 Open - Circuit Voltage [V] **46.2**  
 Voltage at Pmax [V] **37.0**  
 Short - Circuit Current [A] **11.24**  
 Current at Pmax [A] **10.88**  
 Max. System Voltage [V] **1000**  
 Max. Series overcurrent protective device (where required) fuse rating [A] **20**  
 Standard test condition AM=1.5 E=1000W/m<sup>2</sup> Tc=25°C



For field connections, use Cu only, 12AWG (US, CANADA), 4mm<sup>2</sup> (EU, Asia) wires insulated for a minimum of 90°C, rated for wet conditions and resistant to ultra violet radiation (where exposed). See installation manual for PV connector details and compatibility. See installation manual for PV connector product des tensions élevées dans la lumière du soleil. Risque électrique peut choquer, brûler ou de provoquer la mort. Ne pas toucher la borne.



Fire Rating: Type 1  
 Class of Equipment: Class II  
 Design Load: Minimum 3600 Pa front and minimum 1600 Pa back load

Warning  
 PV modules generate voltage even with very weak light. Do not open the junction box. Les modules PV produisent tension même en basse lumière. Ne pas ouvrir la boîte de jonction.



Address:  
 8303 S. New Braunfels Ave.  
 San Antonio, TX 78235  
**ASSEMBLED IN THE USA**







