

























8 9 10 11 4F 1 2 3 4 5
44 45 46 47 48 49 50 51 52 53



48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
































REC N-Peak 3 Black Series
REC400NP3 Black
 Serial Number: FBB-2010182839

Phone: +65 6405 9228
 www.recgroup.com

Power Output (Pmax)	400 W
Watt Class Sorting	0/+ 10 W
Power Production Tolerance	+/- 3 %
Rated Voltage (Vmpp)	37.6 V
Rated Current (Impp)	10.64 A
Open Circuit Voltage (Voc) (+/- 3%)	45.0 V
Short Circuit Current (Isc) (+/- 3%)	11.39 A
Maximum System Voltage (Vsys)	1000 V
Maximum Series Fuse (DC) (UL)	25 A
Maximum Series Fuse (DC) (IEC)	25 A
Design Load	+4666 / -2666 Pa*
Maximum Test Load	+7000 / -4000 Pa*

(Values at STC: 1000 W/m²AM 1.5, cell temp 25°C)



• Conforms to
 UL Std. 61700-1-2
 • Certified to
 CSA Std. C22.2/61700-1-2
 • UL Fire Rating Type 2*



- IEC 61215:2016
 - IEC 61730:2016



See installation manual for *) mechanical installation requirements and
 *) installation requirements to achieve a specified system fire class

Manufactured: 29.06.2023



Warning electrical hazard. This module produces electricity when exposed to light.

CAUTION: DO NOT DISCONNECT UNDER LOAD

Avertissement: Risque de choc électrique. Ce module solaire produit de l'électricité lorsqu'il est exposé à la lumière.

ATTENTION: NE PAS DECONNECTER SOUS TENSION

For field connections, use min. 4 mm² (12 AWG) UL PV wires insulated for a min. of 90°C

Made in Singapore by REC SOLAR PTE. LTD.
 20 TUAS SOUTH AVENUE 14, SINGAPORE 637312, SINGAPORE

EU/Europe Contact: REC Solar EMEA GmbH
 Bolanstr. 71a, 81541 Munich, Germany, Tel: +49 (0)89-442-38390
 For other regions see: www.recgroup.com/contact





