



MISSION SOLAR ENERGY Serial No. **M230905-A0947**

Model Number	M230905-A0947
Rated Maximum Power	381.6Wp
Open-Circuit Voltage	48.2 (V)
Voltage at Pmax	37.5 (V)
Short-Circuit Current	11.24 (A)
Current at Pmax	10.68 (A)
Max. System Voltage	1500 (V)
Max. Current measurement protective device (where required) fuse rating	Standard test condition (A)

For field dimensions, see Cu only 156W (UL CANADA, Series 21). Add wiring required for a minimum of 20°C. Refer for test conditions and modules to the relevant radiation (where applicable). See installation manual for PV connector details and compatibility. **Avvertimento** Rischi di choc. **Attention** Ce module produit des tensions élevées dans la lumière du soleil. **Requis** Un interrupteur peut éliminer le choc ou de provoquer la mort. Ne pas toucher la borne.

Fire Rating : Type 1
 Class of Equipment: Class II
 Design Load: Minimum 3600 Pa front and minimum 1600 Pa back load

Warning
 PV module generates voltage even with very weak light. Do not open the junction box. Les modules PV produisent tension même en faible lumière. Ne pas ouvrir le boîtier de jonction.

Address:
 8303 S. West Brakerley Blvd.
 San Antonio, TX 78225
ASSEMBLED IN THE USA



























