

ANGLER HUNTING W
ANGLER, NC 2750



WARNING: PHOTOVOLTAIC
PC SOURCE

SOLADECK

Conforms to UL 1741, Certified to CSA C22.2 No. 290, Vemco Type 3R
Max Ratings: 600 VDC/180 AMPS 240 VAC/80 AMPS, Short circuit 10KA, Max Temp 75°C
Refer to manual for terminal torque load information



WARNING/AVERTISSEMENT
HIGH VOLTAGE, KEEP OUT OF RISK OF ELECTRICAL SHOCK. ONLY TRAINED SERVICE PERSONNEL ALLOWED ACCESS. SUITABLE FOR PHOTOVOLTAIC USE. APPROVED FOR USE WITH FIELD-INSTALLED CONDUCTORS SIZED FOR ALLOWABLE AMPACITY OF USE. EXTERNAL OUTPUT CIRCUIT DISCONNECTING MEANS SHALL BE PROVIDED WHEN REQUIRED BY THE CANADIAN ELECTRICAL CODE PART I CAUTION: BEFORE SERVICING FUSES, DISCONNECT ALL PHOTOVOLTAIC INPUTS AND OUTPUT CIRCUITS.
HAUTE TENSION, GARDEZ À L'ÉCART LE RISQUE DE CHOC ÉLECTRIQUE. SEUL LE PERSONNEL DE SERVICE FORMÉ A L'AUTORISÉ L'ACCÈS. CONVIENT À L'UTILISATION PHOTOVOLTAÏQUE. APPROUVÉ POUR L'INSTALLATION AVEC DES CONDUCTEURS INSTALLÉS SUR LE TERRAIN. DIMENSIONS EXTERNES POUR L'AMPACITÉ PERMISES EN C. C. UN MOYEN DE DÉCONNEXION DU CIRCUIT DE SORTIE EXTERNES DOIT ÊTRE FOURNI LORSQUE LA PARTIE I DU CODE CANADIEN DE L'ÉLECTRICITÉ L'EXIGE. ATTENTION: AVANT D'ENTREPRENDRE LES FUSIBLES, DÉBRANCHEZ TOUTES LES ENTRÉES ET CIRCUITS DE SORTIE PHOTOVOLTAÏQUES.



Part No. 3134037
RSTC Enterprises

393 HUNTING WOOD DR
ANGIER, NC 27501









