



65W2-R

INDEX OF SHEETS:

ARCHITECTURAL

- A0 COVER SHEET / CODE ANALYSIS
- A1 FLOOR PLAN / DOOR SCHEDULE / WALL DETAILS
- A2 EXTERIOR ELEVATIONS AND NOTES
- A3 EXTERIOR WALL SECTIONS
- A3.1 EXTERIOR WALL SECTIONS

ARCHITECTURAL CON'T

- A4 INTERIOR ELEVATIONS / TILE PLAN
RESTROOM PLAN / ELEVATIONS / DETAILS
- A5 STOREFRONT / DETAILS
- A6 ROOF PLAN / DETAILS

STRUCTURAL

- S0 GENERAL NOTES
- S0.1 GENERAL NOTES / TYP. DETAILS & WIND TABLE
- S0.2 TYPICAL DETAILS
- S1 FOUNDATION PLAN / DETAILS
- S1.0A FOUNDATION PLAN / SECTIONS
- S2 ROOF FRAMING PLAN / DETAILS

MECHANICAL

- M1 HEATING & COOLING
- M1.1 HEATING & COOLING
- M2 PLUMBING

ELECTRICAL

- E1 POWER PLAN / GENERAL NOTES
- E2 UNDERSLAB CONDUIT / UNDER – COUNTER – POWER & DATA PLANS
- E3 LIGHTING PLAN & DETAILS
- E4 PANEL BOARD SCHEDULES / ONE-LINE DIAGRAMS & DETAILS
- E5 LIGHTING CONTROL PANEL & DETAILS
- E6 VENSTAR HVAC AND LIGHTING CONTROL

OWNER: AutoZone Development Corporation
 Contact: CAROLYN THAEMERT
 Voice: (901) 495-8994
 Fax: (901) 495-8991

REVISIONS

1	REV1	
2	REV2	
3	REV3	
4	REV4	
5	REV5	
6	REV6	

LIFE SAFETY NOTES:

DOORS:
 EXIT DOORS TO BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE OR EFFORT. EXCEPTION: MAIN EXIT DOOR HAS KEY-LOCKING HARDWARE. GENERAL CONTRACTOR TO PROVIDE A READABLE VISIBLE, DURABLE SIGN ON OR ADJACENT TO THE DOOR STATING "THIS DOOR TO REMAIN UNLOCKED WHEN BUILDING IS OCCUPIED". SIGN TO BE ONE INCH HIGH LETTERS ON CONTRASTING BACKGROUND.

EXIT ILLUMINATION:
 EXITS TO BE ILLUMINATED AT ANY TIME THE BUILDING IS OCCUPIED WITH LIGHT HAVING INTENSITY OF NOT LESS THAN ONE FOOTCANDLE AT FLOOR LEVEL. THE POWER SUPPLY FOR EXIT ILLUMINATION HAS BATTERY BACKUP IN THE EVENT OF A POWER FAILURE.

EXIT SIGNS:
 EXIT SIGNS TO BE INSTALLED AT THE REQUIRED EXITS FROM THE ROOM OR AREA AND WHEN OTHERWISE NECESSARY TO CLEARLY INDICATE THE DIRECTION OF EGRESS. GRAPHICS, ILLUMINATION AND POWER SUPPLY SHALL COMPLY WITH CHAPTER 10 OF THE IBC.

FLAMMABLE AND COMBUSTIBLE MATERIALS:
 FLAMMABLE AND COMBUSTIBLE MATERIALS WILL NOT EXCEED MAXIMUM QUANTITIES ALLOWED UNDER TABLE 3404.3.4.1 OF THE IFC OR TABLE 7902.5-B OF THE UFC. THERE WILL BE NO HIGH-PILED COMBUSTIBLE STORAGE.

PORTABLE FIRE EXTINGUISHERS:
 TYPE, SIZE, NUMBER AND LOCATION OF FIRE EXTINGUISHERS SHALL BE INSTALLED ACCORDING TO LOCAL REQUIREMENTS.

INTERIOR FINISHES:
 INTERIOR FINISHES TO HAVE A FLAME-SPREAD RATING OF 25 OR LESS.

INSULATION:
 WALL INSULATION TO HAVE A FLAME-SPREAD RATING OF NOT MORE THAN 25 AND A SMOKE DEVELOPMENT RATING OF NOT MORE THAN 450. ROOF INSULATION (FOAM PLASTIC) TO HAVE A FLAME-SPREAD RATING OF NOT MORE THAN 75 AND A SMOKE-DEVELOPED RATING OF NOT MORE THAN 450.

ROOFING:
 ROOF COVERING SPECIFIED IS CLASS A.

SHELVING:
 MAXIMUM HEIGHT OF SHELVING FIXTURES IS 12'-0" THERE IS NO "HIGH PILED STORAGE" IN THE STORE.

BUILDING CODE ANALYSIS

DESIGN CODES: 2018 NC BUILDING CODE
 OCCUPANCY CLASSIFICATION: GROUP M (MERCANTILE)
 TYPE OF CONSTRUCTION: VB UNPROTECTED
 NUMBER OF STORIES: 1 ALLOWED / 1 SHOWN
 BUILDING AREA: 9000 ALLOWED / 6446 SHOWN
 AREA INCREASE: NOT APPLICABLE

EXTERIOR WALL RATINGS:
 EXTERIOR WALLS SHALL BE CONSTRUCTED WITH LIGHT WEIGHT CONCRETE BLOCKS CONFORMING TO NCMA TEK 7-1A 1999 STANDARDS WHICH SAY THAT 8" UNITS ARE RATED FOR 2 HOURS AND THAT IF THE CORES ARE EITHER GROUTED SOLID OR FILLED WITH VERMICULITE THEY ARE RATED FOR 4 HOURS.

OCCUPANT LOAD FOR EGRESS:
 MERCANTILE: 6446 / 60 = 215

EXITS:
 2 EXITS REQUIRED FOR OCCUPANT LOAD > 50
 EXIT WIDTH :107 OCCUPANTS X .2 = 43 IN. REQUIRED
 MINIMUM = 72 IN. PROVIDED
 EXIT SEPARATION: 110 = 55 FT. REQUIRED
 100 FT. PROVIDED

**** MAXIMUM OVERALL DIAGONAL DISTANCE**
 MAXIMUM TRAVEL DISTANCE: 200 / 88 SHOWN
AISLES:
 MINIMUM WIDTH: 36 IN. REQUIRED / 39 IN. PROVIDED (AREAS SERVING EMPLOYEES ONLY)
 MINIMUM WIDTH: 44 IN. REQUIRED / 48 IN.(min) PROVIDED (PUBLIC AREAS)
 MAX. DEAD END LENGTH = 20 FT. / 15 FT. SHOWN

AutoZone Store No. 6890
 1593 N. MAIN ST.

LILLINGTON, NC 27546
COVER SHEET / CODE ANALYSIS

DEFERRED SUBMITTALS: (if required)

THE FOLLOWING ITEMS WILL BE DEFERRED SUBMITTALS IF REQUIRED: ROOF FRAMING LAYOUT PLAN & CALCS
 FIXTURE ANCHORING PLAN & DETAILS
 STORE FRONT PLAN & CALCS

SUBMITTAL DOCUMENTS FOR DEFERRED SUBMITTAL ITEMS SHALL BE SUBMITTED TO THE ARCHITECT OR ENGINEER OF RECORD, WHO SHALL REVIEW AND FORWARD THEM TO THE BUILDING OFFICIAL WITH A NOTATION INDICATING THAT THE DEFERRED SUBMITTAL DOCUMENTS HAVE BEEN REVIEWED AND FOUND TO BE IN GENERAL CONFORMANCE WITH THE DESIGN OF THE BUILDING.
 THE DEFERRED SUBMITTAL ITEMS SHALL NOT BE INSTALLED UNTIL THEIR DESIGN AND SUBMITTED DOCUMENTS HAVE BEEN APPROVED BY THE BUILDING OFFICIAL.

SPECIAL INSPECTIONS: (if required)

IN ADDITION TO THE REGULAR INSPECTIONS, THE FOLLOWING CHECKED ITEMS WILL ALSO REQUIRE SPECIAL INSPECTIONS IN ACCORDANCE WITH SECTION 1704 OF THE INTERNATIONAL BUILDING CODE.

ITEM	REQUIRED
SOIL COMPLIANCE PRIOR TO FOUNDATION INSPECTION	YES
STRUCTURAL CONCRETE OVER 2500 PSI	YES
EXPANSION AND/OR EPOXY ANCHORS	YES
STRUCTURAL MASONRY	YES
WELDING	YES

DESIGNERS OF RECORD:


ARCHITECTURAL
 Name: GEORGE CALLOW
 License No: 5064
 Phone No: (901)495-8705

STRUCTURAL
 Name: BRIAN WAYNE
 License No: 044971
 Phone No: (614) 448-4106

MECHANICAL
 Name: DANNY DOSS
 License No: 12456
 Phone No: (479) 631-1712

ELECTRICAL
 Name: DANNY DOSS
 License No: 12456
 Phone No: (479) 631-1712


Architect: George Callow
 123 South Front Street
 Memphis, Tennessee 38103
 TEL: 901-495-8706 FAX: (901) 495-8969
 For Bidding & Contractor Information Contact:
 Dodge Data & Analytics, Tel. 413-930-4215
 Cindy.searcy@construction.com



George W Callow
 Digitally signed by George W Callow
 Date: 2020.05.21 08:11:17 -05'00'

05/06/20
 65W2-R

A-0



NOTE:
 (F) = 2A 10BC FIRE EXTINGUISHER. GENERAL CONTRACTOR. INSTALL EITHER ON WALL SURFACE OR ALUMINUM MULLION. MOUNTING HEIGHT = 3'-6" ABOVE FINISHED FLOOR TO TOP OF EXTINGUISHER.

1/8" = 1'-0"

1 FLOOR PLAN

- REFER TO STRUCTURAL DRAWINGS FOR ALL DETAILS AND REQUIREMENTS REGARDING FOUNDATIONS, WALL REINFORCING, BOND BEAMS, LINTELS, AND ROOF FRAMING.
- REFER TO CIVIL DRAWINGS FOR LOCATIONS AND DETAILS OF SIDEWALKS, PIPE GUARDS, ETC., AS WELL AS FINISH FLOOR ELEVATION AND EXTERIOR FINISHED GRADES AROUND THE BUILDING.
- INSTALL 6" WIDE, 20 GAUGE GALVANIZED SHEET METAL STRIP BETWEEN THE BACK OF THE GYPSUM BOARD AND THE FACE OF THE METAL STUD AROUND THE ENTIRE PERIMETER OF THE BUILDING, AS WELL AS BOTH SIDES OF THE CURTAIN WALL. TOP OF STRIP TO BE 93" ABOVE FINISHED FLOOR. REFER TO SHEET A-4 FOR DETAILS OF CURTAIN WALL.
- SEE SHEET M-2 FOR LOCATION OF NON FREEZE YARD HYDRANT AND INSTALLATION REQUIREMENTS.
- INSTALL 1/2" X 4'-0" X 8'-0" AC PLYWOOD HORIZONTALLY WITH THE LONG EDGE ON THE FLOOR AND THE END JOINT CENTERING ON A STUD. APPLY PLYWOOD TO THE FACE OF GYPSUM BOARD WITH SCREWS TO FACILITATE FUTURE REPLACEMENT. SEE INTERIOR ELEVATIONS SEE 3/44 DETAIL.
- SEE SPECIFICATIONS FOR INFORMATION ON ITEMS NOT COMPLETELY DELINEATED ON THE DRAWINGS.

1/8" = 1'-0"

2 FLOOR PLAN NOTES

LOCATION	FLOOR		BASE		WALLS		CLG.		REM.
	SEALED CONCRETE	VINYL TILE	VINYL	QUARRY TILE	GYPSUM BOARD	FIBER REINFORCED PANELS	METAL DECK	GYPSUM BOARD	
SALES AREA		●	●		●		●		
REST ROOMS	●		●			●		●	


3/16" = 1'-0"

3 ROOM FINISH SCHEDULE

MK	SIZE	TYPE	FRAME	JAMB DETAIL	HEAD DETAIL	ADA / EXIT HARDWARE	SEE SECTION 08700 OF THE SPECIFICATIONS
A	6'-0" x 8'-0"	STEEL OVERHEAD ROLL-UP	STEEL ANGLE	6&7&8/A1	6&7/A1		
B	3'-0" x 7'-0" x 1-3/4"	HOLLOW METAL	HOLLOW METAL	8/A1	8/A1	PUSH BAR EXIT DEVICE WILL HAVE AN INTEGRAL SOUNDER	
C	3'-0" x 6'-8" x 1-3/4"	SOLID CORE WOOD UNDERCUT DOOR 1"	HOLLOW METAL	8/A1	8/A1	LEVER HANDLE PRIVACY SETS	
D	3'-0" x 6'-8" x 1-3/4"	SOLID CORE WOOD UNDERCUT DOOR 1"	HOLLOW METAL	8/A1	8/A1	LEVER HANDLE PRIVACY SETS	
E	2'-6" x 6'-8" x 1-3/4"	SOLID CORE WOOD PAIR REQUIRED	HOLLOW METAL	8/A1	8/A1	UNDERCUT DOOR 1" (PAIR REQUIRED)	
G	3'-0" x 7'-0" x 1-3/4"	GLASS & ALUMINUM SEE SHEET A-5	ALUMINUM			SEE MANUFACTURER'S SHOP DRAWINGS	
H	3'-0" x 7'-0" x 1-3/4"	GLASS & ALUMINUM SEE SHEET A-5	ALUMINUM			SEE MANUFACTURER'S SHOP DRAWINGS	
J	3'-0" x 7'-0" x 1-3/4"	HOLLOW METAL	HOLLOW METAL	8/A1	8/A1	PUSH BAR EXIT DEVICE	

3/32" = 1'-0"

4 DOOR SCHEDULE - HOLLOW METAL DOORS & FRAMES




NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

5 EXPANSION JOINT DETAIL


CHAIN OPERATED INSULATED DOOR SURFACE MOUNTED

24 GAUGE GALVANIZED METAL HOOD PAINT TO MATCH WALL.




6 OVERHEAD DOOR ELEVATION

NOTE: GENERAL CONTRACTOR TO INSTALL 6" X 8'-0" ALUMINUM CHAIN GUARD ON WALL AT OPERATING SIDE




7 OVERHEAD DELIVERY DOOR (A)


NOTE: OVER HEAD DOOR ANGLE TO BE WELDED TO BENT PLATE




DOOR HEAD SIMILAR



DOOR HEAD SIMILAR



8 JAMB DETAILS



NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

9 REAR GIRDER LINE COLUMN

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS


NOTE: SEE STRUCTURAL DRAWINGS FOR REINFORCING REQUIREMENTS

REVISIONS	1	2	3	4	5	6

REVISIONS	1	2	3	4	5	6

AutoZone Store No. 6890
 1593 N. MAIN ST.
 LILLINGTON, NC 27546
 FLOOR PLAN / DOOR SCHEDULE / WALL DETAILS

Architect: George Callow
 123 South Front Street
 Memphis, Tennessee 38103
 TEL: 901-495-8706 FAX: (901) 495-8969
 For Bidding & Contractor Information Contact:
 Dodge Data & Analytics, Tel. 413-930-4215
 Cindy.searcy@construction.com







05/06/20

65W2-R

A-1

George W. Callow
 Digitally signed by George W. Callow
 Date: 2020.05.21 08:14:30 -05'00'




- 1 TWO PIECE COMPRESSION TRIM SEE DETAIL 4/A6
- 2 BRICK VENEER UNITS SEE PAINT DETAIL SCHEME THIS SHEET
- 3 WALL MOUNTED LIGHT FIXTURE
- 4 PIPE GUARD WITH RED SLEEVE
- 5 MFG. WHITE EXTERIOR INSULATED FINISH - PAINT WHITE
- 6 PAINT MAN DOOR RED & METAL FRAMES BLACK
- 7 DO NOT PAINT OVERHEAD DOOR PAINT ANGLES BLACK
- 8 EXPANSION JOINT
- 9 ALUMINUM STOREFRONT - RED KYNAR FINISH
- 10 GLASS AND ALUMINUM DOORS - CLEAR ANODIZED FINISH
- 11 FRONT WALL SIGN - 46" L.S. CHANNEL LETTERS
- 12 NOT USED
- 13 TOILET WALL VENTS PAINT TO MATCH WALL
- 14 STORE ADDRESS - 6" WHITE REFLECTIVE NUMBERS
- 15 INTERNAL ROOF DRAIN
- 16 ROOF LINE SEE STRUCTURAL DRAWINGS FOR DETAILS
- 17 LEFT SIDE WALL SIGN - 44" AZO CHANNEL LETTERS
- 18 CLERESTORY WINDOW - EVERGREEN GLASS
- 19 FAUX WINDOW - OPAQUE BLACK GLASS
- 20 ROOF DRAIN EXIT

REVISIONS		
NO.	DATE	DESCRIPTION
1	REV1	
2	REV2	
3	REV3	
4	REV4	
5	REV5	
6	REV6	

2 ELEVATION KEY NOTES

NOTE: CENTER ALL WALL SIGNAGE VERTICALLY ON THE PAINTED ORANGE STRIPE OR BETWEEN THE TOP TWO BRICK SOLDIER COURSES. PAINT ORANGE STRIPE TO WITHIN 2' OF WALL SIGN. DO NOT PAINT ORANGE STRIPE BEHIND SIGN.



3 EXTERIOR WALL COLOR SCHEME

- GENERAL NOTES:
- REFER TO SECTION 09900 OF THE SPECIFICATIONS FOR PAINT AND EXTERIOR COATINGS. ALL COLORS ARE BY SHERWIN-WILLIAMS PAINT COMPANY.
 - PAINT RESTROOM WALL VENTS TO MATCH THE ADJACENT WALL COLOR.
 - SEALANT AT EXPANSION JOINTS TO MATCH ADJACENT WALL COLOR.
 - ALL MASONRY JOINTS TO BE CONCAVE TOOLED.

4 GENERAL NOTES

SIGNAGE NOTES:

- AUTOZONE'S SIGN VENDOR WILL FURNISH AND INSTALL ALL SIGNS UNLESS OTHERWISE SPECIFICALLY NOTED ON THE DRAWINGS. WALL SIGNS TO BE INSTALLED ON SURFACES THAT ARE FURNISHED AND PREPARED BY GENERAL CONTRACTOR.

- SIGN INSTALLER SHALL OBTAIN SIGN PERMITS AND INSTALL ALL FREESTANDING SIGNS AND THEIR FOUNDATIONS UNLESS NOTED OTHERWISE. GENERAL CONTRACTOR SHALL INSURE SIGN LOCATION IS TO GRADE AND SHALL MARK WHERE SIGN IS TO BE LOCATED.
- GENERAL CONTRACTOR IS RESPONSIBLE FOR INSTALLATION OF PRIMARY ELECTRICAL, AND FINAL ELECTRICAL HOOK-UP. SEE "SM" SHEETS FOR ADDITIONAL INFORMATION.
- SEE SHEET E3 FOR LOCATIONS OF J-BOXES TERMINATING EACH WALL SIGN CIRCUIT.


5 SIGNAGE NOTES - BUILDING

George W Callow
Digitally signed by George W Callow
Date: 2020.05.21 08:15:28 -05'00'

J.B.H. = JOIST BEARING HEIGHT

AutoZone Store No. 6890
1593 N. MAIN ST.

Architect: George Callow
123 South Front Street
Memphis, Tennessee 38103
TEL: 901-495-8706 FAX: (901) 495-8969
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com




05/06/20

65W2-R


A-2

LILLINGTON, NC 27546
EXTERIOR ELEVATIONS AND NOTES




3/8" = 1'-0"
1 WALL SECTION - HIGH SIDE

AWS01



3/8" = 1'-0"
2 WALL SECTION END WALL

AWS02




3/8" = 1'-0"
3 WALL SECTION LOW SIDE

AWS03

1" = 1'-0"

4 PARAPET DETAIL

AWS05




REVISIONS

1	2	3	4	5	6
---	---	---	---	---	---

AutoZone Store No. 6890
1593 N. MAIN ST.

LILLINGTON, NC 27546
EXTERIOR WALL SECTIONS

Architect: George Callow
123 South Front Street
Memphis, Tennessee 38103
TEL: 901-495-8706 FAX: (901) 495-8969
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com




05/06/20


65W2-R

A-3

George W. Callow
Digitally signed by George W Callow
Date: 2020.05.21 08:16:39 -05'00'



3/8" = 1'-0" AWS07W
1 WALL SECTION - HIGH SIDE




3/8" = 1'-0" AWS04W
1 WALL SECTION HIGH SIDE (storefront)

REVISIONS	
1	REV1
2	REV2
3	REV3
4	REV4
5	REV5
6	REV6

AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546
EXTERIOR WALL SECTIONS


Architect: George Callow
123 South Front Street
Memphis, Tennessee 38103
TEL: 901-495-8706 FAX: (901) 495-8969
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com



05/06/20
65W2-R


A-3.1

George W Callow
Digitally signed by George W Callow
Date: 2020.05.21 08:16:04 -05'00'
AWS04W




- 1. SEALED CONCRETE
- 2. 12" x 12" VINYL COMPOSITION FLOOR TILE
- 3. ALL GYPSUM BOARD WALLS TO RECEIVE 4" BLACK VINYL BASE
- 4. INSTALL BLACK NEOPRENE EDGE STRIP WHERE VINYL MEETS SEALED CONCRETE.


1/8" = 1'-0"
1 INTERIOR TILE PLAN




1/4" = 1'-0" AIS0265W2R
2 CURTAIN WALL AT GIRDER




1/16" = 1'-0" AIE0165W2R
3 INTERIOR ELEVATIONS




4 TRANSITION STRIP AIS01



1/2" = 1'-0" AIS03
5 ACCESS PANEL SECTION



3/16" = 1'-0" ABE0165W2R
6 INTERIOR BATHROOM ELEVATIONS



1/4" = 1'-0" APB0165W2R
7 RESTROOM PLAN


FIXTURES		ACCESSORIES	
P1 TOILET	P5 NOT USED	1 TOILET PAPER HOLDER	4 GRAB BAR 42" LONG 1-1/2" DIA.
P2 LAVATORY	P6 NOT USED	2 PAPER TOWEL HOLDER	5 MIRROR - 18"x36" H. FRAMED GLASS
P3 MOP SINK	P7 WATER HEATER	3 GRAB BAR 36" LONG 1-1/2" DIA.	6 MOP HOLDER
P4 ELECTRIC DRINKING FOUNTAIN	P8 BACKFLOW PREVENTOR		7 GRAB BAR 18" LONG 1-1/2" DIA.

1/8" = 1'-0" ABL01
8 RESTROOM LEGEND

REVISIONS	
1	REV1
2	REV2
3	REV3
4	REV4
5	REV5
6	REV6


AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546
TILE PLAN / INTERIOR ELEVATIONS / RESTROOM PLAN & ELEVATIONS

Architect: George Callow
123 South Front Street
Memphis, Tennessee 38103
TEL: 901-495-8706 FAX: (901) 495-8969
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com




05/06/20
65W2-R
A-4


George W Callow
Digitally signed by George W Callow
Date: 2020.05.21 08:17:31 -05'00'




1" = 1'-0" ASS01W




1" = 1'-0" ASS02W



1" = 1'-0" ASS0365w2



1" = 1'-0" ASS04




3" = 1'-0" ASS05


GENERAL NOTES

- STOREFRONT SHALL BE AS MANUFACTURED BY EITHER VISTAWALL ARCHITECTURAL PRODUCTS, YKK, OR U.S. ALUMINUM PRODUCTS AND SHALL BE 2" WIDE BY 4 1/2" DEEP. IMPACT FRAMING SHALL BE 2 1/2" WIDE BY 5" DEEP.
- CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS PRIOR TO BEGINNING FABRICATION OF THE FRAMING MEMBERS OR ORDERING GLASS. INSTALLATION SHALL CONFORM TO ALUMINUM MANUFACTURER'S PRINTED SHOP DRAWINGS AND INSTRUCTIONS.
- STEEL CLIPS AND ANCHORS SHALL BE HOT ROLLED STEEL A-36 ALLOY WITH A MINIMUM OF ONE COAT OF ZINC CHROMATE PRIMER.
- ALL FASTENERS SHALL BE ZINC OR CADMIUM PLATED OR NON-MAGNETIC STAINLESS STEEL. ALL FASTENERS IN EXPOSED AREAS ARE TO BE PAINTED TO MATCH FINISH OF ALUMINUM.
- FINISH OF ALUMINUM CLADDING AND FORMED ALUMINUM SHAPES SHALL MATCH THE FINISH OF ADJACENT EXTRUDED ALUMINUM.
- MITERING AND NOTCHING OF INTERIOR TRIM IS TO BE DONE IN THE FIELD.

1" = 1'-0" ASS01



1" = 1'-0" ASS0665w2




1/4" = 1'-0" ASS0705w2R

REVISIONS		
1		
2		
3		
4		
5		
6		

AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546
STOREFRONT / VESTIBULE PLAN / DETAILS

George W Callow
Digitally signed by George W Callow
Date: 2020.05.21 08:18:13 -05'00'

Architect: George Callow
123 South Front Street
Memphis, Tennessee 38103
TEL: 901-495-8706 FAX: (901) 495-8969
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com



05/06/20
65W2-R
A-5

GENERAL

- 1. THESE NOTES ARE GENERAL REQUIREMENTS. SEE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
2. UNLESS SHOWN OR NOTED OTHERWISE ON THE CONTRACT DRAWINGS OR IN THE SPECIFICATIONS, THE FOLLOWING NOTES SHALL APPLY TO THE MATERIALS LISTED HEREINAFTER FOR USE ON THIS PROJECT.
3. IF MATERIALS, QUANTITIES, STRENGTHS OR SIZES INDICATED BY THE DRAWINGS OR SPECIFICATIONS ARE NOT IN AGREEMENT WITH THESE NOTES, THE CONTRACTOR SHALL CONTACT THE ARCHITECT/ENGINEER FOR CLARIFICATION.
...
17. EARTH-WORK, FOUNDATION DRAINS, WATERPROOFING, PERIMETER INSULATION, MASONRY AND OTHER REQUIRED NON-STRUCTURAL ITEMS ARE NOT SHOWN ON THE STRUCTURAL DRAWINGS. COORDINATE WITH CIVIL SITE AND ARCHITECTURAL DRAWINGS.

GOVERNING CODES AND SPECIFICATIONS

Table listing governing codes and specifications such as NBC, ASCE 7, ACI 318, ACI 301, ACI 305R, ACI 306R, ACI SP-66, ACI 530, ACI 530.1, AISC 360, AWS D1.1, AWS D1.4, SJI, SDI-RDDM, AISI S100, AISI S200, AISI S210, AISI S211.

DESIGN LOADS

Table of design loads including live loads, snow loads, wind loads, and earthquake design data with values for uniform and concentrated loads.

FOUNDATIONS

- 1. FOUNDATION DESIGN IS BASED ON RECOMMENDATIONS IN THE GEOTECHNICAL REPORT NO. B1803403, PREPARED BY BRAUN INTERTECT CORP. DATED MAY 4, 2018. CONTRACTOR SHALL REVIEW GEOTECHNICAL REPORT PRIOR TO CONSTRUCTION.
2. FOUNDATIONS ARE DESIGNED TO BEAR ON UNDISTURBED NATURAL SOILS OR PROPERLY COMPACTED ENGINEERED FILL WITH A NET ALLOWABLE BEARING CAPACITY OF 2,000 PSF.
...
11. DO NOT PLACE FILL OR CONCRETE ON FROZEN GROUND.

CAST-IN-PLACE CONCRETE AND REINFORCEMENT

- 1. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH ACI 318.
2. CONCRETE SHALL HAVE THE FOLLOWING 28-DAY COMPRESSIVE STRENGTHS:
CAST-IN-PLACE CONCRETE 4,000 PSI
FILL CONCRETE 1,500 PSI
...
27. ALL HOOKS SHALL BE ACI STANDARD HOOKS UNLESS DIMENSIONED OTHERWISE.

CONCRETE MASONRY

- 1. MASONRY IS SUPPORTED IN THE COMPLETED CONSTRUCTION. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR SUPPORTING THE MASONRY DURING CONSTRUCTION IN CONFORMANCE WITH LOCAL, STATE AND NATIONAL LAWS AND AS REQUIRED.
2. MASONRY CONSTRUCTION AND MATERIAL SHALL CONFORM TO ALL REQUIREMENTS OF 'SPECIFICATIONS FOR MASONRY STRUCTURES' (ACI 530.1/ASCE 6) EXCEPT AS MODIFIED IN THE SPECIFICATIONS AND BELOW.
...
25. PROVIDE CLEANOUTS IF GROUT LIFT EXCEEDS 4'-0" IN BLOCK WALLS. MAXIMUM GROUT LIFT SHALL BE 8'-0".

PRECAST CONCRETE LINTELS

- 1. PRECAST CONCRETE LINTELS SHALL BE MANUFACTURED AND INSTALLED IN ACCORDANCE WITH THE PRECAST MANUFACTURER'S SPECIFICATIONS.
2. PROVIDE LINTELS OVER ALL MASONRY OPENINGS AND OVER RECESSES WIDER THAN 12 INCHES IN ACCORDANCE WITH THE ACCOMPANYING LINTEL SCHEDULE ON SHEET S0.2, UNLESS NOTED OTHERWISE ON DRAWINGS.
...
16. WHERE CONTROL JOINTS ARE AT ENDS OF LINTELS, PROVIDE 15 POUND FELT BOND BREAKER UNDER LINTEL BEARING AND DUMMY CONTROL JOINT ON EXPOSED FACES.

STRUCTURAL STEEL

- 1. STEEL SHALL BE FABRICATED BY A FABRICATOR HAVING AN AISC QUALITY CERTIFICATION CATEGORY: "STANDARD FOR STEEL BUILDING STRUCTURES (STD)."
2. STRUCTURAL STEEL WORK SHALL CONFORM TO THE "STEEL CONSTRUCTION MANUAL, AISC 360."
3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE DESIGN OF MEMBERS AND CONNECTIONS FOR ANY PORTION OF THE STRUCTURE NOT INDICATED ON THE PLANS.
...
19. PROVIDE HARDENED STEEL WASHERS CONFORMING TO ASTM F436 AND HEAVY HEX NUTS ON ANCHOR RODS.

STEEL JOISTS AND JOIST GIRDERS

- 1. ALL STEEL JOISTS, INCLUDING ANCHORAGE AND BRIDGING, SHALL BE FABRICATED AND ERECTED IN ACCORDANCE WITH THE STEEL JOIST INSTITUTE 'STANDARD SPECIFICATIONS, LOAD TABLES AND WEIGHT TABLES FOR STEEL JOISTS AND JOIST GIRDERS'.
2. JOIST SIZES INDICATED ON THE PLANS ARE THE MINIMUMS. JOIST AND GIRDER LOADS SHOWN ON THE PLANS ARE SUPERIMPOSED AND DO NOT INCLUDE SELF-WEIGHT.
...
20. JOIST MANUFACTURER SHALL ALIGN WEB MEMBERS OF ADJACENT JOISTS WITH THE SAME DEPTH TO PERMIT MECHANICAL, ELECTRICAL, AND PLUMBING APPURTENANCES TO PASS THROUGH THE JOIST.

REVISIONS

Table with 3 columns for revision numbers (1, 2, 3) and 3 rows for revision details.

AutoZone Store No. 6890
1593 NORTH MAIN STREET
LILLINGTON, NC 27546

DRAWN BY: SMA
DESIGNED BY: CR

AutoZone logo and contact information for Paul J. Ford & Company, Inc.

Professional Engineer Seal for Brian Wayne Starrett, No. 044971.

Professional Engineer Seal for Brian Wayne Starrett, No. 044971.

05/19/2020
05/13/2020
65W2
S0

Vertical text on the left margin: C:\projects\AutoZone\Projects\S02 - AutoZone\AutoZone-462726-0039.dwg - 3/19/2020 1:27:09 PM

METAL DECK

- DESIGN, FABRICATION AND INSTALLATION OF STEEL DECK UNITS SHALL CONFORM TO THE STEEL DECK INSTITUTE 'DESIGN MANUAL FOR COMPOSITE DECKS, FORM DECKS AND ROOF DECKS AND AISI NAs, AISI S210.
- ROOF DECK:
 - 1-1/2 INCH DEEP GALVANIZED WIDE RIB STEEL DECK:

20 GAUGE: $l_{min} = 0.210 \text{ IN}^4$
 $S_{x(min)} = 0.232 \text{ IN}^3$
 $S_{y(min)} = 0.245 \text{ IN}^3$
- GALVANIZED STEEL ROOF DECK AND ACCESSORIES SHALL CONFORM TO ASTM A653 (STRUCTURAL QUALITY) WITH A MINIMUM YIELD STRENGTH OF 33 KSI WITH A MINIMUM G60 GALVANIZING FINISH IN ACCORDANCE WITH ASTM A924. PRIME PAINTED STEEL ROOF DECK AND ACCESSORIES SHALL CONFORM TO ASTM A1008 WITH A MINIMUM YIELD STRENGTH OF 33 KSI.
- STEEL DECKING SHALL BE ATTACHED TO SUPPORTING STRUCTURAL FRAMING AS INDICATED IN TYPICAL DECK ATTACHMENT DETAIL. ATTACHMENT SHALL BE PERFORMED IN ACCORDANCE WITH THE MORE STRINGENT REQUIREMENTS FROM BOTH SDI OR THE DECK MANUFACTURER'S SPECIFICATIONS.
- STEEL DECK SHALL BE CONTINUOUS OVER THREE SPANS. USE HEAVIER GAGE DECK WHEN DECK IS NOT CONTINUOUS OVER THREE SPANS TO PROVIDE SIMILAR ALLOWABLE LOAD CAPACITIES.

COLD-FORMED METAL FRAMING


- COLD FORMED METAL FRAMING SHALL CONFORM TO THE REQUIREMENTS OF THE AISI S100, AISI S200, AISI 211.
- PRIOR TO FABRICATION OF FRAMING, THE CONTRACTOR SHALL SUBMIT FABRICATION AND ERECTION DRAWINGS TO THE ENGINEER FOR APPROVAL. SAID DRAWINGS SHALL BE DESIGNED, DETAILED, SIGNED AND SEALED BY A STRUCTURAL ENGINEER REGISTERED IN THE STATE OF THE PROJECT.
- COLD-FORMED MEMBERS SHALL BE FORMED FROM CORROSION-RESISTANT STEEL CONFORMING TO ASTM 653 WITH YIELD AS FOLLOWS:

18 GAGE AND THINNER	33 KSI
16 GAGE AND THICKER	50 KSI
- MEMBERS THAT ARE PART OF THE EXTERIOR ENVELOPE OF THE BUILDING SHALL HAVE A MINIMUM G90 COATING.
- ALL THE COLD FORMED MEMBERS SHALL COME FROM A SINGLE MANUFACTURER. THE INSTALLATION SHALL COMPLY WITH THE MANUFACTURER'S RECOMMENDATIONS.
- FASTENING OF COMPONENTS SHALL BE WITH SELF-DRILLING CORROSION RESISTANT (OR ZINC COATED) SCREWS. SCREWS SHALL BE OF SUFFICIENT SIZE TO ENSURE THE STRENGTH OF THE CONNECTION.
- SPLICES IN FRAMING COMPONENTS OTHER THAN TRACK ARE NOT PERMITTED.
- STUDS SHALL BE INSTALLED SO THE ENDS ARE POSITIONED AGAINST THE INSIDE OF THE RUNNER TRACK WEB PRIOR TO FASTENING AND SHALL BE ATTACHED TO BOTH FLANGES OF THE UPPER AND LOWER RUNNER TRACKS.
- ATTACH TRACKS TO STRUCTURAL STEEL AND CONCRETE WITH ONE POWDER DRIVEN FASTENER, AS LISTED BELOW, AT EACH STUD LOCATION, UNLESS NOTED OTHERWISE.
 - IN STEEL:
 - KNURLED SHANKS.
 - 1/4" MINIMUM PENETRATION.
 - MINIMUM STRENGTH CAPACITIES OF 350 LB PULLOUT AND 700 LB SHEAR.
 - SPACING NO CLOSER THAN 1-1/2" OC AND NO CLOSER THAN 1/2" TO EDGE OF THE STEEL MEMBER.
- MEMBERS SHALL HAVE THE FOLLOWING MINIMUM PROPERTIES:

MEMBER	SIZE	DEPTH	GAGE	F _y (KSI)	GROSS AREA (IN ²)	I _{eff} (IN ⁴)	S _{eff} (IN ³)
STUD	6"	16	50	0.556	2.86	0.916	
TRACK	6"	16	50	0.509	2.40	0.609	
- ALL STUDS SHALL BE SECURELY SEATED FOR FULL END BEARING ON TOP AND BOTTOM TRACK.

N.T.S.

GENERAL NOTES



N.T.S.

1 TYPICAL SLAB ON GRADE JOINT PATTERN

POST-INSTALLED FASTENERS


- POST-INSTALLED ANCHORS SHALL ONLY BE USED WHERE SPECIFIED ON THE DRAWINGS.
- INSTALL BOLTS AND FASTENERS TO MISS REINFORCING.
- PRIOR TO DRILLING FOR THE ANCHOR CONCRETE REINFORCING STEEL SHALL BE LOCATED WITH A MAGNETIC BAR LOCATOR.
- FASTENERS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S PRINTED INSTALLATION INSTRUCTIONS AND AS GIVEN BELOW. NOTIFY THE ENGINEER IF CONFLICTS EXIST BETWEEN THE MANUFACTURER'S PRINTED INSTALLATION INSTRUCTIONS AND THE BELOW REQUIREMENTS.
- FASTENERS SHALL BE INSTALLED AT NOT LESS THAN THE MANUFACTURER'S MINIMUM EDGE DISTANCES AND/OR SPACINGS INDICATED IN THE MANUFACTURER'S LITERATURE, UNLESS INDICATED ON THE STRUCTURAL DRAWINGS OR APPROVED BY THE ENGINEER OF RECORD.
- DRILL HOLES USING ROTARY PERCUSSION DRILL WITH A DEPTH GAGE. DO NOT DRILL THROUGH FULL THICKNESS OF MASONRY. CLEAN HOLES BY VIGOROUSLY BRUSHING AND THEN BLOW OUT LOOSE MATERIAL USING OIL-FREE COMPRESSED AIR. THE BRUSH SHALL HAVE THE STIFF NON-METALLIC BRISTLES OF TYPE AND DIAMETER RECOMMENDED BY THE ADHESIVE MANUFACTURER. IF CONCRETE IS DAMP BLOW DRY HOLE WITH OIL-FREE COMPRESSED AIR. CLEAN WITH WATER ONLY IF RECOMMENDED BY MANUFACTURER. ADHESIVE ANCHORS MAY NOT BE SET IF WATER IS SEEPING INTO HOLE. NOTIFY THE ENGINEER.
- ADHESIVE DOWELS AND ANCHORS IN MASONRY SHALL BE OF THE TYPE SHOWN AND INSTALLED USING 'HIT HY-270' BY HILTI OR APPROVED EQUAL.
- EXPANSION BOLTS IN CONCRETE AND FULLY GROUTED MASONRY SHALL BE HILTI 'KWIK BOLT 3', SIMPSON 'WEDGE ALL' OR APPROVED EQUAL.
- CONTRACTOR SHALL SUBMIT MANUFACTURER'S LITERATURE FOR THE ANCHOR SYSTEM TO BE USED. THIS LITERATURE SHALL INCLUDE ANCHOR MATERIAL, STRENGTH DATA, EMBEDMENT LENGTH, DRILL BIT SIZE AND THE MANUFACTURER'S PRINTED INSTALLATION INSTRUCTIONS. FOR ADHESIVE ANCHORS INCLUDE ADHESIVE CHEMISTRY.

SPECIAL INSPECTIONS

- PER THE IBC SECTION 1704, SPECIAL INSPECTIONS ARE REQUIRED FOR THE FOLLOWING ITEMS:
- STRUCTURAL STEEL:
 - MATERIAL VERIFICATION OF HIGH STRENGTH BOLTS, NUTS AND WASHERS. (PERIODIC)
 - INSPECTION DURING THE TIGHTENING OF HIGH STRENGTH BOLTS IN:
 - BEARING-TYPE CONNECTIONS (PERIODIC)
 - MATERIAL VERIFICATION OF STRUCTURAL STEEL
 - MATERIAL VERIFICATION OF WELD FILLER MATERIALS
 - VISUAL INSPECTION OF FIELD WELDS:
 - SINGLE-PASS FILLET WELDS $\leq 5/16"$ (PERIODIC)
 - SPECIAL INSPECTIONS ARE NOT REQUIRED FOR WORK DONE ON THE PREMISES OF AN APPROVED FABRICATOR.
 - CONCRETE:
 - INSPECTION OF REINFORCING STEEL AND PLACEMENT. (PERIODIC)
 - INSPECTION DURING WELDING OF REINFORCING STEEL:
 - VERIFICATION OF WELDABILITY OF REINFORCING STEEL OTHER THAN ASTM A706. (PERIODIC)
 - SHEAR REINFORCEMENT. (CONTINUOUS)
 - OTHER REINFORCING STEEL. (PERIODIC)
 - INSPECT BOLTS TO BE INSTALLED IN CONCRETE PRIOR TO AND DURING PLACEMENT OF CONCRETE. (CONTINUOUS)
 - VERIFYING USE OF REQUIRED MIX DESIGN. (PERIODIC)
 - AT THE TIME FRESH CONCRETE IS SAMPLED TO FABRICATE SPECIMENS FOR STRENGTH TESTS, PERFORM SLUMP AND AIR CONTENT TESTS, AND DETERMINE THE TEMPERATURE OF THE CONCRETE. (CONTINUOUS)
 - INSPECTION OF CONCRETE PLACEMENT FOR PROPER APPLICATION TECHNIQUES. (CONTINUOUS)
 - INSPECTION OF SPECIFIED CURING AND TEMPERATURE AND TECHNIQUES. (PERIODIC)
 - INSPECT FORMWORK FOR SHAPE, LOCATION AND DIMENSIONS OF THE CONCRETE MEMBER BEING FORMED. (PERIODIC)
 - NO INSPECTION IS REQUIRED FOR SLABS ON GRADE.


N.T.S.

2 TYPICAL JOINT DETAILS



N.T.S.

3 TYPICAL CONSTRUCTION JOINT DETAIL



N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

5 NOT USED

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.


6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.






6 TYPICAL CONC WALL CORNER DETAIL

N.T.S.

6 TYPICAL CONC WALL CORNER DETAIL




- FOUNDATION PLAN NOTES:**
- SEE S0, S0.1 AND S0.2 FOR GENERAL NOTES AND TYPICAL DETAILS.
 - AT PERIMETER OF BUILDING, DIMENSIONS ARE MEASURED TO THE OUTSIDE FACE OF CMU WALL.
 - SEE ARCHITECTURAL DRAWINGS FOR ALL MEASUREMENTS NOT SHOWN. ALL DIMENSIONS SHALL CONFORM TO THE ARCHITECTURAL DRAWINGS.
 - CONTRACTOR SHALL EXERCISE EXTREME CAUTION SO AS NOT TO UNDERMINE, DISTURB, DAMAGE OR, IN ANY WAY, CAUSE UNDESIRABLE MOVEMENT, CRACKING, AND/OR SETTLEMENT OF THE ADJACENT CONSTRUCTION.
 - TOP OF SLAB ELEVATION = 0'-0". FLOOR CONSTRUCTION: 5" CONCRETE SLAB-ON-GRADE WITH 6X6-W1-4XW1.4 WVF OR FIBERMESH. (SEE SPECIFICATIONS FOR FIBERMESH REQUIREMENTS). MAINTAIN MESH ELEVATION AT ONE HALF THE THICKNESS OF THE SLAB. PLACE SLAB OVER A 10 MIL. POLYETHYLENE VAPOR BARRIER OVER 4" COMPACTED GRANULAR FILL.
 - CONTRACTOR SHALL COORDINATE SLAB FINISHES AND SLOPES WITH ARCH AND CIVIL/SITE DRAWINGS.
 - FOR CONTRACTION JOINTS, SAW CUT ONE QUARTER SLAB THICKNESS, TYPICAL. SEE TYPICAL CONTRACTION JOINT DETAILS ON SHEET S0.1.
 - TOP OF FOOTING ELEVATION SHALL BE -0'-10", TYP. UNO.
 - BOTTOM OF FOOTING DETAILS SHOWN ARE BASED UPON FOUNDATIONS BEARING ON MATERIALS AS LISTED IN FOUNDATION GENERAL NOTE NO. 2 ON SHEET S0. BEARING ELEVATIONS HAVE BEEN ESTABLISHED FROM THE GRADING PLAN AND SOILS REPORT. FOUNDATION BEARING SURFACES MUST BE INSPECTED AND APPROVED IN ACCORDANCE WITH FOUNDATION GENERAL NOTE NO. 4 ON SHEET S0 AND BOTTOM OF FOOTING ELEVATIONS ADJUSTED ACCORDINGLY.
 - WALLS SHALL BE CENTERED ON FOOTING, UNO.
 - COORDINATE LOCATION AND SIZE OF PENETRATIONS AND OPENINGS WITH MECHANICAL AND SITE DRAWINGS. NO PENETRATIONS SHALL DISTURB THE FOUNDATIONS.
 - EXTERIOR PAVEMENT IS NOT SHOWN FOR CLARITY. SEE CIVIL/ARCH DRAWINGS FOR LOCATIONS AND DIMENSIONS.




AutoZone Store No. 6890 1593 NORTH MAIN STREET LILLINGTON, NC 27546		DRAWN BY: SMA DESIGNED BY: CR	
PF PAUL J. FORD & COMPANY 285 E Broad St, Ste 400, Columbus, OH 43215 Phone 614.221.6679 www.pauljford.com A62720-0039 CORP NO. C-2090		05/19/2020 05/13/2020 65W2 S1.0	

C:\constructions\10_Plan\10_Coupler_Plan\10_S1.0 - AutoZone\2020-05-13\10_S1.0.dwg
 05/13/2020 10:21:42 AM
 Lillington, NC
 1/8" = 1'-0"
 3/4" = 1'-0"
 3/4" = 1'-0"
 1/8" = 1'-0"




FOUNDATION PLAN NOTES:


- SEE S0, S0.1 AND S0.2 FOR GENERAL NOTES AND TYPICAL DETAILS.
- AT PERIMETER OF BUILDING, DIMENSIONS ARE MEASURED TO THE OUTSIDE FACE OF CMU WALL.
- SEE ARCHITECTURAL DRAWINGS FOR ALL MEASUREMENTS NOT SHOWN. ALL DIMENSIONS SHALL CONFORM TO THE ARCHITECTURAL DRAWINGS.
- CONTRACTOR SHALL EXERCISE EXTREME CAUTION SO AS NOT TO UNDERMINE, DISTURB, DAMAGE OR, IN ANY WAY, CAUSE UNDESIRABLE MOVEMENT, CRACKING, AND/OR SETTLEMENT OF THE ADJACENT CONSTRUCTION.
- TOP OF SLAB ELEVATION = 0'-0". FLOOR CONSTRUCTION: 5" CONCRETE SLAB-ON-GRADE WITH 6X6-W1.4XW1.4 WWF OR FIBERMESH. (SEE SPECIFICATIONS FOR FIBERMESH REQUIREMENTS). MAINTAIN MESH ELEVATION AT ONE HALF THE THICKNESS OF THE SLAB. PLACE SLAB OVER A 10 MIL. POLYETHYLENE VAPOR BARRIER OVER 4" COMPACTED GRANULAR FILL.
- CONTRACTOR SHALL COORDINATE SLAB FINISHES AND SLOPES WITH ARCH AND CIVIL/SITE DRAWINGS.
- FOR CONTRACTION JOINTS, SAW CUT ONE QUARTER SLAB THICKNESS, TYPICAL. SEE TYPICAL CONTRACTION JOINT DETAILS ON SHEET S0.1.
- TOP OF FOOTING ELEVATION SHALL BE -0'-10", TYP, UNO.
- BOTTOM OF FOOTING DETAILS SHOWN ARE BASED UPON FOUNDATIONS BEARING ON MATERIALS AS LISTED IN FOUNDATION GENERAL NOTE NO. 2 ON SHEET S0. BEARING ELEVATIONS HAVE BEEN ESTABLISHED FROM THE GRADING PLAN AND SOILS REPORT. FOUNDATION BEARING SURFACES MUST BE INSPECTED AND APPROVED IN ACCORDANCE WITH FOUNDATION GENERAL NOTE NO. 4 ON SHEET S0 AND BOTTOM OF FOOTING ELEVATIONS ADJUSTED ACCORDINGLY.
- WALLS SHALL BE CENTERED ON FOOTING, UNO.
- COORDINATE LOCATION AND SIZE OF PENETRATIONS AND OPENINGS WITH MECHANICAL AND SITE DRAWINGS. NO PENETRATIONS SHALL DISTURB THE FOUNDATIONS.
- EXTERIOR PAVEMENT IS NOT SHOWN FOR CLARITY. SEE CIVIL/ARCH DRAWINGS FOR LOCATIONS AND DIMENSIONS.




1 SECTION AT CMU WALL (CONCRETE)




2 SECTION AT STOREFRONT (CONCRETE)



3 SECTION AT DOOR (CONCRETE)




4 SECTION AT PILASTER (CONCRETE)




5 SECTION AT WALL COLUMN (CONCRETE)

FOUNDATION PLAN




6 INTERIOR COLUMN SECTION




7 PLAN AT EXTERIOR PILASTER

REVISIONS		
1	2	3
4	5	6
AutoZone Store No. 6890 1593 NORTH MAIN STREET LILLINGTON, NC 27546		
DRAWN BY: SMA		DESIGNED BY: CR
PF PAUL J. FORD & COMPANY 285 E Broad St., Ste. 400, Columbus, OH 43215 Phone 614.221.6679 www.pauljford.com AA2720-0039 CORP NO. C-2090		
05/19/2020		
05/13/2020		
65W2		
S1.0A		



1/8" = 1'-0"
1 | HVAC ROOF TOP PLAN



MECHANICAL NOTES

DESIGN PARAMETERS

MECHANICAL CODE: 2018 INTERNATIONAL MECHANICAL CODE

OUTSIDE AIR REQUIREMENTS:
 OCCUPANCY CLASSIFICATION - RETAIL (SALES)
 BUILDING AREA FOR OCCUPANCY - 6,446 SQUARE FEET
 OCCUPANT LOAD - 6,446 / 1000 x 15 = 97 PEOPLE
 OCCUPANT OUTSIDE AIR - 98 x 7.5 CFM = 728
 AREA OUTSIDE AIR - 6,446 x .12 CFM = 774 CFM
 TOTAL OUTSIDE AIR REQUIRED - 728 CFM + 774 CFM = 1,502 CFM

GENERAL MECHANICAL NOTES

A. ALL DUCTWORK IS EXPOSED IN THE CONDITIONED SPACE AND DOES NOT REQUIRE ANY INSULATION. THE DUCTWORK PACKAGE AND AIR DEVICES WILL BE FURNISHED BY AUTOZONE FOR INSTALLATION BY THE CONTRACTOR.

B. THE FIRESTATS, SMOKE DETECTORS, FRESH AIR INTAKES AND/OR ECONOMIZERS WILL BE PROVIDED, AS REQUIRED BY LOCAL CODE, BY AUTOZONE FOR INSTALLATION BY THE CONTRACTOR.

C. THE PACKAGE ROOF MOUNTED HEATING / COOLING UNITS, ROOF CURBS, AND VENSTAR THERMOSTATS WILL BE FURNISHED BY AUTOZONE FOR INSTALLATION BY THE CONTRACTOR. SEE SCHEDULE ON SHEET M-1.1 FOR THE AIR FLOW FOR EACH UNIT SCHEDULED. PRIOR TO ACTIVATING ANY RTU PLACE ALL OPERATING MANUALS AND LITERATURE IN THE PHONE/ALARM CLOSET FOR USE BY THE OWNER.

D. THE TOILET EXHAUST FAN WILL BE FURNISHED BY AUTOZONE FOR INSTALLATION BY THE CONTRACTOR. THE FAN IS A BROAN NO. 503 WITH 160 CFM CAPACITY. CONTRACTOR TO FURNISH AND INSTALL METAL DUCT AND WALL CAP.

E. THE THERMOSTATS SHALL BE SET FOR 78° F IN THE COOLING MODE AND 68° F IN THE HEATING MODE.

F. THE FLEXIBLE GAS CONNECTION TO EACH UNIT TO BE NO MORE THAN 2'-0" LONG.

G. CONTRACTOR SHALL STENCIL RTU NUMBER ON ALL ROOFTOP UNITS. STENCILING SHALL BE ON ROOF HATCH SIDE ONLY.

H. REFER TO SHEET A1 FOR BUILDING DIMENSIONS AND S2 FOR HVAC LOCATIONS.

I. ALL ABOVE GROUND WATER SUPPLY PIPING SHALL BE INSULATED.

J. ATTACH LIGHTING CONTROL PANEL PHOTOCELL TO THE NORTH FACING SIDE OF ONE OF THE ROOF TOP HVAC UNITS. DO NOT ATTACH PHOTOCELL TO A REMOVABLE PANEL. CONNECT PHOTOCELL THROUGH ONE OF THE HVAC UNIT HUBS - DO NOT DRILL A HOLE IN THE BOTTOM OF THE UNIT - TO A JUNCTION BOX MOUNTED ON THE UNDERSIDE OF THE ROOF DECK AND THEN ON TO THE LIGHTING CONTROL PANEL. SEE SHEETS M-1.1 AND E-6 FOR ADDITIONAL INFORMATION.

3/32" = 1'-0"

3 | MECHANICAL NOTES

A. THE EQUIPMENT AND MATERIALS FOR THIS PROJECT HAVE BEEN SPECIFICALLY SELECTED FOR THIS APPLICATION. MANY ITEMS FOUND IN THE HVAC PACKAGE ARE UNIQUE TO AUTOZONE. THE HVAC PACKAGE WILL BE FURNISHED TO THE CONTRACTOR FOR INSTALLATION, START-UP, AND SYSTEM VERIFICATION.

B. THE INSTALLING CONTRACTOR IS RESPONSIBLE FOR PROVIDING A COMPLETE SYSTEM THAT CONFORMS TO THE PLANS AND SPECIFICATIONS.

C. ALL DAMAGE AND / OR WARRANTY CLAIMS ARE SUBJECT TO INSPECTION AND REVIEW BY BOTH AUTOZONE AND THE EQUIPMENT MANUFACTURER. SEE NOTES ON SHEET M-1.1 FOR FURTHER INFORMATION REGARDING DAMAGE AND WARRANTY CLAIMS. FILING OF A CLAIM DOES NOT RELIEVE THE HVAC CONTRACTOR OF HIS RESPONSIBILITIES DESCRIBED ABOVE AND IN THE SPECIFICATIONS TO PROVIDE A COMPLETE AND FINISHED SYSTEM.

D. FIRESTATS, SMOKE DETECTORS, DUCT SENSORS AND REMOTE THERMOSTATS TO BE INSTALLED ACCORDING TO THE MANUFACTURERS' SPECIFICATIONS AND INSTRUCTIONS.

E. ROOFTOP UNITS MAY CONTAIN ONE OR MORE OF THE FOLLOWING ITEMS DEPENDENT ON PROJECT GEOGRAPHIC LOCATION AND CODE REQUIREMENTS: ECONOMIZER, HAIL GUARDS, CORROSION PROTECTION, HORN AND STROBE UNITS, ETC.

F. CUT NO HOLES IN BOTTOM PAN OF ROOFTOP UNIT. CONTRACTOR TO USE FACTORY INSTALLED HUB LOCATIONS TO RUN POWER AND/OR CONTROL WIRING.

3/4" = 1'-0"

4 | PIPE SUPPORT

1. SUPPORT ALL PIPING ON TREATED 2"x4" WOOD BLOCKING SET DIRECTLY ON ROOFING, AND CLAMP PIPE TO EACH SUPPORT. BLOCKING SHALL BE SPACED A MAXIMUM OF 6'-0" ON CENTER FOR GAS PIPE AND 3'-0" FOR PVC PIPE. PROVIDE ADDITIONAL SUPPORTS AT EACH BEND AND "T" CONNECTION.

2. MOUNT TWO (2) THERMOSTATS ON THE WALL - SEE SHEET E5.

3. CONTRACTOR TO FURNISH & INSTALL METAL EXHAUST DUCT AND METAL WALL CAP FOR EACH BATHROOM EXHAUST FAN, RUN DUCT WORK IN CEILING JOIST SPACE. SEE ELECTRICAL SHEETS FOR FAN LOCATION AND SPECIFICATIONS FOR ADDITIONAL INFORMATION.

4. COORDINATE WITH THE LOCAL UTILITY COMPANY FOR GAS METER LOCATION AND GAS PIPE SIZES. REFER TO THE SCHEDULE ON SHEET M-1 FOR MAXIMUM ESTIMATED LOAD.

3/4" = 1'-0"

4 | PIPE SUPPORT

CLAMP SIZED TO FIT PIPE ATTACH TO EACH BLOCK

PIPE: SEE PLAN FOR LOCATION AND SIZES. GAS PIPING TO BE PRIMED AND PAINTED.

TREATED WOOD BLOCKING: MINIMUM SIZE OF BLOCK TO BE 4"x4"x8" LONG. (FELT WRAPPED BLOCKING IS NOT ACCEPTABLE) PROVIDE BLOCKING AT ALL CHANGES IN DIRECTION AND 6' CENTERS FOR GAS PIPING AND 3' CENTERS FOR PVC CONDENSATE PIPING.

3/4" = 1'-0"

1/8" = 1'-0"

5 | HVAC PACKAGE NOTES

MARK	BRAND	MODEL	CFM @ 1/8" S.P.	SONES	ELEC. REQUIREMENT	COMMENTS
TEF-1	BROAN	503	160	5	120V-1PH-60HZ	INTERLOCK WITH LIGHT CONTROL
TEF-2	BROAN	503	160	5	120V-1PH-60HZ	INTERLOCK WITH LIGHT CONTROL

NOTE:
CONTRACTOR SHALL FURNISH AND INSTALL AN 8" METAL DUCT AND METAL WALL CAP. THE WALL CAP SHALL HAVE A BACK-DRAFT DAMPER AND INSECT SCREEN.

6 | HEATING & COOLING PLAN NOTES

7 | TOILET EXHAUST FAN SCHEDULE

1/8" = 1'-0"

2 | HVAC LEGEND

- INDICATES ROOF OPENING
- CONDENSATE DRAIN
- THERMOSTAT
- WP GFI WEATHERPROOF GFI OUTLET
- ELECTRICAL DISCONNECT
- DW DOMESTIC WATER
- GAS INLET

1/8" = 1'-0"

8 | GAS RISER

NOTE:
THE OVER ALL LENGTH OF PIPE USED TO CALCULATE PIPE SIZE IS 140 MULTIPLIED BY 1.25 FOR TURNS AND ELBOWS TO GIVE A TOTAL DEVELOPED LENGTH OF 175 FEET. THE TABLE USED TO SIZE THE GAS PIPING IS TABLE 402.4(2) OF THE INTERNATIONAL FUEL GAS CODE. TOTAL MBH OF THIS PROJECT IS 360 MBH.

NOTE 4/M1

NOTE 3/M1

NOTE 2/M1

SEE SHEET M2 FOR PLANS & DETAILS

ROOF HATCH AND SAFETY RAIL SYSTEM SEE SPECS.

ROOF HYDRANT

14 M2

1 1/4"

1 1/4"

1 1/4"

1 1/2"

1 1/4"

RTU-2

RTU-1

4 M1

5 M1

TYPICAL ALL UNITS

ROOF SLOPE DIRECTION OF


8 M1

REVISIONS	4	5	6
1	2	3	

AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546
HEATING AND COOLING

ENGINEER: DANNY E. DOSS P.E.
132 Kelley Drive
Rogers, Arkansas 72756
TEL: (479) 631-1712 FAX: (479) 631-1854
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com

05/06/20
65W2-R
M-1



- PACKAGE DUCTWORK NOTES:
1. PACKAGE DUCTWORK IS FURNISHED BY AUTOZONE AND INSTALLED BY CONTRACTOR.
 2. THE BOTTOM OF THE DUCTS ARE TO BE NO LOWER THAN THE BOTTOM OF THE ROOF JOISTS.
 3. DUCTWORK IS 22ga. STEEL INTERNALLY INSULATED.
 4. DUCTWORK IS SHIPPED K/D DISASSEMBLED, CONTRACTOR TO ASSEMBLE IN THE FIELD.
 5. SUPPLY REGISTERS ARE SINGLE DEFLECTION WITH CURVED ADJUSTABLE BLADES.
 6. FACE BARS ON GRILLES ARE ADJUSTABLE TO CUSTOMIZE THE THROW AND PROFILE.
 7. GRILLES ARE DESIGNED TO THROW 24 FEET AT 450 CFM
 8. DUCT PACKAGE IS DESIGNED TO HANDLE 1600 - 2400 CFM WITH .03 STATIC PRESSURE DROP (ALL GRILLES).
 9. RETURN GRILL IS 1/2" STANDARD EXPANDED METAL WITH GASKET.

1/8" = 1'-0"

1 | POWER PLAN

1. YORK ROOF TOP UNITS WILL BE FURNISHED TO THE JOB SITE ON A SCHEDULED DELIVERY BASIS. THE CURBS, DUCT DROP AND DUCT PACKAGES WILL COME SEPARATELY FROM A THIRD PARTY YORK VENDOR. ALL ITEMS MUST BE REQUESTED WITH A NEEDED DELIVERY DATE IN THE AFI SCHEDULE REQUEST FORM AND SENT TO THE VENDOR AS SOON AS THE JOB NTP'S.

2. ONCE CONSTRUCTION HAS COMMENCED IT WILL BE THE GENERAL CONTRACTOR'S RESPONSIBILITY TO STAY IN TOUCH WITH THE YORK CONTRACT AND TO SCHEDULE THE ACTUAL DATE THE ROOF TOP UNIT ARE TO BE DELIVERED TO THE JOB SITE.

3. IT IS EXPECTED THAT WHEN UNITS ARE DELIVERED THEY WILL GO FROM TRUCK TO ROOF AND NOT BE LEFT ON THE GROUND. IF THE JOB SCHEDULE WILL NOT ACCOMMODATE THE ORIGINAL REQUESTED DELIVERY DATE THEN THE GENERAL CONTRACTOR MUST CALL YORK AND RESCHEDULE. UNITS ARE NOT TO BE LEFT ON THE GROUND WHERE THEY MAY BE SUBJECT TO DAMAGE.

4. WHEN UNITS ARRIVE THEY SHOULD BE INSPECTED FOR DAMAGE, AS THE AUTOZONE POLICY ONLY ALLOWS THE GENERAL CONTRACTOR 72 HOURS TO REPORT DAMAGE OR ANY PROBLEM, AFTER WHICH THE ISSUE BECOMES THE CONTRACTORS TO RESOLVE. IF THE DAMAGE IS SUPERFICIAL OR COSMETIC THEN THE UNITS SHOULD BE ACCEPTED, INSTALLED AND REPAIRED IN THE FIELD. IF THE DAMAGE AFFECTS THE OPERATION OF THE UNIT THEN IT SHOULD BE NOTED ON THE BILL OF LADING, NOTIFY YORK TO SCHEDULE A REPLACEMENT AND PICK-UP, AND NOTIFY THE AUTOZONE AFI MANAGER. SEE AUTOZONE AFI POLICY FOR ADDITIONAL INFORMATION.

5. CONTACTS:
TO SCHEDULE DELIVERY: SHAWNA STEPHENS 405-419-6272
TO REPORT DAMAGE: SHAWNA STEPHENS 405-419-6272
FOR TECHNICAL SUPPORT: LEROY BERRY 800-481-9738 OPTION 4
AUTOZONE AFI MANAGER: LEW ELLIS 901-495-8707

1. DOA (Dead on Arrival): LABOR ALLOWANCES APPLY ONLY TO THOSE SITUATIONS WHERE DEFECTS HAVE OCCURRED DIRECTLY AS A RESULT OF FACTORY WORKMANSHIP AND/OR MATERIALS. REIMBURSEMENT WILL NOT BE ALLOWED WHERE DAMAGE HAS BEEN SUSTAINED AS A RESULT OF MISAPPLICATION OR IMPROPER INSTALLATION.

2. FOR ALL DOA AND ANY OTHER WARRANTY ISSUES THE CONTRACTOR SHALL CALL THE YORK WARRANTY GROUP FOR INSTRUCTIONS ON HOW TO PROCEED. YORK WILL RESPOND TO ALL WARRANTY REQUESTS OR ISSUES WITHIN 24 HOURS. PROCEEDING WITH WORK IN ADVANCE OF NOTIFYING YORK MAY RESULT IN CONTRACTOR NOT BEING REIMBURSED FOR ALL OF HIS COSTS.

3. AS YORK HAS PRE ASSIGNED LABOR VALUES TO ALL PARTS OF THE ROOF TOP UNIT, CONTRACTOR MUST GET YORK'S CONCURRENCE IN THE CONTRACTOR'S ESTIMATED LABOR CHARGE TO DO THE WORK PRIOR TO COMMENCING, OR CONTRACTOR MUST AGREE TO YORK'S LABOR ALLOWANCE. PARTS WILL BE FURNISHED AT NO COST BY YORK, THEY MAY ASK CONTRACTOR TO RETURN THE DEFECTIVE PART AND CONTRACTOR MUST DO SO.

4. FOR EXPEDITED SERVICE CONTRACTOR SHOULD HAVE THE MODEL AND SERIAL NUMBER OF THE UNIT IN QUESTION PRIOR TO MAKING A CALL FOR WARRANTY SERVICE.


5. CONTACTS:
FOR WARRANTY ISSUES: JESSICA RIBBLE 800-481-9738 OPTION 4
FOR TECHNICAL SUPPORT: LEROY BERRY 800-481-9739 OPTION 4

1/8" = 1'-0"

3 | YORK WARRANTY NOTES


1/8" = 1'-0"

2 | YORK HVAC NOTES



No Scale

4 | ROOFTOP UNIT - VIEW OF RTU



No Scale

5 | ROOF CURB

MARK	MANUFACTURER MODEL NO.	SUPPLY AIR	MIN. O.S.A.	E.S.P.	COOLING DATA			HEAT INPUT		ELECTRICAL REQ. UNIT M.C.A. 208/3ø/60Hz	BREAKER	ECONOMIZER	COIL COATING	UNIT WEIGHT			
					ENT. AIR D.B. W.B.	TOTAL	SENSIBLE	EER	ENT. AIR D.B.						INPUT	OUTPUT	
RTU-1	YORK ZYG12D2	4000 CFM	750 CFM	0.25 IN.	80	67	131,300 BTU	94,100 BTU	11.5	70	180,000 BTU	144,000 BTU	51.4	60	Required	No	1005
RTU-2	YORK ZYG12D2	4000 CFM	755 CFM	0.25 IN.	80	67	131,300 BTU	94,100 BTU	11.5	70	180,000 BTU	144,000 BTU	51.4	60	Required	No	1005


3/32" = 1'-0"

6 | ROOFTOP UNIT HEATING AND COOLING SCHEDULE

REVISIONS		
1		
2		
3		
4		
5		
6		

AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546
HEATING AND COOLING


ENGINEER: DANNY E. DOSS P.E.
132 Kelley Drive
Rogers, Arkansas 72756
TEL: (479) 631-1712 FAX: (479) 631-1854
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com



05/06/20
65W2-R

M-1.1



© COPYRIGHT 2007



1/8" = 1'-0" PPI01R
1 PLUMBING WASTE/VENT RISER

- DIG HOLE FOR HYDRANT APPROXIMATELY 2 FEET IN DIAMETER AND DEEPER THAN THE BURY DEPTH.
- FLUSH GRAVEL, DEBRIS, ETC. OUT OF THE SUPPLY LINE BEFORE CONNECTING HYDRANT.
- INSTALL HYDRANT WITH DRAIN HOLE BELOW FROST LINE. USE WRENCHES ON SUPPLY LINE FITTING AND BRASS BODY VALVE ONLY. THIS AVOIDS OVERTIGHTENING THE HYDRANT ASSEMBLY WHICH COULD AFFECT OPERATION.
- IF SUPPLY LINE TO THE HYDRANT WILL NOT SUPPORT HYDRANT, USE RE-BAR, LENGTH OF PIPE OR OTHER SUITABLE SUPPORT DRIVEN IN BOTTOM OF PIT TO HELP SUPPORT HYDRANT. BEFORE FILLING EXCAVATION, TURN ON WATER AND CHECK HYDRANT CONNECTION FOR LEAKS.
- PROVISIONS MUST BE MADE TO ALLOW THE WATER TO DRAIN FROM THE HYDRANT DRAIN HOLE EACH TIME THE HYDRANT IS CLOSED.
 - IF THE HYDRANT IS TO BE INSTALLED IN A CONCRETE DRIVEWAY, CONNECT 1/8 INCH COPPER DRAIN TUBING TO THE DRAIN HOLE AND DIG A REMOTE DRAIN FIELD FOR THE DRAIN PIPE TO EMPTY INTO.
 - SATURATED GROUND IN THE HYDRANT DRAIN FIELD CAN PREVENT THE HYDRANT FROM DRAINING AND MAY RESULT IN THE HYDRANT FREEZING. IF THE AREA WHERE THE HYDRANT IS LOCATED IS LOW LYING OR HAS A TENDENCY TO HAVE STANDING WATER, A LARGER DRAIN FIELD OR PIT MAY BE REQUIRED TO PROVIDE THE HYDRANT A PLACE TO DRAIN.
 - FILL BOTTOM OF PIT WITH 1/2 INCH GRAVEL TO A LEVEL 3 INCHES ABOVE BRASS DRAIN VALVE BODY TO INSURE ADEQUATE DRAINAGE.

1/8" = 1'-0" PPN02
2 YARD HYDRANT INSTALLATION



1/2" = 1'-0" PPS02
4 GRADE CLEANOUT

PLUMBING NOTES:
DESIGN PARAMETERS

1. PLUMBING CODE: 2018 INTERNATIONAL PLUMBING CODE

2. PLUMBING OCCUPANCY CLASSIFICATION: Mercantile
BUILDING AREA FOR OCCUPANCY - See Sheet A-0 for area
OCCUPANT LOAD - See Sheet A-0 for occupancy

FIXTURE REQUIREMENTS:
WATER CLOSETS - 1 per 500 people
LAVATORY - 1 per 750 people
DRINKING FOUNTAIN - 1 per 1000 people
SERVICE (MOP) SINK - 1 per store

3. SEPARATE FACILITIES ARE REQUIRED FOR MEN AND WOMEN. THERE IS 1 WATER CLOSET AND 1 LAVATORY FOR EACH RESTROOM. IF REQUIRED BY CODE, THERE SHOULD BE 1 URINAL IN THE MEN'S RESTROOM.

GENERAL PLUMBING NOTES:

A. PIPE MATERIAL SHALL BE AS FOLLOWS:
SOIL, WASTE AND VENT (INSIDE BLDG.) - ASTM D2665 PVC-DWV WITH NSF SEAL
SOIL AND WASTE (OUTSIDE BLDG.) - ASTM D3034 PVC
DOMESTIC WATER (UNDER SLAB) - PEX PIPE SEE SPECIFICATIONS
DOMESTIC WATER (INSIDE ABOVE SLAB) - PEX PIPE SEE SPECIFICATIONS
DOMESTIC WATER MAIN (TO WITHIN 5' OF BLDG.) - PEX PIPE SEE SPECIFICATIONS
NATURAL GAS - ASTM A120, SCHEDULE 40 BLACK STEEL WITH FACTORY APPLIED PROTECTIVE COATING FOR UNDERGROUND APPLICATION.
CONDENSATE - PVC, SOLVENT WELDED

B. THE PIPE INSULATION SHALL BE AS FOLLOWS:
DOMESTIC COLD WATER - 1/2" POLYOLEFIN CLOSED CELL
DOMESTIC HOT WATER - ABOVE GRADE - SAME AS COLD WATER
BELOW GRADE - 3/8" CLOSED CELL SUITABLE FOR UNDERGROUND USE
CONDENSATE (INSIDE BUILDING) - 1/2" POLYOLEFIN CLOSED CELL

C. THE ELECTRIC WATER HEATER WILL BE A MINITANK, ARISTON MODEL GL-4-TI, FURNISHED BY AUTOZONE FOR INSTALLATION BY THE CONTRACTOR.

D. A BACKFLOW PREVENTER SHALL BE FURNISHED AND INSTALLED BY THE CONTRACTOR, WHEN REQUIRED BY LOCAL CODE. THE BACKFLOW PREVENTER SHALL BE A REDUCED PRESSURE ZONE TYPE, WATTS LF009M2QT SERIES. INSTALL THE BACKFLOW PREVENTER IN ACCORDANCE WITH LOCAL CODE. IF BACKFLOW PREVENTER IS INSTALLED INSIDE THE BUILDING, ROUTE THE DRAIN IN THE WALL TO THE MOP SINK AND TERMINATE ABOVE THE FLOOD RIM OF THE SINK.

E. THE WATER CLOSET SHALL BE A 1.6 GALLON PER FLUSH, MAXIMUM.

F. THE LAVATORY FAUCET SHALL HAVE A MAXIMUM FLOW RATE OF 1.0 GPM. THE HANDLES SHALL BE ALL BRASS AND HANDICAP ACCESSIBLE.


G. THE MOP SINK SHALL BE FLOOR MOUNTED. THE FAUCET SHALL HAVE AN INTEGRAL VACUUM BREAKER AND BUCKET HOOK.

H. ALL ABOVE GROUND WATER SUPPLY PIPING SHALL BE INSULATED.


I. FLOOR DRAINS SHALL BE PROVIDED ONLY WHEN REQUIRED BY CODE.

J. PROVIDE WATTS SERIES SHOCK ABSORBERS AT ALL QUICK CLOSING VALVES WHERE APPLICABLE.

K. SHUT OFF VALVES SHALL BE INSTALLED FOR EACH PLUMBING FIXTURE.



1/8" = 1'-0" PPI02R
5 PLUMBING WATER RISER




1 1/2" = 1'-0" PPS03
6 YARD HYDRANT

- HOLD 4" SANITARY VENT THRU ROOF TIGHT AGAINST EXTERIOR WALL BETWEEN TOILET CEILING AND BOTTOM OF ROOF STRUCTURE. OFFSET VENT A MINIMUM OF 12" FROM FACE OF WALL BEFORE PENETRATING ROOF DECK.
- MOUNT MAIN CUTOFF AT 24" A.F.F. IN RESTROOM, AS INDICATED ON ARCHITECTURAL ELEVATIONS.
- INSTALL FREEZELESS IOWA YARD HYDRANT MODEL Y 34 AS MANUFACTURED BY WOODFORD MANUFACTURING COMPANY. HYDRANT SHALL BE LOCATED IN A GRASS OR LANDSCAPE AREA SEE CIVIL DRAWINGS FOR EXACT DIMENSIONAL LOCATION.
- INSTALL YARD HYDRANT IN STRICT ACCORDANCE WITH MANUFACTURER'S PRINTED INSTRUCTIONS INCLUDING PROVIDING VERTICAL SUPPORT AND A BELOW GRADE DRAIN FIELD FOR YARD HYDRANT TO EMPTY INTO EACH TIME THE HYDRANT IS CLOSED.
- PROVIDE CUT-OFF IN A RECESSED ACCESS BOX IN RESTROOM WHERE INDICATED ON THE DRAWINGS FOR THE 3/4" WATER LINE THAT FEEDS THE YARD HYDRANT.
- SEE SITE PLAN TO VERIFY LANDSCAPE CONNECTION REQUIREMENTS AND LOCATIONS.
- BACKFLOW PREVENTER IF REQUIRED BY LOCAL CODE TO BE INSTALLED INSIDE THE BUILDING - SEE GENERAL PLUMBING NOTES: NOTE "D".


1/8" = 1'-0" PPN01
7 KEYED PLUMBING NOTES

- 12 MOUNTING HEIGHT SCHEDULE
- | FIXTURE | DIM. | REMARKS |
|-----------------------------------|------|-------------------------------------|
| TOILET SEATS (ACCESSIBLE) | 17" | 19" TOP OF SEAT MAX. |
| URINALS (WHEN REQ'D) (ACCESSIBLE) | 17" | TO RIM |
| LAVATORIES (ACCESSIBLE) | 34" | TO RIM, 29" MIN. TO BOTTOM OF APRON |
| WATER COOLER (ACCESSIBLE) | 36" | TO SPOUT |
| WATER HEATER | 60" | A.F.F. TO BOTTOM OF HEATER |
- 1/8" = 1'-0" PPC01
- 13 WATER HEATER INSTALLATION
-

1/8" = 1'-0" PPN01
8 PLUMBING NOTES



3/16" = 1'-0" PPP0165w2R
9 RESTROOM SEWER PLAN




3/16" = 1'-0" PPP0265w2R
10 RESTROOM WATER PLAN

	AMERICAN STANDARD	KOHLER	ELJER
P-1 TOILET (ELONGATED HANDICAP) 1.6 GPF	"CADET 3" #2386.800 R.H. "CADET 3" #2386.012 L.H. NOTE: TOILET TANK TRIP LEVER TO BE LOCATED ON LAVATORY SIDE OF TANK.	"HIGHLINE" #K-3427	"PATRIOT" #091-2175
P-2 LAVATORY	"LUCERNE" #0355.012	"GREENWICH" #2032	"DELWYN" #051-1634
FAUCET	MOEN #8800, 4 INCH CENTERS, 4 INCH WRIST BLADE WITH 1/4 TURN HANDLES, WASHERLESS CARTRIDGES, AND MOEN #52602 1 GALLON PER MINUTE FLOW REDUCER. CONTRACTOR SHALL FURNISH AND INSTALL A WATTS LFMV- MIXING VALVE TO SERVE THE FAUCETS (SET TO 110 F).		
DRAIN	MOEN #52660, OFFSET CHROME PLATED TALKIECE.		
P-3 SERVICE SINK	FIAT #MSB-2424 OR MUSTEE #63		
FAUCET	MOEN #8124		
P-4 WATER FOUNTAIN	HANDICAP ACCESSIBLE DUAL HEIGHT: ELKAY EZTL-8C OR HALSEY TAYLOR HTV8BL-Q		
P-5 URINAL (IF REQUIRED)	"TRIMBROOK" #6561.017	"BARDEN" #K-4960-T	"SAVON" #161-1090
FLUSH VALVE	SLOAN #186-1 OR ZURN #Z6003XL-WS1 OR A/S 6045.101		

1/8" = 1'-0" PPC02

1/8" = 1'-0" PPC02
11 PLUMBING FIXTURE SCHEDULE




1 1/2" = 1'-0" PPS04
14 ROOF HYDRANT

REVISIONS		
4	5	6
1	2	3

AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546
PLUMBING PLAN

ENGINEER: DANNY E. DOSS P.E.
132 Kelley Drive
Rogers, Arkansas 72756
TEL: (479) 631-1712 FAX: (479) 631-1854
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com

05/06/20
65W2-R
M-2



ELECTRICAL NOTES

DESIGN PARAMETERS: 2017 NATIONAL ELECTRICAL CODE
 COMPLY WITH LATEST EDITION OF NATIONAL ELECTRIC CODE ALONG WITH ALL LOCAL, STATE, AND UTILITY REGULATIONS OR LAWS. PROVIDE UL APPROVED MATERIALS AND DEVICES.

LOAD SUMMARY:

AUTOZONE ELECTRICAL LOAD SUMMARY			
LOAD NAME	CONNECTED VA	LOAD NAME	CONNECTED VA
INDOOR LIGHTING	4531	EQUIPMENT	26783
OUTDOOR LIGHTING	2643	COOLING	37440
RECEPTACLES	1620	TOTALS	74517
WATER HEAT	1500		

ITEMS FURNISHED BY AUTOZONE:

A. FUSED DISCONNECTS
 B. PANELBOARDS
 C. CIRCUIT BREAKERS
 D. ALL LIGHT FIXTURES
 E. LAMPS
 F. LIGHTING CONTROL PANEL & ACC.

G. OCCUPANCY SENSING LIGHT SWITCHES
 H. PHOTOCELLS
 I. CONTROL RELAYS
 J. BALLASTS
 K. SITE LIGHT POLES AND BRACKETS

WORK INCLUDED:

A. CONDUIT, WIRES, CABLE, AND WIRING DEVICES.
 B. PRIMARY WIRING, CONDUIT AND FINAL CONNECTIONS FOR ALL SIGN CIRCUITS.
 C. CONDUIT AND PULL STRINGS FOR DATA/TELEPHONE RUNS. (WIRING N.I.C.)
 D. CONDUIT AND PULL STRINGS FOR THERMOSTATS (WIRING BY MECHANICAL CONTRACTOR).
 E. CONDUIT AND PULL STRINGS FOR SECURITY SYSTEM (WIRING N.I.C.)
 F. FIELD TESTING.
 G. ELECTRIC SERVICE ENTRANCE AND UTILITY COORDINATION.
 H. TELEPHONE SERVICE ENTRANCE AND UTILITY COORDINATION.

SERVICE ENTRANCE, ELECTRIC AND TELEPHONE:

A. ALL WIRE CONNECTIONS AND TERMINATIONS IN WIREWAY, SERVICE DISCONNECTS AND PANELBOARDS SHALL BE RATED AT 75 DEG C.
 B. SUBMIT TO LOCAL UTILITY ALL REQUIRED DRAWINGS, LOADS AND ANY OTHER INFORMATION NEEDED TO OBTAIN SERVICE.
 C. PROVIDE ALL MATERIALS AND INSTALLATION REQUIRED TO COMPLETELY CONNECT TO THE SERVING UTILITY. WORK SHOULD INCLUDE, BUT NOT NECESSARILY BE LIMITED TO, PRIMARY CONDUITS, CABLE (IF REQUIRED), PAD MOUNTED TRANSFORMER PADS, GROUNDING METERING PROVISIONS, SECONDARY CONDUCTORS AND CONDUIT, ALL AS REQUIRED BY THE LOCAL UTILITY.
 D. FURNISH AND INSTALL CONDUIT ALONG WITH PULL BOXES, FOR TELEPHONE SERVICE AS REQUIRED BY SERVICE PROVIDER. SEE CIVIL DRAWINGS FOR LOCATIONS AND CONDUIT SIZE. CONDUIT IS TO RUN FROM THE TELEPHONE PANEL LOCATION IN THE BUILDING TO THE TELEPHONE COMPANY'S POINT OF CONNECTION, WHICH WILL EITHER BE A GROUND MOUNTED PEDESTAL OR A POINT USUALLY BETWEEN 10 FEET AND 15 FEET ABOVE GRADE ON A UTILITY POLE. CONDUIT SHALL BE CONTINUOUS FROM END TO END.

PANELBOARDS:

A. INSTALL PANELBOARDS SECURELY INTO POSITION AS SHOWN ON DETAIL 2/E5 AND 3/E5
 B. CONTRACTOR TO VERIFY WITH THE UTILITY COMPANY THAT THE PANELS ARE ACCEPTABLE AND IF NOT, CONTACT THE AUTOZONE PROJECT MANAGER FOR FURTHER INSTRUCTIONS.
 C. CONNECT ALL CIRCUITS EXACTLY AS SHOWN ON THE PANEL SCHEDULE.

EGN01


4 GENERAL NOTES

SYM	DESCRIPTION	FURN.	REMARKS
⊘	EXHAUST FAN RECESSED	AUTOZONE	INSTALLED BY HVAC CONTRACTOR, WIRED BY ELECTRICAL CONTRACTOR.
Ⓝ	JUNCTION BOX	G.C.	SEE SH. E2 FOR ADDITIONAL JUNCTION BOX LOCATIONS AND REQUIREMENTS AT DOORS FOR ALARMS.
Ⓢ	THERMOSTAT	AUTOZONE	WALL MOUNT ABOVE ELECTRICAL PANELS. 9'-0" A.F.F. MAX.
Ⓜ	HVAC DISCONNECT WITH UNIT		REFER TO HVAC SPECIFICATIONS
Ⓟ	POWER POLES	AUTOZONE	REFER TO PLAN FOR LOCATION
Ⓞ	SIMPLEX RECPT.	G.C.	REFER TO PLAN FOR LOCATIONS
Ⓞ/Ⓞ	DUPLEX RECPT./ FLOOR RECPT.	G.C.	REFER TO PLAN FOR LOCATIONS
ⓄⓄ	QUADPLEX RECPT.	G.C.	REFER TO PLAN FOR LOCATIONS
ⓄWP/GFI	WEATHERPROOF DUPLEX RECPT.(GFI)	G.C.	REFER TO PLAN FOR LOCATIONS
ⓄⓄ	JUNCTION BOX WITH 6'-0" FLEX CONDUIT AT WALL & H.P. COUNTERS	G.C. (FIXTURE KICK PLATE BY OWNER)	J-BOX AT FLOOR LEVEL, FLEX CONDUIT SET UNDER DISPLAY FIXTURES. RECEPTACLE MOUNTED TO BASE PLATE. SEE DETAIL 7/E1

EPL01

5 POWER SCHEDULE


- A. ELECTRICAL CONTRACTOR TO PROVIDE EMPTY CONDUIT & BOXES BETWEEN RTU'S AND THERMOSTAT LOCATIONS INDICATED. MECHANICAL CONTRACTOR TO PROVIDE CONTROL WIRING AND COMPLETE INSTALLATION. REFER TO SHEETS E5 AND M1. J-BOXES FOR THERMOSTATS SHALL BE INSTALLED HORIZONTALLY W/ A MINIMUM OF 6" BETWEEN BOXES.
- B. REFER TO SHEET E2 FOR JUNCTION BOX LOCATIONS AND POWER CIRCUITS FOR WALL SIGNAGE. ELECTRICAL CONTRACTOR SHALL MAKE ALL FINAL CONNECTIONS FOR WALL SIGNAGE.
- C. REFER TO SHEET E3 FOR JUNCTION BOX LOCATIONS AND POWER CIRCUITS FOR WALL SIGNAGE. ELECTRICAL CONTRACTOR SHALL MAKE ALL FINAL CONNECTIONS FOR WALL SIGNAGE.
- D. CONDUIT RUN OVERHEAD SHALL BE POSITIONED TO BE TIGHT AGAINST THE BOTTOM OF THE TOP CHORD OF THE BAR JOIST, AND BE IN COMPLIANCE WITH THE REQUIREMENTS OF THE NATIONAL ELECTRIC CODE.
- E. REFER TO CIVIL DRAWINGS FOR PARKING LOT SITE LIGHT LOCATIONS AND PYLON SIGN LOCATION. PARKING LOT SITE LIGHTS TYPICALLY HAVE TWO 400W FIXTURES PER POLE AND SHOULD BE WIRED TWO POLES PER CIRCUIT. FINAL CONNECTIONS FOR PYLON SIGN AND BUILDING WALLS SIGNS TO BE MADE BY ELECTRICAL CONTRACTOR.
- F. REFER TO DETAIL 3 AND 4/M1 FOR RTU CONVENIENCE OUTLET LOCATION.
- G. MOUNT JUNCTION BOX TIGHT TO FLOOR FOR DISPLAY BASE FLEX OUTLET. OUTLET ON FLEX TO BE INSTALLED HORIZONTALLY IN FIXTURE BASE AFTER FIXTURES ARE SET IN PLACE.
- H. NO RECEPTACLE BRANCH CIRCUIT SHALL BE INSTALLED IN A MULTIWIRE BRANCH CIRCUIT CONFIGURATION. NEUTRAL CONDUCTORS SHALL NOT BE SHARED BETWEEN DIFFERENT CIRCUITS.



7 RECEPTACLE DETAIL / SUPPLY FIXTURES


6 ELECTRICAL NOTES

1 POWER PLAN



- NOTES:**
1. AUTOZONE'S EQUIPMENT INSTALLER WILL FURNISH & INSTALL ALL REQUIRED SECURITY ALARM EQUIPMENT INCLUDING FLOOR POSTS, TRANSFORMER CABINET AND REMOTE ALARM SOUNDER AND COUNTER ABOVE THE DOOR.
2. GENERAL CONTRACTOR TO INSTALL DUAL WIREWAY ON THE SURFACE OF THE STOREFRONT IN ROUTING AS INDICATED TO CONNECT FLOOR-MOUNTED EAS POSTS TO THE JUNCTION BOX ABOVE STOREFRONT.
3. GENERAL CONTRACTOR TO LEAVE SNAP-ON COVER OFF THE RACEWAY SO THAT AUTOZONE'S EQUIPMENT VENDOR CAN INSTALL LOW VOLTAGE WIRING FOR THE REMOTE ALARM.

2 ELECTRONIC SECURITY DETAIL



- NOTES:**
1. CONNECT EXHAUST FANS TO RESTROOM LIGHT AND MOTION SENSOR.
2. MOTION SENSOR CMR-9 FURNISHED BY AUTOZONE INSTALLED BY CONTRACTOR.
3. WATER HEATER WILL BE A MINITANK ARISTON MODEL GL 4 TI, PROVIDED BY AUTOZONE. ELECTRICAL CONTRACTOR TO PROVIDE FINAL HOOKUP OF WATER HEATER. WATER HEATER TO BE MOUNTED ON THE WALL ABOVE THE MOP SINK.
4. REFER TO DETAIL 1/E4 FOR LOCATION OF OUTLETS IN THE TELEPHONE AND ALARM CLOSET.
5. CENTER LIGHT FIXTURE ON WALL AT 6'-8" A.F.F.

3 RESTROOM POWER AND LIGHTING

REVISIONS

REV#	DESCRIPTION
1	REV1
2	REV2
3	REV3
4	REV4
5	REV5
6	REV6



AutoZone Store No. 6890
 1593 N. MAIN ST.
 LILLINGTON, NC 27546

POWER PLAN / GENERAL NOTES

ENGINEER: DANNY E. DOSS P.E.
 132 Kelley Drive
 Rogers, Arkansas 72756
 TEL: (479) 631-1712 FAX: (479) 631-1854
 For Bidding & Contractor Information Contact:
 Dodge Data & Analytics, Tel. 413-930-4215
 Cindy.searcy@construction.com



05/06/20
 65W2-R
E-1



6 OVERHEAD DOOR ALARM REQS. 7 TYPICAL MAN DOOR

- A. LABEL ALL CIRCUITS ON J-BOXES AND ALL OUTLETS WITH MULTIPLE CIRCUITS.
- B. ALL WIRING ON FLOOR UNDER COUNTERS SHALL BE IN 3/8" FLEXIBLE CONDUIT.
- C. RUN ALL CONDUIT AND CABLES UNDER AND NOT THROUGH SHELF SUPPORTS.
- D. DO NOT PERMANENTLY ATTACH OUTLET BOXES OR FLEX CONDUIT TO FLOOR.
- E. MOUNT OUTLETS IN KICKPLATES AFTER OWNER'S FIXTURES HAVE BEEN INSTALLED.
- F. INSTALL JUNCTION BOX AT LOCATIONS SHOWN FOR POWER. INSTALL AUTOZONE FURNISHED FLEXIBLE QUICK CONNECTORS TO EACH BOX INDICATED POWER POLE SCHEDULE.
- G. AUTOZONE'S CONTRACTOR CROSSCOM WILL INSTALL CAT. 5 CABLE FOR DATA AND PHONE LINES. IN ADDITION TO TAGGING THE ENDS OF ALL CABLES, CROSSCOM WILL CRIMP THE ENDS OF ALL CABLES WITH A 8 PIN RJ-45 CONNECTOR.
- H. ALL CIRCUITS OVER 100 FEET IN LENGTH SHALL BE RUN WITH #10 AWG.
- I. PROVIDE 2 PULL WIRES IN ALL EMPTY CONDUITS.
- J. LOCATE ALL POWER POLES AFTER FIXTURES ARE IN PLACE.

8 GENERAL WIRING AND POWER NOTES






- 1 OFFICE AREA POWER POLE - ALL CIRCUITS ARE HARD WIRED TO POLE FROM JUNCTION BOX WITH FLEXIBLE CONDUIT.
- 2 CHECKOUT COUNTER POWER POLE WITH ONE DUPLEX OUTLET PRE-WIRED ON POLE FOR CONNECTION TO INDIVIDUAL CIRCUITS IN AUTOZONE FURNISHED QUICK CONNECTOR.
- 3 PARTS POD POWER POLE WITH ONE DUPLEX OUTLET PRE-WIRED ON POLE FOR CONNECTION TO AUTOZONE FURNISHED QUICK CONNECTOR.
- 4 TEST STATION POWER POLE WITH ONE SIMPLEX OUTLET AND ONE DUPLEX OUTLET PRE-WIRED ON POLE FOR CONNECTION TO INDIVIDUAL CIRCUITS IN AUTOZONE FURNISHED QUICK CONNECTOR. ATTACH TOP OF POWER POLE TO ROOF DECK AND STRAP POLE TO THE FACE OF THE FIXTURE UPRIGHT. BOTTOM OF POLE SHOULD BE A MINIMUM OF 30" ABOVE FLOOR AND OUTLETS SHOULD FACE THE TEST STATION.
- 5 CAMERA SYSTEMS POWER POLE TO BE LOCATED ADJACENT TO POWER POLE #1. POLE TO HAVE TWO 10 FOOT LONG 1/2" WHIPS WITH PULL WIRE. DO NOT PLACE ANY OTHER WIRE IN POLE.
- 6 COMMERCIAL COUNTER POWERPOLE WITH TWO DUPLEX OUTLETS PRE-WIRED ON POLE FOR CONNECTION TO INDIVIDUAL CIRCUITS IN AUTOZONE FURNISHED QUICK CONNECTORS.

9 POWER POLE LEGEND

1. CONNECT THE APPROPRIATE OWNER FURNISHED PREWIRED FEMALE FLEXIBLE QUICK CONNECTOR TO THE CIRCUIT(S) IN THE JUNCTION BOX SERVING EACH OF THE PODS. FOR DETAILED WIRING INSTRUCTION, SEE ADDITIONAL INFORMATION IN WIRING DIAGRAMS ON THIS SHEET. COIL UP THE FLEXIBLE CONDUIT AND WIRE TIE TO THE CLOSEST BAR JOIST.
2. POSITION NON-POD POWER POLES AFTER FIXTURES ARE IN PLACE, ANCHOR ALL POLES PER MANUFACTURER'S INSTRUCTIONS. MAKE FINAL CONNECTIONS THROUGH FLEX CONDUIT TO JUNCTION BOXES AT ROOF DECK. POWER POLES FOR THE PODS WILL COME WITH A MALE QUICK CONNECTOR AND WILL BE PLUGGED IN BY OWNER.
3. AT THE BOTTOM OF THE OFFICE POWER POLE MAKE 1" FLEX CONNECTIONS TO JUNCTION BOXES AND FROM THE JUNCTION BOX MAKE CONNECTIONS USING 3/8" FLEX TO EACH OF THE DEVICES.

10 POWER POLE NOTES

1 POWER POLE & JUNCTION BOX LOCATIONS




11 OFFICE AREA POWER PLAN



4	5	6
1	2	3

AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546
CONDUIT / POWER AND DATA PLANS

ENGINEER: DANNY E. DOSS P.E.
132 Kelley Drive
Rogers, Arkansas 72756
TEL: (479) 631-1712 FAX: (479) 631-1854
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com



05/06/20
65W2-R
E-2



#=> A-28
INDICATES BRANCH CIRCUITING REFER TO PANEL SCHEDULE LONG = NEUTRAL; SHORT = PHASE

2 LIGHTING CIRCUIT SYMBOLS

- ALL WALL SIGNS SHALL BE INSTALLED BY AUTOZONE'S SIGN VENDOR WHO WILL PUSH SIGN WIRING THROUGH WALL ASSEMBLY. CONNECTIONS OF SIGN WIRING TO HOME RUN CIRCUITRY WILL BE BY GENERAL CONTRACTOR.
- FOR ALL REMOTE CHANNEL LETTER SIGNS AUTOZONE'S SIGN VENDOR WILL INSTALL AN INTERIOR SURFACE MOUNTED RACEWAY FOR TRANSFORMERS AND WIRE, SO THAT THE GENERAL CONTRACTOR CAN TIE ALL INDIVIDUAL LETTER WIRING TOGETHER AND THEN CONNECT TO THE HOME RUN CIRCUIT.
- SIGN VENDOR SHALL BE RESPONSIBLE FOR SEALING ALL OF HIS WIRING PENETRATIONS THROUGH THE EXTERIOR WALLS WITH THE EXCEPTION OF PENETRATIONS THROUGH PARAPET WALLS OR ROOFING. THOSE PENETRATIONS SHALL BE SEALED BY GENERAL CONTRACTOR SO AS NOT TO VOID ANY WARRANTY CONNECTED WITH THE ROOFING INSTALLATION. GENERAL CONTRACTOR SHALL PAINT ALL EXPOSED BOXES, CONDUIT AND RACEWAYS TO MATCH SURROUNDING WALLS SURFACES.

3 SIGNAGE INSTALLATION GENERAL NOTES


SYMBOL	DESCRIPTION	SUPPLIED	LAMPS	MOUNTING
A	8' LED STRIP 42 WATTS INPUT #C2328X1	AUTOZONE	4 - 10.5 WATT T8 - 4' LED TUBE	SEE PLAN FOR LOCATIONS
B	8' LED STRIP 21 WATTS INPUT #C1328W30X1	AUTOZONE	2 - 10.5 WATT T8 - 4' LED TUBE	SEE PLAN FOR LOCATIONS
C	4' LED STRIP 10.5 WATTS INPUT WALL LIGHT - #555A132X1	AUTOZONE	1 - 10.5 WATT T8 - 4' LED TUBE	SURFACE MOUNTED @ 6'-8" ABOVE FINISHED FLOOR CENTER ON WALL
D	D-Series Size 1 Luminaire DSXW1 LED 10C 1000 40K T3M MVOLT	AUTOZONE	40 WATT	MOUNT TOP OF FIXTURE AT THE SAME ELEVATION AS TOP OF THE STOREFRONT
E	EMERGENCY LIGHT WITH BATTERY BACKUP	AUTOZONE	INCLUDED WITH FIXTURE	MOUNTED TO BOTTOM OF BAR JOIST OR UNISTRUT
F	EXIT SIGN WITH BATTERY BACKUP FOR REMOTE EXIT EMERGENCY HEAD	AUTOZONE	INCLUDED WITH FIXTURE	SEE PLAN FOR LOCATIONS AND MOUNTING INFORMATION
G	GOTHAM 8" LED DOWN LIGHT EVO R 40/30 8AR 120 TRW	AUTOZONE	49 WATT	MOUNTED IN SOFFIT SEE PLAN FOR LOCATIONS
J	EXTERIOR EMERGENCY LIGHT WITH BATTERY BACKUP	AUTOZONE	INCLUDED WITH FIXTURE	REMOTE HEAD MOUNTED OUTSIDE ABOVE DOOR WIRE TO EXIT LIGHT FIXTURE
K	EXIT SIGN WITH BATTERY BACKUP	AUTOZONE	INCLUDED WITH FIXTURE	MOUNTED TO BOTTOM OF BAR JOIST OR UNISTRUT
L	D-Series Size 1 Luminaire DSXW1 LED 10C 530 40K T3M MVOLT	AUTOZONE	20 WATT	MOUNT TOP OF FIXTURE AT THE SAME ELEVATION AS TOP OF THE STOREFRONT
M	4' LED STRIP 21 WATTS INPUT #C232X1	AUTOZONE	2 - 10.5 WATT T8 - 4' LED TUBE	SEE PLAN FOR LOCATIONS
N	4' LED STRIP 10.5 WATTS INPUT #C132W30X1	AUTOZONE	1 - 10.5 WATT T8 - 4' LED TUBE	SEE PLAN FOR LOCATIONS
M	MOTION SENSOR FOR ALC PANEL	AUTOZONE	-----	J-BOX HORIZONTAL BOTTOM OF JOIST OR UNISTRUT
M1	OCCUPANCY SENSOR-CMR-9	AUTOZONE	-----	RESTROOM CEILING - CONNECT TO FAN & LIGHT
M2	MOTION SENSOR-10 MINUTE ON LSXR-50-HL	AUTOZONE	-----	J-BOX HORIZONTAL MOUNT TO SIDE OF LIGHT FIXTURE INSTALL AISLEWAY LENS #50
SITE LIGHT	D-Series Size 1 Luminaire DSX1 LED 60C 1000 40K T3M MVOLT	AUTOZONE	209 WATT	SEE CIVIL SHEETS FOR POLE AND FIXTURE LOCATIONS

LIGHT FIXTURE SCHEDULE NOTES:


- NOT EVERY SYMBOL WILL BE UTILIZED ON EACH PROJECT SEE FLOOR PLAN ON THIS SHEET FOR THE ITEMS THAT APPLY TO THIS SPECIFIC PROJECT.
- AUTOZONE WILL FURNISH LED STRIP FIXTURES AND MOTION SENSORS SHOWN IN SCHEDULE ABOVE AND CALLED FOR ON THE PLAN. SEE MOUNTING DETAILS THIS SHEET.
- MOTION SENSOR M2 WILL BE USED IN HUB AND MEGA HUB STORES ONLY.

4 LIGHT FIXTURE SCHEDULE

1 LIGHTING PLAN



5 LED STRIP FIXTURE MOUNTING DETAIL BETWEEN JOISTS




6 LED STRIP FIXTURE MOUNTING DETAIL FIXTURE AT JOIST

- ALL DIMENSIONS ARE FROM FACE OF CONCRETE BLOCK WALLS AND TO THE CENTERS OR ENDS OF LIGHT FIXTURES.
- INSTALL OCCUPANCY SENSOR IN BATHROOMS TO CONTROL LIGHT / FAN.
- POSITION ALL CONDUIT TO BE TIGHT AGAINST THE BOTTOM OF THE TOP CHORD OF THE BAR JOIST, AND IN COMPLIANCE WITH THE CURRENT VERSION OF THE NATIONAL ELECTRIC CODE. CONDUIT SHALL BE INSTALLED EITHER PARALLEL OR PERPENDICULAR TO THE DECK RIBS. USE FLEX CONDUIT FROM J-BOX TO LIGHT FIXTURE.
- NO INTERIOR LIGHTING BRANCH CIRCUIT SHALL BE INSTALLED IN A MULTI-WIRE BRANCH CIRCUIT CONFIGURATION. NEUTRAL CONDUCTORS SHALL NOT BE SHARED BETWEEN DIFFERENT CIRCUITS.
- INSTALL 8'-0" LONG LED STRIP FIXTURES TO THE BOTTOM OF JOISTS, EITHER CENTERED ON JOIST BOTTOM OR PERPENDICULAR ACROSS MULTIPLE JOISTS. WHERE LIGHT FIXTURES ARE TO BE PLACED AT AN ANGLE TO THE JOISTS OR ARE TO BE LOCATED BETWEEN JOISTS, ATTACH FIXTURE TO CONTINUOUS RUNS OF GALVANIZED UNISTRUT WHICH HAVE BEEN SECURELY ANCHORED TO THE JOISTS.
- EXIT AND EMERGENCY LIGHTS NOT MOUNTED ON WALLS OR JOISTS SHALL BE MOUNTED ON UNISTRUT BETWEEN JOISTS.
- FRONT DOOR EXIT SIGN: SURFACE MOUNT ON WALL 12'-2" ABOVE FINISHED FLOOR TO BOTTOM OF FIXTURE MAN DOOR EXIT SIGN: SURFACE MOUNT ON WALL 9'-0" ABOVE FINISHED FLOOR TO BOTTOM OF FIXTURE. ALL OTHER EXIT SIGNS: MOUNT FIXTURE TO BOTTOM OF JOIST.
- ALL NON-SWITCHED LIGHTING CIRCUITS TO BE CONTROLLED BY AUTOMATIC LIGHTING CONTROL PANEL. SEE LIGHTING CONTROL DIAGRAM FOR DETAILS AND REQUIREMENTS.


7 LIGHTING NOTES

REV4	4	REV5	5	REV6	6
REVISIONS					
AutoZone Store No. 6890 1593 N. MAIN ST. LILLINGTON, NC 27546 LIGHTING PLANS AND DETAILS					
ENGINEER: DANNY E. DOSS P.E. 132 Kelley Drive Rogers, Arkansas 72756 TEL: (479) 631-1712 FAX: (479) 631-1854 For Bidding & Contractor Information Contact: Dodge Data & Analytics, Tel. 413-930-4215 Cindy.searcy@construction.com					
05/06/20					
65W2-R					
E-3					

© COPYRIGHT 2007



5/8" = 1'-0"
1 ALARM / PHONE BOARD REQUIREMENTS



3/32" = 1'-0"
2 SCHEMATIC ONE LINE - ELECTRICAL SERVICE

65W2 PANEL - A
LIGHTING
MAIN LUGS ONLY

VOLTS: 120/208 V.
PHASE: 3φ
WIRE: 4W

MOUNTED: FLUSH
BUSSING: 225 AMPS
FEEDER: 200 AMPS
AIC RATING: 10,000 AIC

LOAD	A	B	C	BKR	CK	CK	BKR	A	B	C	LOAD
LED LIGHTS	1104			20/1	1	2	20/1	720			LED LIGHTS
LED LIGHTS		720			3	4			672		LED LIGHTS
LED LIGHTS			768		5	6				356	FRONT WALL SIGN
SPACE					7	8					SPACE
EXIT / EMERGENCY LIGHTS		75		20/1	9	10					SPACE
SPACE					11	12					SPACE
EXTERIOR BUILDING LIGHTS	180			20/1	13	14	20/1				SPACE
SITE LIGHTS		209		20/1	15	16		256			SIDE WALL SIGN
SITE LIGHTS			209	20/1	17	18	20/1			1224	PYLON SIGN
SITE LIGHTS	209			20/1	19	20					SPACE
SPACE					21	22	20/1	472			RESTROOM LIGHTS/FAN
SPACE					23	24					SPACE
SPACE					25	26					SPACE
WATER HEATER		1500		20/1	27	28					SPACE
SPACE					29	30					SPACE
SPACE					31	32					SPACE
SPACE					33	34					SPACE
SPACE					35	36					SPACE
SPACE					37	38	60/3	5568			LOAD CENTER
SPACE					39	40			5260		
SPACE					41	42				5560	
LIGHTING TOTAL	1493	1004	977					720	1400	1580	LIGHTING TOTAL
POWER TOTAL	0	1500	0					5568	5260	5560	POWER TOTAL
PANEL TOTAL	1493	2504	977					6288	6660	7140	PANEL TOTAL

NOTES:
Aφ LIGHTING 2213 x 1.25 2766 +POWER 5568 TOTAL 8334 /120 = 69.5 A
Bφ LIGHTING 2404 x 1.25 3005 +POWER 6760 TOTAL 9765 /120 = 81.4 A
Cφ LIGHTING 2557 x 1.25 3196 +POWER 5560 TOTAL 8756 /120 = 73.0 A

65W2 PANEL - B
POWER
MAIN LUGS ONLY

VOLTS: 120/208 V.
PHASE: 3φ
WIRE: 4W

MOUNTED: FLUSH
BUSSING: 225 AMPS
FEEDER: 200 AMPS
AIC RATING: 10,000 AIC

LOAD	A	B	C	BKR	CK	CK	BKR	A	B	C	LOAD
RTU-1 10 TON	6240			60/3	1	2	60/3	6240			RTU-2 10 TON
SPACE		6240			3	4			6240		SPACE
SPACE			6240		5	6				6240	SPACE
SPACE					7	8					SPACE
RTU & EXT. RECEPT.	720			20/1	11	12					SPACE
BATTERY CHARGER		1487		20/1	13	14					SPACE
BATTERY CHARGER			1487	20/1	15	16					SPACE
BATTERY CHARGER	1487			20/1	17	18					SPACE
BATTERY CHARGER		1487		20/1	19	20	20/1	1500			H.P. MINI-TUNE
BATTERY CHARGER			1487	20/1	21	22					SPACE
ALC PANEL	480			20/1	23	24	20/1			800	TESTER ACCESSORIES
SPACE					25	26	20/1	360			DRINKING FOUNTAIN
BREAK ROOM REFRIG.			1500	20/1	27	28	20/1		360		LANDSCAPE CONTROL
SPACE					29	30	20/1			900	GEN. RECEPT. (SALES)
SPACE					31	32	20/1	1380			DRINK MACHINE
SPACE					33	34					SPACE
SPACE					35	36					SPACE
SPACE					37	38					SPACE
SPACE					39	40					SPACE
SPACE					41	42					SPACE
LIGHTING TOTAL	0	0	0					0	0	0	LIGHTING TOTAL
POWER TOTAL	8927	9214	10714					9480	6600	7940	POWER TOTAL
PANEL TOTAL	8927	9214	10714					9480	6600	7940	PANEL TOTAL

NOTES:
INSERT 20 AMP HIGH MAGNETIC BREAKER IN CIRCUIT B-20. BREAKER WILL COME WITH A YELLOW STICKER TO BE LEFT IN PLACE.
Aφ LIGHTING 0 x 1.25 0 +POWER 18407 TOTAL 18407 /120 = 153.4 A
Bφ LIGHTING 0 x 1.25 0 +POWER 15814 TOTAL 15814 /120 = 131.8 A
Cφ LIGHTING 0 x 1.25 0 +POWER 18654 TOTAL 18654 /120 = 155.5 A

65W2 PANEL - C
ELECTRONICS
MAIN LUGS ONLY

VOLTS: 120/208 V.
PHASE: 3φ
WIRE: 4W

MOUNTED: FLUSH
BUSSING: 100 AMPS
FEEDER: 60 AMPS
AIC RATING: 10,000 AIC

LOAD	A	B	C	BKR	CK	CK	BKR	A	B	C	LOAD
CK. OUT REG. & PRN	1920			20/1	1	2	20/1				SPACE
SPACE					3	4			1920		OFFICE TRAINING
CCTV MONITOR			300		5	6				1920	OFFICE IT EQUIPMENT
POD #1	1920				7	8		928			EAS POST & ALARM
SPACE					9	10			1820		OFFICE UPS
POD #2			800		11	12				1820	COMMERCIAL
SPACE					13	14					COMMERCIAL
ALARM		720		20/1	15	16			800		COMMERCIAL
TEL. CO.			720		17	18					SPACE
SPACE					19	20					SPACE
SPACE					21	22					SPACE
SPACE					23	24					SPACE
LIGHTING TOTAL											LIGHTING TOTAL
POWER TOTAL	3840	720	1820					1728	4540	3740	POWER TOTAL
PANEL TOTAL	3840	720	1820					1728	4540	3740	PANEL TOTAL

NOTES:
Aφ LIGHTING 0 x 1.25 0 +POWER 5568 TOTAL 5568 /120 = 46.4 A
Bφ LIGHTING 0 x 1.25 0 +POWER 5260 TOTAL 5260 /120 = 43.8 A
Cφ LIGHTING 0 x 1.25 0 +POWER 5560 TOTAL 5560 /120 = 46.3 A

LOAD TABULATION
TOTAL LOAD Aφ = PANEL "A" 69.5 A + PANEL "B" 153.4 A, TOTAL = 222.9 A
TOTAL LOAD Bφ = PANEL "A" 81.4 A + PANEL "B" 131.8 A, TOTAL = 213.2 A
TOTAL LOAD Cφ = PANEL "A" 73.0 A + PANEL "B" 155.5 A, TOTAL = 228.5 A

LARGEST PHASE = 228.5 + 25% OF LARGEST MOTOR (.25 x 20.5A = 5.1A) = 233.6 A

AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546


REVISIONS

REV1	1	4
REV2	2	5
REV3	3	6
REV4	4	
REV5	5	
REV6	6	


ENGINEER: DANNY E. DOSS P.E.
132 Kelley Drive
Rogers, Arkansas 72756
TEL: (479) 631-1712 FAX: (479) 631-1854
For Bidding & Contractor Information Contact:
Dodge Data & Analytics Tel. 413-930-4215
Cindy.searcy@construction.com

05/06/20
65W2-R
E-4


© COPYRIGHT 2007




3/32" = 1'-0" SCHEMATIC WIRING 1 | SCHEMATIC WIRING DIAGRAM - VENSTAR / LIGHTING CONTROL PANEL



1/2" = 1'-0" EXS03 2 | PANELBOARD - DIAGRAM



3/8" = 1'-0" EXS04 3 | PANELBOARD - MOUNTING HEIGHT SECTION 4 | NOT USED




3" = 1'-0" EXD0365W2 5 | LIGHTING CONTROL SCHEDULE

REVISIONS	
1	REV1
2	REV2
3	REV3
4	REV4
5	REV5
6	REV6


AutoZone Store No. 6890
 1593 N. MAIN ST.
 LILLINGTON, NC 27546
LIGHTING CONTROL PANEL AND DETAILS

ENGINEER: DANNY E. DOSS P.E.
 132 Kelley Drive
 Rogers, Arkansas 72756
 TEL: (479) 631-1712 FAX: (479) 631-1854
 For Bidding & Contractor Information Contact:
 Dodge Data & Analytics, Tel. 413-930-4215
 Cindy.searcy@construction.com




05/06/20
 65W2-R
E-5


© COPYRIGHT 2007




1 LOCATION OF CONTROLS




2 WIRING DIAGRAM - LCP




3 OPEN / CLOSE BUTTON




4 PHOTOCELL SENSOR




5 MOTION SENSOR




6 ALARM INTERFACE




7 ECP SENSOR CONNECTIONS




8 LOCATION OF SENSORS




9 LOCATION OF SENSORS




10 LOCATION OF SENSORS




11 SENSOR LOCATION




12 HVAC CONNECTIONS



13 THERMOSTAT CONNECTIONS



14 ECONOMIZER CONNECTIONS



15 CONCENTRATOR CONNECTIONS

VENSTAR CONTROL WIRING GENERAL NOTES - PROTOTYPE


- AUTOZONE WILL FURNISH VENSTAR LIGHTING AND HVAC CONTROL DEVICES AS INDICATED ON THIS SHEET, CONTRACTOR WILL FURNISH ALL OTHER MATERIAL AND LABOR REQUIRED TO COMPLETE THE INSTALLATION.
- UNLESS NOTED OTHERWISE ELSEWHERE IN THE DRAWINGS ROOF TOP UNITS WILL COME WITH FACTORY INSTALLED SUCTION, DISCHARGE, SUPPLY, RETURN AND AIRFLOW SENSORS, AS WELL AS AN EQUIPMENT CONTROL PAC INSIDE THE UNIT. THE OUTDOOR TEMP. AND REMOTE TEMP. SENSORS ARE TO BE INSTALLED BY CONTRACTOR. MOUNT THE DATA CONCENTRATOR ON THE PHONE BOARD UPPER LEFT HAND SIDE ABOVE THE LOCAL PHONE COMPANY'S EQUIPMENT SPACE, AND MOUNT THE LIGHTING CONTROL UNIT AND THERMOSTATS ON THE WALL ABOVE THE ELECTRIC PANELS, ALL AS INDICATED ON DRAWINGS.
- ALL WIRING TO BE RUN IN 1/2" CONDUIT.
- FOLLOW VENSTAR INSTALLATION INSTRUCTIONS OUTLINED ON THIS SHEET. FOR ANY QUESTIONS OR CLARIFICATIONS CONTACT AUTOZONE'S PROJECT MANAGER.
- AUTOZONE'S VENDOR WILL RUN ONE CATEGORY 5 DATA CABLE FROM THE DATA CONCENTRATOR IN THE TELEPHONE CLOSET DOWN THROUGH THE POWER POLE IN THE MANAGER'S OFFICE AREA IN ORDER TO ACTIVATE THE COMMUNICATIONS.
- NORMALLY THE HVAC CONTRACTOR WILL INSTALL ALL HVAC SENSORS AND WIRING FOR SAME, AND THE ELECTRICAL CONTRACTOR WILL INSTALL LIGHTING CONTROL PANEL, ALL ACCESSORIES, DATA CONCENTRATOR AND DATA CABLE.
- CONTRACTOR MAY USE ONE OF THE CONTACTORS DEDICATED TO SIGNAGE FOR ADDITIONAL SITE LIGHT CIRCUITS IF NEEDED. CONTRACTOR WILL NEED TO CHANGE THE CONTACTORS CONNECTION ON THE CONTROL BOARD TO MATCH THE SITE LIGHT CONTACTORS.
- THE PHONE NUMBER FOR VENSTAR TECHNICAL SERVICES IS: 818-812-9812.

16 CONTROL WIRING GENERAL NOTES

REVISIONS	
1	REV1
2	REV2
3	REV3
4	REV4
5	REV5
6	REV6

AutoZone Store No. 6890
1593 N. MAIN ST.
LILLINGTON, NC 27546
VENSTAR HVAC AND LIGHTING CONTROL

ENGINEER: DANNY E. DOSS P.E.
132 Kelley Drive
Rogers, Arkansas 72756
TEL: (479) 631-1712 FAX: (479) 631-1854
For Bidding & Contractor Information Contact:
Dodge Data & Analytics, Tel. 413-930-4215
Cindy.searcy@construction.com



05/06/20

65W2-R

E-6