

# StarLink Fire Universal StarLink™ Cellular &/or IP Fire Alarm LTE-Series Communicators

## StarLink Commercial Fire Alarm Communicators For Universal 12V or 24V FACP Account Reporting

### FEATURING

- **Universal full event dual path cellular &/or IP commercial fire alarm reporting from any panel brand, virtually anywhere** (also sole path vsn)
- **Code-compliant, replaces 2 POTs lines per FACP** saves thousands of dollars per year over leased landlines.
- **Supports 12V-24V control panels and FACP**s that communicate using Contact ID and 4/2 (such as on legacy panels), as primary or backup
- **Full data reporting to any Central Station, via Verizon LTE Network, "The Nation's Largest and Most Reliable 4GLTE Network**, Rated #1 Overall Network, proven to deliver consistently fast speeds and in more places than any other network\*
- **Communicate critical life and safety alarm reports on LTE (Long Term Evolution) 10+ year life, cyberprotected multibillion-dollar cellular network**, for maximum life safety & liability protection
- **Easiest installation, powered by panel, NO extra power supply, NO conduit, self-supervised on 4wires.**
- **Over-the-Air Upgradeable Communicator Firmware.** Remote ability for critical/mandatory updates, without a truck-roll
- **Cost-saving models and choice of "unlimited-signal" plans for any code requirement.** Substantial savings over monthly dedicated landline charges plus unlimited signal plans for no surprise overages. And, **\$100 tradeup saving incentive for system upgrades** from old radios (all makes) and old POTs landlines, as well as new installations.

**UL and NFPA 72 Fire Code-Compliant**, the StarLink Series Wireless Commercial Dual Path Cell/IP & Sole Path Cellular Fire Alarm Communicators provide universal support for any brand 12V to 24V fire alarm control panel, reporting in Contact ID and 4/2. With broadest Verizon® LTE coverage footprint available, via most-extensively-deployed, LTE CAT1, using proven StarLink circuitry, they are also available in mercantile locking metal models. All provide the most economical solution for easy, versatile installation. Also regional compliances, i.e., CSFM, NYCFD, LAFD and more.

**Flexible Performance & Reporting Options.** StarLink Fire provides full data reporting in dual path, as a primary or backup, to any central station of your choice, without requiring any special equipment on premises. Ultra-affordable plans are available to meet various codes and requirements, with supervisory check-ins from 200 seconds, to 5-minutes, to an hour. The units are very easily activated, plans and options are selected, and 24/7 account management is provided all through [www.napccomnet.com](http://www.napccomnet.com).

**Easy, Universal Installation at Every Application; Panel-Powered Technology™** StarLink Fire Communicators are easily connected to any panel or Fire Alarm Control Panel (FACP) standardly operating between 12V and 24V. Flexible in any application, StarLink Fire also comes in standard, or Mercantile Models in metal housings, with code-compliant supervision, and choice of power options, **Panel-Powered Technology™** (powered by the panel) or direct-connect 120VAC models. **Signal Boost™ circuitry & Dual diversity antennae** for maximum signal acquisition & null-avoidance, receiving signals simultaneously on both antennae.

### SPECIFICATIONS (STANDARD MODELS)

- **Advanced LTE Dual Diversity Antennae** for optimized performance
- **Durable ABS plastic housing** includes three keyhole slots for mounting (for commercial application, aligns with triple gang boxes.)
- **Panel-Powered Technology™** (powered by panel), typ. Low current draw, 71mA standby, 200mA transmit
- **Dimensions:** 5-3/8" x 7-7/8" x 1-7/8" (HxWxD)
- **Weight:** 13.5 oz
- **3 LED Indicators** - Green, Signal Strength; Amber- Busy/Activation; Red-Trouble
- **Patented Signal Boost™** signal amplification circuit and high-gain performance antenna
- **Operating Environment:** 0 to 49° C (32-120°F), up to 93% humidity (non-condensing)
- **12V - 24V Universal FACP Support**, auto-current sensing. Support all brands communicating in Contact ID and 4/2

### ORDERING INFORMATION:

**SLE-LTEVI-FIRE** Dual Path Commercial Fire Alarm Communicator, Cellular & IP, Connected by Verizon LTE™, ABS. Low current draw, panel-powered-technology™ (powered directly from the control panel.)

**SLE-LTEV-FIRE** As above, but sole path cellular model.

**SLELTEVI-CFB** Commercial Fire Dual Path Mercantile model in red metal housing, LTE, Verizon LTE Network powered directly from control panel

**SLELTEVI-CFBPS** Commercial Fire Dual Path Mercantile model in red metal housing, CDMA, Verizon LTE Network. Direct 120VAC Powered (w/ provisions for backup battery/charger). Or, Optional TRF12 plug-in transformer may be used, where codes permit

**A720 Commercial Fire Tradeup Trifold Brochures /Mailers/Stuffers** for new and existing fire accounts

**SLE-ANTEXT75** Optional Extended Antenna with 75' cable, (new conical shape)

**SLE-ANTEXT50** As above, but with 50' cable

**SLE-ANTEXT30** As above, but with 30' cable

**COMPLIANCES:** NFPA 72 Editions: 2016, 2013, 2010, 2007; UL 864, 10th Ed., UL1610, UL985, UL1023; NYCFD; CSFM; LAFD



**BROAD RANGE INCLUDING MERCANTILE MODELS**



**StarLink**  
NAPCO

NAPCO Security Technologies, Inc. 1-800-645-9445 • 1-631-842-9400 • fax: 1-631-789-9292

StarLink, StarLink Fire, SignalBoost, Panel-Powered Technology, Gemini & Gemini Commercial are trademarks of Napco. Verizon, LTE, etc. are trademarks of their respective companies. \*StarLink offers full data coverage in US from virtually all panel brands reporting in Contact ID or 4/2. For full details on the StarLink tradeup incentive see online under [www.napcosecurity.com/starlink](http://www.napcosecurity.com/starlink). \*Promo subject to change w/o prior notice. LTE lifespan claims are based on those of carriers. †Verizon® rankings based on the RootMetrics 5 National RootScore® Report: 1H 2017.