

1. GENERAL

- THE WORK COVERED BY THESE SPECIFICATIONS CONSISTS OF FURNISHING ALL LABOR, EQUIPMENT, MATERIALS, AND SUPPLIES AS NECESSARY FOR THE COMPLETE AND SATISFACTORY OPERATING ELECTRICAL SYSTEMS AS SHOWN ON THE PLANS.
- ALL WORK SHALL BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, NFPA, STATE BUILDING CODE, AND ANY OTHER LOCAL CODES APPLICABLE TO THE LIGHTING FIXTURE SCHEDULE OR SYSTEMS WITH AN 'F' RATING EQUAL TO THE RATING OF THE ASSEMBLY BEING PENETRATED.
- CONTRACTOR SHALL OBTAIN AND PAY FOR ALL ELECTRICAL PERMITS AND INSPECTION FEES.
- ALL MATERIALS AND EQUIPMENT SHALL BE NEW AND SHALL BE LISTED BY THE UNDERWRITER'S LABORATORIES, INC. OR BY A STATE APPROVED THIRD PARTY TESTING AGENCY FOR THE USE IN THE DRAWINGS. ALL MATERIALS AND EQUIPMENT SHALL BE IDENTICAL TO THE SAME TYPE AND RATING SHALL BE IDENTICAL AND OF THE SAME MANUFACTURER.
- CONTRACTOR SHALL SUBMIT SHOP DRAWINGS AND CATALOG DATA IN ELECTRONIC FORMAT (PDF) FOR ALL ELECTRICAL ITEMS IN THE SCOPE OF WORK, INCLUDING BUT NOT LIMITED TO, RACEWAYS, BOXES, FITTINGS, CONNECTORS, LUMINAIR, FINISH SCHEDULES, SAFETY SWITCHES, DISCONNECTS, TRANSFORMERS, PANELBOARDS, FIRE ALARM, TELECOMMUNICATIONS, ETC. FOR APPROVAL AS APPLICABLE FOR THE PROJECT. ONE COMPLETE SET OF APPROVED SUBMITTALS SHALL BE MAINTAINED AT THE JOB SITE.
- ALL COST ASSOCIATED WITH SUBSTITUTED EQUIPMENT TO COMPLY WITH THE BASIS OF DESIGN INCLUDING PROVIDING MAINTENANCE ACCESS, CLEARANCE, CONDUIT, WIRING, REPLACEMENT OF OTHER SYSTEM COMPONENTS, BUILDING ALTERATIONS, METHODS, ETC., SHALL BE INCLUDED IN THE ORIGINAL BASE BID. NO ADDITIONAL COSTS ASSOCIATED WITH SUBSTITUTED EQUIPMENT WILL BE APPROVED AFTER BIDS HAVE BEEN ACCEPTED AND ALL COSTS WILL BE THE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR. CREDITS SHALL BE GIVEN TO THE OWNER WHERE SUCH EQUIPMENT AND METHODS RESULT IN LESS EXPENSE TO THE CONTRACTOR.
- ONE COMPLETE SET OF THE LATEST CONSTRUCTION PLANS OF ALL TRADES SHALL BE MAINTAINED AT THE JOB SITE. IN ADDITION, ALL ADDENDUMS, BULLETINS, AND/OR SKETCHES SHALL BE INCORPORATED INTO THE ON-SITE CONSTRUCTION PLANS AS THE JOB PROGRESSES.
- COMPLETELY ADEQUATE HOUSING SHALL BE PROVIDED FOR ALL MATERIALS STORED ON JOB SITE. ONLY CONDUIT MAY BE STORED OUTSIDE, BUT NOT IN CONTACT WITH THE GROUND.
- THE CONDUIT AND RACEWAY SYSTEM SHALL BE GROUNDED AT THE MAIN SERVICE EQUIPMENT. GROUNDING ELECTRODE SYSTEM SHALL BE INSTALLED PER NEC 250.
- PROVIDE AN INTERSYSTEM BONDING TERMINATION DEVICE AT THE MAIN ELECTRICAL SERVICE PER NEC 250.94.
- ALL WIRING SHALL BE TESTED FOR CONTINUITY AND GROUNDS BEFORE BEING ENERGIZED. FAULTY WIRING SHALL BE REPLACED AT NO ADDITIONAL EXPENSE TO THE OWNER.
- ELECTRICAL ALL CUTTING AND PATCHING FOR INSTALLATION OF WORK AND REPAIR ANY DAMAGE DONE.
- THE ELECTRICAL CONTRACTOR SHALL CONNECT ALL EQUIPMENT REQUIRING ELECTRICAL CONNECTIONS (UNLESS OTHERWISE NOTED), EXCEPT FOR CONTROL WIRING FOR EQUIPMENT NOT PROVIDED BY THE ELECTRICAL CONTRACTOR. CONTROL WIRING FOR SUCH EQUIPMENT SHALL BE PROVIDED BY THE RESPECTIVE DISCIPLINE.
- ALL ELECTRICAL JUNCTION BOXES, SWITCHGEAR, CABLE, VOICE/DATA OUTLETS, LOW VOLTAGE CABINETS, EMERGENCY RECEPTACLES, ETC. SHALL BE LABELED ACCORDING TO PANEL/RACK AND CIRCUIT NUMBER.
- UPON COMPLETION OF WORK, CONTRACTOR SHALL PRESENT ENGINEER WITH CERTIFICATE OF APPROVAL FROM LOCAL INSPECTOR AND/OR AUTHORITY HAVING JURISDICTION BEFORE WORK WILL BE APPROVED FOR FINAL PAYMENT.
- CONTRACTOR SHALL GUARANTEE ALL WORK AND MATERIALS FOR A PERIOD OF ONE YEAR EFFECTIVE THE DATE THE PROJECT IS ACCEPTED BY THE OWNER. ANY DEFECTIVE MATERIALS OR WORKMANSHIP SHALL BE REPLACED WITHOUT ADDED COST TO THE PROJECT.
- IT SHALL NOT BE THE INTENT OF ISSUED PLANS AND/OR SPECIFICATIONS TO SHOW EVERY MINOR DETAIL OF CONSTRUCTION. THE ELECTRICAL CONTRACTOR IS EXPECTED TO FURNISH AND INSTALL ALL NECESSARY ITEMS FOR A COMPLETE AND OPERATING SYSTEM.
- THE WORD "PROVIDE" MEANS THAT THIS CONTRACTOR SHALL FURNISH, FABRICATE, ERECT, CONNECT, AND COMPLETELY INSTALL SYSTEMS IN PROPER OPERATING CONDITION. ALL LABOR, PRODUCT OPTIONS, ACCESSORIES AND INCIDENTAL MATERIALS REQUIRED SHALL BE INCLUDED AS PART OF THIS WORK AND THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SAME.
- THE WORD "CONNECT" MEANS THAT THIS CONTRACTOR SHALL PROVIDE (SEE DEFINITION ABOVE) ALL DISCONNECTING MEANS, OVERCURRENT PROTECTION AND WIRING REQUIRED TO PLACE THE EQUIPMENT AND SYSTEMS IN PROPER OPERATING CONDITION AND TO COMPLY WITH CODE REQUIREMENTS.
- CONTRACTOR SHALL COORDINATE THE ROUGH-IN OF ALL OUTLET LOCATIONS WITH ARCHITECTURAL FLOOR PLANS, ELEVATIONS, AND MILLWORK SHOP DRAWINGS PRIOR TO ROUGH-IN.
- ELECTRICAL CONTRACTOR SHALL SCALE PLANS. CONTRACTOR SHALL REFER TO ARCHITECTURAL PLANS AND ELEVATIONS FOR EXACT LOCATIONS OF ALL EQUIPMENT. UNLESS OTHERWISE NOTED.
- CONTRACTOR SHALL TEST ALL "LIFE SAFETY" EQUIPMENT AND SYSTEMS FOR PROPER FUNCTION AND OPERATION. UPON SUCCESSFUL COMPLETION OF TESTS, CONFIRMATION SHALL BE SENT TO THE ENGINEER OF RECORD IN THE FORM OF A LETTER STATING THE TESTS PERFORMED, THE RESULTS, AND THE DATE THE TESTS WERE SUCCESSFULLY COMPLETED. "LIFE SAFETY" EQUIPMENT AND SYSTEMS CONSIST OF THOSE AS SPECIFIED IN THE STATE BUILDING CODE, THE NATIONAL ELECTRICAL CODE, NFPA 101, AND ANY OTHER LOCAL REQUIREMENTS THAT MAY APPLY.
- IF DURING THE COURSE OF WORK, THE CONTRACTOR DISCOVERS A PROBLEM WITH THE PERFORMANCE OF THE INSTALLATION RELATIVE TO THE PLANS AND SPECIFICATIONS, THE NEC, OR OTHER CODES OR REQUIREMENTS, THE CONTRACTOR SHALL IMMEDIATELY BRING THE PROBLEM TO THE ATTENTION OF THE ARCHITECT AND/OR ENGINEER FOR RESOLUTION PRIOR TO THE EXECUTION OF THE WORK.
- WHERE THERE ARE CONFLICTS BETWEEN THE PLANS AND SPECIFICATIONS, THE CONTRACTOR SHALL BRING THE ISSUE TO THE ATTENTION OF THE ENGINEER FOR RESOLUTION PRIOR TO THE EXECUTION OF THE WORK OR ORDERING ANY MATERIALS. NO ADDITIONAL COSTS SHALL BE WARRANTED WITHOUT A CHANGE TO THE PROJECT SCOPE.
- THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING AND PROVIDING TEMPORARY POWER AND LIGHTING FOR ALL TRADES. AT NO TIME SHALL EXISTING BUILDING POWER SYSTEMS BE UTILIZED WITHOUT WRITTEN PERMISSION FROM THE OWNER.
- COORDINATE LOCATION AND REQUIREMENTS FOR ELECTRICAL SERVICE WITH THE POWER COMPANY. WHEN MORE THAN ONE SERVICE IS SUPPLIED TO A BUILDING, PROVIDE IDENTIFICATION AT EACH SERVICE PER NEC 230-2(E).
- AA. THE CONTRACTOR SHALL PROVIDE A MINIMUM TWO WEEK NOTICE FOR ANY PLANNED UTILITY OUTAGES. WRITTEN AUTHORIZATION FROM THE OWNER SHALL BE PROVIDED PRIOR TO ANY OUTAGE. ALL PLANNED UTILITY OUTAGES SHALL BE COORDINATED WITH THE OWNER TO OCCUR DURING NON-OPERATING TIMES, INCLUDING NIGHTS, WEEKENDS AND HOLIDAYS. ALL PLANNED UTILITY OUTAGES SHALL INCLUDE PROVISIONS FOR PROPER BACK-UP OF ALL LIFE-SAFETY SYSTEMS AND INCLUDE AN APPROVED FIRE-WATCH PROGRAM AS REQUIRED BY THE LOCAL FIRE MARSHAL. THE CONTRACTOR SHALL EXIST BIDDER SHALL VISIT THE JOB SITE PRIOR TO BIDDING TO FAMILIARIZE THEMSELVES WITH EXISTING CONDITIONS AND TO ASCERTAIN THE EXTENT OF WORK REQUIRED. FAILURE TO VISIT SITE SHALL NOT EXCUSE CONTRACTOR FROM PERFORMING REQUIRED WORK NOR SHALL IT BE AN ACCEPTABLE REASON FOR REQUESTING ADDITIONS TO THE CONTRACT.

2. RACEWAY:

- CONDUIT SHALL BE MANUFACTURED BY ALLIED, WHEATLAND, REPUBLIC CONDUIT, WESTERN TUBE, OR APPROVED EQUIVALENT.
- FOR INTERIOR WORK, CONDUIT SHALL BE ZINC COATED EMT EXCEPT WHERE NOT PERMITTED BY CODE. USE SCHEDULE 40 PVC BELOW CONCRETE SLAB, IN DUCTBANKS, AND FOR EXTERIOR WORK WHERE NOT SUBJECT TO DAMAGE. USE IMC WHERE SUBJECT TO PHYSICAL DAMAGE.
- ALL FITTINGS SHALL BE COMPRESSION STEEL. CONNECTORS SHALL HAVE INSULATED THROATS. CAST, SET SCREW, OR INDENTER TYPE FITTINGS ARE NOT ACCEPTABLE. ALL FITTINGS FOR EMT SHALL BE MADE OF STEEL.
- ALL RACEWAY SHALL BE RUN CONCEALED, UNLESS OTHERWISE NOTED. FISH ALL NEW OUTLETS IN BUSHINGS, WHERE POSSIBLE. ALL RUNS SHALL BE CONCEALED WITH THE UNDERWRITER'S APPROVED FIRE-WATCH PROGRAM AS REQUIRED BY THE LOCAL FIRE MARSHAL.
- LOW VOLTAGE CABLING NOT SPECIFIED TO BE INSTALLED IN CONDUIT, SHALL BE INSTALLED IN A CABLE TRAY SYSTEM OR J-HOOK SYSTEM CONSISTING OF MINIMUM 2" DIAMETER HOOKS LOCATED ON 3'-0" CENTERS IN ALL ACCESSIBLE CEILING, WHERE THERE ARE INACCESSIBLE CEILING, PROVIDE CONDUIT FOR ENTIRE LENGTH OF INACCESSIBILITY.
- RACEWAYS USED FOR LOW VOLTAGE SYSTEMS SUCH AS TELECOMMUNICATIONS, FIRE ALARM, SECURITY, CCTV, CONTROLS, AND SIMILAR CONDUITS ABOVE THE CEILING AND BACKBOARD(S) SHALL BE PROVIDED WITH INSULATED THROAT BUSHINGS AT EACH CONDUIT TERMINATION. THESE BUSHINGS SHALL BE INSTALLED PRIOR TO PULLING LOW-VOLTAGE CABLES.
- RACEWAY PENETRATIONS THROUGH FLOOR SLABS AND FIRE-RATED WALLS SHALL BE FILLED WITH IMPERVIOUS, NON-SHRINK GROUT SUFFICIENTLY TIGHT TO PREVENT THE TRANSFER OF SMOKE, WATER, AND DUST. ROOF PENETRATIONS SHALL BE WITHIN THE EQUIPMENT ROOF CURB.
- SUPPORT ALL CONDUIT WITH STRAPS AND CLAMPS.
- ALL CONDUIT SHALL BE RUN PARALLEL OR PERPENDICULAR TO BUILDING LINES, WHETHER EXPOSED OR NOT AND SUPPORTED FROM STRUCTURE AND PROPERLY SECURED.
- WHERE CONDUITS PASS THROUGH A BUILDING EXPANSION JOINT, PROVIDE GALVANIZED EXPANSION FITTINGS WITH BONDING JUMPER.
- MINIMUM CONDUIT SIZE SHALL BE 3/4" FOR INTERIOR WORK, 1" FOR EXTERIOR WORK.
- PROVIDE MINIMUM 210# TEST NYLON PULL CORD AND NYLON BUSHINGS IN ALL EMT/ RACEWAYS.
- LIQUID-TIGHT METAL CONDUIT SHALL ONLY BE USED FOR FINAL CONNECTIONS TO EQUIPMENT AND ALL OTHER ROTATING AND VIBRATING EQUIPMENT, MAXIMUM LENGTH OF 3'-0".
- FLEXIBLE METAL CONDUIT, MINIMUM SIZE 3/8", SHALL ONLY BE USED FOR FINAL CONNECTION TO LIGHTING FIXTURES, MAXIMUM LENGTH OF 6'-0".
- PROVIDE PULL BOXES, SUCH THAT NO SINGLE CONDUIT RUN HAS BENDS IN EXCESS OF 360°. PULL BOXES SHALL BE SUITABLE AND APPROVED FOR THE INTENDED USE. WHERE CONDUITS PASS UNDER PAVED AREAS, THEY SHALL BE RGS.
- ALL CONDUIT BENDS/ELBOWS EMERGING FROM UNDERGROUND SHALL BE IMC AND SHALL EXTEND A MINIMUM OF 18" BELOW GRADE.
- ALL UNDERGROUND RACEWAYS SHALL BE THOROUGHLY COATED WITH TWO COATS OF ASPHALTUM BITUMASTIC.
- ALL CONDUITS INSTALLED UNDERGROUND OR IN CONCRETE SHALL HAVE JOINTS MADE WATERTIGHT BY USE OF POLYETHYLENE FLUOROPOLYMER TAPE.
- THE USE OF AC OR NM CABLE IS NOT PERMITTED.
- MC CABLE IS NOT ALLOWED, EXCEPT FOR FINAL CONNECTION TO LIGHT FIXTURES, PER NOT 2.N.

3. OUTLET BOXES:

- JUNCTION AND PULL BOXES SHALL BE CODE GAUGE GALVANIZED STEEL. ACCEPTED MANUFACTURERS SHALL BE STEEL CITY (THOMAS & BETTS), RACO, CROUSE-HINDS, APPLETON (EMERSON), OR APPROVED EQUIVALENT.
- OUTLET BOXES SHALL NOT BE MOUNTED BACK TO BACK IN COMMON WALLS.
- ATTACH EMT WITH CONNECTORS HAVING INSULATED THROAT.
- ATTACH BOXES TO STUD WORK USING CADDY BAR STRAPS THAT CONNECT TO TWO ADJACENT STUDS TO PREVENT TWISTING OF BOX IN WALL.
- ALL OUTLET BOXES (INCLUDING TELEPHONE, CABLE TV, AND COMPUTER) SHALL HAVE COVER PLATES, BLANK IF NOT USED.
- ALL EXTERIOR BOXES SHALL BE WATER-TIGHT.



E

D

C

B

A


WALL LEGEND	
SYMBOL	DESCRIPTION
	1 HR FIRE RATED
	2 HR FIRE RATED

GENERAL NOTES - SITE PLAN

- A. ALL LIGHTING AND POWER CONDUCTORS SHALL BE INSTALLED BETWEEN 24" (MINIMUM) AND 36" (MAXIMUM) BELOW FINISHED GRADE.
- B. ALL COMMUNICATIONS CONDUIT AND CABLES SHALL BE INSTALLED 36" (MINIMUM) BELOW FINISHED GRADE.
- C. ALL CONDUCTORS FOR EXTERIOR LIGHTING AND POWER CIRCUITS SHALL BE #10 AWG MINIMUM.
- D. PROVIDE TRANSFORMER BASE AT ALL POLE MOUNTED FIXTURES, TAP 2 LEGS OF THREE PHASE FEEDER (CIRCUITS DENOTED), PROVIDE BALLAST FUSES AT TAP, AND PROVIDE BRANCH CIRCUITS TO FIXTURES.

KEYNOTES

- 1 G.C. TO COORDINATE CONNECTION TO EXISTING SERVICE WITH SCHOOL ACTIVITIES. PATCH AND REPAIR EXISTING WALLS AND CEILING AS NEEDED TO RUN NEW FEEDER.



1 OVERALL ELECTRICAL PLAN
1" = 30'-0"

...Becoming the
Leading Designer of
High Performance Facilities
in the Nation with a
Specialty in Alternative
Delivery Methods

333 Fayetteville St, Ste 225
Raleigh, NC 27601
P: 919-573-6350
F: 919-573-6355
www.sfl+a.com

sfl+a
ARCHITECTS



CONSTRUCTION
DRAWINGS

optima
engineering
150 Fayetteville St., Suite 520, Raleigh, NC 27601
Phone: 919-565-2250 - www.optimaengineering.com
North Carolina License Number C-0914

Harnett County Schools
LILLINGTON-SHAWTOWN ELEMENTARY ADDITION
855 Old US Highway 421
Lillington, NC 27546



No.	Date	Description

ISSUE DATE: 07-26-24
PROJECT #: 02110.300
DRAWN BY: JSD
CHECKED BY: MKG
© 2024 Sfl+a Architects, PA
All Rights Reserved

OVERALL
ELECTRICAL PLAN

E-010



WALL LEGEND	
SYMBOL	DESCRIPTION
	1 HR FIRE RATED
	2 HR FIRE RATED

GENERAL NOTES - LIGHTING


- A. ALL RECESSED LIGHTING FIXTURES IN LAY-IN CEILINGS SHALL BE INSTALLED WITH 6'-0" LONG FLEXIBLE METAL CONDUIT.
- B. SEE ARCHITECTURAL EXTERIOR ELEVATIONS FOR MOUNTING HEIGHTS OF EXTERIOR LIGHTING FIXTURES.
- C. CONNECT EMERGENCY EXIT SIGNS AND THE UNSWITCHED INPUT OF BATTERY PACKS TO LOCAL LIGHTING CIRCUIT, AHEAD OF SWITCHING.
- D. CONTRACTOR SHALL MAKE SURE TO MAINTAIN CONTINUITY OF ELECTRICAL DEVICES THAT ARE OUTSIDE AREA OF WORK THAT ARE INTENDED TO MAIN ENERGIZED.
- E. MAINTAIN CONTINUITY OF BRANCH CIRCUITRY ASSOCIATED WITH ALL EXISTING LIGHTS TO REMAIN.
- F. HATCHED AREAS ARE NOT IN SCOPE OF WORK.

KEYNOTES

- 1. DISCONNECT AND REMOVE EXTERIOR LIGHTING FIXTURE. ELECTRICAL CONTRACTOR SHALL RETAIN CIRCUIT CONTINUITY TO ENSURE PROPER OPERATION OF ALL FIXTURES OUTSIDE SCOPE OF WORK WHICH ARE CONNECTED TO EXISTING CIRCUIT.
- 2. PROVIDE 300VA EMERGENCY INVERTER WITH 90 MINUTES OF BATTERY BACKUP TO PROVIDE EMERGENCY BACKUP POWER FOR GYM HIGH BAY FIXTURES. LIGHTS SHALL BE CONTROLLED BY ADDRESSABLE LIGHTING CONTROL SYSTEM DURING NORMAL OPERATION. UPON POWER FAILURE, LIGHTS SHALL TURN ON AT FULL BRIGHTNESS.
- 3. 3 ZONE OVERRIDE SWITCH: DIMMING CONTROL FOR 3 ZONES IN LOBBY 101.
 ZONE 1: TYPE 'L4', 'L4E', AND 'DL1E' FIXTURES IN MAIN LOBBY AREA AND RESTROOM HALLWAY.
 ZONE 2: TYPE 'TL' FIXTURES IN TROPHY CASEWORK.
 ZONE 3: TYPE 'DL1' FIXTURES IN MAIN LOBBY AREA.
- 4. PROVIDE LABELS INDICATING ZONES SERVED BY OVERRIDE SWITCH IN LOBBY 101:
 ZONE 1: "LOBBY"
 ZONE 2: "TROPHY"
 ZONE 3: "BENCH"
- 5. LOCATE POWER PACK IN ELECTRICAL ROOM ADJACENT TO PANEL SERVING EXTERIOR LIGHTING.



2 ENLARGED LIGHTING DEMOLITION PLAN
1/4" = 1'-0"



3 ADDITION LIGHTING PLAN - ROOF
1/8" = 1'-0"



1 ADDITION LIGHTING PLAN
1/8" = 1'-0"

...Becoming the
Leading Designer of
High Performance Facilities
in the Nation with a
Specialty in Alternative
Delivery Methods

333 Fayetteville St, Ste 225
Raleigh, NC 27601
P: 919-573-4350
F: 919-573-4355
www.sfl+a.com

sfl+a
ARCHITECTS



CONSTRUCTION
DRAWINGS

optima
engineering

150 Fayetteville St., Suite 520, Raleigh, NC 27601
Phone: 919-555-2200 • www.optimaengineering.com
North Carolina License Number C-0914

Harnett County Schools
LILLINGTON-SHAWTOWN ELEMENTARY ADDITION
855 Old US Highway 421
Lillington, NC 27546



No.	Date	Description

ISSUE DATE: 07-26-24
PROJECT #: 02110.300
DRAWN BY: JSD
CHECKED BY: MKG
© 2024 Sfl+a Architects, PA
All Rights Reserved

ADDITION LIGHTING
PLAN



WALL LEGEND	
SYMBOL	DESCRIPTION
	1 HR FIRE RATED
	2 HR FIRE RATED

GENERAL NOTES

- A. RECEPTACLES AND DATA OUTLETS SHALL NOT BE MOUNTED IN TRIM OF WINDOWS. LOCATE IN WHERE FULL WALL IS AVAILABLE.
- B. COORDINATE LOCATION OF ALL FLOOR BOXES IN THE SAME AREA SHALL BE NEATLY ALIGNED AND PARALLEL TO BUILDING LINES.
- C. CIRCUIT NUMBERS ARE DIAGRAMMATIC. EXACT NUMBERS SHALL BE DETERMINED IN THE FIELD AND REFLECTED ON AS-BUILT DOCUMENTATION BY THE ELECTRICAL CONTRACTOR. THE ASSOCIATED CIRCUIT NUMBERS THAT ARE APPLIED TO EACH DEVICE AND PIECE OF EQUIPMENT INFERS INTERCONNECTING BRANCH CIRCUITRY.
- D. WHERE CONNECTED TO A 20A BRANCH CIRCUIT SUPPLYING AN INDIVIDUAL RECEPTACLE (SIMPLEX OR DUPLEX), THE RECEPTACLE SHALL BE RATED AT 20A.
- E. PROVIDE HOUSEKEEPING PADS FOR ALL FLOOR MOUNTED AND GRADE MOUNTED ELECTRICAL EQUIPMENT. MINIMUM REQUIREMENTS: 4" HIGH, 4% AIR ENTRAINED, POLYFIBER REINFORCED CONCRETE, 4" WIDER AND 4" LONGER THAN EQUIPMENT TO BE PLACED ON IT. REFER TO ELECTRICAL DETAIL DRAWINGS FOR TRANSFORMER OR SWITCHGEAR PADS THAT MAY EXCEED THESE REQUIREMENTS.
- F. REFER TO SECTION 26 0519 FOR MINIMUM CONDUCTOR SIZE ADJUSTMENTS FOR VOLTAGE DROP.
- G. WIRE COUNTS FOR CIRCUIT CONDUCTORS ARE NOT SHOWN. PROVIDE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUIT AND SWITCHING CONNECTIONS SHOWN.
- H. MODIFICATIONS TO NUMBER OF CONDUCTORS IN HOME RUNS IN ADDITION TO CIRCUIT INDICATED ON THIS DRAWING ARE PROHIBITED.
- I. COORDINATE EXACT LOCATION OF ALL FLOOR BOXES WITH ARCHITECT AND FURNITURE VENDOR.

KEYNOTES

- 1. KEYED SWITCH FOR MOTORIZED GOALS. TYPICAL OF 6. SEE DETAILS 12, 13 / SHEET E-601.
- 2. KEYED IN/OUT/STOP SWITCH FOR MOTORIZED BLEACHER CONTROL. SEE DETAIL 11 / SHEET E-601.
- 3. 120V CONNECTION TO SCOREBOARD. COORDINATE WITH SCOREBOARD INSTALLER PRIOR TO ROUGH-IN.
- 4. PROVIDE DOUBLE GANG JUNCTION BOX FOR SCOREBOARD. PROVIDE 1-1/2" FROM JUNCTION BOX TO CONTROLLER JACK LOCATION. COORDINATE WITH SCOREBOARD INSTALLER PRIOR TO ROUGH-IN.
- 5. SCOREBOARD CONTROLLER JACK. PROVIDE 4" SQUARE BOX WITH A SINGLE GANG OPENING AND PLASTER RING. COORDINATE WITH SYSTEMS CONTRACTOR.
- 6. PROVIDE 120V CONNECTION FOR MECHANICAL CONTROLS. COORDINATE WITH MECHANICAL CONTROLS CONTRACTOR PRIOR TO ROUGH-IN.
- 7. PROVIDE 3/4" FIRE RETARDANT PLYWOOD BACKBOARD FROM FLOOR TO CEILING INSTALLED VERTICALLY STARTING AT 6" A.F.F. PAINT WITH TWO COATS OF COLOR WHITE FIRE RETARDANT PAINT.
- 8. CONTRACTOR SHALL FIELD VERIFY EXISTING CONDITION AND INCLUDE IN BID ALL CONDUCTORS, CABLING, CONDUIT, AND EQUIPMENT FOR A FULLY FUNCTIONING EMERGENCY RESPONDER RADIO AMPLIFICATION SYSTEM.
- 9. 120V CONNECTION FOR GYMNASIUM MOTORIZED SHADES. COORDINATE EXACT REQUIREMENTS WITH SHADE INSTALLER AND ARCHITECT PRIOR TO ROUGH-IN.
- 10. INTERLOCK FAN WITH LIGHTING CONTROLS IN THIS ROOM. PROVIDE RELAY TO INTERLOCK 277V LIGHTING CONTROLS WITH 120V FAN.
- 11. RAISE/LOWER/STOP SWITCH FOR PLAN EAST GYM MOTORIZED SHADES. COORDINATE EXACT REQUIREMENTS WITH SHADE INSTALLER PRIOR TO ROUGH-IN. ROUTE CONDUIT TO SHADE CONTROLLER.
- 12. RAISE/LOWER/STOP SWITCH FOR PLAN WEST GYM MOTORIZED SHADES. COORDINATE EXACT REQUIREMENTS WITH SHADE INSTALLER PRIOR TO ROUGH-IN. ROUTE CONDUIT TO SHADE CONTROLLER.



1 ADDITION POWER PLAN
1/8" = 1'-0"

2 ENLARGED UTIL. 107 POWER PLAN
1/4" = 1'-0"

...Becoming the
Leading Designer of
High Performance Facilities
in the Nation with a
Specialty in Alternative
Delivery Methods

333 Fayetteville St, Ste 225
Raleigh, NC 27601
P: 919.573.4350
F: 919.573.4355
www.sfl+a.biz

sfl+a
ARCHITECTS


7/26/2024

CONSTRUCTION
DRAWINGS

optima
engineering

150 Fayetteville St., Suite 520, Raleigh, NC 27601
Phone: 919-565-2200 | www.optimaengineering.com
North Carolina License Number C-0914

Harnett County Schools
LILLINGTON-SHAWTOWN ELEMENTARY ADDITION
855 Old US Highway 421
Lillington, NC 27546



No.	Date	Description

ISSUE DATE: 07-26-24
PROJECT #: 02110.300
DRAWN BY: JSD
CHECKED BY: MKG
© 2024 Sfl+a Architects, PA
All Rights Reserved

ADDITION POWER
PLAN

7/25/2024 6:03:43 PM Autodesk Docs://02110.300.Lillington-Shawtown ES Addition_MEPFP_R23.rvt

E

D

C

B

A


WALL LEGEND	
SYMBOL	DESCRIPTION
	1 HR FIRE RATED
	2 HR FIRE RATED

GENERAL NOTES

- A. RECEPTACLES AND DATA OUTLETS SHALL NOT BE MOUNTED IN TRIM OF WINDOWS. LOCATE IN WHERE FULL WALL IS AVAILABLE.
- B. COORDINATE LOCATION OF ALL FLOOR BOXES IN THE SAME AREA SHALL BE NEATLY ALIGNED AND PARALLEL TO BUILDING LINES.
- C. CIRCUIT NUMBERS ARE DIAGRAMMATIC. EXACT NUMBERS SHALL BE DETERMINED IN THE FIELD AND REFLECTED ON AS-BUILT DOCUMENTATION BY THE ELECTRICAL CONTRACTOR. THE ASSOCIATED CIRCUIT NUMBERS THAT ARE APPLIED TO EACH DEVICE AND PIECE OF EQUIPMENT INFERS INTERCONNECTING BRANCH CIRCUITRY.
- D. WHERE CONNECTED TO A 20A BRANCH CIRCUIT SUPPLYING AN INDIVIDUAL RECEPTACLE (SIMPLEX OR DUPLEX), THE RECEPTACLE SHALL BE RATED AT 20A.
- E. PROVIDE HOUSEKEEPING PADS FOR ALL FLOOR MOUNTED AND GRADE MOUNTED ELECTRICAL EQUIPMENT. MINIMUM REQUIREMENTS: 4" HIGH, 4% AIR ENTRAINED, POLYFIBER REINFORCED CONCRETE, 4" WIDER AND 4" LONGER THAN EQUIPMENT TO BE PLACED ON IT. REFER TO ELECTRICAL DETAIL DRAWINGS FOR TRANSFORMER OR SWITCHGEAR PADS THAT MAY EXCEED THESE REQUIREMENTS.
- F. REFER TO SECTION 26 0519 FOR MINIMUM CONDUCTOR SIZE ADJUSTMENTS FOR VOLTAGE DROP.
- G. WIRE COUNTS FOR CIRCUIT CONDUCTORS ARE NOT SHOWN. PROVIDE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUIT AND SWITCHING CONNECTIONS SHOWN.
- H. MODIFICATIONS TO NUMBER OF CONDUCTORS IN HOME RUNS IN ADDITION TO CIRCUIT INDICATED ON THIS DRAWING ARE PROHIBITED.
- I. COORDINATE EXACT LOCATION OF ALL FLOOR BOXES WITH ARCHITECT AND FURNITURE VENDOR.

KEYNOTES

- 1 INTERLOCK FAN WITH LIGHTING CONTROLS IN THE ROOM BELOW. PROVIDE RELAY TO INTERLOCK 277V LIGHTING CONTROLS WITH 120V FAN.



1 ADDITION ROOF EQUIPMENT CONNECTIONS PLAN
1/8" = 1'-0"

...Becoming the
Leading Designer of
High Performance Facilities
in the Nation with a
Specialty in Alternative
Delivery Methods


333 Fayetteville St, Ste 225
Raleigh, NC 27601
P: 919-573-8350
F: 919-573-8355
www.sfl+a.biz



CONSTRUCTION
DRAWINGS

optima
engineering
150 Fayetteville St., Suite 520, Raleigh, NC 27601
Phone: 919-565-2200 - www.optimaengineering.com
North Carolina License Number C-0914

Harnett County Schools
LILLINGTON-SHAWTOWN ELEMENTARY ADDITION
855 Old US Highway 421
Lillington, NC 27546



No.	Date	Description

ISSUE DATE: 07-26-24
PROJECT #: 02110.300
DRAWN BY: JSD
CHECKED BY: MKG
© 2024 SFL+A Architects, PA
All Rights Reserved

ADDITION ROOF
EQUIPMENT
CONNECTIONS PLAN

E-301

5
4
3
2
1

E

D

C

B

A


WALL LEGEND	
SYMBOL	DESCRIPTION
	1 HR FIRE RATED
	2 HR FIRE RATED

GENERAL NOTES

A. ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL ELECTRICAL ITEMS SHOWN ON THE DRAWINGS, EXCEPT ITEMS LISTED ON SHEET E0.01 GENERAL ELECTRICAL NOTES.

KEYNOTES


1. PROVIDE (3) 4" X 4" EZ-PATH FIRE RATED PATHWAYS THROUGH FIRE RATED WALL. PROVIDE GROUNDING BUSHING FOR ALL PATHWAYS AND CONNECT TO GROUND BUS BAR WITH #6 AWG CONDUCTOR.
2. ROUTE (2) 4" CONDUITS FROM CABLE TRAY TO PLYWOOD BACKBOARD.



1 ADDITION SPECIAL SYSTEMS PLAN
1/8" = 1'-0"

...Becoming the
Leading Designer of
High Performance Facilities
in the Nation with a
Specialty in Alternative
Delivery Methods

333 Fayetteville St., Ste 225
Raleigh, NC 27601
P: 919-573-4350
F: 919-573-4355
www.sfl+a.com



CONSTRUCTION
DRAWINGS

optima
engineering
150 Fayetteville St., Suite 520, Raleigh, NC 27601
Phone: 919-565-2200 - www.optimaengineering.com
North Carolina License Number C-0914

Harnett County Schools
LILLINGTON-SHAWTOWN ELEMENTARY ADDITION
855 Old US Highway 421
Lillington, NC 27546



No.	Date	Description

ISSUE DATE: 07-26-24
PROJECT #: 02110.300
DRAWN BY: JSD
CHECKED BY: MKG
© 2024 SFL+A Architects, PA
All Rights Reserved

ADDITION SPECIAL
SYSTEMS PLAN

7/25/2024 6:03:49 PM Autodesk Docs://02110.300 Lillington-Shawtown ES/24-0045R_Lillington-Shawtown ES Addition_MEFPF_R23.rvt

5
4
3
2
1















E

D

C

B

A



...Becoming the
Leading Designer of
High Performance Facilities
in the Nation with a
Specialty in Alternative
Delivery Methods

333 Fayetteville St, Ste 225
Raleigh, NC 27601
P: 919-573-8350
F: 919-573-8355
www.sfi+a.biz

sfi+a
ARCHITECTS

7/26/2024

CONSTRUCTION DRAWINGS

optima
engineering

150 Fayetteville St., Suite 520, Raleigh, NC 27601
Phone: 919-565-2200 www.optimaengineering.com
North Carolina License Number C-0914

LILLINGTON-SHAWTOWN ELEMENTARY ADDITION

Harnett County Schools

855 Old US Highway 421
Lillington, NC 27546

ENERGY STAR PARTNER

No.	Date	Description

ISSUE DATE: 07-26-24
PROJECT #: 02110.300
DRAWN BY: JSD
CHECKED BY: MKG

© 2024 Sfi+a Architects, PA
All Rights Reserved

ELECTRICAL DETAILS

E-601

E

D

C

B

A


5

4


3

2


1




3 TYPICAL TV/MONITOR AND POWER BACK BOX DIAGRAM FOR WALL MOUNTED FLAT SCREEN
NOT TO SCALE




2 EXTERIOR NETWORK DEVICE DETAIL (ACCESSIBLE CEILING)
NOT TO SCALE




1 TYPICAL RECESSED DOWN LIGHT FIXTURE INSTALLATION
DIAGRAM
NOT TO SCALE



6 DOOR CONTACT ONLY
NOT TO SCALE



5 CAMERA MOUNT EXTERIOR WALL
NO SCALE



4 CAMERA MOUNTING FOR EXTERIOR CORNER MOUNT
NO SCALE

...Becoming the Leading Designer of High Performance Facilities in the Nation with a Specialty in Alternative Delivery Methods

333 Fayetteville St., Ste 225
Raleigh, NC 27601
P: 919-573-4350
F: 919-573-4355
www.sfl+a.biz

sfl+a
ARCHITECTS

STATE OF NORTH CAROLINA
REGISTERED PROFESSIONAL ARCHITECT
J. S. DODD
LICENSE NO. 27667
7/26/2024

CONSTRUCTION DRAWINGS

optima
engineering

150 Fayetteville St., Suite 520, Raleigh, NC 27601
Phone: 919-565-2200 | www.optimaengineering.com
North Carolina License Number: C-0914

Harnett County Schools
LILLINGTON-SHAWTOWN ELEMENTARY ADDITION
855 Old US Highway 421
Lillington, NC 27546

ENERGY STAR PARTNER

No.	Date	Description

ISSUE DATE: 07-26-24
PROJECT #: 02110.300
DRAWN BY: JSD
CHECKED BY: MKG
© 2024 Sfl+a Architects, PA
All Rights Reserved

ELECTRICAL DETAILS

E-602

7/25/2024 6:03:51 PM Autodesk Docs://02110.300 Lillington-Shawtown ES/24-0045R_Lillington-Shawtown ES Addition_MEPFP_R23.rvt

LIGHTING SEQUENCE OF OPERATION

A COMPLETE AND OPERATIONAL LIGHTING CONTROL SYSTEM SHALL BE INSTALLED IN ACCORDANCE WITH THE SPECIFICATIONS (SECTION 260923 AND 260943) AND AS INTENDED ON THESE PLANS. ALL CONTROL POINTS AND EQUIPMENT SEQUENCES OF OPERATION LISTED IN SPECIFICATION SECTION 260923 SHALL BE CONSIDERED IN ADDITION TO THOSE LISTED HERE. IN THE EVENT THAT THE VERBIAGE IS IN CONFLICT OR CONTRADICTS THE REQUIREMENTS LISTED HERE, THE QUESTION SHALL BE ASKED PRIOR TO BIDDING OR THE MORE STRINGENT SHALL APPLY.

SYSTEM DESCRIPTION:

LIGHTING CONTROLS ARE BASED ON ETHERNET CONNECTED DEVICES THAT HAVE INDIVIDUAL ADDRESS LOCATIONS FOR PROGRAMMING AND CONTROL. INDEPENDENT OF THE ETHERNET BASED CONTROLS ARE STAND ALONE OCCUPANCY SENSORS. THESE SHALL BE INDEPENDENT AND NOT TIED INTO THE BAS/SYSTEM SOFTWARE.

SENSORS:

- 1. CEILING MOUNTED OCCUPANCY AND VACANCY SENSORS SHALL OPERATE AS PART OF THE ETHERNET BASED SYSTEM AND AS STAND ALONE CONTROLS AS SHOWN ON THE PLANS.
2. WALL MOUNTED NON SWITCH TYPE OCCUPANCY/VACANCY SENSORS SHALL OPERATE AS PART OF THE ETHERNET BASED SYSTEM.
3. ALL OCCUPANCY SENSORS SHALL BE PROGRAMMED FOR AUTOMATIC ON (FULL LEVELS) AND AUTOMATIC OFF.
4. ALL VACANCY SENSORS SHALL BE PROGRAMMED FOR MANUAL ON AND AUTOMATIC OFF.
5. *LARGE PUBLIC SPACES SHALL BE OCCUPANCY BASED WHERE PROVIDED WITH A SENSOR.

TIMER SETTINGS:

- A. WALL SWITCH PASSIVE INFARED: 2 MINUTES FOR INDIVIDUAL RESTROOMS AND STORAGE ROOMS.
B. CLASSROOM VACANCY: 15 MINUTES.
C. WALL SWITCH VACANCY SENSORS OFFICES: 5 MINUTES.
D. OTHER SPACES NOT LISTED: 30 MINUTES.

BAS INTEGRATION:

- A. EXTERIOR LIGHTING ZONES, TIME SCHEDULE AND PHOTOCCELL CONTROL.
B. INTERIOR LIGHTING:
- CORRIDORS
- CLASSROOMS
- OFFICES

COMMISSIONING AND COORDINATION OF BAS:

- 1. BAS CONTROL SHALL BE THE PRIORITY SYSTEM WITH LOCAL OVERRIDES.
2. LIGHTING SYSTEM SHALL ALSO BE INDEPENDENTLY CONTROLLED BY A SOFTWARE BASED SYSTEM.
3. LIGHTING SYSTEM IS CONNECTED TO THE BAS VIA BACNET PROTOCOL OR EQUAL. COORDINATE LANGUAGE REQUIREMENTS WITH MECHANICAL CONTROLS CONTRACTOR SUPPLYING BUILDING AUTOMATION SYSTEM.

LIGHTING COORDINATION AND QUALITY CONTROL:

- 1. ELECTRICAL CONTRACTOR SHALL HAVE A PRE-CONSTRUCTION MEETING WITH CONTROLS SUPPLIER PRIOR TO CONDUIT ROUGH-IN TO VERIFY BOXES, CONDUIT PATHS, AND GENERAL LIGHTING CONTROL STRATEGY FOR INSTALLATION.
2. ELECTRICAL CONTRACTOR SHALL HAVE A POST-SUBMITTAL MEETING WITH BAS CONTROLS SUPPLIER TO IDENTIFY LINE AND LOW VOLTAGE ROUTING, INTENT OF LIGHTING CONTROL DESIGN, AND GENERAL CONSTRUCTION STRATEGIES.

EXTERIOR LIGHTING CONTROL:

- A. EXTERIOR LIGHTING CONTROL IS VIA SCHEDULED TIME CONTROL AND PHOTOCCELL.

OTHER SYSTEM INTEGRATION:

- 1. UPON A FIRE ALARM EVENT, ALL CORRIDOR ZONES SHALL SWEEP ON.

FIXTURE NOTES:

- A. ARCHITECT TO APPROVE ALL EXTERIOR FIXTURE LOCATIONS. E.C. TO MARK OFF LOCATIONS WITH TEMPORARY "CHALK" OUTLINE AND PLAN FOR ARCHITECT ON-SITE APPROVAL OF LOCATIONS BEFORE INSTALLATION. E.C. TO CONTACT ARCHITECT WITH (1) WEEK PRIOR NOTICE.

TIME SCHEDULES:

- A. TIME SCHEDULES ARE TO BE DETERMINED BY THE OWNER. THIS SHALL BE COORDINATED AND DIRECTED BY OWNER AND INPUT BY THE LIGHTING PROGRAMMER AND THE BAS PROGRAMMER. SEE THE BELOW INITIAL SETTING UNTIL OWNER HAS GIVEN INPUT.
B. INITIAL TIME SCHEDULES SHALL BE:
MONDAY - FRIDAY: 6 AM ON, 7 PM OFF
SATURDAY: 8 AM ON, 4 PM OFF
SUNDAY: OFF

INDIVIDUAL AREAS INTENT OF CONTROL:

- MAIN CORRIDORS/HALLWAYS: TIME SCHEDULE ZONED. MANUAL LOW VOLTAGE OVERRIDE IN LOCAL CORRIDOR. CORRIDOR SWITCHES SHALL BE LOCKED OUT (PUBLIC AREAS) DURING "NORMAL OPERATING HOURS."
- GROUP RESTROOMS: ON/OFF WALL SWITCH VACANCY SENSORS (PASSIVE INFARED). OCCUPANCY SENSORS SHALL OPERATE NORMAL AND EMERGENCY FIXTURES IN THIS AREA.
- UTILITY ROOMS, ETC.: ON/OFF WALL SWITCH OCCUPANCY SENSORS.
- STORAGE ROOMS: ON/OFF WALL SWITCH VACANCY SENSORS (PASSIVE INFARED).
- CIVIL TIME SCHEDULE ZONED. ON/OFF WITH FULL DIMMING. EMERGENCY BATTED RELAYS FOR SWITCHED EMERGENCY APPLICATION OF ON/OFF DIMMING. EMERGENCY IS ZONED WITH LOCAL NORMAL ZONE.

LIGHTING SYSTEM NOTES:

- 1. SYSTEM ARCHITECTURE SHALL BE DESIGNED BY RESPECTIVE CONTROLS PROVIDER.
2. SYSTEM IS BASED ON NX DISTRIBUTED INTELLIGENCE. BY HUBBELL. ALL ALTERNATIVE MANUFACTURERS SHALL PROVIDE EQUIPMENT TO MEET THE DESIGN INTENT. (GRAPHIC WALL PODS FOR EXAMPLE.) APPROVED EQUALS: WATSTOPPER DLM, COOPER GREENGATE, OR ACUITY NLIGHT.
3. SEE VENDOR DRAWINGS/DETAILS FOR ALL 0-10V DIMMING WIRING.
4. PROVIDE DEVICE LAYOUT AS PART OF LIGHTING CONTROL SUBMITTAL. INCLUDE ALL DEVICE LOCATIONS, CABLING, EQUIPMENT, ETC.

LIGHTING FIXTURE SCHEDULE

Table with columns: TYPE, DESCRIPTION, LAMP, MINIMUM LUMENS, TOTAL FIXTURE WATTAGE, DRIVER, VOLTAGE, MANUFACTURER, MODEL, REMARKS. Rows include DL1, DLIE, EX1B, EX1G, FPL4, FPL4E, HBL, HBLE, L4, LAE, OWL1, OWLIE, STL1, STLIE, TL.

LIGHTING FIXTURE SCHEDULE NOTES:

- 1. ALL FIXTURES SHALL BE LED UNLESS OTHERWISE SPECIFIED. COLOR TEMPERATURE SHALL BE 3500K UNLESS OTHERWISE NOTED.
2. LED DRIVERS SHALL BE PROVIDED FROM PER MANUFACTURER RECOMMENDATION. AS PART OF THIS RECOMMENDATION COORDINATE THE REQUIRED WAVE OUTPUT SO THEY ARE COMPATIBLE. THIS INCLUDES EMERGENCY DRIVERS.
3. SEE ARCHITECTURAL REFLECTED CEILING PLAN FOR EXACT FIXTURE LOCATIONS.
4. FIXTURES IN FIRE RATED CEILING SHALL BE PROVIDED WITH FIRE RATED TENTS AS REQUIRED.
5. SUSPEND ALL FOUR CORNERS WITH WIRE TO STRUCTURE. DO NOT ALLOW GRID ALONE TO SUPPORT FIXTURE.
6. FIXTURES WITH EMERGENCY BATTERY PACKS SHALL BE SUPPLIED WITH 1100 LUMEN INVERTERS.
7. PROVIDE INTEGRAL SURGE PROTECTION ON ALL EXTERIOR LED DRIVER FIXTURE TYPES.
8. DIMMING OF FIXTURES SHALL BE WITH A SWITCH AS RECOMMENDED BY THE DRIVER MANUFACTURER.
9. THE CONTRACTOR SHALL VERIFY THE LEAD TIME OF ALL PRODUCTS SPECIFIED IN THIS SCHEDULE AT THE TIME OF PACKAGE QUOTE.
10. DURING THE BID PROCESS, THE CONTRACTOR SHALL NOTIFY THE ARCHITECT/ENGINEER OF ANY DELIVERY/SCHEDULING ISSUES.
11. NO SUBSTITUTIONS WILL BE ALLOWED DUE TO LACK OF COORDINATION OF DELIVERY DATES AND CONSTRUCTION SCHEDULE AFTER BID.
12. ALL EXPEDITED EXPENSES SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
13. FIXTURES TO BE INSTALLED IN CEILINGS, INDICATED ON ARCHITECTURAL PLANS AS HAVING INSULATION IN CONTACT WITH CEILING SURFACE, SHALL BE IC RATED BY MANUFACTURER.
14. LED DRIVERS LOCATED IN UNCONDITIONED SPACES SHALL BE RATED FOR 90 DEGREES F.
15. PROVIDE 90 MINUTE EMERGENCY BATTERY BACK UP. EMERGENCY BACK UP SHALL BE BASED ON TYPE OF FIXTURE, LED DRIVER, BALLAST, ETC. EMERGENCY BACKUP SHALL BE DUAL INPUT FOR BOTH SWITCHING AND CHARGING. PROVIDE UNSWITCHED "HOT" FROM LOCAL CIRCUIT UNLESS OTHERWISE INDICATED ON PLANS. PROVIDE WITH INDICATOR LIGHT. INSTALL LED INDICATOR ON LIGHT FIXTURE UNLESS DECORATIVE. DECORATIVE FIXTURES SHALL HAVE INDICATOR PLACED AT LOCAL CEILING. BODINE, PHILLIPS, POWER SENTRY OR EQUAL.
16. PROVIDE EMERGENCY RELAY BASED ON MINIMUM BODINE GLCD-20B OR EQUAL. SEE PLANS FOR INTENT. PROVIDE EMERGENCY GENERATOR/INVERTER CIRCUIT AND SWITCH LEG NORMAL CIRCUIT. SEE DETAIL.
17. POLES PROVIDED FOR LED FIXTURES SHALL BE METAL, REGARDLESS OF SPECIFICATION FOR GROUNDING PURPOSES.

...Becoming the Leading Designer of High Performance Facilities in the Nation with a Specialty in Alternative Delivery Methods

333 Fayetteville St, Ste 225 Raleigh, NC 27601 P: 919-573-4350 F: 919-573-4355 www.sfi+a.biz



CONSTRUCTION DRAWINGS

optima engineering 150 Fayetteville St., Suite 520, Raleigh, NC 27601 Phone: 919-565-2200 www.optimaengineering.com North Carolina License Number C-0914

Harnett County Schools LILLINGTON-SHAWTOWN ELEMENTARY ADDITION 855 Old US Highway 421 Lillington, NC 27546




Table with columns: No., Date, Description. Empty rows for revision tracking.

ISSUE DATE: 07-26-24

PROJECT #: 02110.300

DRAWN BY: JSD

CHECKED BY: MKG

© 2024 Sfi+a Architects, PA All Rights Reserved

LIGHTING FIXTURE SCHEDULE

E-801

5

4

3

2

1

Autodesk Docs://02110.300.Lillington-Shawtown ES/24-0049R_Lillington-Shawtown ES Addition_MEFPF_R23.rvt 7/25/2024 6:03:57 PM