нте# 07-500-21472 Ha...ett County Department of Public nealth 25227

Improvement Permit

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: (\\\ SUBDIVISION Raises ISSUED TO-Ront EXPANSION Site Improvements required prior to Construction Authorization Issuance: Type of Structure: MH 14x73 3BR Proposed Wastewater System Type: GRAVE Projected Daily Flow: 360 GPD Number of bedrooms: 3 Number of Occupants: Basement Yes May be required based on final location and elevations of facilities Pump Required: ☐Yes ☐ No Type of Water Supply:

Community Public Well Distance from well Maintain Allset Backs Permit conditions: MEET OASITE FOR FINAL LAYOUT TUB Out Jumbing Shallow At Grand level or higher Where Shown Authorized State Agent:: SEE ATTACHED SITE SKETCH The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit. Construction Authorization (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: Scale Juan Antonio Torres PROPERTY LOCATION: /// SUBDIVISION ROUSES ROOT LOT # 20 Facility Type: MH 14x70 = 33R New Expansion Repair Basement Fixtures? Yes No Type of Wastewater System** (Initial) Wastewater Flow: GPD (See note below, if applicable) Installation Requirements/Conditions Exact length of each trench 240 Septic Tank Size 1000 gallons Trench Spacing: Feet on Center Trenches shall be installed on contour at a Pump Tank Size gallons Maximum Trench Depth of: 18 (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: ft. TDH vs. inches below pipe inches above pipe **If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Date: 01-27-09 Authorized State Agent: _ Construction Authorization Expiration Date: 0/27-2014

Harnett County Department of Public Health Site Sketch

Authorized State Agent: Quality Date: Q1-27-39 Meet onsite for final Layout Maintain all set Backs Stuß out Plumbing Shallow at ground to ochigher where show and in the whole of grane Is Tostall 240' of grane Is 120' 2 380 Hx70 STUB OUT TOSTAL BY' of grane Is 18° Deep.	ISSUED TO: Juan Artoni	Torres	PROPERTY LOCATO	N: 1111 ROY.KS	ROOM	LOT # 25
Meet consite for final layout maintain all set Backs STUB out Plumbing Shallow at ground to or higher where show Install Dyo'd gravel as 18" Deep.		WARI				
Mickey Rouse Lane TosaIIII	122 Mickey	25° 1. 555×	5	20000000	Layout Maintain STUB OUT Shallow OR higher Install 6 18" Deep	All set Backs + Plumbing At ground le where show 143' gravel a-