## Harnett County Department of Public Health

HTE# 11-5-26593 R

Improvement Permit

26575

A building permit cannot be issued with only an Improvement Permit

i i i i i	PROPERTY LOCATION: DHVE	KO .	
ISSUED TO: WANOA (ARE-)	SUBDIVISION PAULINE T	ERRISON	LOT # 1
NEW C REPAIR E EXPANSION	Site Improvements	required prior to Construction Author	rization Issuance:
Type of Structure: MAN HOME (32+68)		· · · · · · · · · · · · · · · · · · ·	
Proposed Wastewater System Type: 25% REDUCTION			
Projected Daily Flow: <u>360</u> GPD			
Number of bedrooms: Number of Occupants:	max		
Basement 🗆 Yes 🔀 No			
Pump Required: I Yes 🛛 No 🗌 May be required based on final			
Type of Water Supply: 🗆 Community 🔀 Public 🗆 Well Dista	nce from well $\underline{100}$ feet	Permit valid for:	Five years
Permit conditions:			No expiration
the fill the	S Date: 5)25/11		
Authorized State Agent::			ACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of oth site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement	t Permit shall not be affected by a change in ov	cnecking with appropriate governing bodies in whershin of the site. This nermit is subject to	meeting their requirements. This compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit		nie en	compnance with the provisions of
			·····
Const	ruction Authorization		
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .195	equired for Building Permit)	no into this name and shall be need for a	
with the attached system layout.	, .1956. and .1959 are incorporated by reference	es into this permit and shall be met. Systems	shall be installed in accordance
	C	~	
ISSUED TO: WANOR CAREY	property location:	AVE KO	
2	SUBDIVISION YOULING	- IERRYSON	LOT # <u>1</u>
Facility Type: MAN HOME (32+68) X New	🗌 🗆 Expansion 🗖 Repai	r	
Basement? 🗆 Yes 🛛 🔀 No 🛛 Basement Fixtures? 🗖 Yes	X No		
Type of Wastewater System** 25% REDUCTION	System	(Initial) Wastewater Flow:	360 GPD
(See note below, if applicable 🔲)			
25% REDUCTION S	275TEM (Redair)		
Installation Requirements/Conditions Number of tren			
	each trench 75 feet	Trench Spacing:	Feat on Center
-	e installed on contour at a		inches
	h Depth of: $24-36$ inches		
		•	
•	s shall be level to +/-1/4"	36" above the trench both	loinj
in all directions	1		<b></b>
Pump Requirements:ft. TDH vs GPM		• • ·	inches below pipe
		Aggregate Depth:	inches above pipe
Conditions:			inches total

## WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.

