


F52)



8d each side of web through flange at bearing—

Minimum 1-3/4"

BCI® Joist to limit splitting

10

10

2

3

2

4

13

bearing length

Nails placed 1-1/2" minimum from end o

www.BLDR.com 1135 Robeson St Favetteville, NC 28305 V (910) 485-1111 F (910) 485-6475

Boise Cascade Engineered Wood Produc

**Builders** 

FirstSource

7601 BOEING DRIVE GREENSBORO, NC 27409 V: 336.884.5454

3189 NC HIGHWAY5 ABERDEEN NC 28315 V: 910.944.2516

This layout and associated aterials list has been prepared based on project plans and/or information provided to Builders FirstSource (BFS). It

remains the responsibility of the builder, architect, designer, or other responsible persons to view this information to assure that it is appropriate, accurate,

complies with applicable building

2.) ALL WALL SHOW UNLESS NOTES SHOWN HAVE BEEN

덩 & H HOMES FREELANCE (CRAWL EWP PLACEMENT F I

MINIMUM DESIGN DATA LIVE LOAD 40 PSF DEAD LOAD 10 PSF

TOTAL LOAD 50 PSF

STRESS DURATION = 100% DEFLECTION CRITERIA L/480 (MINIMUM)

ARCHITECTUAL PLAN DATE 11-16-17 REVISED ARCH. PLAN DATE XX-XX-XX

SEALED PLAN DATE 12-27-17

> Sheet 1 of 1