HTE# 5701808-008472 Harnett County Department of Public Health

Improvement Permit

A	building permit cannot be issued with only an Improvement Permit	160,772	
ISSUED TO: Timathe + Cartise.	PROPERTY LOCATION: 230 Antioch Church Rd.	101 # 1	
	SSUED TO: Timothy + Cardise Coaca SUBDIVISION LOT #		
Type of Structure: 481 60'x58'	site improvements required prior to construction nation	zation issuance:	
Proposed Wastewater System Type: 25% ne			
Projected Daily Flow: 486 GPD	<u> </u>		
Number of bedrooms: 4 Number of Occu	nants: S may		
Basement Yes No	idittsillax		
	ired based on final location and elevations of facilities		
	☐ Well Distance from well feet Permit valid for:	Five years	
Permit conditions:	Territor validation.	☐ No expiration	
	Carrier State Control of the Control		
Authorized State Agent::		ACHED SITE SKETCH	
The issuance of this permit by the Health Department in no way guaran site is subject to revocation if the site plan, plat, or the intended use of the Laws and Rules for Sewage Treatment and Disposal and to condition	ntees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to as of this permit.	meeting their requirements. This compliance with the provisions of	
	Construction Authorization		
	(Required for Building Permit)		
The construction and installation requirements of Rules .1950, .1952, .1 with the attached system layout.	954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems	shall be installed in accordance	
ISSUED TO: Timothy & Candise	ZABANZIAN	nd. (SR1735	
Facility Type: 431 60'x 58 550	> New Expansion Repair	cor nr	
Basement? Yes No Basement Fixtures? No			
	leduction system (Initial) Wastewater Flow:	480 GPD	
(See note below, if applicable \square)	(IIIIIai) Wastewater How.	drv	
	see red. Sys. (Repair)		
Installation Requirements/Conditions	Number of trenches 3 (Repair)		
Septic Tank Size 1250 gallons	Exact length of each trench 120 feet Trench Spacing:	Fact on Center	
Pump Tank Size gallons	Trenches shall be installed on contour at a Soil Cover: 16 36 in		
Tulip Talik Size gallolis	50		
	The second secon		
	(Trench bottoms shall be level to +/-1/4" 36" above the trench bottoms	om)	
D	in all directions)		
Pump Requirements:ft. TDH vs		inches below pipe	
	Aggregate Depth: NA	inches above pipe	
Conditions: N-BOX Regulad, 12	Deep (28In) To Shallow (18In)	inches total	
WATER LINES (INCLUDING IRRIGATION) MUST IN NO UTILITIES ALLOWED IN INITIAL OR REPAIR D	BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. Brain field area.		
**If applicable: I understand the system type specified	is different from the type specified on the application. I accept the specifications of the	his permit.	
Owner/Legal Representative Signature:			
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This			
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH			
Authorized State Agent:	Date: 01/11/2019		
ANDREW CURRI	Construction Authorization Expiration Date:		

Permit # 30327

Harnett County Department of Public Health Site Sketch

PROPERTY LOCATON: 230 Antioch	Church ad (SRIZ35)
ISSUED TO: Timothy + Cardise Cower SUBDIVISION	LOT #
Authorized State Agent:	1/11/2019
ANDRE : S COOL	

* DEEP(28IN) TO SHALLOW (18IN)
INSTALL REQUIRED

