



Products				
PlotID	Length	Product	Plies	Net Qty
J-38	38' 0"	11-7/8" BCI@ 4500s-1.8	1	22
J-28	28' 0"	11-7/8" BCI@ 4500s-1.8	1	5
J-26	26' 0"	11-7/8" BCI@ 4500s-1.8	1	3
J-20	20' 0"	11-7/8" BCI@ 4500s-1.8	1	5
J-14	14' 0"	11-7/8" BCI@ 4500s-1.8	1	4
RIM	12' 0"	1" x 11-7/8" BC RIM BOARD OSB	1	15
BK	9' 0"	11-7/8" BCI@ 4500s-1.8	1	1

Builders FirstSource
Engineered Wood Products

Boise Cascade
Engineered Wood Products

www.BLDR.com

1135 Robeson St.
Fayetteville, NC 28305
V (910) 485-1111
F (910) 485-6475

7601 BOEING DRIVE
GREENSBORO, NC 27409
V: 336.884.5454

3189 NC HIGHWAY5
ABERDEEN NC 28315
V: 910.944.2516

This layout and associated materials list has been prepared based on project plans and/or information provided to Builders FirstSource (BFS). It remains the responsibility of the builder, architect, designer, or other responsible persons to review this information to assure that it is appropriate, accurate, complete and complies with applicable building codes.

GENERAL NOTES

- 1.) READ THE INSTALLATION GUIDE BEFORE FRAMING.
- 2.) ALL WALL SHOWN ARE LOAD BEARING UNLESS NOTES OTHERWISE. WALLS NOT SHOWN HAVE BEEN CONSIDERED NON-LOAD BEARING.
- 3.) UNLESS STATED OTHERWISE ALL CEILING & ROOF LOADS BRACE DIRECTLY TO LOAD BEARING WALLS SUPPORTED BY FOUNDATION.
- 4.) CONTACT YOUR LOCAL BUILDERS FIRSTSOURCE & ADJUSTMENTS. FAILURE MAY RESULT IN COSTLY REPAIRS.

H & H HOMES	EMBAK GL	JOB #
	CRAWL EWP PLACEMENT PLAN	DATE: 3-21-18
Builders FirstSource, Central Carolina Markets		SCALE: NTS
DRAWN BY: LEE ATKINS		

MINIMUM DESIGN DATA

LIVE LOAD 40 PSF
DEAD LOAD 10 PSF

TOTAL LOAD 50 PSF

STRESS DURATION = 100%

DEFLECTION CRITERIA
L/480 (MINIMUM)

ARCHITECTURAL PLAN DATE
11-17-17

REVISED ARCH. PLAN DATE
XX-XX-XX

SEALED PLAN DATE
12-15-17

Sheet

1 of 1