Department of Environment, Health and Natural Resources Division of Environmental Health On-Site Wastewater Section

Description

Site LTAR

Available Space (.1945) System Type(s)

Initial

System

2540 Md

Repair System

2590 Nd

0.4

## SOIL/SITE EVALUATION for ON-SITE WASTEWATER SYSTEM

Owner: - Applicant: 661 Homes Address: 356 Mineral Spriger Date Evaluated: 02/14/2019

Sheet: Property ID:

Lot #: File #: Code:

SED1902-0009

WELL POND

LOT 192

Evalua	sed Facility: ion of Site: Supply: ation Method of Wastewate	l: Auge	Design Prop	gn Flow (.1949): 49 erty Recorded: ndividual Pit Industrial	Sc C(○ Property Si  Well □ Spring □ Cut	ze: 6.46AC			
P R O F I L	.1940 Landscape Position/ Slope %	Horizon Depth (In.)	SOIL MORPHOLOGY		OTHER PROFILE FACTORS				
E #			.1941 Structure/ Texture	.1941 Consistence Mineralogy	Soil Wetness/ Color	.1943 Soil Depth (IN.)	.1956 Sapro Class	.1944 Restr Horiz	Profile Class & LTAR
1,2	L3%	0-26	GL LS	un work	7.5702/1044"				P3
		20-48	BN SU	rn 5358	7.58270244"	48			0.4
					-				

Other Factors (.1946):

Others Present:

Site Classification (.1948): Provisionally Soltable
Evaluated By:
Others Present:

Andrew Corring MEHD

R-RIDGE S-SHOULDER SLOPE L-LINEAR SLOPE L-LINEAR SLOPE H-HEAD SLOPE CC-CONCLAVE SLOPE T-TERRACE FP-FLOOD PLAN  IV  SIC-SILTY CLAY C-CLAY SC-SANDY CLAY  STRUCTURE SG-SINGLE GRAIN M-MASSIVE CR-CRUMB  R-RIDGE S-SAND L.2 - 0.8  VFR-VERY FRIABLE FR-FRIABLE FR-FRIABLE FR-FRIABLE FR-FRIABLE FR-FRIABLE FR-FRIABLE FR-FRIABLE FI-FIRM VFI-VERY FIRM VFI-VERY FIRM EFI-EXTREMELY FIRM FI-EXTREMELY FIRM O.6 - 0.3  VFR-VERY FRIABLE FI-FIRM VFI-VERY FIRM VFI-VERY FIRM FR-FRIABLE FI-FIRM VFI-VERY FIRM VFI-
S-SHOULDER SLOPE L-LINEAR SLOPE FS-FOOT SLOPE N-NOSE SLOPE H-HEAD SLOPE CC-CONCLAVE SLOPE T-TERRACE FP-FLOOD PLAN  IV  SIC-SILTY CLAY C-CLAY SC-SANDY CLAY  STRUCTURE SG-SINGLE GRAIN M-MASSIVE  LS-LOAMY SAND  VFR-VERY FRIABLE FR-FRIABLE SS-SLIGHTY STICKY SS-SLIGHTLY STICKY P-PLASTIC VP-VERY PLASTIC
FS-FOOT SLOPE N-NOSE SLOPE H-HEAD SLOPE CC-CONCLAVE SLOPE T-TERRACE FP-FLOOD PLAN  IV  SIC-SILTY CLAY C-CLAY SC-SANDY CLAY SC-SANDY CLAY  STRUCTURE SG-SINGLE GRAIN M- MASSIVE  III SL-SANDY LOAM 0.8 - 0.6 FI-FIRM VS-VERY STICKY VFI-VERY FIRM EFI-EXTREMELY FIRM NP-NON-PLASTIC SP-SLIGHTLY STICKY P-PLASTIC VP-VERY PLASTIC VP-VERY PLASTIC VP-VERY PLASTIC VP-VERY PLASTIC
CC-CONCLAVE SLOPE CV-CONVEX SLOPE T-TERRACE FP-FLOOD PLAN  IV SIC-SILTY CLAY C-CLAY SC-SANDY CLAY SC-SANDY CLAY  STRUCTURE SG-SINGLE GRAIN M-MASSIVE  III SI-SILT 0.6 - 0.3 SP-SLIGHTLY STICKY P-PLASTIC VP-VERY PLASTIC
C-CLAY SC-SANDY CLAY  STRUCTURE SG-SINGLE GRAIN M-MASSIVE  MINERALOGY SLIGHTLY EXPANSIVE
SG-SINGLE GRAIN M-MASSIVE SLIGHTLY EXPANSIVE
GR-GRANULAR SBK-SUBANGULAR BLOCKY
ABK-ANGULAR BLOCKY PL-PLATY PR. PRISMATIC
Show profile locations and other site features (dimensions, references or benchmark, and North)
a con
(2) 1 = 100FER
TONTIAL
45.

Plw

MINERAL SPRINGE AD