Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

ICCUED TO DOTHODY COOT		ION: MCDouga		
ISSUED TO: Bethany Scott	SUBDIVISION			LOT # 4
NEW REPAIR EXPANSION	ON 🔲	Site Improvements re-	quired prior to Construction	on Authorization Issuance:
Type of Structure: SFD (50'x40')				
Proposed Wastewater System Type: 25% Reduc	tion System			
Projected Daily Flow: 480 GPD				
Number of bedrooms: 4 Number of Occu	pants: 8max			
Basement Yes No	0.0000000			
Pump Required: ☐Yes ☒ No ☐ May be requ	ired based on final location and elevati	ions of facilities		
Type of Water Supply: Community Public			Permit vali	d for: Five years
Permit conditions: Clear lot (underbrush				No expiration
design.				
Authorized State Agent::	REAS Date: 3	/27/2019		SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guara	ntees the issuance of other permits. The permit h			
site is subject to revocation if the site plan, plat, or the intended use	changes. The Improvement Permit shall not be af	fected by a change in own	ership of the site. This permit is	subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to condition	ns of this permit.			
	Construction Aut	horization		
	(Required for Buildin			
The construction and installation requirements of Rules .1950, .1952, .1			into this parmit and shall be m	not Sustante shall be installed in accordance
with the attached system layout.	774, 1773, 1770, 1771, 1770, and 1777 are	incorporated by references	into tins permit and snan be n	ec. systems shall be installed in accordance
ISSUED TO:	PROPERTY	LOCATION:		
	SUBDIVISION	ł		LOT #
Facility Type:	New Expansion	on 🔲 Repair		
	tures? Yes No			
Ivne of Wastewater (vstem**			(Initial) Wastewate	r Flow: CPD
Type of Wastewater System**			(Initial) Wastewate	r Flow: GPD
			(Initial) Wastewate	r Flow: GPD
(See note below, if applicable)		(Repair)	(Initial) Wastewate	r Flow: GPD
(See note below, if applicable)	Number of trenches	(Repair)		
(See note below, if applicable) Installation Requirements/Conditions Septic Tank Sizegallons		(Repair)		r Flow: GPD
(See note below, if applicable)	Number of trenches	(Repair)		Feet on Center
(See note below, if applicable) Installation Requirements/Conditions Septic Tank Sizegallons	Number of trenches	(Repair)feet ntour at a	Trench Spacing: Soil Cover:	Feet on Center
(See note below, if applicable) Installation Requirements/Conditions Septic Tank Sizegallons	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of:	(Repair)feet ntour at ainches	Trench Spacing: Soil Cover: (Maximum soil cove	Feet on Center inches r shall not exceed
(See note below, if applicable) Installation Requirements/Conditions Septic Tank Sizegallons	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to	(Repair)feet ntour at ainches	Trench Spacing: Soil Cover:	Feet on Center inches r shall not exceed
(See note below, if applicable	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions)	(Repair)feet ntour at ainches	Trench Spacing: Soil Cover: (Maximum soil cove	Feet on Center inches r shall not exceed nch bottom)
(See note below, if applicable	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to	(Repair)feet ntour at ainches	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tre	Feet on Centerinches r shall not exceed nch bottom) inches below pipe
See note below, if applicable	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM	(Repair)feet ntour at ainches +/-1/4"	Trench Spacing: Soil Cover: (Maximum soil cove	Feet on Center inches r shall not exceed nch bottom) inches below pipe inches above pipe
(See note below, if applicable	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM	(Repair)feet ntour at ainches +/-1/4"	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tre	Feet on Centerinches r shall not exceed nch bottom) inches below pipe
See note below, if applicable	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM	(Repair)feet ntour at ainches +/-1/4"	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tre	Feet on Center inches r shall not exceed nch bottom) inches below pipe inches above pipe
See note below, if applicable	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM	(Repair)feet ntour at ainches +/-1/4"	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tre	Feet on Center inches r shall not exceed nch bottom) inches below pipe inches above pipe
Installation Requirements/Conditions Septic Tank Size	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SE	(Repair)feet ntour at ainches +/-1/4"	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tre	Feet on Center inches r shall not exceed nch bottom) inches below pipe inches above pipe
Installation Requirements/Conditions Installation Requirements/Conditions	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SE	(Repair)feet ntour at ainches +/-1/4"	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tre Aggregate Depth:	Feet on Centerinches r shall not exceed nch bottom) inches below pipe inches above pipe inches total
Installation Requirements/Conditions Installation Requirements/Conditions	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SE	(Repair)feet ntour at ainches +/-1/4"	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tre Aggregate Depth:	Feet on Centerinches r shall not exceed nch bottom) inches below pipe inches above pipe inches total
Installation Requirements/Conditions Septic Tank Size	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SEI ORAIN FIELD AREA. It is different from the type specified	(Repair) —————feet ntour at ainches +/-1/4" PTIC SYSTEM OR F	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tree Aggregate Depth: REPAIR AREA.	Feet on Centerinches r shall not exceed nch bottom) inches below pipe inches above pipe inches total
Installation Requirements/Conditions Installation Requirements/Conditions Septic Tank Size	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SEI ORAIN FIELD AREA. It is different from the type specified	(Repair) ————————————————————————————————————	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tree Aggregate Depth: REPAIR AREA. / accept the specificate Date:	Feet on Centerinches r shall not exceed nch bottom) inches below pipe inches above pipe inches total
Installation Requirements/Conditions Installation Requirements/Conditions Septic Tank Size	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SEL DRAIN FIELD AREA. It is different from the type specified	(Repair)feet ntour at ainches +/-1/4" PTIC SYSTEM OR F	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tree Aggregate Depth: REPAIR AREA. I accept the specificate Date: be transferred when there is a continuous process.	Feet on Centerinches r shall not exceed nch bottom) inches below pipe inches above pipe inches total
(See note below, if applicable	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SEL DRAIN FIELD AREA. It is different from the type specified	(Repair)feet ntour at ainches +/-1/4" PTIC SYSTEM OR F	Trench Spacing: Soil Cover: (Maximum soil cove 36" above the tree Aggregate Depth: REPAIR AREA. I accept the specificate Date: be transferred when there is a continuous process.	Feet on Centerinches r shall not exceed nch bottom) inches below pipe inches above pipe inches total
Installation Requirements/Conditions Installation Requirements/Conditions Septic Tank Size	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SEL DRAIN FIELD AREA. It is different from the type specified plat, or the intended use changes. The Construction If the Laws and Rules for Sewage Treatment and	(Repair) feet ntour at ainches +/-1/4" PTIC SYSTEM OR F	Trench Spacing:	Feet on Centerinches r shall not exceed nch bottom) inches below pipeinches above pipeinches total ions of this permit.
Installation Requirements/Conditions Installation Requirements/Conditions Septic Tank Size	Number of trenches Exact length of each trench Trenches shall be installed on cor Maximum Trench Depth of: (Trench bottoms shall be level to in all directions) GPM BE 10FT. FROM ANY PART OF SEL DRAIN FIELD AREA. It is different from the type specified plat, or the intended use changes. The Construction If the Laws and Rules for Sewage Treatment and	(Repair) feet ntour at ainches +/-1/4" PTIC SYSTEM OR F	Trench Spacing:	Feet on Center