## Harnett County Department of Public Health

## Improvement Permit

A building permit cannot be issued with only an Improvement Permit

PROPERTY LOCATION: 22 Treasure Dr. (Neills Creek Rd. - SR 1513)

ICCURD TO Cumberland Homes Inc	PROPERTY LOCATION: 22 Treasure L		
ISSUED TO: Cumberland Homes Inc.	SUBDIVISION South Creek		LOT # 24
NEW REPAIR EXPANSION Type of Structure: 76.8X57 3BR 2BA SFD Slab	Site Improvements re	quired prior to Construction Authori	ization Issuance:
Proposed Wastewater System Type: 25% Reduction Sys			
Projected Daily Flow: 360 GPD	6		
	ts: 6max		
Basement Tres No	A based on Carl based and a based on a Carloin		
Pump Required: Yes No May be required  Type of Water Supply: Community Public	d based on final location and elevations of facilities	Permit valid for:	▼ Five years
			No expiration
Permit conditions:			Mo expiration
	2 _		
Authorized State Agent::	11/1645 Date: 03/611	8019 SEE ATTI	ACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantee			
site is subject to revocation if the site plan, plat, or the intended use chan			
the Laws and Rules for Sewage Treatment and Disposal and to conditions of	f this permit.		
	Construction Authorization		
	(Required for Building Permit)		
The construction and installation requirements of Rules .1950, .1952, .1954,		into this permit and shall be mot Systems	shall be installed in accordance
with the attached system layout.	1775, 1776, 1775, 1775. and 1777 are mediporated by references	into this perint and shall be met. systems	shall be histaned in accordance
* *			
ISSUED TO: Cumberland Homes Inc.		sure Dr. (Neills Creek Rd S	
	SUBDIVISION South Creek		LOT # <u>24</u>
Facility Type: 76.8X57 3BR 2BA SFD Slab	New □ Expansion □ Repair		
Basement? Yes No Basement Fixture	es? Yes No		
Type of Wastewater System** 25% Reduction System	tem	(Initial) Wastewater Flow:	360 GPD
	tem	(Initial) Wastewater Flow: _	360 GPD
(See note below, if applicable )		(Initial) Wastewater Flow: _	360 GPD
(See note below, if applicable )	s. (Repair)	(Initial) Wastewater Flow: _	360 GPD
(See note below, if applicable )  25% Reduction Systems   10   10   10   10   10   10   10   1	s. (Repair)		
(See note below, if applicable)	s(Repair)  Number of trenches 1  Exact length of each trench 225feet	Trench Spacing: 9	Feet on Center
(See note below, if applicable)  25% Reduction Systems	s. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Frenches shall be installed on contour at a	Trench Spacing: 9 Soil Cover: 12i	Feet on Center nches
(See note below, if applicable)  25% Reduction Systems	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches	Trench Spacing: 9 Soil Cover: 12ii (Maximum soil cover shall n	Feet on Center nches not exceed
(See note below, if applicable)	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a inches  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 12i	Feet on Center nches not exceed
(See note below, if applicable)  25% Reduction Systems   25% Reduction S	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Frenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  Trench bottoms shall be level to +/-1/4"  n all directions)	Trench Spacing: 9 Soil Cover: 12i (Maximum soil cover shall n 36" above the trench botto	Feet on Center nches not exceed om)
(See note below, if applicable)  25% Reduction Systems   25% Reduction S	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a inches  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 12 (Maximum soil cover shall n 36" above the trench botto	Feet on Center nches not exceed
(See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM	Trench Spacing: 9 Soil Cover: 12 (Maximum soil cover shall n 36" above the trench botto	Feet on Center nches not exceed om)
(See note below, if applicable)  25% Reduction Systems   25% Reduction S	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM	Trench Spacing: 9 Soil Cover: 12 (Maximum soil cover shall n 36" above the trench botto	Feet on Center nches not exceed om) inches below pipe
(See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM	Trench Spacing: 9  Soil Cover: 12i  (Maximum soil cover shall n 36" above the trench botto  NA  Aggregate Depth: NA	Feet on Center nches not exceed om) inches below pipe inches above pipe
(See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM  allows	Trench Spacing: 9  Soil Cover: 12	Feet on Center nches not exceed om) inches below pipe inches above pipe
(See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  allows	Trench Spacing: 9  Soil Cover: 12	Feet on Center nches not exceed om) inches below pipe inches above pipe
(See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  allows	Trench Spacing: 9  Soil Cover: 12	Feet on Center nches not exceed om) inches below pipe inches above pipe
(See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a feet  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM  allows  10FT. FROM ANY PART OF SEPTIC SYSTEM OR I	Trench Spacing: 9  Soil Cover: 12  (Maximum soil cover shall n 36" above the trench botto  Aggregate Depth: NA  NA  NA  REPAIR AREA.	Feet on Center nches not exceed om) inches below pipe inches above pipe inches total
(See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a feet  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM  allows  10FT. FROM ANY PART OF SEPTIC SYSTEM OR I	Trench Spacing: 9  Soil Cover: 12  (Maximum soil cover shall n 36" above the trench botto  Aggregate Depth: NA  NA  NA  REPAIR AREA.	Feet on Center nches not exceed om) inches below pipe inches above pipe inches total
See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a feet  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM  allows  10FT. FROM ANY PART OF SEPTIC SYSTEM OR I	Trench Spacing: 9  Soil Cover: 12  (Maximum soil cover shall n 36" above the trench bottom  Aggregate Depth: NA  NA  NA  REPAIR AREA.	Feet on Center nches not exceed om) inches below pipe inches above pipe inches total
See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM  allows  10FT. FROM ANY PART OF SEPTIC SYSTEM OR INTELD AREA.  In different from the type specified on the application.	Trench Spacing: 9  Soil Cover: 12	Feet on Center nches not exceed nom) inches below pipe inches above pipe inches total
See note below, if applicable   25% Reduction Systematical   25% Reducti	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM  allows  10FT. FROM ANY PART OF SEPTIC SYSTEM OR IN FIELD AREA.  different from the type specified on the application.  or the intended use changes. The Construction Authorization shall not intended.	Trench Spacing: 9  Soil Cover: 12  (Maximum soil cover shall n 36" above the trench botto  Aggregate Depth: NA  NA  REPAIR AREA.  Date:  Date:  Date:	Feet on Center nches not exceed nom) inches below pipe inches above pipe inches total
See note below, if applicable	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM  allows  10FT. FROM ANY PART OF SEPTIC SYSTEM OR IN FIELD AREA.  different from the type specified on the application.  or the intended use changes. The Construction Authorization shall not intended.	Trench Spacing: 9  Soil Cover: 12  (Maximum soil cover shall n 36" above the trench botto  Aggregate Depth: NA  NA  REPAIR AREA.  Date:  Date:  Date:	Feet on Center nches not exceed nom inches below pipe inches above pipe inches total whis permit.
See note below, if applicable   25% Reduction Systematical Requirements/Conditions   Septic Tank Size 1000   gallons   Pump Tank Size   gallons   gallons   gallons   Pump Tank Size   ft. TDH vs.   Conditions: Four (4) 60ft lines with D-Box if contour   WATER LINES (INCLUDING IRRIGATION) MUST BE NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRA   **If applicable:   understand the system type specified is   Owner/Legal Representative Signature:   This Construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the provisions of the construction Authorization is subject to compliance with the construction Authorization is subject to compliance with the construction Authorization is subject to complianc	Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" n all directions)  GPM  allows  10FT. FROM ANY PART OF SEPTIC SYSTEM OR IN FIELD AREA.  different from the type specified on the application.  or the intended use changes. The Construction Authorization shall not le Laws and Rules for Sewage Treatment and Disposal and to the conditional contents.	Trench Spacing: 9  Soil Cover: 12  (Maximum soil cover shall n 36" above the trench bottom  Aggregate Depth: NA  NA  REPAIR AREA.  Date:  De transferred when there is a change in owe ions of this permit.  SEE A	Feet on Center nches not exceed om)  inches below pipe inches above pipe inches total  this permit.  whership of the site. This ATTACHED SITE SKETCH
See note below, if applicable   25% Reduction Systematical   25% Reducti	S. (Repair)  Number of trenches 1  Exact length of each trench 225 feet  Trenches shall be installed on contour at a  Maximum Trench Depth of: 24 inches  (Trench bottoms shall be level to +/-1/4" and directions)  GPM  allows  10FT. FROM ANY PART OF SEPTIC SYSTEM OR INTELD AREA.  If different from the type specified on the application of the intended use changes. The Construction Authorization shall not be laws and Rules for Sewage Treatment and Disposal and to the conditional contents.  Date:	Trench Spacing: 9  Soil Cover: 12  (Maximum soil cover shall n 36" above the trench bottom  Aggregate Depth: NA  NA  REPAIR AREA.  Date:  De transferred when there is a change in owe ions of this permit.  SEE A	Feet on Center nches not exceed om)  inches below pipe inches above pipe inches total  this permit.  whership of the site. This ATTACHED SITE SKETCH

HTE#	SED	1902	-0026
111 - 11			

Permit # ~ ~ ~ ~ ~ ~ \_ \_\_\_\_

## Harnett County Department of Public Health Site Sketch

PROPERTY LOCATON: 22 Trensure Dr. (No:116/rock 2)

ISSUED TO: Cum kerland Homes, Fr.c. SUBDIVISION South Creek LOT # 24

Authorized State Agent: Date: 03/01/2019

