





Truss Placement Plan SCALE: NTS

____ = Indicates Left End of Truss (Reference Engineered Truss Drawing) Do NOT Erect Truss Backwards

			_		_		
LOAD CHART FOR JACK STUDS (BASED ON TABLES 8502.5(1) & (b)) NUMBER OF JACK STUDS REQUIRED @ EA END OF			BUILDER	Site Name	COUNTY	County	THIS IS A TO These trusses the building de sheets for each
	END REACTION (UP TC) (UP TC) REQ'D STUDS FOR SIGNER (3) PLY HEADER BARBER (3) PLY HEADER	3400 1 6800 2 10200 3 13600 4 17000 5	JOB NAME	Prelude C	ADDRESS	Site Address	is responsible the overall stru walls, and coluregarding bract or online @ sbo Bearing react prescriptive C (derived from foundation sizthan 3000# bb be retained to specified in the retained to de
			PLAN	Prelude C	MODEL	Model	
1700 1 3400 2 5100 3	2550 1 5100 2 7650 3		SEAL DATE	12/27/17	DATE REV.	//	
8500 5 1	10200 4 12750 5 15300 6		QUOTE#	B0318-1246	DRAWN BY	Marshall Naylor	
			JOB#	Order#	SALESMAN	Marshall Naylor	

S A TRUSS PLACEMENT DIAGRAM ONLY.
usses are designed as individual building components to be incorporated into ing design at the specification of the building designer. See individual design reach truss design identified on the placement drawing. The building designer isible for temporary and permanent bracing of the roof and floor system and for II structure. The design of the truss support structure including headers, beams, a columns is the responsibility of the building designer. For general guidance | bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package @ sbcindustry.com

eactions less than or equal to 3000# are deemed to comply with the vive Code requirements. The contractor shall refer to the attached Tables from the prescriptive Code requirements) to determine the minimum on size and number of wood studs required to support reactions greater ## but not greater than 15000#. A registered design professional shall ed to design the support system for any reaction that exceeds those in the attached Tables. A registered design professional shall be to design the support system for all reactions that exceed 15000#.

Marshall Naylor



Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444