


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AH	Roof Special Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:25 2020 Page 1
 ID:hjOMp88mnrQZrZrEntywViFyWSr_-rKi4Ez0rvkM5wYsMdXIP90a0e6xGiG1w0u3o7yW5rG



Scale = 1:78.0




Plate Offsets (X,Y)-- [2:0-2-14,0-2-0], [9:0-4-4,0-2-4]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.48	Vert(LL) 0.13 15 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.58	Vert(CT) -0.23 15-17 >999 180		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.57	Horz(CT) 0.03 11 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 547 lb FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.); 7-9.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

REACTIONS. (lb/size) 19=1773/0-3-8 (min. 0-1-8), 11=2363/Mechanical
 Max Horz 19=269(LC 9)
 Max Uplift 19=272(LC 12), 11=750(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2348/521, 3-4=-2140/545, 4-5=-2067/609, 5-6=-1999/632,
 6-7=-4267/1267, 7-8=-3504/1128, 8-20=-3504/1128, 9-20=-3504/1128,
 9-10=-3162/1070, 2-19=-1687/437, 10-11=-2197/747
 BOT CHORD 18-19=-290/559, 17-18=-367/1886, 16-17=-500/2341, 16-21=-500/2341,
 15-21=-500/2341, 14-15=-893/3589, 13-14=-893/3589, 13-22=-800/2525,
 22-23=-800/2525, 12-23=-800/2525, 12-24=-184/368, 24-25=-184/368,
 11-25=-184/368
 WEBS 4-17=-442/253, 5-17=-550/1853, 6-17=-1632/582, 6-15=-855/2737,
 7-15=-2446/881, 7-13=-738/398, 8-13=-335/208, 9-13=-271/1418,
 9-12=-298/425, 2-18=-202/1501, 10-12=-630/2187

- NOTES-**
- 2-ply truss to be connected together with 10d (0.120"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=750.
 - One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 19. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AH	Roof Special Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:25 2020 Page 2
 ID:hjOMp88mnrQZrZEntywViFyWSr_-rKi4Ez0rvkM5wYsMdXIP90aoe6xGiG1w0u3o7yW5rG

NOTES-

- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 13) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 120 lb down and 162 lb up at 29-5-4 on top chord, and 675 lb down and 225 lb up at 27-11-8, 45 lb down and 40 lb up at 29-5-4, 169 lb down and 143 lb up at 31-5-4, and 120 lb down and 102 lb up at 33-5-4, and 120 lb down and 89 lb up at 35-5-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.


LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 - Uniform Loads (plf)
 - Vert: 1-2=-60, 2-5=-60, 5-7=-60, 7-9=-60, 9-10=-60, 11-19=-20
 - Concentrated Loads (lb)
 - Vert: 12=-120(F) 20=-40(F) 22=-675(F) 23=-23(F) 24=-120(F) 25=-120(F)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHA	Roof Special	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:27 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-njqqff26RLdp9s0klyntFRf30wV4A5cDIKNAtoYw5rE



Scale = 1:78.1




Plate Offsets (X,Y)-- [2:0-3-0,Edge], [4:0-4-0,Edge], [6:0-3-0,Edge], [14:0-3-0,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.81	Vert(LL) -0.32 12-14 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 1.00	Vert(CT) -0.57 12-14 >787 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.83	Horz(CT) 0.10 11 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 249 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2 *Except*
 T2,T3: 2x6 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2 *Except*
 B2: 2x4 SP No.1
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 3-7-4 oc purlins, except end verticals, and 2-0-0 oc purlins (3-9-5 max.): 6-8.
 BOT CHORD Rigid ceiling directly applied or 1-4-12 oc bracing.
 WEBS 1 Row at midpt 6-14, 7-12, 3-17, 9-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 17=1550/0-3-8 (min. 0-2-8), 11=1487/Mechanical
 Max Horz 17=272(LC 11)
 Max Uplift 17=-149(LC 12), 11=-208(LC 13)
 Max Grav 17=1606(LC 19), 11=1487(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-590/255, 3-4=-1971/444, 4-5=-1865/473, 5-6=-2534/613, 6-7=-2102/456,
 7-8=-1515/369, 8-9=-1891/399, 9-10=-282/92, 2-17=-543/242
 BOT CHORD 17-18=-231/1758, 18-19=-231/1758, 16-19=-231/1758, 16-20=-94/1427,
 15-20=-94/1427, 15-21=-94/1427, 14-21=-94/1427, 14-22=-260/1914,
 13-22=-260/1914, 13-23=-260/1914, 12-23=-260/1914, 11-12=-262/1505
 WEBS 3-16=-259/273, 5-16=-149/581, 5-14=-372/1816, 6-14=-1584/437,
 7-14=-36/393, 7-12=-707/172, 8-12=-104/793, 3-17=-1618/154,
 9-11=-1782/337


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=208.
 - One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHA1	Roof Special Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:30 2020 Page 1
 ID:hjOMp88mnrQzrZEntyVIFyWSr_-BIWYHh4_kG?OOJkQ4Las3Hex7bQNVsfRlCqULyW5rB



Scale = 1:78.3




Plate Offsets (X,Y)-- [2:0-2-14,0-2-0], [9:0-4-4,0-2-4], [12:0-9-7,0-2-8], [16:0-3-8,0-2-0]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.51	Vert(LL)	0.15	16	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.70	Vert(CT)	-0.27	16	>999		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.67	Horz(CT)	0.04	12	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 547 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-7-13 oc purlins, except end verticals, and 2-0-0 oc purlins (5-9-9 max.): 7-9.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 20=1900/0-3-8 (min. 0-1-8), 12=2707/0-3-8 (min. 0-2-2)
 Max Horz 20=-267(LC 10)
 Max Uplift 20=-324(LC 12), 12=-901(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2533/596, 3-4=-2331/620, 4-5=-2296/694, 5-6=-2228/717,
 6-7=-4832/1478, 7-8=-4212/1399, 8-21=-4212/1399, 21-22=-4212/1399,
 9-22=-4212/1399, 9-10=-3594/1265, 2-20=-1813/486, 10-12=-2546/917
 BOT CHORD 19-20=-280/556, 18-19=-395/2030, 18-23=-579/2644, 17-23=-579/2644,
 17-24=-579/2644, 16-24=-579/2644, 15-16=-1040/4080, 14-15=-1040/4080,
 14-25=-920/2876, 25-26=-920/2876, 26-27=-920/2876, 13-27=-920/2876,
 13-28=-239/465, 28-29=-239/465, 12-29=-239/465
 WEBS 4-18=-431/263, 5-18=-649/2121, 6-18=-1941/689, 6-16=-1040/3252,
 7-16=-2974/1060, 7-14=-819/595, 8-14=-402/293, 9-14=-416/1854,
 9-13=-245/383, 2-19=-269/1662, 10-13=-739/2443

- NOTES-**
- 2-ply truss to be connected together with 10d (0.120"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 12=901.
 - One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 20. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHA1	Roof Special Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:31 2020 Page 2
 ID:hjOMp88mnrQZrZEntywViFyWSr_-gU4LV15cVa7EeTJV_ospPHppgXxf6x6pgyLN0nyW5rA

NOTES-

12) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 120 lb down and 162 lb up at 27-11-4, and 120 lb down and 162 lb up at 29-5-4 on top chord, and 1022 lb down and 265 lb up at 27-1-0, 45 lb down and 40 lb up at 27-11-4, 45 lb down and 40 lb up at 29-5-4, 169 lb down and 143 lb up at 31-5-4, and 120 lb down and 102 lb up at 33-5-4, and 120 lb down and 89 lb up at 35-5-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-5=-60, 5-7=-60, 7-9=-60, 9-10=-60, 10-11=-60, 12-20=-20

Concentrated Loads (lb)

Vert: 13=-120(B) 21=-40(B) 22=-40(B) 25=-1022(B) 26=-23(B) 27=-23(B) 28=-120(B) 29=-120(B)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHA2	Roof Special	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:32 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_8hdjiM6EGtF5FduiYVN2yUMwPxDSrMTyvc5xYDyW5r9

0-10-8	6-10-10	13-5-12	17-6-4	22-9-8	28-0-12	32-7-10	37-6-0	38-4-8
0-10-8	6-10-10	6-7-2	4-0-8	5-3-4	5-3-4	4-6-14	4-10-6	0-10-8

Scale = 1:78.3




Plate Offsets (X,Y)-- [2:0-3-0,Edge], [4:0-4-0,Edge], [10:0-2-0,0-1-12]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.76	Vert(LL) -0.25 16-18 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.92	Vert(CT) -0.42 16-18 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.79	Horz(CT) 0.10 12 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 258 lb FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2 *Except* T2,T3: 2x6 SP No.2	TOP CHORD Structural wood sheathing directly applied or 3-8-12 oc purlins, except end verticals, and 2-0-0 oc purlins (3-10-5 max.): 6-8.
BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 18-19.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 6-16, 6-14, 3-19, 9-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 19=1550/0-3-8 (min. 0-2-8), 12=1550/0-3-8 (min. 0-2-7)
 Max Horz 19=270(LC 11)
 Max Uplift 19=-146(LC 12), 12=-234(LC 13)
 Max Grav 19=1598(LC 19), 12=1550(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-550/248, 3-4=-1977/445, 4-5=-1875/474, 5-6=-2510/614, 6-7=-1944/465,
 7-8=-1945/467, 8-9=-1870/405, 9-10=-349/120, 2-19=-517/236,
 10-12=-355/144
 BOT CHORD 19-20=-195/1758, 20-21=-195/1758, 18-21=-195/1758, 18-22=-67/1444,
 17-22=-67/1444, 17-23=-67/1444, 16-23=-67/1444, 16-24=-219/2098,
 15-24=-219/2098, 14-15=-219/2098, 14-25=-131/1510, 13-25=-131/1510,
 12-13=-227/1490
 WEBS 3-18=-241/265, 5-18=-146/559, 5-16=-385/1827, 6-16=-1457/444,
 6-14=-285/59, 7-14=-383/168, 8-14=-150/736, 8-13=0/280, 3-19=-1658/159,
 9-12=-1694/311

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 19 and 12. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHA3	Roof Special	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:34 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWViFyWSr_-43IT727VoVvPw24fwPW1vRILLI_3JJYFMwa1d6yW5r7

-0-10-8	6-10-10	13-5-12	14-6-4	19-9-8	25-0-12	31-1-10	37-6-0	38-4-8
0-10-8	6-10-10	6-7-2	1-0-8	5-3-4	5-3-4	6-0-14	6-4-6	0-10-8

Scale = 1:78.1




Plate Offsets (X,Y)-- [2:0-2-12,0-2-0], [3:0-4-0,Edge], [11:0-2-12,0-2-0], [13:Edge,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.61	Vert(LL) -0.11 17-19 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.60	Vert(CT) -0.22 17-19 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.63	Horz(CT) 0.07 13 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 275 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2 *Except* T2,T3: 2x6 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 3-8-8 oc purlins, except end verticals, and 2-0-0 oc purlins (4-2-13 max.): 6-8. Rigid ceiling directly applied or 10-0-0 oc bracing.
 BOT CHORD 1 Row at midpt 4-19, 6-19, 6-17, 7-17, 7-15

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 21=1550/0-3-8 (min. 0-2-7), 13=1550/0-3-8 (min. 0-2-7)
 Max Horz 21=270(LC 11)
 Max Uplift 21=-146(LC 12), 13=-234(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2003/351, 3-4=-1807/379, 4-5=-1694/419, 5-6=-1612/464, 6-7=-1557/436, 7-8=-1364/400, 8-9=-1747/423, 9-10=-1792/370, 10-11=-1979/348, 2-21=-1485/326, 11-13=-1487/327
 BOT CHORD 20-21=-261/414, 19-20=-199/1663, 19-22=-98/1492, 18-22=-98/1492, 18-23=-98/1492, 17-23=-98/1492, 16-17=-120/1557, 16-24=-120/1557, 15-24=-120/1557, 14-15=-193/1562, 13-14=-87/254
 WEBS 4-19=-404/221, 5-19=-352/1415, 6-19=-1085/327, 6-17=-109/292, 7-15=-456/152, 8-15=-94/623, 9-15=-332/174, 2-20=-129/1379, 11-14=-126/1360

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 21 and 13. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHA5	Piggyback Base	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:38 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_yq?_zQB?rj?FzYLrumUSBlcvaMLdF8?rHYFmtyW5r3

-0-10-8	7-10-6	15-5-4	22-0-12	29-7-10	37-6-0	38-4-8
0-10-8	7-10-6	7-6-14	6-7-8	7-6-14	7-10-6	0-10-8

Scale = 1:76.5




Plate Offsets (X,Y)-- [5:0-6-8,0-1-12], [6:0-5-12,0-2-0], [11:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.91	Vert(LL)	-0.13 14-15	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.68	Vert(CT)	-0.24 14-15	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.54	Horz(CT)	0.06 11	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 245 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3 *Except*
 W1: 2x4 SP No.2 or 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-9-3 max.): 5-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-15, 5-14, 7-14

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 18=1550/0-3-8 (min. 0-2-7), 11=1550/0-3-8 (min. 0-2-7)
 Max Horz 18=-303(LC 10)
 Max Uplift 18=-159(LC 12), 11=-159(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2001/341, 3-4=-1794/369, 4-5=-1615/417, 5-6=-1226/408,
 6-7=-1614/417, 7-8=-1780/369, 8-9=-2001/341, 2-18=-1475/328,
 9-11=-1475/328
 BOT CHORD 17-18=-312/543, 17-19=-192/1717, 16-19=-192/1717, 15-16=-192/1717,
 15-20=-42/1287, 14-20=-42/1287, 13-14=-171/1562, 13-21=-171/1562,
 12-21=-171/1562, 11-12=-133/365
 WEBS 4-15=-545/249, 5-15=-74/601, 6-14=-48/536, 7-14=-547/249, 2-17=-56/1294,
 9-12=-57/1284

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 18 and 11. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHB	Roof Special	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:40 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWViFyWSr_vD6kO6CFNLfzDrVE0BWwGAhKk9?oJ0z7ks1MqmyW5r1



Scale = 1:78.0




Plate Offsets (X,Y)-- [2:0-2-12,0-2-0], [3:0-4-0,Edge], [8:0-2-12,0-0-12], [10:Edge,0-1-12]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.61	Vert(LL) -0.29 13-15 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.77	Vert(CT) -0.55 13-15 >819 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.70	Horz(CT) 0.06 11 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 274 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2 *Except*
 T2,T3: 2x6 SP No.2
 BOT CHORD 2x4 SP No.1 *Except*
 B1: 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3 *Except*
 W4: 2x4 SP No.2 or 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-5-7 oc purlins, except end verticals, and 2-0-0 oc purlins (4-4-1 max.): 6-8.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-15, 6-15, 6-13, 7-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

(lb/size) 18=1550/0-3-8 (min. 0-2-7), 11=1487/Mechanical
 Max Horz 18=272(LC 9)
 Max Uplift 18=-149(LC 12), 11=-208(LC 13)
 Max Grav 18=1558(LC 19), 11=1487(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2016/350, 3-4=-1846/377, 4-5=-1692/408, 5-6=-1769/481,
 6-7=-1586/474, 7-8=-1427/393, 8-9=-1977/555, 9-10=-1978/369,
 2-18=-1490/327, 10-11=-1419/283
 BOT CHORD 17-18=-273/422, 17-19=-235/1763, 16-19=-235/1763, 15-16=-235/1763,
 15-20=-134/1609, 20-21=-134/1609, 14-21=-134/1609, 13-14=-134/1609,
 13-22=-113/1422, 22-23=-113/1422, 12-23=-113/1422
 WEBS 4-15=-437/235, 5-15=-365/1591, 6-15=-1095/368, 7-13=-396/176,
 8-13=-49/614, 8-12=-250/437, 9-12=-422/296, 2-17=-127/1403,
 10-12=-180/1424

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=208.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 18. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHC	Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:42 2020 Page 1
 ID:hjOMp88mnrQZrZEntywVfYWSr_-rcEVonEWvyWhS9fd7bYOMbnaciaByXQCAWSveyW5r?

0-10-8	7-10-6	15-5-4	22-0-12	29-7-10	37-6-0
0-10-8	7-10-6	7-6-14	6-7-8	7-6-14	7-10-6

Scale = 1:78.0




Plate Offsets (X,Y)-- [9:Edge,0-1-12], [10:Edge,0-1-8]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.97	Vert(LL) -0.13 13-14 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.68	Vert(CT) -0.24 13-14 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.56	Horz(CT) 0.06 10 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 243 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3 *Except*
 W1: 2x4 SP No.2 or 2x4 SPF No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-8-2 max.): 5-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-14, 5-13, 7-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 17=1550/0-3-8 (min. 0-2-7), 10=1487/Mechanical
 Max Horz 17=295(LC 9)
 Max Uplift 17=159(LC 12), 10=138(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2002/341, 3-4=-1794/369, 4-5=-1618/416, 5-6=-1239/407,
 6-7=-1620/417, 7-8=-1780/366, 8-9=-2001/337, 2-17=-1476/328,
 9-10=-1413/283
 BOT CHORD 16-17=-316/533, 16-18=-211/1707, 15-18=-211/1707, 14-15=-211/1707,
 14-19=-54/1290, 13-19=-54/1290, 12-13=-212/1571, 12-20=-212/1571,
 11-20=-212/1571
 WEBS 4-14=-528/245, 5-14=-72/590, 6-13=-47/529, 7-13=-541/249, 2-16=-55/1294,
 9-11=-132/1364


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=138.
 - 8) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17. This connection is for uplift only and does not consider lateral forces.
 - 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	AHD	Piggyback Base	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:44 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_n_MFDTFmRZmOhTp?F0bsR0sw5nO1fs1jfU?ZyXyW5qz



Scale = 1:76.4




Plate Offsets (X,Y)-- [5:0-6-8,0-1-12], [6:0-6-8,0-1-12], [9:Edge,0-1-12], [10:Edge,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.98	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.68	Vert(LL) -0.13 13-14 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.56	Vert(CT) -0.24 13-14 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.06 10 n/a n/a		
	Code IRC2015/TPI2014			Weight: 243 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3 *Except*
 W1: 2x4 SP No.2 or 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-8-11 max.); 5-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-14, 5-13, 7-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 17=1550/0-3-8 (min. 0-2-7), 10=1487/Mechanical
 Max Horz 17=298(LC 11)
 Max Uplift 17=159(LC 12), 10=137(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2002/341, 3-4=-1795/369, 4-5=-1616/417, 5-6=-1227/408,
 6-7=-1618/418, 7-8=-1781/366, 8-9=-2001/337, 2-17=-1476/328,
 9-10=-1413/283
 BOT CHORD 16-17=-318/535, 16-18=-212/1709, 15-18=-212/1709, 14-15=-212/1709,
 14-19=-50/1280, 13-19=-50/1280, 12-13=-212/1571, 12-20=-212/1571,
 11-20=-212/1571
 WEBS 4-14=-545/249, 5-14=-74/601, 6-13=-51/540, 7-13=-557/253, 2-16=-57/1294,
 9-11=-133/1364

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=137.
- 8) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17. This connection is for uplift only and does not consider lateral forces.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	B	Common	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:46 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_jNU0e9H0zB06xmzOMRdKWRxKZa0C7nD07oUg1PyW5qx



4x6 ||

Scale: 3/16"=1'





Plate Offsets (X,Y)-- [2:0-3-0,Edge], [3:0-2-0,Edge], [7:0-2-0,Edge], [8:0-3-0,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.66	Vert(LL)	-0.23 11-13	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.89	Vert(CT)	-0.35 10-11	>947	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.46	Horz(CT)	0.05 10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 171 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-11-13 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-14, 6-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 14=1163/0-3-8 (min. 0-1-15), 10=1163/0-3-8 (min. 0-1-15)
 Max Horz 14=-278(LC 10)
 Max Uplift 14=-136(LC 12), 10=-136(LC 13)
 Max Grav 14=1229(LC 19), 10=1229(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-508/206, 3-4=-417/230, 4-5=-1400/368, 5-6=-1400/368, 6-7=-416/230, 7-8=-508/206, 2-14=-486/222, 8-10=-485/222
 BOT CHORD 14-15=-173/1314, 15-16=-173/1314, 13-16=-173/1314, 13-17=0/904, 12-17=0/904, 12-18=0/904, 11-18=0/904, 11-19=-108/1157, 19-20=-108/1157, 10-20=-108/1157
 WEBS 5-11=-162/689, 6-11=-330/287, 5-13=-162/689, 4-13=-330/287, 4-14=-1148/71, 6-10=-1148/71

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14 and 10. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 2000811-2000811A	Truss B1	Truss Type Common	Qty 2	Ply 1	Hicks Residence - Milltown Job Reference (optional)
-------------------------	-------------	----------------------	----------	----------	--

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:48 2020 Page 1
ID:hjOMp88mnrQZrZEntyWViFyWSr_gmbm3rIHVoGqA46mUsfobs0g4OifbhFJa5zn5lyW5qv



4x6 ||

Scale: 3/16"=1'




Plate Offsets (X,Y)-- [2:0-3-0,Edge], [3:0-2-0,Edge], [7:0-2-0,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.66	Vert(LL)	-0.23	10-12	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.90	Vert(CT)	-0.35	9-10	>947	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.49	Horz(CT)	0.05	9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS							
									Weight: 170 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-11-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-13, 6-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 13=1164/0-3-8 (min. 0-1-15), 9=1101/0-3-8 (min. 0-1-13)
 Max Horz 13=272(LC 9)
 Max Uplift 13=-135(LC 12), 9=-114(LC 13)
 Max Grav 13=1230(LC 19), 9=1170(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-508/205, 3-4=-416/230, 4-5=-1402/368, 5-6=-1408/370, 6-7=-318/164,
 7-8=-419/139, 2-13=-485/222, 8-9=-367/149
 BOT CHORD 13-14=-184/1307, 14-15=-184/1307, 12-15=-184/1307, 12-16=-2/897,
 11-16=-2/897, 11-17=-2/897, 10-17=-2/897, 10-18=-148/1155,
 18-19=-148/1155, 9-19=-148/1155
 WEBS 5-10=-164/697, 6-10=-336/290, 5-12=-162/689, 4-12=-330/287,
 4-13=-1150/72, 6-9=-1208/140

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 13 and 9. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	BH	Hip Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:55 2020 Page 1
 ID:hjOMp88mnrQZrZEntywVfYWSr_-z6WPXE0gry8qW997OqHRNKpxpCF0kuRLBh9erOyW5sq

0-10-8	6-5-4	11-4-8	16-5-8	21-4-12	27-10-0	28-8-8
0-10-8	6-5-4	4-11-4	5-1-0	4-11-4	6-5-4	0-10-8

Scale = 1:57.9



2-0-12	4-0-12	6-0-12	6-5-4	11-4-8	16-5-8	21-4-12	21-9-423-9-4	25-9-4	27-10-0
2-0-12	2-0-0	2-0-0	0-4-8	4-11-4	5-1-0	4-11-4	0-4-8 2-0-0	2-0-0	2-0-12

Plate Offsets (X,Y)-- [2:0-1-0,0-1-12], [3:0-4-4,0-2-4], [6:0-4-4,0-2-4], [7:0-1-0,0-1-12]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.43	Vert(LL)	0.08 11-13	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.25	Vert(CT)	-0.08 11-13	>999	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.26	Horz(CT)	0.02 9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 382 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-6.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

REACTIONS. (lb/size) 15=1745/0-3-8 (min. 0-1-8), 9=1744/0-3-8 (min. 0-1-8)
 Max Horz 15=-152(LC 10)
 Max Uplift 15=-922(LC 12), 9=-921(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2114/1331, 3-16=-2192/1577, 16-17=-2192/1577, 4-17=-2192/1577, 4-18=-2192/1577, 18-19=-2192/1577, 19-20=-2192/1577, 5-20=-2192/1577, 5-21=-2195/1579, 21-22=-2195/1579, 6-22=-2195/1579, 6-7=-2112/1329, 2-15=-1555/962, 7-9=-1554/960
 BOT CHORD 15-23=-313/535, 23-24=-313/535, 14-24=-313/535, 14-25=-1038/1704, 25-26=-1038/1704, 13-26=-1038/1704, 13-27=-1407/2241, 12-27=-1407/2241, 12-28=-1407/2241, 11-28=-1407/2241, 11-29=-975/1650, 29-30=-975/1650, 10-30=-975/1650, 10-31=-261/445, 31-32=-261/445, 9-32=-261/445
 WEBS 3-14=-102/280, 3-13=-663/852, 4-13=-434/442, 5-11=-456/463, 6-11=-668/858, 6-10=-98/277, 2-14=-924/1404, 7-10=-927/1402

- NOTES-**
- 2-ply truss to be connected together with 10d (0.120"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 15, 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Two H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15 and 9. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	BH	Hip Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:55 2020 Page 2
 ID:hjOMp88mnrQZrZEntywViFyWSr_-z6WPXE0gry8qW997OqHRNKpXPFOkuRLBh9erOyW5sq

NOTES-

12) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 120 lb down and 162 lb up at 8-0-12, 120 lb down and 162 lb up at 10-0-12, 120 lb down and 162 lb up at 12-0-12, 120 lb down and 162 lb up at 13-9-4, 120 lb down and 162 lb up at 15-9-4, and 120 lb down and 162 lb up at 17-9-4, and 120 lb down and 162 lb up at 19-9-4 on top chord, and 120 lb down and 89 lb up at 2-0-12, 120 lb down and 102 lb up at 4-0-12, 169 lb down and 143 lb up at 6-0-12, 45 lb down and 40 lb up at 8-0-12, 45 lb down and 40 lb up at 10-0-12, 45 lb down and 40 lb up at 12-0-12, 45 lb down and 40 lb up at 13-9-4, 45 lb down and 40 lb up at 15-9-4, 45 lb down and 40 lb up at 17-9-4, 45 lb down and 40 lb up at 19-9-4, 169 lb down and 143 lb up at 21-9-4, and 120 lb down and 102 lb up at 23-9-4, and 120 lb down and 89 lb up at 25-9-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-3=-60, 3-6=-60, 6-7=-60, 7-8=-60, 9-15=-20

Concentrated Loads (lb)

Vert: 12=-23(F) 14=-120(F) 10=-120(F) 16=-40(F) 17=-40(F) 18=-40(F) 19=-40(F) 20=-40(F) 21=-40(F) 22=-40(F) 23=-120(F) 24=-120(F) 25=-23(F) 26=-23(F) 27=-23(F) 28=-23(F) 29=-23(F) 30=-23(F) 31=-120(F) 32=-120(F)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	BH1	Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:57 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-vUeAyywPwNZOYITIVFKvSluGZ0nhCfyef?elwGyW5qm

-0-10-8	4-10-6	9-5-4	13-11-0	18-4-12	22-11-10	27-10-0	28-8-8
0-10-8	4-10-6	4-6-14	4-5-12	4-5-12	4-6-14	4-10-6	0-10-8

Scale = 1:56.8




Plate Offsets (X,Y)-- [2:0-1-0,0-1-8], [4:0-4-0,0-1-9], [6:0-4-0,0-1-9], [8:0-1-0,0-1-8]						
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc)	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.48	Vert(LL) -0.30 11-13 >999	240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.84	Vert(CT) -0.40 11-13 >830	180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.84	Horz(CT) 0.05 10 n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS				Weight: 173 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-10-15 oc purlins, except end verticals, and 2-0-0 oc purlins (5-8-9 max.): 4-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 5-13, 5-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 14=1163/0-3-8 (min. 0-1-13), 10=1163/0-3-8 (min. 0-1-13)
 Max Horz 14=-202(LC 10)
 Max Uplift 14=-108(LC 12), 10=-108(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-315/119, 3-4=-1264/298, 4-5=-986/286, 5-6=-986/286, 6-7=-1264/298,
 7-8=-315/119, 2-14=-322/142, 8-10=-322/142
 BOT CHORD 13-14=-155/1050, 12-13=-92/1089, 12-15=-92/1089, 11-15=-92/1089,
 10-11=-151/1050
 WEBS 4-13=-50/422, 5-13=-269/161, 5-11=-269/160, 6-11=-50/422, 3-14=-1154/211,
 7-10=-1154/211

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14 and 10. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	BH2	Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:55:59 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWviFyWSr_rtmwNbRAvAFg?mSudgMNYA_b9qY9ggcw6J7s_9yW5qk

-0-10-8	6-4-6	12-5-4	15-4-12	21-5-10	27-10-0	28-8-8
0-10-8	6-4-6	6-0-14	2-11-8	6-0-14	6-4-6	0-10-8

Scale = 1:59.0




Plate Offsets (X,Y)-- [2:0-2-12,0-2-0], [6:0-4-0,0-1-9], [9:0-2-12,0-2-0]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.54	Vert(LL) -0.04 15 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.45	Vert(CT) -0.10 15-16 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.44	Horz(CT) 0.03 11 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 190 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-6-15 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 5-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 17=1163/0-3-8 (min. 0-1-13), 11=1163/0-3-8 (min. 0-1-13)
 Max Horz 17=-251(LC 10)
 Max Uplift 17=-129(LC 12), 11=-129(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1413/240, 3-4=-1226/263, 4-5=-1118/305, 5-6=-838/302, 6-7=-1119/305,
 7-8=-1226/263, 8-9=-1412/240, 2-17=-1103/254, 9-11=-1103/254
 BOT CHORD 16-17=-242/376, 15-16=-140/1101, 14-15=-1/837, 13-14=-1/837,
 12-13=-105/1092
 WEBS 4-15=-387/193, 5-15=-74/336, 6-13=-58/337, 7-13=-386/192, 2-16=-39/907,
 9-12=-40/906

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17 and 11. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	C	Common	3	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:01 2020 Page 1
ID:hjOMp88mnrQZrZEntyVIFyWSr_nGuhoHSQRov_E4cGk5Ordb3vVd9n8aYDZdcz32yW5qj



4x6 ||

Scale = 1:62.7





Plate Offsets (X,Y)-- [2:0-3-0,Edge], [3:0-2-0,Edge], [7:0-2-0,Edge], [8:0-3-0,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.61	Vert(LL)	-0.20 11-13	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.83	Vert(CT)	-0.31 10-11	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.42	Horz(CT)	0.04 10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 166 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-3-6 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-14, 6-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 14=1128/0-3-8 (min. 0-1-14), 10=1128/0-3-8 (min. 0-1-14)
 Max Horz 14=270(LC 11)
 Max Uplift 14=-132(LC 12), 10=-132(LC 13)
 Max Grav 14=1181(LC 19), 10=1182(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-477/197, 3-4=-393/220, 4-5=-1336/356, 5-6=-1338/356, 6-7=-393/220, 7-8=-477/196, 2-14=-464/215, 8-10=-463/215
 BOT CHORD 14-15=-166/1255, 15-16=-166/1255, 13-16=-166/1255, 12-13=0/866, 12-17=0/866, 11-17=0/866, 11-18=-104/1104, 18-19=-104/1104, 10-19=-104/1104
 WEBS 5-11=-156/657, 6-11=-316/278, 5-13=-156/653, 4-13=-316/278, 4-14=-1105/72, 6-10=-1107/72

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14 and 10. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	C1	Common	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:02 2020 Page 1
ID:hjOMp88mnrQZrZEntywViFyWSr_-FSS3?dT3C51rsEBTlov49pc4G1V0t1MNoHMWbUyW5qh



4x6 ||

Scale = 1:62.0





Plate Offsets (X,Y)-- [2:0-3-0,Edge], [3:0-2-0,Edge], [7:0-2-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.61	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.83	Vert(LL) -0.20 10-12 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.44	Vert(CT) -0.31 9-10 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.04 9 n/a n/a		
	Code IRC2015/TPI2014			Weight: 165 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-3-1 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-13, 6-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 13=1129/0-3-8 (min. 0-1-14), 9=1065/Mechanical
 Max Horz 13=265(LC 11)
 Max Uplift 13=-132(LC 12), 9=-110(LC 13)
 Max Grav 13=1182(LC 19), 9=1124(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-477/196, 3-4=-392/220, 4-5=-1337/356, 5-6=-1345/358, 6-7=-301/158, 7-8=-395/133, 2-13=-464/215, 8-9=-349/143
 BOT CHORD 13-14=-177/1248, 14-15=-177/1248, 12-15=-177/1248, 11-12=-1/859, 11-16=-1/859, 10-16=-1/859, 10-17=-144/1102, 17-18=-144/1102, 9-18=-144/1102
 WEBS 5-10=-159/665, 6-10=-323/281, 5-12=-157/654, 4-12=-317/278, 4-13=-1107/72, 6-9=-1162/137

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 9=110.
- 7) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 13. This connection is for uplift only and does not consider lateral forces.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	CH	Hip Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MITek Industries, Inc. Tue Oct 6 15:56:13 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWlFyWSr_-RZcDJOCycUQHgwXaRccf67ZOFTOly1t_KUWbULyW5qW



Scale = 1:55.8



2-0-12	4-0-12	6-0-12	6-5-4	11-1-0	15-10-8	20-6-4	22-10-12	24-10-12	26-11-8
2-0-12	2-0-0	2-0-0	0-4-8	4-7-12	4-9-8	4-7-12	0-4-8	2-0-0	2-0-12

Plate Offsets (X,Y)-- [2:0-1-0,0-1-12], [3:0-4-4,0-2-4], [6:0-4-4,0-2-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.43	Vert(LL) 0.07 10-12 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.24	Vert(CT) -0.08 10-12 >999 180		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.27	Horz(CT) 0.02 8 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 370 lb FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-6.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

REACTIONS. (lb/size) 14=1712/0-3-8 (min. 0-1-8), 8=1646/0-3-8 (min. 0-1-8)
 Max Horz 14=146(LC 11)
 Max Uplift 14=925(LC 12), 8=897(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2064/1324, 3-15=-2110/1554, 15-16=-2110/1554, 4-16=-2110/1554, 4-17=-2110/1554, 17-18=-2110/1554, 18-19=-2110/1554, 5-19=-2110/1554, 5-20=-2103/1544, 20-21=-2103/1544, 6-21=-2103/1544, 6-7=-2057/1310, 2-14=-1522/957, 7-8=-1455/906
 BOT CHORD 14-22=-327/528, 22-23=-327/528, 13-23=-327/528, 13-24=-1037/1670, 24-25=-1037/1670, 12-25=-1037/1670, 12-26=-1404/2143, 11-26=-1404/2143, 11-27=-1404/2143, 10-27=-1404/2143, 10-28=-1004/1612, 28-29=-1004/1612, 9-29=-1004/1612, 9-30=-206/348, 30-31=-206/348, 8-31=-206/348
 WEBS 3-13=-101/277, 3-12=-660/818, 4-12=-429/456, 5-10=-440/466, 6-10=-658/813, 6-9=-88/271, 2-13=-915/1370, 7-9=-893/1389

- NOTES-**
- 2-ply truss to be connected together with 10d (0.120"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 14, 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Two H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14 and 8. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	CH	Hip Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:13 2020 Page 2
 ID:hjOMp88mnrQZrZEntywViFyWSr_-RZcDJOCycUQHgwXaRccf67Z0FTOly1t_KUWbULyW5qW

NOTES-

12) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 120 lb down and 162 lb up at 8-0-12, 120 lb down and 162 lb up at 10-0-12, 120 lb down and 162 lb up at 12-0-12, 120 lb down and 162 lb up at 12-10-12, 120 lb down and 162 lb up at 14-10-12, and 120 lb down and 162 lb up at 16-10-12, and 120 lb down and 162 lb up at 18-10-12 on top chord, and 120 lb down and 89 lb up at 2-0-12, 120 lb down and 102 lb up at 4-0-12, 169 lb down and 143 lb up at 6-0-12, 45 lb down and 40 lb up at 8-0-12, 45 lb down and 40 lb up at 10-0-12, 45 lb down and 40 lb up at 12-0-12, 45 lb down and 40 lb up at 12-10-12, 45 lb down and 40 lb up at 14-10-12, 45 lb down and 40 lb up at 16-10-12, 45 lb down and 40 lb up at 18-10-12, 169 lb down and 143 lb up at 20-10-12, and 120 lb down and 102 lb up at 22-10-12, and 120 lb down and 89 lb up at 24-10-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-3=-60, 3-6=-60, 6-7=-60, 8-14=-20


Concentrated Loads (lb)

Vert: 11=-23(B) 13=-120(B) 9=-120(B) 15=-40(B) 16=-40(B) 17=-40(B) 18=-40(B) 19=-40(B) 20=-40(B) 21=-40(B) 22=-120(B) 23=-120(B) 24=-23(B) 25=-23(B) 26=-23(B) 27=-23(B) 28=-23(B) 29=-23(B) 30=-120(B) 31=-120(B)


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	CH1	Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:15 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWViFyWSr_-Nykzk3dD85g?vEhzZ1e7BYeLeGy1Qp2Hno?iZEyW5qU



Scale = 1:55.0



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.50	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.76	Vert(LL) -0.20 11-13 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.80	Vert(CT) -0.35 13-14 >904 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.04 10 n/a n/a		
	Code IRC2015/TPI2014			Weight: 169 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-6 oc purlins, except end verticals, and 2-0-0 oc purlins (5-11-2 max.): 4-6. Rigid ceiling directly applied or 10-0-0 oc bracing.
 BOT CHORD

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 14=1128/0-3-8 (min. 0-1-12), 10=1128/0-3-8 (min. 0-1-12)
 Max Horz 14=202(LC 11)
 Max Uplift 14=-108(LC 12), 10=-108(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-317/115, 3-4=-1206/289, 4-5=-937/278, 5-6=-937/278, 6-7=-1206/289, 7-8=-317/115, 2-14=-322/139, 8-10=-322/140
 BOT CHORD 13-14=-149/1009, 12-13=-76/1021, 12-15=-76/1021, 15-16=-76/1021, 11-16=-76/1021, 10-11=-144/1009
 WEBS 4-13=-49/400, 6-11=-50/400, 3-14=-1098/206, 7-10=-1098/205

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14 and 10. This connection is for uplift only and does not consider lateral forces.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	CH2	Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:17 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-JLsk9lTgiwj9XqLgShbGzjfi4iRuo_af6Upd6yW5qS

0-10-8	6-4-6	12-5-4	14-6-4	20-7-2	26-11-8	27-10-0
0-10-8	6-4-6	6-0-14	2-1-0	6-0-14	6-4-6	0-10-8

Scale = 1:59.3



6-4-6	12-5-4	14-6-4	20-7-2	26-11-8
6-4-6	6-0-14	2-1-0	6-0-14	6-4-6

Plate Offsets (X,Y)-- [2:0-2-12,0-2-0], [6:0-4-0,0-1-9], [9:0-2-12,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.53	Vert(LL)	-0.04 16-17	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.45	Vert(CT)	-0.10 14-16	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.45	Horz(CT)	0.03 11	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 187 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-8-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 5-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 17=1128/0-3-8 (min. 0-1-12), 11=1128/0-3-8 (min. 0-1-12)
 Max Horz 17=251(LC 11)
 Max Uplift 17=-127(LC 12), 11=-127(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1361/230, 3-4=-1175/252, 4-5=-1061/294, 5-6=-808/293, 6-7=-1062/294,
 7-8=-1174/252, 8-9=-1361/230, 2-17=-1068/247, 9-11=-1068/247
 BOT CHORD 16-17=-242/375, 15-16=-138/1072, 14-15=-138/1072, 13-14=0/790,
 12-13=-97/1050
 WEBS 4-14=-392/192, 5-14=-78/328, 6-13=-69/329, 7-13=-389/192, 2-16=-31/866,
 9-12=-32/864

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17 and 11. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	CJ1	Diagonal Hip Girder	3	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:19 2020 Page 1
ID:hjOMp88mnrQZrZEntywViFyWSr_GjzUZRgjBKAROr_kotj3MOp2nuP3MpvtiQzwi?yW5qQ



Scale = 1:14.3



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.37	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.37	Vert(LL) -0.04 7-8 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Vert(CT) 0.04 7-8 >999 180		
BCDL 10.0	Rep Stress Incr NO	Matrix-MS	Horz(CT) -0.00 7 n/a n/a		
	Code IRC2015/TPI2014			Weight: 21 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-6-6 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 7=79/Mechanical, 8=290/0-4-10 (min. 0-1-8)
 Max Horz 8=53(LC 11)
 Max Uplift 7=-17(LC 12), 8=-128(LC 8)
 Max Grav 7=89(LC 43), 8=290(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) One MTS12 Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7. This connection is for uplift only and does not consider lateral forces.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 81 lb down and 94 lb up at 2-9-8, and 81 lb down and 94 lb up at 2-9-8 on top chord, and 3 lb down and 63 lb up at 2-9-8, and 3 lb down and 63 lb up at 2-9-8 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-4=-60, 4-5=-20, 6-9=-20
 Concentrated Loads (lb)
 Vert: 10=64(F=32, B=32) 11=70(F=35, B=35)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	D	Piggyback Base	6	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:20 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWsr_-kwXsnhLydlH0?ZwMaEluL9ZHfo54C0x4jTERyW5qP




Plate Offsets (X,Y)-- [4:0-4-4,0-1-12], [5:0-6-4,0-1-12]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.62	Vert(LL) -0.17 9-10 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.73	Vert(CT) -0.35 9-10 >806 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.80	Horz(CT) 0.02 9 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 180 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5. Rigid ceiling directly applied or 10-0-0 oc bracing.
 BOT CHORD 1 Row at midpt
 WEBS 5-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 13=1030/0-3-8 (min. 0-1-10), 9=1030/0-3-8 (min. 0-1-10)
 Max Horz 13=-305(LC 10)
 Max Uplift 13=-88(LC 12), 9=-88(LC 13)
 Max Grav 13=1033(LC 2), 9=1043(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-306/193, 3-4=-851/298, 4-5=-568/273, 5-6=-864/298, 6-7=-306/193, 2-13=-363/209, 7-9=-363/209
 BOT CHORD 13-14=-173/705, 14-15=-173/705, 12-15=-173/705, 11-12=-36/587, 11-16=-36/587, 10-16=-36/587, 10-17=-23/577, 17-18=-23/577, 9-18=-23/577
 WEBS 4-12=-65/317, 5-10=-92/386, 3-13=-806/76, 6-9=-805/76

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 13 and 9. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	D1	Piggyback Base	6	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:22 2020 Page 1
 ID:hjOMp88mnrQzrZEntyWViFyWSr_glfcdCTjCUFY?FJjJT?Gmz1RV_5K_ZzBJOOCalkyW5qN



Scale = 1:61.0





Plate Offsets (X,Y)-- [3:0-4-4,0-1-12], [4:0-6-4,0-1-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.62	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.81	Vert(LL) -0.22 11-12 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.84	Vert(CT) -0.45 11-12 >648 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.02 8 n/a n/a		
	Code IRC2015/TPI2014			Weight: 180 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-11-4 oc purlins, except end verticals, and 2-0-0 oc purlins (5-11-9 max.): 3-4.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 12=973/0-3-8 (min. 0-1-9), 8=1059/0-3-8 (min. 0-1-11)
 Max Horz 12=-285(LC 8)
 Max Uplift 12=-67(LC 12), 8=-89(LC 13)
 Max Grav 12=980(LC 2), 8=1070(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-465/133, 2-3=-917/302, 3-4=-604/279, 4-5=-896/305, 5-6=-308/193,
 1-12=-401/126, 6-8=-364/208
 BOT CHORD 12-13=-174/805, 13-14=-174/805, 11-14=-174/805, 10-11=-34/608,
 10-15=-34/608, 9-15=-34/608, 9-16=-26/597, 16-17=-26/597, 8-17=-26/597
 WEBS 2-11=-270/253, 3-11=-64/353, 4-9=-95/378, 2-12=-734/143, 5-8=-839/81

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- One MTS12 Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 12. This connection is for uplift only and does not consider lateral forces.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	DE	Piggyback Base Structural Gable COMMON	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:25 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-4tKlqUlUnAwa6mRu87qTbf30jINcmOY15MQEvfyW5qk



Scale = 1:62.8

Plate Offsets (X,Y)-- [4:0-4-4,0-1-12], [5:0-6-4,0-1-12]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.59	Vert(LL) -0.16 9-10 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.68	Vert(CT) -0.31 9-10 >595 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.60	Horz(CT) 0.02 9 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 262 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-11, 5-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 8-6-8 except (it=length) 9=0-3-8, 12=0-3-8.
 (lb) - Max Horz 18=305(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 9 except 18=109(LC 12), 14=189(LC 2), 12=101(LC 12)
 Max Grav All reactions 250 lb or less at joint(s) 14, 15, 16, 17 except 18=660(LC 1), 9=864(LC 2), 12=607(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-4=-461/258, 4-5=-348/245, 5-6=-653/271, 6-7=-293/194, 2-18=-298/232, 7-9=-350/209
 BOT CHORD 17-18=-180/459, 16-17=-180/459, 15-16=-180/459, 15-38=-180/459, 14-38=-180/459, 13-14=-180/459, 12-13=-180/459, 11-12=-180/459, 11-39=-35/451, 10-39=-35/451, 10-40=-5/448, 40-41=-5/448, 9-41=-5/448
 WEBS 5-11=-332/67, 5-10=-81/451, 3-18=-528/56, 6-9=-607/43

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 18, 9, and 14. This connection is for uplift only and does not consider lateral forces.
- One MTS12 Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 12. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	EE	Common Supported Gable	1	1	Job Reference (optional)


84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:27 2020 Page 1
 ID:hjOMp88mnrQZrZEntyVViFyWSr_-1GSWFAmkJnAlM4bGGYsXg48RI6B7ENP2YgvL_XyW5qI



4x4 =

Scale = 1:57.1



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.30	Vert(LL) -0.01	11	n/r	120	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.17	Vert(CT) -0.01	11	n/r	90		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.20	Horz(CT) -0.00	12	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-R						
	Code IRC2015/TPI2014							
							Weight: 124 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS 1 Row at midpt 6-16

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 15-9-0.
 (lb) - Max Horz 20=279(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) 18, 15, 14 except 20=198(LC 8), 12=184(LC 9), 17=100(LC 12), 19=193(LC 12), 13=190(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 17, 18, 15, 14 except 20=271(LC 20), 12=260(LC 19), 16=386(LC 13), 19=280(LC 10), 13=271(LC 11)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 4-5=-203/282, 5-6=-283/373, 6-7=-283/373, 7-8=-203/281
 WEBS 6-16=-454/274

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 20, 12, 17, 18, 19, 15, 14, and 13. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	GE	Common Supported Gable	1	1	Job Reference (optional)


84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:29 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-zeaGgso?rOR0bNifNzuPIVDpEwufiH8L?_OS2QyW5qG

-0-10-8 5-6-0 | 11-0-0 11-10-8
 0-10-8 5-6-0 | 5-6-0 0-10-8

4x4 =

Scale = 1:41.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.18	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.10	Vert(LL) -0.00 9 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.25	Vert(CT) -0.00 9 n/r 90		
BCDL 10.0	Rep Stress Incr YES	Matrix-R	Horz(CT) -0.00 10 n/a n/a		
	Code IRC2015/TPI2014			Weight: 77 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 11-0-0.
 (lb) - Max Horz 16=-203(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 14, 12 except 16=-140(LC 8), 10=-128(LC 9), 15=-162(LC 12), 11=-160(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 16, 10, 13, 14, 15, 12, 11

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 4-5=-195/261, 5-6=-195/260
 WEBS 5-13=-301/154

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 16, 10, 14, 15, 12, and 11. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	GR1	Common Girder	1	3	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:31 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWvIFyWSr_-v1i05YqFN0hkqhv1VOxtrwl_BJU_A55eTItY7lyW5qE



4x4 ||

Scale = 1:41.7





Plate Offsets (X,Y)-- [4:Edge,0-2-0], [5:0-4-0,0-4-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.85	Vert(LL)	0.05	5-6	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.43	Vert(CT)	-0.09	5-6	>999		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.60	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 230 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP DSS
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 6=4433/0-3-8 (min. 0-2-5), 4=4687/0-3-8 (min. 0-2-7)
 Max Horz 6=-174(LC 31)
 Max Uplift 6=-928(LC 13), 4=-638(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-3409/648, 2-3=-3408/647, 1-6=-2911/519, 3-4=-2889/565
 BOT CHORD 6-7=-361/652, 7-8=-361/652, 5-8=-361/652, 5-9=-117/495, 9-10=-117/495, 10-11=-117/495,
 4-11=-117/495
 WEBS 2-5=-736/4354, 1-5=-294/1767, 3-5=-436/1896

NOTES-

- 3-ply truss to be connected together with 10d (0.120"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 3 rows staggered at 0-4-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Two H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6 and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 2343 lb down and 770 lb up at 2-2-0, 1467 lb down and 228 lb up at 4-1-4, 1467 lb down and 228 lb up at 6-1-4, and 1467 lb down and 158 lb up at 8-1-4, and 1470 lb down and 155 lb up at 10-1-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-3=-60, 4-6=-20

Job	Truss	Truss Type	Qty	Ply	
2000811-2000811A	GR1	Common Girder	1	3	Hicks Residence - Milltown Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:31 2020 Page 2
ID:hjOMp88mnrQZrZEntywViFyWSr_-v1i05YqFN0hkqhv1VOxtrwl_BjU_A55eTItY7lyW5qE

LOAD CASE(S) Standard

Concentrated Loads (lb)

Vert: 1=-48 7=-2343(B) 8=-1467(B) 9=-1467(B) 10=-1467(B) 11=-1470(B)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	H	Common	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:33 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWfFYWSr_rQpnVDrVudxR4?3QcpzLwL00XCMe7exwcMfBBYw5qc




Plate Offsets (X,Y)-- [1:Edge,0-1-12], [3:0-3-0,0-1-12]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.57	Vert(LL) -0.02 6-7 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.31	Vert(CT) -0.05 6-7 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.09	Horz(CT) 0.00 5 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 67 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=466/0-3-8 (min. 0-1-8), 5=532/0-3-8 (min. 0-1-8)
 Max Horz 7=-139(LC 10)
 Max Uplift 7=-47(LC 12), 5=-68(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-483/107, 2-3=-490/111, 1-7=-413/116, 3-5=-480/163
 BOT CHORD 6-7=-135/263, 5-6=-117/260

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	HE	Common Supported Gable	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:35 2020 Page 1
ID:hjOMp88mnrQZrZEntyWvIFyWSr_-ooXxwvtQE9JICpkE?p?mTr8Kyk62IEOvmG4yW5qA



Scale = 1:29.1

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.08	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.06	Vert(LL) -0.00 8 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Vert(CT) -0.00 8 n/r 90		
BCDL 10.0	Rep Stress Incr YES	Matrix-R	Horz(CT) 0.00 9 n/a n/a		
	Code IRC2015/TPI2014			Weight: 65 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 12-0-0.
 (lb) - Max Horz 15=-139(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 15, 9, 13, 14, 11, 10
 Max Grav All reactions 250 lb or less at joint(s) 15, 9, 12, 13, 14, 11, 10

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15, 9, 13, 14, 11, and 10. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J1	Jack-Open	7	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:36 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWvFiFyWSr_-G?Vv8FtOBYJ0xSn?lxW2Y_0?2kGdrVqNdZbJoWyW5q9



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.14	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.08	Vert(LL) -0.00 5-6 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.06	Vert(CT) -0.01 5-6 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) 0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 14 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=72/Mechanical, 5=22/Mechanical, 6=270/0-3-0 (min. 0-1-8)
 Max Horz 6=43(LC 8)
 Max Uplift 4=-38(LC 12), 6=-92(LC 8)
 Max Grav 4=72(LC 1), 5=53(LC 3), 6=270(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J2	Jack-Open	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:38 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_CNdgZxvej9ZkAmxNPMZWdP5MkYyBJPCg4t4QtOyW5q7



Scale = 1:14.1

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.13	Vert(LL) 0.00	5	>999	240	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT) -0.00	4-5	>999	180		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT) -0.00	3	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-MR					Weight: 9 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=152/0-3-8 (min. 0-1-8), 3=41/Mechanical, 4=16/Mechanical
 Max Horz 5=59(LC 12)
 Max Uplift 3=44(LC 12), 4=5(LC 12)
 Max Grav 5=152(LC 1), 3=50(LC 19), 4=34(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J3	Jack-Open	6	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:39 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_gZB2mHwGUTHbowWaz44l9ceX?ylw2s7pJXpzPryW5q6



Scale = 1:8.2

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.11	Vert(LL) 0.00 7 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) 0.00 7 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) -0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 9 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 1-10-15 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 4=-9/Mechanical, 5=-35/Mechanical, 7=245/0-3-0 (min. 0-1-8)
 Max Horz 7=30(LC 8)
 Max Uplift 4=-9(LC 1), 5=-35(LC 1), 7=-109(LC 8)
 Max Grav 4=12(LC 8), 5=18(LC 8), 7=245(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 5.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J5	Jack-Open	17	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:41 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWViFyWSr_cyloByxW04xJ1Dgy4U6DF1jmVlw6Wmy6mrl4TjyW5q4



Scale = 1:28.4

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.54	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.38	Vert(LL) 0.03 4-5 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.04 4-5 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MR	Horz(CT) -0.08 3 n/a n/a		
	Code IRC2015/TPI2014			Weight: 18 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=221/0-3-8 (min. 0-1-8), 3=100/Mechanical, 4=43/Mechanical
 Max Horz 5=164(LC 12)
 Max Uplift 3=-130(LC 12), 4=-20(LC 12)
 Max Grav 5=221(LC 1), 3=127(LC 19), 4=73(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4 except (jt=lb) 3=130.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J5A	Half Hip	6	1	Job Reference (optional)


84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:42 2020 Page 1

ID:hjOMp88mnrQZrZEntywViFyWSr_-58sAOly8nO3AfNF9eCdSnFGzq9lkFCqG?V2e0AyW5q3



Scale = 1:27.0



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.44	Vert(LL)	-0.01	4-5	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.16	Vert(CT)	-0.02	4-5	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.09	Horz(CT)	-0.00	4	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP							
									Weight: 30 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 9-11-12 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=218/0-3-8 (min. 0-1-8), 4=140/Mechanical
 Max Horz 5=202(LC 9)
 Max Uplift 5=-25(LC 8), 4=-123(LC 9)
 Max Grav 5=254(LC 20), 4=202(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

BOT CHORD 4-5=-346/316
 WEBS 2-4=-259/299

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 4. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J5B	Half Hip	6	1	Job Reference (optional)

84 Components, Dunn, NC 28334

ID:hjOMp88mnrQZrZEntywViFyWSr_-1X_xp_PJ?JuuhOXmdgwsGLMmzzlj5gYSpXk42yW5q1
8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:44 2020 Page 1



Scale = 1:20.6




Plate Offsets (X,Y)-- [3:0-2-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.22	Vert(LL) 0.02	6-7	>999	240	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.22	Vert(CT) -0.02	6-7	>999	180		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.07	Horz(CT) -0.00	5	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS						
	Code IRC2015/TPI2014						Weight: 30 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-4.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=140/Mechanical, 7=218/0-3-8 (min. 0-1-8)
 Max Horz 7=148(LC 9)
 Max Uplift 5=-82(LC 9), 7=-18(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 BOT CHORD 6-7=-269/260

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 7. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J5C	Half Hip Girder	6	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:46 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWViFyWSr_zw6hEg?fqcab7?Ywt2iOy5QjwmguB0Mrw70r9xyW5q?




Plate Offsets (X,Y)-- [3:0-2-8,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.18	Vert(LL)	0.01	6	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.15	Vert(CT)	-0.01	5-6	>999	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.05	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS							
									Weight: 24 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-4.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=140/Mechanical, 7=218/0-3-8 (min. 0-1-8)
 Max Horz 7=98(LC 9)
 Max Uplift 5=-69(LC 9), 7=-50(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-10-8 to 3-10-4 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Provide adequate drainage to prevent water ponding.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Refer to girder(s) for truss to truss connections.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at it(s) 5 and 7. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 94 lb down and 61 lb up at 1-0-8, and 88 lb down and 68 lb up at 2-0-12 on top chord, and 15 lb down and 17 lb up at 2-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard


- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-3=-60, 3-4=-60, 5-7=-20
 Concentrated Loads (lb)
 Vert: 9=1(F)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J5GR	Jack-Open Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:47 2020 Page 1

ID:hjOMp88mnrQZrZEntywViFyWSr_-R6g3R00HbwiSI876RIDdUlrGAvywT6?8nlPhNyW5q_



Scale = 1:28.4

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.33	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.61	Vert(LL) -0.02 3-4 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) -0.04 3-4 >999 180		
BCDL 10.0	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.00 n/a n/a		
	Code IRC2015/TPI2014			Weight: 53 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 4=1350/0-3-8 (min. 0-1-8), 3=1042/Mechanical
 Max Horz 4=128(LC 12)
 Max Uplift 4=-100(LC 8), 3=-245(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 2-ply truss to be connected together with 10d (0.120"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-6-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B;
 Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 3=245.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1064 lb down and 126 lb up at 0-8-12, and 1060 lb down and 130 lb up at 2-8-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.


LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 3-4=-20
 Concentrated Loads (lb)
 Vert: 5=-1050(F) 6=-1045(F)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J5GR1	Jack-Open Girder	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:49 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWsr_-NVnqsi2X7XyA_SHVYAF6Zj2By_ajONbHc5EVkGyW5py



Scale = 1:28.4

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.32	Vert(LL)	-0.02 3-4	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.61	Vert(CT)	-0.04 3-4	>999	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.02	Horz(CT)	0.00	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 53 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 4=682/0-3-8 (min. 0-1-8), 3=695/Mechanical
 Max Horz 4=128(LC 12)
 Max Uplift 4=-24(LC 8), 3=-205(LC 12)
 Max Grav 4=682(LC 1), 3=695(LC 41)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 2-ply truss to be connected together with 10d (0.120"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 3=205.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1105 lb down and 134 lb up at 2-0-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.


LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 3-4=-20
 Concentrated Loads (lb)
 Vert: 5=-1081(B)

Job 2000811-2000811A	Truss J6	Truss Type Jack-Open	Qty 1	Ply 1	Hicks Residence - Milltown Job Reference (optional)
-------------------------	-------------	-------------------------	----------	----------	--

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:50 2020 Page 1
ID:hjOMp88mnrQZrZEntywViFyWSr_-shLC412Aur41ccsh6tmL6xbPsN207qARrl_3HiyW5px



Scale = 1:14.5

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.12	Vert(LL)	-0.00	4	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.07	Vert(CT)	-0.00	3-4	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.01	2	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MR						Weight: 8 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=74/0-3-8 (min. 0-1-8), 2=52/Mechanical, 3=21/Mechanical
Max Horz 4=46(LC 9)
Max Uplift 2=47(LC 12), 3=4(LC 12)
Max Grav 4=74(LC 1), 2=61(LC 19), 3=36(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 3.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J7	Jack-Open	4	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:52 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWfYWSr_-o4TyVj4QQSKlsw04ElppBMgk0BkLbkgk13T9LayW5pv



Scale = 1:14.5



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.14	Vert(LL)	-0.00	5	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(CT)	-0.00	4-5	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MR						Weight: 9 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=152/0-3-8 (min. 0-1-8), 3=41/Mechanical, 4=16/Mechanical
 Max Horz 5=58(LC 12)
 Max Uplift 3=45(LC 12), 4=6(LC 12)
 Max Grav 5=152(LC 1), 3=51(LC 19), 4=34(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J8	Jack-Open Structural Gable	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:53 2020 Page 1



Scale = 1:14.1



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.13	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.09	Vert(LL) 0.00 6 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) 0.00 6 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MR	Horz(CT) -0.01 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 14 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-3-14 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=-25/Mechanical, 6=241/0-6-5 (min. 0-1-8), 4=15/Mechanical
 Max Horz 6=86(LC 9)
 Max Uplift 5=-33(LC 20), 6=43(LC 12), 4=-33(LC 9)
 Max Grav 5=23(LC 8), 6=241(LC 1), 4=29(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable studs spaced at 2-0-0 oc.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5.
- 8) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4 and 6. This connection is for uplift only and does not consider lateral forces.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) Gap between inside of top chord bearing and first diagonal or vertical web shall not exceed 0.500in.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J9	Jack-Open	4	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:55 2020 Page 1
 ID:hjOMp88mnrQZrZEntywiFyWSr_-Ce85716ljNiKjNkfVrMwP_IEsOlzo5PA_1hqvyW5ps



Scale = 1:14.1

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.23	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.09	Vert(LL) -0.00 5 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.00 5 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MR	Horz(CT) -0.01 3 n/a n/a		
	Code IRC2015/TPI2014			Weight: 10 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 1-8-15 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=230/0-5-3 (min. 0-1-8), 3=1/Mechanical, 4=3/Mechanical
 Max Horz 5=61(LC 9)
 Max Uplift 5=-26(LC 12), 3=-27(LC 12), 4=-10(LC 9)
 Max Grav 5=230(LC 1), 3=16(LC 10), 4=26(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.
- 6) One MTS12 Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J10	Jack-Open	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:56 2020 Page 1

ID:hjOMp88mnrQZrZEntywViFyWSr_griTK57wUHQBKXJrT8tIMCrRLo5QXYfJdHRNUmyW5pr



Scale = 1:14.5

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.12	Vert(LL) -0.00	4	>999	240	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT) -0.00	3-4	>999	180		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT) 0.01	2	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-MR					Weight: 8 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=74/0-3-8 (min. 0-1-8), 2=52/Mechanical, 3=21/Mechanical
 Max Horz 4=46(LC 9)
 Max Uplift 2=47(LC 12), 3=4(LC 12)
 Max Grav 4=74(LC 1), 2=61(LC 19), 3=36(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 3.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	J11	Jack-Open	1	1	Job Reference (optional)


84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:57 2020 Page 1

ID:hjOMp88mnrQZrZEntywViFyWSr_-81GrYR8ZF?y1yhu10sO_uPNaGCRLG?vTSKAw1oyW5pq



Scale = 1:14.5



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.23	Vert(LL)	-0.00	5	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.09	Vert(CT)	-0.00	5	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.01	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MR						
								Weight: 11 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 1-10-11 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=230/0-5-3 (min. 0-1-8), 3=10/Mechanical, 4=5/Mechanical
 Max Horz 5=63(LC 9)
 Max Uplift 5=-25(LC 12), 3=-31(LC 12), 4=-8(LC 9)
 Max Grav 5=230(LC 1), 3=20(LC 19), 4=29(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.
- 6) One MTS12 Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	K	Common	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:56:59 2020 Page 1
ID:hjOMP88mnrQZrZEntyWViFyWsr_5QOcz69pncCIB_2Q8GRSsqTlo01ykuhmvef15hyW5po



Scale = 1:36.3

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.93	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.47	Vert(LL) -0.05 5-6 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.11	Vert(CT) -0.11 5-6 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.01 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 81 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-11-15 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=638/0-3-8 (min. 0-1-8), 5=573/0-3-8 (min. 0-1-8)
Max Horz 7=161(LC 9)
Max Uplift 7=-79(LC 12), 5=-58(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-620/129, 3-4=-612/124, 2-7=-575/180, 4-5=-509/135
BOT CHORD 6-7=-260/464, 5-6=-118/257
WEBS 3-6=0/290, 2-6=-109/268, 4-6=-58/251

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	KGR	Common Girder	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

ID:hjOMp88mnrQZrZEntyWvIFyWSr_-1oWMOoB3IDTTRICoFhTw2FYGnpMECI2My88AZyW5pm

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:01 2020 Page 1



Scale = 1:38.3




Plate Offsets (X,Y)-- [4:0-2-0,0-0-0]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.20	Vert(LL) -0.02 9-10 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.22	Vert(CT) -0.04 9-10 >999 180		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.30	Horz(CT) 0.01 7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 126 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 2-4-15 except (jt=length) 11=0-3-8, 8=0-3-8.
 (lb) - Max Horz 12=158(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) 7, 11, 8 except 12=114(LC 12)
 Max Grav All reactions 250 lb or less at joint(s) 11, 8 except 12=676(LC 1), 7=610(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-4=-713/233, 4-5=-718/234
 BOT CHORD 11-12=-117/628, 10-11=-117/628, 9-10=-28/457, 8-9=-112/583, 7-8=-112/583
 WEBS 4-9=-104/331, 4-10=-102/321, 3-12=-665/91, 5-7=-677/110

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 12, 7, 11, and 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).


LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-4=-60, 4-6=-60, 7-12=-54(F=-34)


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	LH	Hip Girder	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:04 2020 Page 1
ID:hjOMp88mnrQZrZEntyWViFyWSr_-RNBV0qDyb8r2ImwNlxq0dguAau1iuP9qV3wNomuyW5pj



Scale = 1:29.5



0-8-8	4-0-0	10-4-0	13-7-8	14-4-0
0-8-8	3-3-8	6-4-0	3-3-8	0-8-8

Plate Offsets (X,Y)-- [2:0-2-15,0-9-8], [2:0-0-0,0-1-4], [3:0-3-0,0-2-12], [5:0-0-0,0-1-4], [5:0-2-15,0-9-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.98	Vert(LL)	-0.05	7-8	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.61	Vert(CT)	-0.12	7-8	>999	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.05	Horz(CT)	0.01	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS							
									Weight: 74 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-1-15 oc purlins, except 2-0-0 oc purlins (2-9-12 max.): 3-4.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=719/0-3-0 (min. 0-1-8), 5=719/0-3-0 (min. 0-1-8)
 Max Horz 2=-21(LC 32)
 Max Uplift 2=-184(LC 8), 5=-184(LC 9)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1169/292, 3-19=-1118/309, 19-20=-1118/309, 20-21=-1118/309, 4-21=-1118/309, 4-5=-1185/298
 BOT CHORD 2-8=-238/1116, 8-22=-260/1133, 22-23=-260/1133, 23-24=-260/1133, 7-24=-260/1133, 5-7=-250/1131

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 31 lb down and 67 lb up at 4-0-0, 28 lb down and 65 lb up at 6-0-12, 28 lb down and 65 lb up at 7-2-0, and 28 lb down and 65 lb up at 8-3-4, and 31 lb down and 67 lb up at 10-4-0 on top chord, and 64 lb down and 28 lb up at 4-0-0, 18 lb down at 6-0-12, 18 lb down at 7-2-0, and 18 lb down at 8-3-4, and 64 lb down and 28 lb up at 10-3-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-3=-60, 3-4=-60, 4-6=-60, 9-14=-20

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	LH	Hip Girder	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:04 2020 Page 2
 ID:hjOMp88mnrQZrZEntyWiFyWSr_-RNBV0qDyb8r2ImwNxxq0dguAau1iuP9qV3wNomuyW5pj

LOAD CASE(S) Standard


Concentrated Loads (lb)

Vert: 3=-12(F) 8=-58(F) 4=-12(F) 7=-58(F) 19=-12(F) 20=-12(F) 21=-12(F) 22=-3(F) 23=-3(F) 24=-3(F)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	LH1	Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:06 2020 Page 1
 ID:hjOMp88mnrQZrZEtywViFYWSr_-OmJFRWFC7m5mX34m2E35JF48qT_t3VoWEsvrnyW55ph



Scale = 1:30.0





Plate Offsets (X,Y)-- [2:0-0-0,0-1-8], [2:0-2-15,0-9-8], [5:0-0-0,0-1-8], [5:0-2-15,0-9-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.35	Vert(LL)	-0.03	7-8	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.31	Vert(CT)	-0.06	7-8	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.04	Horz(CT)	0.01	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS							
								Weight: 70 lb	FT = 20%	

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-10-5 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 3-4.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=626/0-3-0 (min. 0-1-8), 5=626/0-3-0 (min. 0-1-8)
 Max Horz 2=28(LC 12)
 Max Uplift 2=-126(LC 8), 5=-126(LC 9)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-897/233, 3-4=-833/246, 4-5=-899/234
 BOT CHORD 2-8=-162/835, 7-8=-173/836, 5-7=-170/837

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M1	Monopitch	6	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:07 2020 Page 1
ID:hjOMp88mnrQZrZEntywViFyWSr_-sytderFqu3Dd9DfycyaKIWoBqEnQcVmxlubSNDyW5pg



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.61	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.43	Vert(LL) -0.07 5-6 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.10	Vert(CT) -0.15 5-6 >501 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) -0.00 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 27 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=238/0-3-8 (min. 0-1-8), 6=383/0-3-0 (min. 0-1-8)
Max Horz 6=88(LC 11)
Max Uplift 5=49(LC 12), 6=111(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-6=364/351

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 6. This connection is for uplift only and does not consider lateral forces.
- 5) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M1A	Half Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:09 2020 Page 1
 ID:hjOMp88mnrQZrZEntywVIFyWSr_oL?O3XH4QhTLOxpLjNcoNxtZ32R54PeECC4ZS5yW5pe



Scale = 1:17.3



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.50	Vert(LL)	-0.07	7-8	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.48	Vert(CT)	-0.16	7-8	>459	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.08	Horz(CT)	-0.00	6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						Weight: 29 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=238/0-3-8 (min. 0-1-8), 8=383/0-3-0 (min. 0-1-8)
 Max Horz 8=77(LC 11)
 Max Uplift 6=43(LC 8), 8=-113(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 3-8=-273/267

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6 and 8. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M1B	Half Hip Girder	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:11 2020 Page 1
ID:hjOMp88mnrQZrZEntyWViFyW5r_-kj68UDJLylj2dryjrofGSMyzrrCvYJmXgWZgW_yW5pc



Scale = 1:17.3




Plate Offsets (X,Y)-- [2:0-0-0,0-1-4]

LOADING (psf)	SPACING-	CSL	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.23	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.14	Vert(LL) -0.00 6 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.10	Vert(CT) -0.01 6 >999 180		
BCDL 10.0	Rep Stress Incr NO	Matrix-MP	Horz(CT) 0.00 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 39 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-4.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

(lb/size) 5=293/0-3-8 (min. 0-1-8), 2=418/0-3-0 (min. 0-1-8)
 Max Horz 2=54(LC 11)
 Max Uplift 5=67(LC 9), 2=-115(LC 8)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-376/123
 BOT CHORD 2-6=-152/340, 6-13=-155/334, 5-13=-155/334
 WEBS 3-5=-363/151

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 31 lb down and 70 lb up at 4-0-0, and 28 lb down and 67 lb up at 6-0-12 on top chord, and 64 lb down and 28 lb up at 4-0-0, and 18 lb down at 6-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).


LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-3=-60, 3-4=-60, 5-7=-20
 Concentrated Loads (lb)
 Vert: 6=-58(B) 3=-12(B) 12=-12(B) 13=-3(B)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M2	Monopitch	6	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:12 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-CwgWhZjzjcvF_XwPVAV?aV30FUHHm5guAJD2QyW5pb



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES GRIP		
TCLL	20.0	Plate Grip DOL	1.15	TC	0.56	in	(loc)	l/defl	L/d	MT20	197/144	
TCDL	10.0	Lumber DOL	1.15	BC	0.38	Vert(LL)	-0.05	5-6	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.10	Vert(CT)	-0.12	5-6	>582	180	M18SHS	
BCDL	10.0	Code IRC2015/TPI2014		Matrix-MS		Horz(CT)	-0.00	5	n/a	n/a		
											Weight: 26 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=372/0-3-0 (min. 0-1-8), 5=226/0-1-8 (min. 0-1-8)
 Max Horz 6=85(LC 11)
 Max Uplift 6=-109(LC 8), 5=-46(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 3-6=-344/333

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) All plates are MT20 plates unless otherwise indicated.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 6) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
- 7) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6 and 5. This connection is for uplift only and does not consider lateral forces.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M3	Monopitch	14	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:14 2020 Page 1
ID:hjOMp88mnrQZrZEntywViFyWSr_9loH6FLDED5dUIhIWwCz4?aQ23A_lh7zMUoK7JyW5pZ



Scale = 1:14.7

LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.48	Vert(LL)	0.06	5-8	>999	240	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.37	Vert(CT)	-0.11	5-8	>643	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.03	2	n/a	n/a		
BCDL	10.0	Code IRC2015/TPI2014		Matrix-MP								
											Weight: 23 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 - ü 1-6-0

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-10-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=284/0-3-8 (min. 0-1-8), 5=223/0-1-8 (min. 0-1-8)
 Max Horz 2=73(LC 11)
 Max Uplift 2=-73(LC 8), 5=-46(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 5. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M3B	Half Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:22 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-RfjwaeQcbN_eqNjeQuqcsTNZVtZjujS?z3_CtOyW5pS




Plate Offsets (X,Y)-- [2:0-0-0,0-1-4], [4:0-4-4,0-1-12], [6:0-4-7,0-1-7]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.66	Vert(LL) -0.05 9 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.36	Vert(CT) -0.10 9 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.54	Horz(CT) 0.02 6 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 116 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-10-8 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=763/0-3-8 (min. 0-1-8), 6=708/0-1-8 (min. 0-1-8)
 Max Horz 2=261(LC 11)
 Max Uplift 2=-106(LC 12), 6=-119(LC 9)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1546/298, 3-4=-737/190
 BOT CHORD 2-9=-408/1444, 8-9=-410/1440, 7-8=-410/1440, 7-13=-213/471,
 6-13=-213/471
 WEBS 3-7=-1086/313, 4-7=-81/626, 4-6=-641/209

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 6.
- 8) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 6. This connection is for uplift only and does not consider lateral forces.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M3C	Half Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:23 2020 Page 1
 ID:hjOMp88mnrQzrZEntyWViFyWSr_-O1rg?KSs7_EL4ht1YJs4yuSs9hFLMhMIQNTIxHyW5pQ




Plate Offsets (X,Y)-- [2:0-0-0,0-1-4], [4:0-4-4,0-1-12], [5:Edge,0-1-8], [6:0-4-7,0-1-7]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.84	Vert(LL) -0.05 9 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.35	Vert(CT) -0.10 9 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.32	Horz(CT) 0.02 6 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 110 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-10-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=763/0-3-8 (min. 0-1-8), 6=708/0-1-8 (min. 0-1-8)
 Max Horz 2=210(LC 11)
 Max Uplift 2=-109(LC 8), 6=-115(LC 9)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1535/305, 3-4=-927/221
 BOT CHORD 2-9=-414/1432, 8-9=-416/1430, 7-8=-416/1430, 6-7=-226/598
 WEBS 3-7=-971/280, 4-7=-83/687, 4-6=-706/199

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 6.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 6. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M3D	Half Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:25 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWViFyWSr_KQyRQ?T7fbU3J_1QfkvY1JYFRUwHqXSbuhyP0AyW5pO



Scale = 1:38.1



7-0-0		9-0-0		17-10-8			
7-0-0		2-0-0		8-10-8			
Plate Offsets (X,Y)-- [2:0-0-0,0-1-4], [4:0-2-4,0-1-12], [7:0-4-7,0-1-7]							
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.67	Vert(LL) -0.05	7-8 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.39	Vert(CT) -0.12	7-8 >999 180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.54	Horz(CT) 0.02	7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS				
						Weight: 107 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 3-10-9 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=763/0-3-8 (min. 0-1-8), 7=708/0-1-8 (min. 0-1-8)
 Max Horz 2=160(LC 11)
 Max Uplift 2=-126(LC 8), 7=-114(LC 9)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1534/314, 3-4=-1153/256, 4-5=-797/207
 BOT CHORD 2-10=-408/1432, 9-10=-409/1434, 8-9=-409/1434, 7-8=-214/579
 WEBS 3-8=-918/279, 4-8=-109/630, 5-8=-20/351, 5-7=-767/234

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 7.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 7. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M3E	Half Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:26 2020 Page 1
ID:hjOMp88mnrQZrZEntywVIFyWSr_ocWpdLUIQvcwx8ccDRQnZX4QHGMZ?Qk6LizYcyW5pN



Scale = 1:37.5




Plate Offsets (X,Y)-- [2:0-0-0,0-1-4], [4:0-6-4,0-1-12], [7:0-2-7,0-1-7], [10:0-3-4,0-4-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.66	Vert(LL)	-0.06 11	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.40	Vert(CT)	-0.12 11-14	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.49	Horz(CT)	0.02 7	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 105 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-10-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-7-12 max.): 4-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=763/0-3-8 (min. 0-1-8), 7=708/0-1-8 (min. 0-1-8)
 Max Horz 2=110(LC 11)
 Max Uplift 2=149(LC 8), 7=118(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1506/309, 3-4=-2111/537, 4-5=-965/241, 5-6=-965/241, 6-7=-650/172
 BOT CHORD 2-11=-371/1404, 10-11=-310/1161, 9-10=-310/1161, 8-9=-311/1176
 WEBS 3-11=-1314/418, 4-11=-320/1186, 4-9=-39/290, 5-8=-337/159, 6-8=-237/1072

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 7.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 7. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M4	Monopitch	11	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:28 2020 Page 1
ID:hjOMp88mnrQZrZEntyWvIFyWSr_k?eZ21W?xWseASm?LsSFfyAq4_d1um1afB3dVyW5pL



Scale = 1:24.5

Plate Offsets (X,Y)-- [2:0-0-0,0-1-4], [2:0-2-15,0-9-8]				
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.38	Vert(LL) -0.02 6 >999 240	MT20 197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.22	Vert(CT) -0.04 5-6 >999 180	
BCLL 0.0 *	Rep Stress Incr YES	WB 0.56	Horz(CT) 0.01 5 n/a n/a	
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS		Weight: 64 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=546/0-3-0 (min. 0-1-8), 5=455/0-1-8 (min. 0-1-8)
 Max Horz 2=134(LC 11)
 Max Uplift 2=-118(LC 8), 5=-92(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-834/238
 BOT CHORD 2-6=-322/780, 5-6=-322/780
 WEBS 3-5=-785/284

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 5. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M4E	Monopitch Supported Gable	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:29 2020 Page 1

ID:hjOMp88mnrQZrZEntywVIFyWSr_-CBCyGNXdiq_VocLBUazUB9i3w6MHmTwApJwd9xyW5pK



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	-0.00	1	n/r	120	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.13	Vert(CT)	0.00	1	n/r	90		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.06	Horz(CT)	-0.00	7	n/a	n/a		
BCDL	10.0	Code IRC2015/TPI2014		Matrix-P								
											Weight: 35 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2 or 2x4 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2 or 2x4 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 10'-0" oc bracing.
WEBS	2x4 SP No.3		
OTHERS	2x4 SP No.3		
SLIDER	Left 2x4 SP No.3 -ü 1'-6"-0		

REACTIONS. All bearings 7-7-8.
 (lb) - Max Horz 2=93(LC 9)
 Max Uplift All uplift 100 lb or less at joint(s) 7, 2, 8, 9
 Max Grav All reactions 250 lb or less at joint(s) 7, 2, 8 except 9=308(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable studs spaced at 2'-0" oc.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-6" tall by 2'-0" wide will fit between the bottom chord and any other members.
 - 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7, 2, 8, and 9. This connection is for uplift only and does not consider lateral forces.
 - 7) Non Standard bearing condition. Review required.
 - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M4E1	Monopitch Supported Gable	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:31 2020 Page 1
ID:hjOMP88mnrQZrZEntywiFyWSr_-9aKih3YuERED1vUZ0??yGaoPPv2IENMTGdPkDqyW5pl




Plate Offsets (X,Y)-- [2:0-4-3,0-0-13]				
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.19	Vert(LL) -0.00 1 n/r 120	MT20 197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.13	Vert(CT) 0.00 1 n/r 90	
BCLL 0.0 *	Rep Stress Incr YES	WB 0.06	Horz(CT) 0.00 6 n/a n/a	
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P		Weight: 26 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 -ü 1-6-0

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 6=16/5-7-8 (min. 0-1-8), 2=191/5-7-8 (min. 0-1-8), 7=313/5-7-8 (min. 0-1-8)
 Max Horz 2=73(LC 9)
 Max Uplift 6=-2(LC 9), 2=-53(LC 8), 7=-72(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable studs spaced at 2-0-0 oc.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at it(s) 6, 2, and 7. This connection is for uplift only and does not consider lateral forces.
- 7) Non Standard bearing condition. Review required.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M7	Monopitch	10	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:32 2020 Page 1
 ID:hjOMp88mnrQZrZEntyWViFyWSr_-dmu4uPZW?IN4f33maiXBpoKWQJNRzpdDvVH9HmGyW5pH



Scale = 1:28.0

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.43	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.16	Vert(LL) -0.01 4-5 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.09	Vert(CT) -0.02 4-5 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) -0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 30 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=218/0-3-8 (min. 0-1-8), 4=140/0-1-8 (min. 0-1-8)
 Max Horz 5=199(LC 9)
 Max Uplift 5=23(LC 8), 4=119(LC 9)
 Max Grav 5=251(LC 20), 4=200(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

BOT CHORD 4-5=-343/312
 WEBS 2-4=-254/294

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 4. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M7A	Half Hip	1	1	Job Reference (optional)


84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:34 2020 Page 1

ID:hjOMp88mnrQZrZEntywViFyWSr_-Z9?rJ4amXMdnuND8h7ZfuDPsw62vRjivybeOq9yW5pF



Scale = 1:26.6



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.43	Vert(LL)	-0.01	4-5	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.16	Vert(CT)	-0.02	4-5	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.09	Horz(CT)	-0.00	4	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP							
									Weight: 30 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=218/0-3-8 (min. 0-1-8), 4=140/0-1-8 (min. 0-1-8)
 Max Horz 5=199(LC 9)
 Max Uplift 5=23(LC 8), 4=119(LC 9)
 Max Grav 5=251(LC 20), 4=200(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 BOT CHORD 4-5=-343/312
 WEBS 2-4=-254/294

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 4. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M7B	Half Hip	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

ID:hjOMp88mnrQZrZEntywViFyWSr_-1LZDWQbOlgleWXoLFq4uRQy4?WNKAAJ3BFNxMbyW5pE 8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:35 2020 Page 1



Scale = 1:20.3




Plate Offsets (X,Y)-- [3:0-2-8,0-2-0], [5:Edge,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.21	Vert(LL)	0.02	6-7	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.21	Vert(CT)	-0.02	6-7	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.06	Horz(CT)	-0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS							
									Weight: 30 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-4.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=218/0-3-8 (min. 0-1-8), 5=140/0-1-8 (min. 0-1-8)
 Max Horz 7=145(LC 11)
 Max Uplift 7=-18(LC 12), 5=-79(LC 9)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 BOT CHORD 6-7=-266/258

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M7C	Half Hip Girder	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:37 2020 Page 1

ID:hjOMp88mnrQZrZEntywViFyWSr_-zkhzx6deqH?MlqyjMF6MWr1QCK5Be55MeZs2RUyW5pC



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.17	Vert(LL)	0.01	6	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.13	Vert(CT)	-0.01	5-6	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS							
									Weight: 23 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-4.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=218/0-3-8 (min. 0-1-8), 5=140/0-1-8 (min. 0-1-8)
 Max Horz 7=95(LC 9)
 Max Uplift 7=-47(LC 12), 5=-65(LC 9)
 Max Grav 7=218(LC 1), 5=141(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 3-10-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 88 lb down and 67 lb up at 2-0-12 on top chord, and 14 lb down and 15 lb up at 2-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).


LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-3=-60, 3-4=-60, 5-7=-20
 Concentrated Loads (lb)
 Vert: 9=1(F)

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	M8	Monopitch Supported Gable	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:39 2020 Page 1
 ID:hjOMp88mnrQZrZEntywVIFyWSr_-w6pkMoevMvF4_856Ug9qbG7lw7nP6xHe6tL9WMYw5pA



Scale = 1:60.7

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.22	Vert(LL)	0.00	1	n/r	120	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(CT)	0.00	1	n/r	90	
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.19	Horz(CT)	-0.00	8	n/a	n/a	
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						
								Weight: 89 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 12-13.
 WEBS 1 Row at midpt 7-8, 6-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 9-4-0.
 (lb) - Max Horz 13=374(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 8 except 13=-228(LC 10), 9=-109(LC 12), 10=-106(LC 12), 11=-114(LC 12), 12=-527(LC 12)
 Max Grav All reactions 250 lb or less at joint(s) 8, 9, 10, 11 except 13=737(LC 12), 12=284(LC 10)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-13=-781/581, 2-3=-466/415, 3-4=-400/330, 4-5=-280/232
 BOT CHORD 12-13=-407/322
 WEBS 2-12=-518/653

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) All plates are 1.5x4 MT20 unless otherwise indicated.
- 4) Gable requires continuous bottom chord bearing.
- 5) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 9) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 13, 8, 9, 10, 11, and 12. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	PB1	Piggyback	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:40 2020 Page 1
ID:hjOMp88mnrQZrZEntyWViFyWSr_-OJM6Z8fX7CNxclgl2Ng38UfzaX7drR1oKX5i2oyW5p9



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.03	in	(loc)	l/defl	L/d	MT20	197/144		
TCDL	10.0	Lumber DOL	1.15	BC	0.01	Vert(LL)	0.00	6	n/r	Weight: 27 lb FT = 20%			
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.03	Vert(CT)	0.00	6	n/r				
BCDL	10.0	Code IRC2015/TPI2014		Matrix-P		Horz(CT)	0.00	6	n/a				

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 5-1-8.
 (lb) - Max Horz 2=-72(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 6, 10, 8
 Max Grav All reactions 250 lb or less at joint(s) 2, 6, 9, 10, 8

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 6, 10, and 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	PB2	Piggyback	12	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:42 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-KhUs_phneqdfbqh9oiXDvIHwLoFJLj5Sorap6hyW5p7



LOADING (psf)		SPACING-		CSI.	DEFL.				PLATES	GRIP
TCLL	20.0	Plate Grip DOL	1.15	TC	0.13	in (loc)	l/defl	L/d	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.07	Vert(LL)	0.00	5	n/r	120
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.02	Vert(CT)	0.00	5	n/r	90
BCDL	10.0	Code IRC2015/TPI2014		Matrix-P		Horz(CT)	0.00	4	n/a	n/a
									Weight: 24 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=146/5-1-8 (min. 0-1-8), 4=146/5-1-8 (min. 0-1-8), 6=159/5-1-8 (min. 0-1-8)
 Max Horz 2=-72(LC 10)
 Max Uplift 2=-34(LC 13), 4=-40(LC 13)
 Max Grav 2=146(LC 1), 4=146(LC 1), 6=160(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 8) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	PB3	Piggyback	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:43 2020 Page 1
ID:hjOMp88mnrQZrZEntywViFyWSr_-ot2EC9hPP7IWTIPtjWDml6HTGI8W2owE1VJMf7yW5p6



Scale = 1:15.2




Plate Offsets (X,Y)-- [3:0-2-0,Edge], [5:0-2-0,Edge]

LOADING (psf)	SPACING-	CSL.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.07	Vert(LL) 0.00	7	n/r	120	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT) 0.00	7	n/r	90		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Horz(CT) 0.00	6	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2015/TPI2014						Weight: 21 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 3-5.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=136/5-1-10 (min. 0-1-8), 6=136/5-1-10 (min. 0-1-8), 8=196/5-1-10 (min. 0-1-8)
 Max Horz 2=-43(LC 10)
 Max Uplift 2=-33(LC 12), 6=-39(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 6. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	V1	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:45 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_kGA?drjgl?Ei3ZGqxGErXNkxYn5WhmXUooTj0yW5p4



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.44	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.31	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.07	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2015/TPI2014			Weight: 38 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=190/9-2-8 (min. 0-1-8), 3=190/9-2-8 (min. 0-1-8), 4=304/9-2-8 (min. 0-1-8)
 Max Horz 1=106(LC 9)
 Max Uplift 1=-37(LC 13), 3=-37(LC 13), 4=-5(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 3, and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	V2	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:47 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_hflI1XkwTMFxyNjeyMliwyS6sMU8_crqx6HaouyW5p2



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.28	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.15	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.03	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2015/TPI2014			Weight: 26 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=140/6-6-8 (min. 0-1-8), 3=140/6-6-8 (min. 0-1-8), 4=189/6-6-8 (min. 0-1-8)
 Max Horz 1=73(LC 9)
 Max Uplift1=-35(LC 13), 3=-35(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 3. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Hicks Residence - Milltown
2000811-2000811A	V3	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Tue Oct 6 15:57:52 2020 Page 1
 ID:hjOMp88mnrQZrZEntywViFyWSr_-1c5e5Eo3luuE28bclvutd09?pNDxftLZ5O?LS6yW5oz



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.08	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.01	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						
								Weight: 15 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-11-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=77/3-10-8 (min. 0-1-8), 3=77/3-10-8 (min. 0-1-8), 4=103/3-10-8 (min. 0-1-8)
 Max Horz 1=-40(LC 8)
 Max Uplift1=-19(LC 13), 3=-19(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 3. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard