4	SFD	900	-00	66
App#				

## Harnett County Department of Public Health

Improvement Permit A building permit cannot be issued with only an Improvement Permit

PROPERTY LOCATION: 247 Mineral Springs La. (Chalybeane Rd.) LGI HONES NCLL Avery Pond 101# SUBDIVISION \_\_\_\_ EXPANSION REPAIR | NEW 1 Site Improvements required prior to Construction Authorization Issuance: 3-Bedroom 39'x48' 5FD Proposed Wastewater System Type: 25% 10 2016100 573. Projected Daily Flow: 360 Number of Occupants: \_\_ 6 max Number of bedrooms: \_ Basement Yes Pump Required: Yes Mo May be required based on final location and elevations of facilities Type of Water Supply: Community Public Well Distance from well NA feet Live years Permit valid for: No expiration Permit conditions: Date: \_\_\_ Authorized State Agent:: \_ SEE ATTACHED SITE SKETCH The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit. Construction Authorization (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. Facility Type: 3-Bedresom 39'x 48' STD | Hew | Expansion | Repair Basement? Yes Basement Fixtures? Yes No Type of Wastewater System\*\* 25% Neduction System (Initial) Wastewater Flow: 360 (See note below, if applicable ) 25% reduction sys. (Repair) Number of trenches Installation Requirements/Conditions Septic Tank Size 1000 gallons Exact length of each trench \_\_\_ Pump Tank Size \_\_\_\_\_gallons Trenches shall be installed on contour at a Maximum Trench Depth of: 26→18 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: \_\_\_\_\_\_ft. TDH vs. \_\_\_\_\_GPM \_ inches below pipe NA inches above pipe inches total WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA. \*\*If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This SEE ATTACHED SITE SKETCH Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. Authorized State Agent: Construction Authorization Expiration Date: 66/24/2024

ANDREW CURRIN

HTE#	SED1905-Q	566
------	-----------	-----

Permit # \_\_\_\_ NA

## Harnett County Department of Public Health Site Sketch

Site Sketch
ISSUED TO: LGI Homes NC US SUBDIVISION Avery pond LOT # 76
Authorized State Agent: (26/24/20/2
AND OF THE CONTRACTOR
Authorized State Agent  ANDREW CURLIN  **O,  ANDREW CURLIN  **ISFT SETBACK OFF  SIDE DAINAGE  ESMT  **STACK OFF  DOWNHILL DRAINAGE  ESMT  **DEEP (26IN) TO  SHALLOW (18IN)  FINSTALL LIKELY  AEGUINED TO  KEEP UPHILL  **O,  **ISFT SETBACK OFF  DOWNHILL DRAINAGE  ESMT  **ADECTION  SHALLOW (18IN)  FINSTALL LIKELY  AEGUINED TO  KEEP UPHILL
7 30
382
46 500
23.51
36'1 9/2
36 /10
81'
MINEROL STANS