Harnett County Department of Public Health

Improvement Permit

_	PROPERTY LOCATION: 1041		- Red Bondy
ISSUED TO: JOSE KWOTO	SUBDIVISION	resser riniva	Int # 2
	SION Site Improvement	s required prior to Construction Autho	rization Issuance:
Type of Structure: ST-D 44 x 5- Proposed Wastewater System Type: 25% Rec	<u> </u>	The state of the s	
Projected Daily Flow: 480 GPD	AUCTIOY)		
Number of bedrooms: Number of Occ	cupants: 8 max		
Basement Yes 🔀 No			
Pump Required: Yes No May be re-	quired based on final location and elevations of facilities	The sales of the s	
Type of Water Supply: Community Public Permit conditions:	Well Distance from well feet	Permit valid for:	🔀 Five years
remit conditions.			No expiration
	1 1		
Authorized State Agent::	Q(30 Date: 4)2)1	SEE ATT	ACHED SITE SKETCH
site is subject to revocation if the site plan, plat, or the intended use	rance the hishance of other permits. The permit holder is responsible to e changes. The Improvement Permit shall not be affected by a change in	r checking with appropriate governing bodies in	meeting their requirements. This
the Laws and Rules for Sewage Treatment and Disposal and to conditi	ions of this permit.	ownership of the site. This permit is subject to	compliance with the provisions of
	_		
	Construction Authorization		
•	(Required for Building Permit)		
The construction and installation requirements of Rules .1950, .1952, with the attached system layout.	.1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by referen	nces into this permit and shall be met. Systems	shall be installed in accordance
		111 17 211	DI.
ISSUED TO: Dose Kubio	PROPERTY LOCATION: 10	41 Rosser Pith	nanka,
facility Type: SFD 44' x 57'	SUBDIVISION		LOT # 2
Basement? Yes No Basement Fix	IXI New □ Expansion □ Repa xtures? □ Yes . IXI No	ıır	
Type of Wastewater System** 26%.		(Initial) Wassess El	LICO 500
See note below, if applicable (20,000	(Initial) Wastewater Flow:	480 GPD
75/12	eduction (Repair)		
nstallation Requirements/Conditions	Number of trenches 4		
eptic Tank Size 1000 gallons	Exact length of each trenchfeet	Trench Spacing: 9	Feet on Center
ump Tank Sizegallons	Trenches shall be installed on contour at a		ches
	Maximum Trench Depth of: 18-24 inches	s (Maximum soil cover shall no	ot exceed
	(Trench bottoms shall be level to +/-1/4"	36" above the trench botto	m)
Imp Possing to TDII	in all directions)		
ump Requirements:ft. TDH vs	GPM		inches below pipe
anditions:		Aggregate Depth:	
notions.			inches total
ATER LINES (INCLUDING IRRIGATION) MUST I	BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR	DEDAID ADEA	
O UTILITIES ALLOWED IN INITIAL OR REPAIR D	DEVILLE LEGIT AND LAKE OF SELLIC STREM OF	KETAIK AKEA.	
The same of the sa	and the state of t		-
n applicable. I understand the system type specified	is different from the type specified on the application	n. I accept the specifications of th	is permit.
vner/Legal Representative Signature:		Data	
s construction authorization is subject to revocation if the site plan, p	plat, or the intended use changes. The Construction Authorization shall not	t he transferred when there is a change in own	perhip of the rise This
estruction Authorization to tubiect to compliance with the provisions of	f the Laws and Rules for Sewage Treatment and Disposal and to the cond	itions of this permit.	TACHED SITE SKETCH
		1 2	
thorized State Agent:	Date:	3/12/19	
Bellah	Construction Authorization Expiration	Date: 3 1224	
0	HS		

HTE#	SFD	190	7-0020
------	-----	-----	--------

#	_
	#

Harnett County Department of Public Health Site Sketch

15SUED TO: Jose Rubio	PROPERTY LOCATON: 1041 ROSSET Pitman Rd SUBDIVISION LOT #
	(A) (OLI162 TOLKSDOR) Date: 8 12/17
This drawing is fac il	lustrative purposes only.
System installation m	ust meet all pertinent laws

