



Products				
PlotID	Length	Product	Plies	Net Qty
FJ-27	27' 10"	14" BCI@ 4500s-1.8	1	7
FJ-27-2	27' 10"	14" BCI@ 4500s-1.8	2	2
FJ-15	15' 7"	14" BCI@ 4500s-1.8	1	1
FJ-15	15' 3 3/4"	14" BCI@ 4500s-1.8	1	5
FJ-15	15' 3 1/2"	14" BCI@ 4500s-1.8	1	3
FJ-12	12' 6 1/2"	14" BCI@ 4500s-1.8	1	1
FJ-12	12' 1 1/4"	14" BCI@ 4500s-1.8	1	9
FJ-8A	8' 4 3/4"	14" BCI@ 4500s-1.8	1	1
FJ-8	8' 4 1/2"	14" BCI@ 4500s-1.8	1	7
FJ-7	7' 3 1/2"	14" BCI@ 4500s-1.8	1	1
FJ-7	7' 0"	14" BCI@ 4500s-1.8	1	1
FJ-6	6' 0 1/4"	14" BCI@ 4500s-1.8	1	2
FJ-4	4' 0"	14" BCI@ 4500s-1.8	1	1
FJ-3	3' 6 3/4"	14" BCI@ 4500s-1.8	1	1
FJ-3	3' 6 1/4"	14" BCI@ 4500s-1.8	1	1
FB1-3	18' 0"	1-3/4" x 14" VERSA-LAM@ 2.0 3100 SP	3	3
Rim1	12' 0"	1" x 14" BC RIM BOARD OSB	1	11
Bk1	2' 0"	14" BCI@ 4500s-1.8	1	14

Wall Framing				
PlotID	Length	Product	Plies	Net Qty
Hdr1	8' 0"	1-3/4" x 9-1/4" VERSA-LAM@ 2.0 3100 SP	2	2

Hangers				
PlotID	Qty	Manuf	Product	
H1	31	Simpson	IUS 1.81/14	



www.BLDR.com

1135 Robeson St.  
Fayetteville, NC 28305  
V (910) 485-1111  
F (910) 485-6475

7601 BOEING DRIVE  
GREENSBORO, NC 27409  
V: 336.884.5454

3189 NC HIGHWAY5  
ABERDEEN NC 28315  
V: 910.944.2516

This layout and associated materials list has been prepared based on project plans and/or information provided to Builders FirstSource (BFS). It remains the responsibility of the builder, architect, designer, or other responsible persons to review this information to assure that it is appropriate, accurate, complete and complies with applicable building codes.

- GENERAL NOTES
- 1.) READ THE INSTALLATION GUIDE BEFORE FRAMING.
  - 2.) ALL WALL SHOWN ARE LOAD BEARING UNLESS NOTES OTHERWISE WALLS NOT SHOWN HAVE BEEN CONSIDERED NON-LOAD BEARING
  - 3.) UNLESS STATED OTHERWISE ALL CEILING & ROOF LOADS BRACE DIRECTLY TO LOAD BEARING WALLS SUPPORTED BY FOUNDATION
  - 4.) CONTACT YOU LOCAL BUILDERS FIRSTSOURCE LOCATION BEFORE MAKING ANY ALTERATION & ADJUSTMENTS. FAILURE MAY RESULT IN COSTLY REPAIRS

<b>H &amp; H HOMES</b>	<b>ENGAGE-A GL</b>	2nd FLOOR EWP PLACEMENT PLAN	DATE: 3-20-18	JOB #
	Builders FirstSource, Central Carolina Markets	DRAWN BY: LEE ATKINS	SCALE: NTS	

MINIMUM DESIGN DATA  
LIVE LOAD 40 PSF  
DEAD LOAD 10 PSF

TOTAL LOAD 50 PSF  
STRESS DURATION = 100%  
DEFLECTION CRITERIA  
L/480 (MINIMUM)

ARCHITECTURAL PLAN DATE  
11-16-17  
REVISED ARCH. PLAN DATE  
XX-XX-XX  
SEALED PLAN DATE  
12-22-17